

MAXIMUM PERMISSIBLE EXPOSURE

This Maximum Permissive Exposure (MPE) report demonstrates compliance for Gobi2000 Module with FCC CFR 47 §1.1310 and 2.1091 and IC Safety Code 6, Section 2.2.1 (a) for standalone and collocated simultaneous transmission in mobile exposure conditions. The MPE analysis is valid for transmitters operating within the parameters defined in Table B used for analysis.

Any collocated transmitter must have a valid FCC ID documenting equivalent or degraded RF Output Power with the collocated parameters calculated in this MPE analysis.

The mobile classification applies when 20 cm or more separation distance is maintained between the end user and both WLAN and Bluetooth transmission antennas.

Portable user conditions or additional collocated modules not allowed based on this RF exposure analysis require a Class II permissive change and updated MPE or SAR report.

FCC RULES

§1.1310 The criteria listed in Table 1 shall be used to evaluate the environmental impact of human exposure to radio-frequency (RF) radiation as specified in §1.1307(b), except in the case of portable devices which shall be evaluated according to the provisions of §2.1093 of this chapter.

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3–3.0	614	1.63	*(100)	6
3.0–30	1842/f	4.89/f	*(900/f ²)	6
30–300	61.4	0.163	1.0	6
300–1500	f/300	6
1500–100,000	5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)—Continued

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
30–300	27.5	0.073	0.2	30
300–1500	f/1500	30
1500–100,000	1.0	30

f = frequency in MHz

* = Plane-wave equivalent power density

NOTE 1 TO TABLE 1: Occupational/controlled limits apply in situations in which persons are exposed as a consequence of their employment provided those persons are fully aware of the potential for exposure and can exercise control over their exposure. Limits for occupational/controlled exposure also apply in situations when an individual is transient through a location where occupational/controlled limits apply provided he or she is made aware of the potential for exposure.

NOTE 2 TO TABLE 1: General population/uncontrolled exposures apply in situations in which the general public may be exposed, or in which persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or can not exercise control over their exposure.

IC RULES

IC Safety Code 6, Section 2.2.1 (a) A person other than an RF and microwave exposed worker shall not be exposed to electromagnetic radiation in a frequency band listed in Column 1 of Table 5, if the field strength exceeds the value given in Column 2 or 3 of Table 5, when averaged spatially and over time, or if the power density exceeds the value given in Column 4 of Table 5, when averaged spatially and over time.

Table 5
Exposure Limits for Persons Not Classed As RF and Microwave Exposed Workers (Including the General Public)

1 Frequency (MHz)	2 Electric Field Strength; rms (V/m)	3 Magnetic Field Strength; rms (A/m)	4 Power Density (W/m ²)	5 Averaging Time (min)
0.003–1	280	2.19		6
1–10	280/ <i>f</i>	2.19/ <i>f</i>		6
10–30	28	2.19/ <i>f</i>		6
30–300	28	0.073	2*	6
300–1 500	1.585 <i>f</i> ^{0.5}	0.0042 <i>f</i> ^{0.5}	<i>f</i> /150	6
1 500–15 000	61.4	0.163	10	6
15 000–150 000	61.4	0.163	10	616 000 / <i>f</i> ^{1.2}
150 000–300 000	0.158 <i>f</i> ^{0.5}	4.21 x 10 ⁻⁴ <i>f</i> ^{0.5}	6.67 x 10 ⁻⁵ <i>f</i>	616 000 / <i>f</i> ^{1.2}

* Power density limit is applicable at frequencies greater than 100 MHz.

Notes: 1. Frequency, *f*, is in MHz.
2. A power density of 10 W/m² is equivalent to 1 mW/cm².
3. A magnetic field strength of 1 A/m corresponds to 1.257 microtesla (μT) or 12.57 milligauss (mG).

EQUATIONS

Power density is given by:

$$S = \text{EIRP} / (4 * \text{Pi} * D^2)$$

where

S = Power density in W/m²

EIRP = Equivalent Isotropic Radiated Power in W

D = Separation distance in m

Power density in units of W/m² is converted to units of mWc/m² by dividing by 10.

In the table(s) below, Power and Gain are entered in units of dBm and dBi respectively and conversions to linear forms are used for the calculations.

LIMITS

From FCC §1.1310 Table 1 (B),

the maximum value of

S = 0.549 mW/cm² @ 850MHz

S = 1.0 mW/cm² @ 1900MHz, 2.4GHz / 5GHz

From IC Safety Code 6, Section 2.2 Table 5 Column 4,

S = 5.49 W/m² @ 850MHz

S = 10 W/m² @ 1900MHz, 2.4GHz, 5GHz

1. Stand Alone Transmitter Calculation

RESULTS

Table A1: Gobi2000

Technology	Frequency (MHz)	Separation Distance (m)	Output Power (dBm)	Antenna Gain (dBi)	Duty Cycle (%)	IC Power Density (W/m ²)	FCC Power Density (mW/cm ²)
GPRS 850 (2 UL Slots)	824	0.20	33.00	7.0	25	4.98	0.498
WCDMA 850MHz	824	0.20	25.00	7.0	100	3.15	0.315
CDMA 850MHz	824	0.20	25.00	7.0	100	3.15	0.315
GPRS 1900 (2 UL Slots)	1850	0.20	29.50	3.5	25	0.99	0.099
WCDMA 1900MHz	1850	0.20	25.00	3.5	100	1.41	0.141
CDMA 1900MHz	1850	0.20	25.00	3.5	100	1.41	0.141

Table A2: WLAN + Bluetooth

Technology	Separation Distance (m)	Output Power (dBm)	Antenna Gain (dBi)	IC Power Density (W/m ²)	FCC Power Density (mW/cm ²)
2412 - 2462	0.20	25.00	6.0	2.51	0.251
5150 - 5250	0.20	20.00	6.0	0.79	0.079
5250 - 5350	0.20	20.00	6.0	0.79	0.079
5470 - 5725	0.20	20.00	6.0	0.79	0.079
5725 - 5850	0.20	25.00	6.0	2.51	0.251
2402 - 2480	0.20	13.00	5.0	0.13	0.013

2. Collocated MPE Calculations

RESULTS

Table B1: Gobi2000 (850MHz) + WLAN + Bluetooth

Technology	Separation Distance (m)	WLAN/BT IC Power Density (W/m ²)	WLAN/BT FCC Power Density (mW/cm ²)	WWAN IC Power Density (W/m ²)	WWAN FCC Power Density (mW/cm ²)	IC WLAN + BT+ WWAN (W/m ²)	FCC WLAN + BT + WWAN (mW/cm ²)
2412 - 2462	0.20	2.51	0.251	4.980	0.498	7.62	0.762
5150 - 5250	0.20	0.79	0.079	4.980	0.498	5.90	0.590
5250 - 5350	0.20	0.79	0.079	4.980	0.498	5.90	0.590
5470 - 5725	0.20	0.79	0.079	4.980	0.498	5.90	0.590
5725 - 5850	0.20	2.51	0.251	4.980	0.498	7.62	0.762

Table B2: Gobi2000 (1900MHz) + WLAN + Bluetooth

Technology	Separation Distance (m)	WLAN IC Power Density (W/m ²)	WLAN FCC Power Density (mW/cm ²)	WWAN IC Power Density (W/m ²)	WWAN FCC Power Density (mW/cm ²)	IC WLAN + WWAN (W/m ²)	FCC WLAN + WWAN (mW/cm ²)
2412 - 2462	0.20	2.51	0.251	1.410	0.141	4.05	0.405
5150 - 5250	0.20	0.79	0.079	1.410	0.141	2.33	0.233
5250 - 5350	0.20	0.79	0.079	1.410	0.141	2.33	0.233
5470 - 5725	0.20	0.79	0.079	1.410	0.141	2.33	0.233
5725 - 5850	0.20	2.51	0.251	1.410	0.141	4.05	0.405

As shown in the calculations above, when all devices are operational, the worst case combination is within the limit at a distance of 20cm from the device.