

FCC RF Exposure Report

FCC ID : N7NHL7519

Equipment: Wireless Module

Model No. : HL7519

Brand Name : AirPrime

Applicant : Sierra Wireless Inc.

Address : 13811 Wireless Way Richmond, BC, V6V 3A4

Canada

Standard : 47 CFR FCC Part 2.1091

Received Date : Aug. 18, 2015

Tested Date : Aug. 23 ~ Sep. 04, 2015

We, International Certification Corp., would like to declare that the tested sample has been evaluated and in compliance with the requirement of the above standards. The test results contained in this report refer exclusively to the product. It may be duplicated completely for legal use with the approval of the applicant. It shall not be reproduced except in full without the written approval of our laboratory.

Approved & Reviewed by:

Gary Chang / Manager

Ilac-MRA

TAF)
Testing Laboratory

Page: 1 of 7

Report No.: FA581801



Table of Contents

1	MPE EVALUATION OF MOBILE DEVICES	4
1.1	LIMITS FOR GENERAL POPULATION/UNCONTROLLED EXPOSURE	4
1.2	MPE EVALUATION FORMULA	4
1.3	MPE EVALUATION RESULTS	5
1.4	MAXIMUM ANTENNA GAIN EVALUATION (REFERENCE ONLY)	6
_	TEST LABORATORY INFORMATION	_
7	TEST LABORATORY INFORMATION	/

Report No.: FA581801

Page : 2 of 7



Release Record

Report No.	Version	Description	Issued Date
FA581801	Rev. 01	Initial issue	Sep. 16, 2015

Report No.: FA581801 Page: 3 of 7



1 MPE EVALUATION OF MOBILE DEVICES

Human exposure to RF emissions from mobile devices (47 CFR §2.1091) may be evaluated based on the MPE limits adopted by the FCC for electric and magnetic field strength and/or power density, as appropriate, since exposures are assumed to occur at distances of 20 cm or more from persons.

1.1 LIMITS FOR GENERAL POPULATION/UNCONTROLLED EXPOSURE

Frequency Range (MHz)	Power Density (mW /cm²)	Averaging Time (minutes)		
300~1500	F/1500	30		
1500~100000	1.0	30		

1.2 MPE EVALUATION FORMULA

$$Pd = \frac{Pt}{4*Pi*R^2}$$

Where

Pd= Power density in mW/cm²

Pt= EIRP in mW Pi= 3.1416

R= Measurement distance

Report No.: FA581801 Page: 4 of 7



1.3 MPE EVALUATION RESULTS

Mode	Frequency Range (MHz)	Maximum Conducted Power (dBm)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm²)	Limit (mW/cm²)
	779.5	22.32	2	20	0.054	0.520
LTE Band 13	782.0	22.38	2	20	0.055	0.521
	784.5	22.33	2	20	0.054	0.523
	1850.7	23.24	2	20	0.066	1.000
LTE Band 2	1880.0	23.23	2	20	0.066	1.000
	1909.3	23.52	2	20	0.071	1.000
	1710.7	23.03	2	20	0.063	1.000
LTE Band 4	1732.5	23.02	2	20	0.063	1.000
	1754.3	23.02	2	20	0.063	1.000

Report No.: FA581801 Page: 5 of 7



1.4 MAXIMUM ANTENNA GAIN EVALUATION (REFERENCE ONLY)

Mode	Freq. Conducted tune up Max Gain to comply with				with MPE	Max Gain to comply with ERP		
Mode	(MHz)	power (dBm)	power (dBm)	Antenna Gain (dBi)	Distance (cm)	Limit (mW/cm²)	Antenna Gain (dBi)	Limit (ERP,W)
	779.5	22.32	24.00	10.17	20	0.520	12.92	3
LTE Band 13	782.0	22.38	24.00	10.18	20	0.521	12.92	3
	784.5	22.33	24.00	10.20	20	0.523	12.92	3

Note: In order to comply with both Maximum Permissible Exposure and ERP limit, the maximum antenna gain shall not be greater than 10.17 dBi in LTE band 13

Mode	Freq. Conducted		Maximum tune up	Max Gai	n to comply	Max Gain to comply with EIRP		
Wiode	(MHz)	power (dBm)	power (dBm)	Antenna Gain (dBi)	Distance (cm)	Limit (mW/cm²)	Antenna Gain (dBi)	Limit (EIRP,W)
	1850.7	23.24	24.00	13.01	20	1.000	9.01	2
LTE Band 2	1880.0	23.23	24.00	13.01	20	1.000	9.01	2
	1909.3	23.52	24.00	13.01	20	1.000	9.01	2

Note: In order to comply with both Maximum Permissible Exposure and EIRP limit, the maximum antenna gain shall not be greater than 9.01 dBi in LTE band 2

Mode	Freq. Conducted Maximum tune up			Max Gai	n to comply	Max Gain to comply with EIRP		
Wode	(MHz)	power (dBm)	power (dBm)	Antenna Gain (dBi)	Distance (cm)	Limit (mW/cm²)	Antenna Gain (dBi)	Limit (EIRP,W)
	1710.7	23.03	24.00	13.01	20	1.000	6.00	1
LTE Band 4	1732.5	23.02	24.00	13.01	20	1.000	6.00	1
	1754.3	23.02	24.00	13.01	20	1.000	6.00	1

Note: In order to comply with both Maximum Permissible Exposure and EIRP limit, the maximum antenna gain shall not be greater than 6 dBi in LTE band 4

Report No.: FA581801 Page: 6 of 7



2 Test laboratory information

Established in 2012, ICC provides foremost EMC & RF Testing and advisory consultation services by our skilled engineers and technicians. Our services employ a wide variety of advanced edge test equipment and one of the widest certification extents in the business.

International Certification Corp, it is our definitive objective is to institute long term, trust-based associations with our clients. The expectation we set up with our clients is based on outstanding service, practical expertise and devotion to a certified value structure. Our passion is to grant our clients with best EMC / RF services by oriented knowledgeable and accommodating staff.

Our Test sites are located at Linkou District and Kwei Shan Hsiang. Location map can be found on our website http://www.icertifi.com.tw.

Linkou

Tel: 886-2-2601-1640

No. 30-2, Ding Fwu Tsuen, Lin Kou District, New Taipei City, Taiwan,

R.O.C.

Kwei Shan

Tel: 886-3-271-8666 No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan Hsiang, Tao Yuan Hsien 333, Taiwan, R.O.C. Kwei Shan Site II

Tel: 886-3-271-8640 No. 14-1, Lane 19, Wen San 3rd

St., Kwei Shan Hsiang, Tao Yuan Hsien 333, Taiwan, R.O.C.

If you have any suggestion, please feel free to contact us as below information

Tel: 886-3-271-8666 Fax: 886-3-318-0155

Email: ICC_Service@icertifi.com.tw

==END==

Report No.: FA581801 Page: 7 of 7