

RF Exposure Evaluation declaration

Product Name : Module
Model No. : HL7618RD
FCC ID : N7NHL7618RD

Applicant : Sierra Wireless Inc.

Address : 13811 Wireless Way, Richmond, BC, V6V 3A4 Canada

Date of Receipt : Aug. 29, 2016
Date of Declaration : Sep. 09, 2016
Report No. : 1690025R-SAUSP22V00
Report Version : V1.0



The test results relate only to the samples tested.

The test results shown in the test report are traceable to the national/international standard through the calibration of the equipment and evaluated measurement uncertainty herein.

This report must not be used to claim product endorsement by TAF or any agency of the government.

The test report shall not be reproduced without the written approval of QuieTek Corporation.

1. GENERAL INFORMATION

1.1. EUT Description

Product Name	Module
Model No.	HL7618RD
Trade Name	AirPrime
IMEI No.	359998070020005
FCC ID	N7NHL7618RD
Modulation	LTE Band 4 : QPSK/16-QAM
	LTE Band 13 : QPSK/16-QAM
TX Frequency	LTE Band 4 : 1710MHz ~1755MHz
	LTE Band 13 : 777MHz ~ 787MHz
Rx Frequency	LTE Band 4: 2110~2155MHz
	LTE Band 13 : 746 MHz~756 MHz
Bandwidth	LTE Band 4: 1.4MHz/3 MHz/5 MHz/10 MHz/15 MHz/20 MHz
	LTE Band 13: 5 MHz/10 MHz
HW Version	1.0
SW Version	AHL7618RD.V.1.0
Antenna Type	Dipole

1.2. Antenna List :

No.	Manufacturer	Part No.	Peak Gain
1	Pulse	SPDA24700/2700	2dBi

2. RF Exposure Evaluation

2.1. Limits

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b).

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (Minutes)
(A) Limits for Occupational/ Control Exposures				
300-1500	--	--	F/300	6
1500-100,000	--	--	5	6
(B) Limits for General Population/ Uncontrolled Exposures				
300-1500	--	--	F/1500	30
1500-100,000	--	--	1	30

F= Frequency in MHz

Friis Formula

Friis transmission formula: $Pd = (Pout * G) / (4 * \pi * R^2)$

Where

Pd = power density in mW/cm²

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

Pd is the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

2.2. Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

The temperature and related humidity: 21°C and 60% RH.

2.3. Test Result of RF Exposure Evaluation

Product : Module
 Test Item : RF Exposure Evaluation
 Test Site : N/A

LTE Band 4 -Peak Gain: 2dBi

Frequency	Conducted Peak Power (dBm)	Maximum ERP/EIRP (W)	Maximum ERP/EIRP Limit (W)	Duty Cycle (%)	Conducted Average Power (dBm)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm ²)	Limit (mW/cm ²)	Pass/Fail
1717.5	23.68	0.370	1	100	23.68	233.3	0.0736	1.00	Pass
1732.5	24.03	0.401	1	100	24.03	252.9	0.0797	1.00	Pass
1747.5	24.27	0.424	1	100	24.27	267.3	0.0843	1.00	Pass

LTE Band 13 -Peak Gain: 2dBi

Frequency	Conducted Peak Power (dBm)	Maximum ERP/EIRP (W)	Maximum ERP/EIRP Limit (W)	Duty Cycle (%)	Conducted Average Power (dBm)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm ²)	Limit (mW/cm ²)	Pass/Fail
779.5	23.20	0.202	5	100	23.20	208.9	0.0659	0.52	Pass
782.0	23.14	0.199	5	100	23.14	206.1	0.0650	0.52	Pass
784.5	23.15	0.200	5	100	23.15	206.5	0.0651	0.52	Pass

Note: The conducted output power is refer to report No.: 1690025R-HPUSP41V00 from the Quietek.

2.4. Maximum Antenna Gain Evaluation (Reference Only)

Mode	Frequency	Conducted Peak Power (dBm)	Maximum tune up Power (dBm)	Max Gain to comply with ERP/EIRP		Max Gain to comply with MPE		
				Antenna Gain(dBi)	Maximum ERP/EIRP Limit (W)	Antenna Gain(dBi)	Distance (cm)	Limit (mW/cm ²)
LTE Band 4	1717.5	23.68	25.00	5	1	12.01	20	1.00
	1732.5	24.03	25.00	5	1	12.01	20	1.00
	1747.5	24.27	25.00	5	1	12.01	20	1.00

Note: In order to comply with both ERP/EIRP and Maximum Permissible Exposure limit, the maximum antenna gain shall not be greater than 5 dBi in LTE Band 4.

Mode	Frequency	Conducted Peak Power (dBm)	Maximum tune up Power (dBm)	Max Gain to comply with ERP/EIRP		Max Gain to comply with MPE		
				Antenna Gain(dBi)	Maximum ERP/EIRP Limit (W)	Antenna Gain(dBi)	Distance (cm)	Limit (mW/cm ²)
LTE Band 13	779.5	23.20	25.00	11.99	5	9.17	20	0.52
	782.0	23.14	25.00	11.99	5	9.18	20	0.52
	784.5	23.15	25.00	11.99	5	9.20	20	0.52

Note: In order to comply with both ERP/EIRP and Maximum Permissible Exposure limit, the maximum antenna gain shall not be greater than 9.17 dBi in LTE Band 13.