


FCC RF Test Report

APPLICANT : Sierra Wireless
EQUIPMENT : multi-band radio module
BRAND NAME : Sierra Wireless
MODEL NAME : MC8201
FCC ID : N7NMC8201
STANDARD : FCC 47 CFR Part 2, 22(H), 24(E)
CLASSIFICATION : PCS Licensed Transmitter (PCB)
TX/RX FREQUENCY RANGE : GSM850 : 824.2 ~ 848.8 MHz /
869.2 ~ 893.8 MHz
GSM1900 : 1850.2 ~ 1909.8 MHz /
1930.2 ~ 1989.8 MHz
WCDMA Band V : 826.4 ~ 846.6 MHz /
871.4 ~ 891.6 MHz
WCDMA Band II : 1852.4 ~ 1907.6 MHz /
1932.4 ~ 1987.6 MHz
MAXIMUM OUTPUT POWER : GSM850 : 32.10 dBm
GSM1900 : 28.40 dBm
WCDMA Band V : 22.22 dBm
WCDMA Band II : 21.85 dBm
EMISSION DESIGNATOR : GMSK : 248KGXW
8PSK : 248KG7W
QPSK : 4M18F9W

The product was received on Dec. 16, 2009 and completely tested on Feb. 25, 2010. We, SPORTON INTERNATIONAL (KUNSHAN) INC., would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI / TIA / EIA-603-C-2004 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL (KUNSHAN) INC., the test report shall not be reproduced except in full.

Reviewed by:



Roy Wu / Manager



SPORTON INTERNATIONAL (KUNSHAN) INC.

No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P.R.C.



TABLE OF CONTENTS

REVISION HISTORY 3

SUMMARY OF TEST RESULT 4

1 GENERAL DESCRIPTION 5

 1.1 Applicant..... 5

 1.2 Manufacturer 5

 1.3 Feature of Equipment Under Test..... 6

 1.4 Testing Site..... 7

 1.5 Applied Standards 7

 1.6 Ancillary Equipment List 7

2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST 8

 2.1 Test Mode..... 8

 2.2 Connection Diagram of Test System 9

3 TEST RESULT 10

 3.1 Conducted Output Power Measurement 10

 3.2 Occupied Bandwidth Measurement 12

 3.3 Band Edge Measurement..... 25

 3.4 Conducted Emission Measurement 38

 3.5 Field Strength of Spurious Radiation Measurement 54

 3.6 Frequency Stability Measurement..... 68

4 LIST OF MEASURING EQUIPMENT 72

5 UNCERTAINTY OF EVALUATION 73



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FG9D1629	Rev. 01	Initial issue of report	Feb. 11, 2010
FG9D1629	Rev. 02	Update report for revising GSM850 conducted power	Feb. 25, 2010



SUMMARY OF TEST RESULT

Report Section	FCC Rule	IC Rule	Description	Limit	Result	Remark
3.1	§2.1046	N/A	Conducted Output Power	N/A	PASS	
3.2	§2.1049 §22.917(a) §24.238(a)	N/A	Occupied Bandwidth	N/A	PASS	-
3.3	§2.1051 §22.917(a) §24.238(a)	RSS-132 (4.5.1) RSS-133 (6.5.1)	Band Edge Measurement	$< 43+10\log_{10}(P[\text{Watts}])$	PASS	-
3.4	§2.1051 §22.917(a) §24.238(a)	RSS-132 (4.5.1) RSS-133 (6.5.1)	Conducted Emission	$< 43+10\log_{10}(P[\text{Watts}])$	PASS	-
3.5	§2.1053 §22.917(a) §24.238(a)	RSS-132 (4.5.1) RSS-133 (6.5.1)	Field Strength of Spurious Radiation	$< 43+10\log_{10}(P[\text{Watts}])$	PASS	Under limit 12.68 dB at 1674 MHz
3.6	§2.1055 §22.355 §24.235	RSS-132(4.3) RSS-133(6.3)	Frequency Stability for Temperature & Voltage	$< 2.5 \text{ ppm}$	PASS	-



1 General Description

1.1 Applicant

Sierra Wireless

13811 Wireless Way, Richmond, BC V6V 3A4

1.2 Manufacturer

Sierra Wireless

13811 Wireless Way, Richmond, BC V6V 3A4

1.3 Feature of Equipment Under Test

Product Feature & Specification	
Equipment	multi-band radio module
Brand Name	Sierra Wireless
Model Name	MC8201
FCC ID	N7NMC8201
Tx Frequency	GSM850 : 824 MHz ~ 849 MHz GSM1900 : 1850 MHz ~ 1910 MHz WCDMA Band V : 824 MHz ~ 849 MHz WCDMA Band II : 1850 MHz ~ 1910 MHz
Rx Frequency	GSM850 : 869 MHz ~ 894 MHz GSM1900 : 1930 MHz ~ 1990 MHz WCDMA Band V : 869 MHz ~ 894 MHz WCDMA Band II : 1930 MHz ~ 1990 MHz
Maximum Output Power to Antenna	GSM850 : 32.10 dBm GSM1900 : 28.40 dBm WCDMA Band V : 22.22 dBm WCDMA Band II : 21.85 dBm
HW Version	1.0
SW Version	L2_0_0_16
Type of Modulation	GSM / GPRS : GMSK EDGE : 8PSK WCDMA : QPSK HSDPA : QPSK / 16QAM
Type of Emission	GMSK : 248KGXW 8PSK : 248KG7W QPSK : 4M18F9W
EUT Stage	Identical Prototype

Remark:

1. This test report recorded only product characteristics and test results of PCS Licensed Transmitter (PCB).
2. The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.4 Testing Site

Test Site	SPORTON INTERNATIONAL (KUNSHAN) INC.
Test Site Location	No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P.R.C. TEL: +86-0512-5790-0158 FAX: +86-0512-5790-0958
Test Site No.	Sporton Site No. TH01-KS ; 03CH01-KS

1.5 Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- Preliminary Guidance for Receiving Applications for Certification of 3G Device. May 9, 2006.
- FCC 47 CFR Part 2, 22(H), 24(E)
- ANSI / TIA / EIA-603-C-2004
- IC RSS-132 Issue 2
- IC RSS-133 Issue 5

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B (DoC), recorded in a separate test report.

1.6 Ancillary Equipment List

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord
1.	System Simulator	R&S	CMU200	N/A	N/A	Unshielded, 1.8 m
2.	DC Power Supply	GW	GPC-60300	N/A	N/A	Unshielded, 1.8 m
3.	Dipole Antenna	N/A	N/A	N/A	N/A	N/A

2 Test Configuration of Equipment Under Test

2.1 Test Mode

During all testing, EUT is in link mode with base station emulator at maximum power level. The spurious emission measurements were carried out in semi-anechoic chamber with 3-meter test range.

Frequency range investigated for radiated emission is as follows:

1. 30 MHz to 9000 MHz for GSM850 and WCDMA Band V.
2. 30 MHz to 19000 MHz for GSM1900 and WCDMA Band II.

Test Modes		
Band	Radiated TCs	Conducted TCs
GSM 850	<ul style="list-style-type: none"> ■ GSM Link ■ EDGE 8 Link 	<ul style="list-style-type: none"> ■ GSM Link ■ EDGE 8 Link
GSM 1900	<ul style="list-style-type: none"> ■ GSM Link ■ EDGE 8 Link 	<ul style="list-style-type: none"> ■ GSM Link ■ EDGE 8 Link
WCDMA Band V	<ul style="list-style-type: none"> ■ RMC 12.2Kbps Link 	<ul style="list-style-type: none"> ■ RMC 12.2Kbps Link
WCDMA Band II	<ul style="list-style-type: none"> ■ RMC 12.2Kbps Link 	<ul style="list-style-type: none"> ■ RMC 12.2Kbps Link


Note: The maximum power levels are GSM mode for GMSK link, EDGE multi-slot class 8 mode for 8PSK link, and RMC 12.2Kbps mode for WCDMA band V and WCDMA band II, only these modes were used for all tests.

The conducted power tables are as follows:

Conducted Power (*Unit: dBm)						
Band	GSM850			GSM1900		
Channel	128	189	251	512	661	810
Frequency	824.2	836.4	848.8	1850.2	1880.0	1909.8
GSM	32.10	32.10	32.10	28.40	28.20	28.10
GPRS 8	32.10	32.10	32.10	28.30	28.20	28.10
GPRS 10	31.90	32.00	31.90	28.10	28.00	27.90
GPRS 12	31.90	31.90	31.90	28.10	28.00	27.90
EGPRS 8	27.40	27.50	27.50	25.40	25.20	25.10
EGPRS 10	27.40	27.40	27.50	25.40	25.20	25.10
EGPRS 12	27.40	27.40	27.40	25.40	25.20	25.10

Conducted Power (*Unit: dBm)						
Band	WCDMA Band V			WCDMA Band II		
Channel	4132	4182	4233	9262	9400	9538
Frequency	826.4	836.4	846.6	1852.4	1880.0	1907.6
RMC 12.2K	22.22	21.97	21.93	21.85	21.78	21.56
HSDPA Subtest-1	22.17	21.67	22.07	21.72	21.66	21.42
HSDPA Subtest-2	21.84	21.38	21.60	21.47	21.44	21.20
HSDPA Subtest-3	21.33	20.95	21.15	21.05	20.99	20.94
HSDPA Subtest-4	21.09	20.62	20.79	20.75	20.71	20.71

2.2 Connection Diagram of Test System



3 Test Result

3.1 Conducted Output Power Measurement

3.1.1 Description of the Conducted Output Power Measurement

A base station simulator was used to establish communication with the EUT. Its parameters were set to transmit the maximum power on the EUT. The measured power in the radio frequency on the transmitter output terminals shall be reported.


3.1.2 Measuring Instruments

See list of measuring instruments of this test report.

3.1.3 Test Procedures

1. The transmitter output port was connected to base station.
2. Set EUT at maximum power through base station.
3. Select lowest, middle, and highest channels for each band and different modulation.

3.1.4 Test Setup



3.1.5 Test Result of Conducted Output Power

Cellular Band				
Modes	Channel	Frequency (MHz)	Conducted Power (dBm)	Conducted Power (Watts)
GSM850 (GSM)	128 (Low)	824.2	32.10	1.62
	189 (Mid)	836.4	32.10	1.62
	251 (High)	848.8	32.10	1.62
GSM850 (EDGE 8)	128 (Low)	824.2	27.40	0.55
	189 (Mid)	836.4	27.50	0.56
	251 (High)	848.8	27.50	0.56
WCDMA Band V (RMC 12.2Kbps)	4132 (Low)	826.4	22.22	0.17
	4182 (Mid)	836.4	21.97	0.16
	4233 (High)	846.6	21.93	0.16

PCS Band				
Modes	Channel	Frequency (MHz)	Conducted Power (dBm)	Conducted Power (Watts)
GSM1900 (GSM)	512 (Low)	1850.2	28.40	0.69
	661 (Mid)	1880.0	28.20	0.66
	810 (High)	1909.8	28.10	0.65
GSM1900 (EDGE 8)	512 (Low)	1850.2	25.40	0.35
	661 (Mid)	1880.0	25.20	0.33
	810 (High)	1909.8	25.10	0.32
WCDMA Band II (RMC 12.2Kbps)	9262 (Low)	1852.4	21.85	0.15
	9400 (Mid)	1880.0	21.78	0.15
	9538 (High)	1907.6	21.56	0.14

3.2 Occupied Bandwidth Measurement

3.2.1 Description of Occupied Bandwidth Measurement

The emission bandwidth is defined as the width of the signal between two points, located at the 2 sides of the carrier frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.


3.2.2 Measuring Instruments

See list of measuring instruments of this test report.

3.2.3 Test Procedures

1. The EUT was connected to Spectrum Analyzer and Base Station via power divider.
2. The 99% and 26 dB occupied bandwidth (BW) of the middle channel for the highest RF powers were measured.


3.2.4 Test Setup




3.2.5 Test Result (Plots) of Occupied Bandwidth

Band :	GSM 850	Power Stage :	High
Test Mode :	GSM Link		

99% Occupied Bandwidth Plot on Channel 189




Date: 2.FEB.2010 04:52:15



Date: 2.FEB.2010 04:58:00



26dB Bandwidth Plot on Channel 189




Date: 2.FEB.2010 04:46:47




Band :	GSM 850	Power Stage :	High
Test Mode :	EDGE 8 Link		

99% Occupied Bandwidth Plot on Channel 189




Date: 2.FEB.2010 06:45:56



Date: 2.FEB.2010 06:51:42



26dB Bandwidth Plot on Channel 189




Date: 2.FEB.2010 06:37:56




Band :	GSM 1900	Power Stage :	High
Test Mode :	GSM Link		

99% Occupied Bandwidth Plot on Channel 661




Date: 2.FEB.2010 05:15:59



Date: 2.FEB.2010 06:23:57



26dB Bandwidth Plot on Channel 661




Date: 2.FEB.2010 05:10:07




Band :	GSM 1900	Power Stage :	High
Test Mode :	EDGE 8 Link		

99% Occupied Bandwidth Plot on Channel 661




Date: 2.FEB.2010 07:16:35



Date: 2.FEB.2010 07:22:49



26dB Bandwidth Plot on Channel 661




Date: 3.FEB.2010 04:33:43




Band :	WCDMA Band V	Power Stage :	High
Test Mode :	RMC 12.2Kbps Link		

99% Occupied Bandwidth Plot on Channel 4182




Date: 2.FEB.2010 10:02:49



Date: 2.FEB.2010 10:16:57



26dB Bandwidth Plot on Channel 4182




Date: 2.FEB.2010 09:58:40




Band :	WCDMA Band II	Power Stage :	High
Test Mode :	RMC 12.2Kbps Link		

99% Occupied Bandwidth Plot on Channel 9400




Date: 2.FEB.2010 09:23:04



Date: 2.FEB.2010 09:46:53



26dB Bandwidth Plot on Channel 9400



Date: 2.FEB.2010 09:19:17

3.3 Band Edge Measurement

3.3.1 Description of Band Edge Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.

3.3.2 Measuring Instruments


See list of measuring instruments of this test report.

3.3.3 Test Procedures

1. The EUT was connected to Spectrum Analyzer and Base Station via power divider.
2. The band edges of low and high channels for the highest RF powers were measured. Setting RBW as roughly BW/100.

3.3.4 Test Setup

<Conducted Band Edge >







3.3.5 Test Result (Plots) of Conducted Band Edge

Band :	GSM850	Power Stage :	High
Test Mode :	GSM Link		

Lower Band Edge Plot on Channel 128




Date: 2.FEB.2010 04:49:49




Date: 2.FEB.2010 04:56:45



Higher Band Edge Plot on Channel 251



Date: 2.FEB.2010 04:48:55




Date: 2.FEB.2010 04:55:49




Band :	GSM850	Power Stage :	High
Test Mode :	EDGE 8 Link		

Lower Band Edge Plot on Channel 128




Date: 2.FEB.2010 06:42:23




Date: 2.FEB.2010 06:49:43



Higher Band Edge Plot on Channel 251



Date: 2.FEB.2010 06:41:34




Date: 2.FEB.2010 06:48:54




Band :	GSM1900	Power Stage :	High
Test Mode :	GSM Link		

Lower Band Edge Plot on Channel 512




Date: 2.FEB.2010 05:13:39




Date: 2.FEB.2010 06:22:55



Higher Band Edge Plot on Channel 810



Date: 2.FEB.2010 05:12:33




Date: 2.FEB.2010 06:22:24




Band :	GSM1900	Power Stage :	High
Test Mode :	EDGE 8 Link		

Lower Band Edge Plot on Channel 512




Date: 2.FEB.2010 07:13:59




Date: 2.FEB.2010 07:21:33



Higher Band Edge Plot on Channel 810



Date: 2.FEB.2010 07:12:00




Date: 2.FEB.2010 07:20:43




Band :	WCDMA Band V	Power Stage :	High
Test Mode :	RMC 12.2Kbps Link		

Lower Band Edge Plot on Channel 4132




Date: 2.FEB.2010 10:00:36




Date: 2.FEB.2010 10:11:53



Higher Band Edge Plot on Channel 4233



Date: 2.FEB.2010 10:00:08




Date: 2.FEB.2010 10:11:21




Band :	WCDMA Band II	Power Stage :	High
Test Mode :	RMC 12.2Kbps Link		

Lower Band Edge Plot on Channel 9262




Date: 2.FEB.2010 09:21:04




Date: 2.FEB.2010 09:39:43



Higher Band Edge Plot on Channel 9538



Date: 2.FEB.2010 09:21:30



Date: 2.FEB.2010 09:39:13

3.4 Conducted Emission Measurement

3.4.1 Description of Conducted Emission Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.

It is measured by means of a calibrated spectrum analyzer and scanned from 30 MHz up to a frequency including its 10th harmonic.


3.4.2 Measuring Instruments

See list of measuring instruments of this test report.

3.4.3 Test Procedures

1. The EUT was connected to spectrum analyzer and base station via power divider.
2. The middle channel for the highest RF power within the transmitting frequency was measured.
3. The conducted spurious emission for the whole frequency range was taken.


3.4.4 Test Setup



3.4.5 Test Result (Plots) of Conducted Emission


Band :	GSM850	Channel :	CH189
Test Mode :	GSM Link		

Conducted Emission Plot between 30MHz ~ 1GHz



Date: 2.FEB.2010 05:00:45


Conducted Emission Plot between 1GHz ~ 3GHz



Date: 2.FEB.2010 05:02:25




Conducted Emission Plot between 3GHz ~ 7GHz



Date: 2.FEB.2010 05:04:58

Conducted Emission Plot between 7GHz ~ 9GHz




Date: 2.FEB.2010 05:05:48




Band :	GSM850	Channel :	CH189
Test Mode :	EDGE 8 Link		

Conducted Emission Plot between 30MHz ~ 1GHz



Date: 2.FEB.2010 06:54:36


Conducted Emission Plot between 1GHz ~ 3GHz



Date: 2.FEB.2010 06:57:02




Conducted Emission Plot between 3GHz ~ 7GHz



Date: 2.FEB.2010 06:58:07

Conducted Emission Plot between 7GHz ~ 9GHz




Date: 2.FEB.2010 07:00:05




Band :	GSM1900	Channel :	CH661
Test Mode :	GSM Link		

Conducted Emission Plot between 30MHz ~ 1GHz



Date: 2.FEB.2010 06:25:23


Conducted Emission Plot between 1GHz ~ 3GHz



Date: 2.FEB.2010 06:26:56




Conducted Emission Plot between 3GHz ~ 7GHz



Date: 2.FEB.2010 06:29:23


Conducted Emission Plot between 7GHz ~ 13.6GHz



Date: 2.FEB.2010 06:30:37



Conducted Emission Plot between 13.6GHz ~ 19.1GHz




Date: 2.FEB.2010 06:31:40




Band :	GSM1900	Channel :	CH661
Test Mode :	EDGE 8 Link		

Conducted Emission Plot between 30MHz ~ 1GHz



Date: 2.FEB.2010 07:24:33


Conducted Emission Plot between 1GHz ~ 3GHz



Date: 2.FEB.2010 07:25:28




Conducted Emission Plot between 3GHz ~ 7GHz



Date: 2.FEB.2010 07:27:18


Conducted Emission Plot between 7GHz ~ 13.6GHz



Date: 2.FEB.2010 07:28:44



Conducted Emission Plot between 13.6GHz ~ 19.1GHz




Date: 2.FEB.2010 07:29:51




Band :	WCDMA Band V	Channel :	CH4182
Test Mode :	RMC 12.2Kbps Link		

Conducted Emission Plot between 30MHz ~ 1GHz



Date: 2.FEB.2010 10:19:00


Conducted Emission Plot between 1GHz ~ 3GHz



Date: 2.FEB.2010 10:20:35




Conducted Emission Plot between 3GHz ~ 7GHz



Date: 2.FEB.2010 10:21:23

Conducted Emission Plot between 7GHz ~ 9GHz




Date: 2.FEB.2010 10:22:08




Band :	WCDMA Band II	Channel :	CH9400
Test Mode :	RMC 12.2Kbps Link		

Conducted Emission Plot between 30MHz ~ 1GHz



Date: 2.FEB.2010 09:48:31


Conducted Emission Plot between 1GHz ~ 3GHz



Date: 11.FEB.2010 10:17:47




Conducted Emission Plot between 3GHz ~ 7GHz



Date: 2.FEB.2010 09:52:15


Conducted Emission Plot between 7GHz ~ 13.6GHz



Date: 2.FEB.2010 09:52:54



Conducted Emission Plot between 13.6GHz ~ 19.1GHz



Date: 2.FEB.2010 09:53:43

3.5 Field Strength of Spurious Radiation Measurement

3.5.1 Description of Field Strength of Spurious Radiated Measurement

The radiated spurious emission was measured by substitution method according to ANSI / TIA / EIA-603-C-2004. The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.


3.5.2 Measuring Instruments

See list of measuring instruments of this test report.

3.5.3 Test Procedures

1. The EUT was placed on a rotatable wooden table with 0.8 meter about ground.
2. The EUT was set 3 meters from the receiving antenna, which was mounted on the antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest spurious emission.
4. The height of the receiving antenna is varied between one meter and four meters to search the maximum spurious emission for both horizontal and vertical polarizations.
5. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, Sweep = 500ms, Taking the record of maximum spurious emission.
6. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
7. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
8. Taking the record of output power at antenna port.
9. Repeat step 7 to step 8 for another polarization.
10. $EIRP \text{ (dBm)} = S.G. \text{ Power} - Tx \text{ Cable Loss} + Tx \text{ Antenna Gain}$
11. $ERP \text{ (dBm)} = EIRP - 2.15$


3.5.4 Test Setup





3.5.5 Test Result of Field Strength of Spurious Radiated

Band :	GSM850	Temperature :	23~24°C
Test Mode :	GSM Link	Relative Humidity :	44~45%
Test Engineer :	Harvey Tang	Polarization :	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH01-KS
 Condition: FCC PART22 24 HF EIRP FACTOR-09020 HORIZONTAL

Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1674	-42.14	-13	-29.14	-42.15	-42.79	0.57	3.37	H	Pass
2508	-40.27	-13	-27.27	-44.40	-42.50	0.78	5.16	H	Pass
3344	-52.47	-13	-39.47	-54.35	-56.11	0.87	6.66	H	Pass
4178	-54.96	-13	-41.96	-57.72	-59.55	0.97	7.71	H	Pass



Band :	GSM850	Temperature :	23~24°C
Test Mode :	GSM Link	Relative Humidity :	44~45%
Test Engineer :	Harvey Tang	Polarization :	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH01-KS
 Condition: FCC PART22 24 HF EIRP FACIOR-09020 VERTICAL

Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1674	-25.68	-13	-12.68	-32.02	-26.33	0.57	3.37	V	Pass
2510	-32.32	-13	-19.32	-39.22	-34.55	0.78	5.16	V	Pass
4178	-52.10	-13	-39.10	-56.40	-56.69	0.97	7.71	V	Pass
5854	-50.06	-13	-37.06	-58.26	-56.50	1.22	9.81	V	Pass



Band :	GSM850	Temperature :	23~24°C
Test Mode :	EDGE 8 Link	Relative Humidity :	44~45%
Test Engineer :	Harvey Tang	Polarization :	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH01-KS
 Condition: FCC PART22 24 HF EIRP FACTOR-09020 HORIZONTAL

Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1674	-45.78	-13	-32.78	-45.18	-46.43	0.57	3.37	H	Pass
2508	-46.31	-13	-33.31	-49.35	-48.54	0.78	5.16	H	Pass



Band :	GSM850	Temperature :	23~24°C
Test Mode :	EDGE 8 Link	Relative Humidity :	44~45%
Test Engineer :	Harvey Tang	Polarization :	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH01-KS
 Condition: FCC PART22 24 HF EIRP FACTOR-09020 VERTICAL

Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1674	-30.73	-13	-17.73	-37.14	-31.38	0.57	3.37	V	Pass
2508	-36.51	-13	-23.51	-43.06	-38.74	0.78	5.16	V	Pass



Band :	GSM1900	Temperature :	23~24°C
Test Mode :	GSM Link	Relative Humidity :	44~45%
Test Engineer :	Harvey Tang	Polarization :	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH01-KS
 Condition: FCC PART22 24 HF EIRP FACTOR-09020 HORIZONTAL

Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3758	-54.70	-13	-41.70	-55.81	-61.08	0.78	7.16	H	Pass
5642	-54.59	-13	-41.59	-59.72	-63.13	1.04	9.58	H	Pass
9401	-54.76	-13	-41.76	-58.22	-65.82	1.75	12.81	H	Pass
13157	-34.86	-13	-21.86	-56.32	-46.57	2.04	13.75	H	Pass



Band :	GSM1900	Temperature :	23~24°C
Test Mode :	GSM Link	Relative Humidity :	44~45%
Test Engineer :	Harvey Tang	Polarization :	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH01-KS
 Condition: FCC PART22 24 HF EIRP FACIOR-09020 VERTICAL

Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3758	-52.72	-13	-39.72	-55.95	-59.10	0.78	7.16	V	Pass
5636	-53.18	-13	-40.18	-58.28	-61.72	1.04	9.58	V	Pass
9401	-56.97	-13	-43.97	-58.21	-68.03	1.75	12.81	V	Pass
11276	-43.05	-13	-30.05	-58.15	-54.14	2	13.09	V	Pass
13157	-45.41	-13	-32.41	-58.23	-57.12	2.04	13.75	V	Pass
16916	-43.4	-13	-30.40	-58.87	-54.50	1.94	13.04	V	Pass



Band :	GSM1900	Temperature :	23~24°C
Test Mode :	EDGE 8 Link	Relative Humidity :	44~45%
Test Engineer :	Harvey Tang	Polarization :	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH01-KS
 Condition: FCC PART22 24 HF EIRP FACTOR-09020 HORIZONTAL

Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3758	-54.54	-13	-41.54	-55.72	-60.92	0.78	7.16	H	Pass
13157	-38.54	-13	-25.54	-57.95	-50.25	2.04	13.75	H	Pass



Band :	GSM1900	Temperature :	23~24°C
Test Mode :	EDGE 8 Link	Relative Humidity :	44~45%
Test Engineer :	Harvey Tang	Polarization :	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH01-KS
 Condition: FCC PART22 24 HF EIRP FACTOR-09020 VERTICAL

Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3758	-50.42	-13	-37.42	-54.39	-56.80	0.78	7.16	V	Pass
5636	-36.82	-13	-23.82	-49.54	-45.36	1.04	9.58	V	Pass
11276	-44.41	-13	-31.41	-59.28	-55.50	2	13.09	V	Pass
13157	-48.57	-13	-35.57	-59.93	-60.28	2.04	13.75	V	Pass
16916	-37.22	-13	-24.22	-58.07	-48.32	1.94	13.04	V	Pass



Band :	WCDMA Band V	Temperature :	23~24°C
Test Mode :	RMC 12.2Kbps Link	Relative Humidity :	44~45%
Test Engineer :	Harvey Tang	Polarization :	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH01-KS
 Condition: FCC PART22 24 HF EIRP FACIOR-09020 HORIZONTAL

Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1668	-48.18	-13	-35.18	-42.26	-48.83	0.57	3.37	H	Pass



Band :	WCDMA Band V	Temperature :	23~24°C
Test Mode :	RMC 12.2Kbps Link	Relative Humidity :	44~45%
Test Engineer :	Harvey Tang	Polarization :	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH01-KS
 Condition: FCC PART22 24 HF EIRP FACIOR-09020 VERTICAL

Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1668	-47.76	-13	-34.76	-43.15	-48.41	0.57	3.37	V	Pass



Band :	WCDMA Band II	Temperature :	23~24°C
Test Mode :	RMC 12.2Kbps Link	Relative Humidity :	44~45%
Test Engineer :	Harvey Tang	Polarization :	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH01-KS
 Condition: FCC PART22 24 HF EIRP FACIOR-09020 HORIZONTAL

Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
5642	-49.55	-13	-36.55	-56.49	-58.09	1.04	9.58	H	Pass



Band :	WCDMA Band II	Temperature :	23~24°C
Test Mode :	RMC 12.2Kbps Link	Relative Humidity :	44~45%
Test Engineer :	Harvey Tang	Polarization :	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Site : 03CH01-KS
 Condition: FCC PART22 24 HF EIRP FACTOR-09020 VERTICAL

Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
5642	-41.86	-13	-28.86	-52.35	-50.40	1.04	9.58	V	Pass

3.6 Frequency Stability Measurement

3.6.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within $\pm 0.00025\%$ ($\pm 2.5\text{ppm}$) of the center frequency.

3.6.2 Measuring Instruments

See list of measuring instruments of this test report.


3.6.3 Test Procedures for Temperature Variation

1. The EUT was set up in the thermal chamber and connected with the base station.
2. With power OFF, the temperature was decreased to -30°C and the EUT was stabilized for three hours. Power was applied and the maximum change in frequency was recorded within one minute.
3. With power OFF, the temperature was raised in 10°C step up to 50°C . The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.
4. If the EUT can not be turned on at -30°C , the testing lowest temperature will be raised in 10°C step until the EUT can be turned on.

3.6.4 Test Procedures for Voltage Variation

1. The EUT was placed in a temperature chamber at $25\pm 5^{\circ}\text{C}$ and connected with the base station.
2. The power supply voltage to the EUT was varied from BEP to 115% of the nominal value measured at the input to the EUT.
3. The variation in frequency was measured for the worst case.

3.6.5 Test Setup



3.6.6 Test Result of Temperature Variation

Band :	GSM 850	Channel :	189
Limit (ppm) :	2.5		

Temperature (°C)	GSM		EDGE 8		Result
	Freq. Dev. (Hz)	Deviation (ppm)	Freq. Dev. (Hz)	Deviation (ppm)	
-30	N/A	N/A	N/A	N/A	PASS
-20	-23	-0.03	45	0.05	
-10	-39	-0.05	-37	-0.04	
0	-38	-0.04	36	0.04	
10	-32	-0.04	34	0.04	
20	-50	-0.06	34	0.04	
30	-27	-0.03	24	0.03	
40	-34	-0.04	32	0.04	
50	-36	-0.04	-62	-0.07	

Note: The manufacturer declared that the EUT could work properly between temperatures -20°C~55°C.

Band :	GSM 1900	Channel :	661
Limit (ppm) :	2.5		

Temperature (°C)	GSM		EDGE 8		Result
	Freq. Dev. (Hz)	Deviation (ppm)	Freq. Dev. (Hz)	Deviation (ppm)	
-30	N/A	N/A	N/A	N/A	PASS
-20	-45	-0.02	49	0.03	
-10	-68	-0.04	-70	-0.04	
0	-64	-0.03	31	0.02	
10	-86	-0.05	47	0.02	
20	-68	-0.04	-40	-0.02	
30	-69	-0.04	29	0.02	
40	-53	-0.03	-35	-0.02	
50	-61	-0.03	-88	-0.05	

Note: The manufacturer declared that the EUT could work properly between temperatures -20°C~55°C.



Band :	WCDMA Band V	Channel :	4182
Limit (ppm) :	2.5		

Temperature (°C)	RMC 12.2Kbps		Result
	Freq. Dev. (Hz)	Deviation (ppm)	
-30	N/A	N/A	PASS
-20	-24	-0.03	
-10	-25	-0.03	
0	-22	-0.03	
10	18	0.02	
20	-21	-0.02	
30	-25	-0.03	
40	-24	-0.03	
50	-28	-0.03	

Note: The manufacturer declared that the EUT could work properly between temperatures -20°C~55°C.

Band :	WCDMA Band II	Channel :	9400
Limit (ppm) :	2.5		

Temperature (°C)	RMC 12.2Kbps		Result
	Freq. Dev. (Hz)	Deviation (ppm)	
-30	N/A	N/A	PASS
-20	-26	-0.01	
-10	-25	-0.01	
0	23	0.01	
10	-18	-0.01	
20	-29	-0.02	
30	-27	-0.01	
40	-31	-0.02	
50	-32	-0.02	

Note: The manufacturer declared that the EUT could work properly between temperatures -20°C~55°C.



3.6.7 Test Result of Voltage Variation

Band & Channel	Mode	Voltage (Volt)	Freq. Dev. (Hz)	Deviation (ppm)	Limit (ppm)	Result
GSM 850 CH189	GSM	3.8	-29	-0.03	2.5	PASS
		3.4	15	0.02		
		4.2	-28	-0.03		
	EDGE 8	3.8	-41	-0.05		
		3.4	-23	-0.03		
		4.2	29	0.03		
GSM 1900 CH661	GSM	3.8	-57	-0.03		
		3.4	-59	-0.03		
		4.2	-61	-0.03		
	EDGE 8	3.8	-53	-0.03		
		3.4	-32	-0.02		
		4.2	-41	-0.02		
WCDMA Band V CH4182	RMC 12.2Kbps	3.8	16	0.02		
		3.4	25	0.03		
		4.2	-17	-0.02		
WCDMA Band II CH9400	RMC 12.2Kbps	3.8	-25	-0.01		
		3.4	35	0.02		
		4.2	-28	-0.01		



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Due Date	Remark
Spectrum Analyzer	R&S	FSP40	100319	9kHz~40GHz	Jan. 18, 2010	Jan. 17, 2011	Conducted (TH01-KS)
Thermal Chamber	Ten Billion	TTC-B3S	TBN-960502	N/A	Dec. 28, 2009	Dec. 27, 2010	Conducted (TH01-KS)
EMI Test Receiver	R&S	ESCI	100724	9kHz – 2.75GHz	Mar. 04, 2009	Mar. 03, 2010	Radiation (03CH01-KS)
Spectrum Analyzer	R&S	FSP40	100319	9kHz~40GHz	Jan. 18, 2010	Jan. 17, 2011	Radiation (03CH01-KS)
Bilog Antenna	SCHAFFNER	CBL6112D	23182	25MHz~2GHz	Jan. 18, 2010	Jan. 17, 2011	Radiation (03CH01-KS)
Double Ridge Horn Antenna	EMCO	3117	75959	1GHz~18GHz	Jan. 18, 2010	Jan. 17, 2011	Radiation (03CH01-KS)
Amplifier	Wireless	FPA6592G	60004	30MHz~2GHz	Dec. 16, 2009	Dec. 15, 2010	Radiation (03CH01-KS)
Amplifier	Agilent	8449B	3008A02370	1GHz~26.5GHz	Jan. 18, 2010	Jan. 17, 2011	Radiation (03CH01-KS)
active horn antenna	com-power	AHA-118	701023	1G-18GHz	Nov. 18, 2009	Nov. 17, 2010	Radiation (03CH01-KS)
Signal Generator	R&S	SMR40	100455	10MHz~40GHz	Jan. 18, 2010	Jan. 17, 2011	Radiation (03CH01-KS)
SHF-EHF Horn	Schwarzbeck	BBHA 9170	BBHA170249	15-40GHz	Oct. 22, 2009	Oct. 21, 2010	Radiation (03CH01-KS)
System Simulator	R&S	CMU200	837587/066	Full-Band	Jan. 08, 2009	Jan. 07, 2011	Radiation (03CH01-KS)

5 Uncertainty of Evaluation

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Contribution	Uncertainty of X_i		$u(X_i)$
	dB	Probability Distribution	
Receiver Reading	0.41	Normal (k=2)	0.21
Antenna Factor Calibration	0.83	Normal (k=2)	0.42
Cable Loss Calibration	0.25	Normal (k=2)	0.13
Pre-Amplifier Gain Calibration	0.27	Normal (k=2)	0.14
RCV/SPA Specification	2.50	Rectangular	0.72
Antenna Factor Interpolation for Frequency	1.00	Rectangular	0.29
Site Imperfection	1.43	Rectangular	0.83
Mismatch	+0.39 / -0.41	U-Shape	0.28
Combined Standard Uncertainty $Uc(y)$	1.27		
Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.54		

Uncertainty of Radiated Emission Measurement (1 GHz ~ 40 GHz)

Contribution	Uncertainty of X_i		$u(X_i)$	C_i	$C_i * u(X_i)$
	dB	Probability Distribution			
Receiver Reading	± 0.10	Normal (k=2)	0.10	1	0.10
Antenna Factor Calibration	± 1.70	Normal (k=2)	0.85	1	0.85
Cable Loss Calibration	± 0.50	Normal (k=2)	0.25	1	0.25
Receiver Correction	± 2.00	Rectangular	1.15	1	1.15
Antenna Factor Directional	± 1.50	Rectangular	0.87	1	0.87
Site Imperfection	± 2.80	Triangular	1.14	1	1.14
Mismatch Receiver VSWR $\Gamma_1 = 0.197$ Antenna VSWR $\Gamma_2 = 0.194$ Uncertainty = $20\text{Log}(1-\Gamma_1*\Gamma_2)$	+0.34 / -0.35	U-Shape	0.244	1	0.244
Combined Standard Uncertainty $Uc(y)$	2.36				
Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.72				