

Co-Located RF Exposure Condition

FCC ID: N7NMC8781-F (IC ID: 2417C-MC8781)
with
FCC ID: EJE-WB0063 (IC ID: 337J-WB0063)
FCC ID: EJE-WB0065 (IC ID: 337J-WB0065)

In accordance with this section and also section 2.1091 this device has been defined as a portable device and SAR testing was performed in accordance with OET Bulletin 65.

The intention of this Class II Permissive Change application is to enable the certified MC8781 Sierra Wireless UMTS module (FCC ID: N7NMC8781-F (IC ID: 2417C-MC8781)) to be co-located with the followings WLAN and BT modules:

FCC ID: EJE-WB0063 (IC: 337J-WB0063) – 533AN_HMW WLAN and EYTF3CSFS Bluetooth.
FCC ID: EJE-WB0065 (IC: 337J-WB0065) – AR5BHB92 WLAN and EYTF3CSFS Bluetooth.

Refer to Appendix B3 – Location Photographs for WLAN, BT and UMTS modules and antenna locations. Independent antennas are used for each of the Radio modules and simultaneous transmission is possible.

The 533AN_HMW Intel WLAN module and EYTF3CSFS TAIYO YUDEN Bluetooth Module have been recently certified by Fujitsu under the FCC ID: EJE-WB0065 (IC ID: 337J-WB0065). The highest SAR value measured 1.05 mW/g and complies with the FCC human exposure requirements of 47 CFR 2.1093(d).

The AR5BHB92 Atheros WLAN module and EYTF3CSFS TAIYO YUDEN Bluetooth Module have been recently certified by Fujitsu under the FCC ID: EJE-WB0063 (IC ID: 337J-WB0063). The highest SAR value measured 0.266 mW/g and complies with the FCC human exposure requirements of 47 CFR 2.1093(d).

The UMTS module was certified by Sierra Wireless INC as a modular approval under FCC ID: N7NMC8781-F (Canada ID: 2417C-MC8781). Fujitsu has now tested this UMTS radio module in this tablet convertible notebook T2020 for RF exposure. The highest SAR value measured 0.67 mW/g complied with the FCC human exposure requirements of 47 CFR 2.1093 (d). Refer to EMC Technologies reports M080762_Cert_MC8781_SAR_GSM-UMTS.

EMC Technologies Pty Ltd – 176 Harrick Road, Keilor Park VIC 3042 Australia
www.emctech.com.au