



EMC Technologies Pty Ltd

ABN 82 057 105 549
176 Harrick Road
Keilor Park Victoria Australia 3042

Ph: + 613 9365 1000
Fax: + 613 9331 7455
email: melb@emctech.com.au

**EMI TEST REPORT FOR CERTIFICATION
to
FCC PART 24(E) – Broadband PCS and
FCC PART 22(H) – Cellular Radiotelephone Service
RSS-132 and RSS-133
Class II Permissive Change**

FCC ID: N7NMC8781-F
Industry Canada ID: 2417C-MC8781

Transmitter: Sierra Wireless Mini-Card UMTS Module
UMTS Features: EGPRS, GPRS, UMTS and HSDPA and HSUPA
Model: MC8781

Host NoteBook: T2010 LifeBook

Report Number: M071032_Cert_MC8781_C2PC

Issue Date: 14th December 2007

EMC Technologies Pty Ltd reports apply only to the specific samples tested under stated test conditions. It is the manufacturer's responsibility to assure that additional production units of this model are manufactured with identical electrical and mechanical components. EMC Technologies Pty Ltd shall have no liability for any deductions, inferences or generalisations drawn by the client or others from EMC Technologies Pty Ltd issued reports. This report shall not be used to claim, constitute or imply product endorsement by EMC Technologies Pty Ltd. This document shall not be reproduced, except in full. The certificate on page 3 may be reproduced in full.

EMI TEST REPORT FOR CERTIFICATION
to
FCC PART 24 Subpart E – Broadband PCS and
FCC PART 22 Subpart H - Cellular Radiotelephone Service
RSS-132 and RSS-133
Class II Permissive Change

EMC Technologies Report No. M071032_Cert_MC8781_C2PC

Issue Date: 14th December 2007

CONTENTS

- 1.0 INTRODUCTION**
- 2.0 GENERAL INFORMATION**

RESULTS

- 3.0 POWER OUTPUT MEASUREMENTS**
- 4.0 EIRP and OUT of BAND EMISSIONS MEASUREMENTS**
- 5.0 FREQUENCY STABILITY**
- 6.0 CHANNEL BANDWIDTH**
- 7.0 CONDUCTED EMISSION MEASUREMENTS**
- 8.0 RADIO FREQUENCY EXPOSURE**
- 9.0 COMPLIANCE STATEMENT**
- 10.0 UNCERTAINTIES**
- 11.0 APPENDICES**

APPENDIX A: MEASUREMENT INSTRUMENT DETAILS

APPENDIX B: PHOTOGRAPHS

APPENDIX C: ANTENNA INFORMATION

APPENDIX D: FCC LABELLING DETAILS

APPENDIX E: USER MANUAL

APPENDIX F: CONDUCTED AND RADIATED EMISSIONS PLOTS

Attachment 1: Sierra Wireless FCC Part 22 and 24 Test Report

EMI TEST REPORT FOR CERTIFICATION
to
FCC PART 24 Subpart E – Broadband PCS and
FCC PART 22 Subpart H - Cellular Radiotelephone Service
RSS-132 and RSS-133
Class II Permissive Change

Report No. M071032_Cert_MC8781_C2PC

Transmitter: Sierra Wireless Mini-Card UMTS Module
UMTS Features: EGPRS, GPRS, UMTS and HSDPA and HSUPA
Model: MC8781
Manufacturer: Sierra Wireless INC

FCC ID: N7NMC8781-F
Industry Canada ID: 2417C-MC8781
Equipment Type: Intentional Radiator (Transceiver)

Host Notebook: T2010 LifeBook
Manufacturer (LifeBook): Fujitsu Ltd - Mobile Computing Division
Address: 1-1 Kamikodanaka 4-Chome, Nakahara-Ku, Kawasaki, Japan
Contact: Mr. Tsuyoshi Uchihara


Test Standards: FCC Part 24 Subpart E – Broadband PCS
FCC Part 22 Subpart H - Cellular Radiotelephone Service
ANSI/TIA/EIA-603
ANSI C63.4 – 2003
OET Bulletin No. 65
RSS-132 – Cellular Telephones
RSS-133 – 2 GHz Personal Communications Services
RSP-100 – Radio Equipment Certification Procedure
RSS-102 - Evaluation Procedure for Mobile and Portable Radio Transmitters with respect to Health Canada's Safety Code 6 for Exposure of Humans to Radio Frequency Fields

Test Dates: 10th to 12th December 2007

Senior Test Engineer: 

Chieu Huynh - B.Eng (Hons) Electronics/ Communications
Lee Hopkins

Attestation: *I hereby certify that the device(s) described herein were tested as described in this report and that the data included is that which was obtained during such testing.*

Authorised Signatory: 

Chris Zombolas
Technical Director
EMC Technologies Pty Ltd

EMI TEST REPORT FOR CERTIFICATION
to
FCC PART 24 Subpart E – Broadband PCS and
FCC PART 22 Subpart H - Cellular Radiotelephone Service
RSS-132 and RSS-133
Class II Permissive Change

1.0 INTRODUCTION

EMI testing was performed on the Sierra Wireless Mini-Card UMTS Module, model: MC8781 installed in Fujitsu notebook PC, Model: T2010. The test results and procedures were performed in accordance with the following Federal Communications Commission (FCC) standards/regulations. The test sample **complied** with the requirements of 47 CFR, Part 24 Subpart E – Broadband PCS and Part 22 Subpart H - Cellular Radiotelephone Service. The test sample also complied with the Industry Canada RSS-132 and RSS-133 and the RF exposure requirements of RSS-102.

The MC8781 UMTS module was certified by Sierra Wireless INC as a modular approval under FCC ID: N7NMC8781-F (Canada ID: 2417C-MC8781).

The other transmitters installed in the T2010 notebook are 4965AGN Intel Kedron WLAN module, and EYTF3CSFT TAIYO YUDEN Bluetooth Module. These Radio modules have already been recently certified by Fujitsu under the FCC ID: EJE-WB0052 (IC: 337J-WB0052).

The intention of this Class II Permissive Change application is to enable the certified MC8781 Sierra Wireless UMTS module to be co-located with WLAN and BT modules. Independent antennas are used for each of the Radio modules and simultaneous transmission is possible. The transmitter modules are installed in a controlled environment at the Fujitsu notebook production/assembly factory.

Test results and procedures were performed in accordance with the following Federal Communications Commission (FCC) standards/regulations:

1.1 Summary of Results

FCC Part 24 Subpart E Clauses	FCC Part 22 Subpart H Clauses	IC RSS-132 Clauses	IC RSS-133 Clauses	Test Performed	Result
24.232	22.913	4.4	6.4	Power Limits	Complies (1)*
24.235	22.355	4.3	6.3	Frequency Stability	Complies (1)*
24.238	22.917	4.5.1	6.5.1	Emission Limits	Complies

(1)* Refer to the manufacturer's (Sierra Wireless) FCC Part 22 and 24 test report. Report dated: 18, April 2007, tested by Sierra Wireless INC, Canada.

Note: Refer to M071033_Cert_MC8781_SAR_GSM-UMTS (FCC SAR Report) for details of SAR Compliance.

The measurement procedure used was in accordance with ANSI/TIA/EIA-603, ANSI C63.4-2003, RSP-100 and OET Bulletin No. 65. The instrumentation conformed to the requirements of ANSI C63.2-1996.

1.2 Modifications by EMC Technologies

No modifications were required.

2.0 GENERAL INFORMATION

(Information supplied by the Client)

2.1 Transmitter (UMTS) Details

MC8780 Transmitter: Mini-Card UMTS Module
Wireless Module: UMTS
Model Number: MC8781
Manufacturer: Sierra Wireless, Inc.

GSM Frequency Bands: 850 / 900 / 1800 / 1900 MHz
UMTS Frequency Bands: Band I (2100MHz) / Band II (1900MHz) / Band V (850MHz)

Features: EGPRS, GPRS, UMTS and HSDPA and HSUPA
Antenna Type: Nissei Electric
Antenna Gain: Max peak gain 2.34 dBi
Output Power: **GPRS:** 850 MHz = 33 dBm and 1900 MHz = 30 dBm
EGPRS: 850 MHz = 27 dBm and 1900 MHz = 26 dBm
UMTS: 850 MHz and 1900 MHz bands = 24 dBm

2.2 Host (Notebook PC) Details

Host notebook: LifeBook T series
Model Name: T2010
Serial Number: Pre-production Sample
Manufacturer: FUJITSU LIMITED

CPU Type and Speed: Core2 Duo U7600 1.20GHz/U7500 1.06GHz
LCD: 12.1" WXGA
Wired LAN: Marvell 88E8055 : 10 Base-T/100 Base-TX/1000Base-T
Modem: Agere MDC1.5 modem Model: D40
Port Replicator Model: FPCPR77 / FPCPR79 / FPCPR80

AC Adapter Model: 60W:SEC80N2-16.0(Sanken)
Voltage: 16V
Current Specs: 3.75A
Watts: 60W

2.3 Operational Description

The Windows HyperTerminal program and the 3G Watcher were used to establish a connection between the EUT and the Communication test set.

2.4 Test Configuration

Radiated Measurements - The CMU200 Rohde & Schwarz Universal Radio Communication Tester and a dipole antenna were used to establish a connection. The EUT was transmitted continuously during all tests.

Testing was performed in the two operating frequency ranges: 824.0 – 849 MHz and 1850 – 1910 MHz. The transmitter continuously transmitted at maximum output power on a low, middle and high frequency channel for each band.

The UMTS module supports GPRS, EGPRS, WCDMA and HSDPA mode. All four modes were tested and are reported.

The following CMU 200 settings were used to establish a connection:

- (a) Network Support: GPRS and EGPRS
Service Selection: Test Mode A
Main Service: Packet Data

- (b) Network Support: WCDMA and HSDPA
Band Select: Operating Band II (1900 MHz) and V (850 MHz)
Dedicated Channel: RMC

2.5 Support Equipment

Rohde & Schwarz Universal Radio Communication Tester, Model: CMU200.
Rohde & Schwarz Signal Generator, Model: SMR40
Refer to Appendix A for measurement instruments used.

2.6 Test Procedure

Emissions measurements were performed in accordance with the procedures of ANSI/TIA/EIA-603 and ANSI C63.4-2003. Radiated emissions tests were performed at a distance of 3 metres from the EUT. OET Bulletin 65 dated June 2001 was used for reference.

2.7 Test Facility

2.7.1 General

Radiated Emission measurements were performed at EMC Technologies open area test site (OATS) situated at Lerderberg Gorge, near the township of Bacchus Marsh in Victoria, Australia. Conducted measurements at an antenna ports were performed at EMC Technologies' laboratory in Keilor Park, Victoria Australia.

The above test sites have been accepted for testing by the Federal Communications Commission (FCC) - **FCC Registration Number 90560**.

EMC Technologies open area test site (OATS) has also been accepted by Industry Canada for the performance of radiated measurements in accordance with RSS 212, Issue 1 (Provisional). **Industry Canada File Number IC 4161**.

2.7.2 NATA Accreditation

EMC Technologies is accredited in Australia to test to the following standards by the National Association of Testing Authorities (NATA).

“FCC Part 15 unintentional and intentional emitters in the frequency range 9kHz to 18 GHz excluding TV receivers (15.117 and 15.119), TV interface devices (15.115), cable ready consumer electronic equipment (15.118), cable locating equipment (15.213) and unlicensed national information infrastructure devices (Sub part E).”

The current full scope of accreditation can be found on the NATA website: www.nata.asn.au
It also includes a large number of emissions, immunity, SAR, EMR and Safety standards.

NATA is the Australian national laboratory accreditation body and has accredited EMC Technologies to operate to the IEC/ISO17025 requirements. A major requirement for accreditation is the assessment of the company and its personnel as being technically competent in testing to the standards. This requires fully documented test procedures, continued calibration of all equipment to the National Standard at the National Measurements Institute (NMI) and an internal quality system to ISO 9002. NATA has mutual recognition agreements with the National Voluntary Laboratory Accreditation Program (NVLAP) and the American Association for Laboratory Accreditation (A²LA).

2.8 Test Equipment Calibration

All measurement instrumentation and transducers were calibrated in accordance with the applicable standards by an independent NATA registered laboratory such as Agilent Technologies (Australia) Pty Ltd or the National Measurement Institute (NMI). All equipment calibration is traceable to Australia national standards at the National Measurements Institute. The reference antenna calibration was performed by NMI and the working antennas (biconical and log-periodic) calibrated by the NATA approved procedures. The complete list of test equipment used for the measurements, including calibration dates and traceability is contained in Appendix A.

2.9 Ambients at OATS

The Open Area Test Site (OATS) is an area of low background ambient signals. No significant broadband ambients are present however commercial radio and TV signals exceed the limit in the FM radio, VHF and UHF television bands. Radiated prescan measurements were performed in the shielded enclosure to check for possible radiated emissions at the frequencies where the OATS ambient signals exceeded the test limit.

RESULTS

3.0 PEAK POWER OUTPUT MEASUREMENTS

Refer to the manufacturer's (Sierra Wireless) FCC Part 22 and 24 test report. Report dated: 18, April 2007, tested by Sierra Wireless INC, Canada.

Complied – refer to attachment 1 (Sierra Wireless FCC Part 22 and 24 Test Report).

4.0 EIPR and OUT of BAND EMISSIONS (Fundamental & Spurious/ Harmonics)

4.1 Test Procedure

Measurements were made at the open area test site (OATS). The EUT was set up on the table top (placed on turntable) of total height 80 cm above the ground plane, and operated as described in section 2 of this report.

The EUT was slowly rotated with the Peak Detector set to Max-Hold. This was performed for two antenna heights. When an emission was located, it was positively identified and its maximum level found by rotating the automated turntable, and by varying the antenna height. Each significant peak was investigated. This process was performed for both horizontal and vertical antenna polarisations.

The resolution bandwidth of 1 MHz and the video bandwidth of 1 MHz were utilised. Except, band-edge measurement the resolution bandwidth and the video bandwidth is 10 kHz.

The receiver bandwidth was set to 6 dB.

All measurements above 1 GHz were initially made over a distance of 3 metres. This was decreased to 1.0 metre as the emission levels from the device were very low.

Calibrated EMCO 3115, EMCO 3116 and ETS Standard Horn antennas were used for measurements between 1 to 20 GHz.

A substitution measurement was used to measure the fundamental and harmonics. The EUT was replaced with a calibrated horn antenna (above 1 GHz) and calibrated dipole antenna (below 1 GHz) that was connected to a calibrated signal generator. The output level of the signal generator was adjusted until the same level on the spectrum analyser observed. The level of the signal generator output in dBm less any loss/gain due to the coax cable and the antenna.

4.2 Radiated Emissions Results

Testing was performed in accordance with the requirements of FCC Part 24.238 and FCC Part 22.917(a).

As per 24.238(a) – The limits of any emissions outside the frequency band shall be attenuated by at least $43 + 10\log(P)$ dB, where P is the measured transmitter output power.

Testing was performed while transmitter continuously transmitted on a low, middle and high frequency channel. Worst case levels of harmonics are reported.

4.2.1 Frequency Band: 1 – 20 GHz

4.2.1.1 850 MHz GPRS

Low Channel – 824.2 MHz

Frequency MHz	Antenna Polarization	Level dBm	Limit dBm	Result
824.20	Vertical	30.6	38.5	Pass
1648.4	Vertical	-35.3	-13	Pass
2472.6	Vertical	-33.8	-13	Pass
3296.8	Vertical	-49.7	-13	Pass
4121.0	Vertical	-42.2	-13	Pass
824.0 Band Edge	Vertical	-17.1	-13	Pass

Middle Channel – 836.6 MHz

Frequency MHz	Antenna Polarization	Level dBm	Limit dBm	Result
836.6	Vertical	29.8	38.5	Pass
1673.2	Vertical	-34.5	-13	Pass
2509.8	Vertical	-36.7	-13	Pass
3346.4	Vertical	-54.1	-13	Pass
4183.0	Vertical	-39.3	-13	Pass

High Channel – 848.8 MHz

Frequency MHz	Antenna Polarization	Level dBm	Limit dBm	Result
848.8	Vertical	29.4	38.5	Pass
1697.6	Vertical	-32.8	-13	Pass
2546.4	Vertical	-39.1	-13	Pass
3395.2	Vertical	-54.9	-13	Pass
4244	Vertical	-45.0	-13	Pass
849.0 Band Edge	Vertical	-17.7	-13	Pass

4.2.1.2 850 MHz EGPRS**Low Channel – 824.2 MHz**

Frequency MHz	Antenna Polarization	Level dBm	Limit dBm	Result
824.20	Vertical	27.6	38.5	Pass
1648.4	Vertical	-41.1	-13	Pass
2472.6	Vertical	-37.8	-13	Pass
824.0 Band Edge	Vertical	-21.2	-13	Pass

Middle Channel – 836.6 MHz

Frequency MHz	Antenna Polarization	Level dBm	Limit dBm	Result
836.6	Vertical	27.0	38.5	Pass
1673.2	Vertical	-39.1	-13	Pass
2509.8	Vertical	-40.6	-13	Pass

High Channel – 848.8 MHz

Frequency MHz	Antenna Polarization	Level dBm	Limit dBm	Result
848.8	Vertical	27.2	38.5	Pass
1697.6	Vertical	-36.1	-13	Pass
2546.4	Vertical	-40.7	-13	Pass
849.0 Band Edge	Vertical	-22.3	-13	Pass

4.2.1.3 850 MHz WCDMA**Low Channel – 826.4 MHz**

Frequency MHz	Antenna Polarization	Level dBm	Limit dBm	Result
826.4	Vertical	21.8	38.5	Pass
1652.8	Vertical	-46.4	-13	Pass
824.0 Band Edge	Vertical	-26.5	-13	Pass

Middle Channel – 836.4 MHz

Frequency MHz	Antenna Polarization	Level dBm	Limit dBm	Result
836.4	Vertical	21.3	38.5	Pass
1672.8	Vertical	-47.0	-13	Pass

High Channel – 846.6 MHz

Frequency MHz	Antenna Polarization	Level dBm	Limit dBm	Result
846.6	Vertical	21.1	38.5	Pass
1693.2	Vertical	-46.8	-13	Pass
849.0 Band Edge	Vertical	-28.2	-13	Pass

4.2.1.4 850 MHz HSDPA**Low Channel – 826.4 MHz**

Frequency MHz	Antenna Polarization	Level dBm	Limit dBm	Result
826.4	Vertical	22.1	38.5	Pass
1652.8	Vertical	-52.9	-13	Pass
824.0 Band Edge	Vertical	-24.4	-13	Pass

Middle Channel – 836.4 MHz

Frequency MHz	Antenna Polarization	Level dBm	Limit dBm	Result
836.4	Vertical	21.4	38.5	Pass
1672.8	Vertical	-54.2	-13	Pass

High Channel – 846.6 MHz

Frequency MHz	Antenna Polarization	Level dBm	Limit dBm	Result
846.6	Vertical	21.6	38.5	Pass
1693.2	Vertical	-53.8	-13	Pass
849.0 Band Edge	Vertical	-25.0	-13	Pass

4.2.1.5 1900 MHz GPRS**Low Channel – 1850.2 MHz**

Frequency MHz	Antenna Polarization	Level dBm	Limit dBm	Result
1850.2	Horizontal	27.6	33.0	Pass
3700.4	Horizontal	-46.8	-13	Pass
9251.0	Vertical	-44.2	-13	Pass
1850 Band Edge	Horizontal	-20.1	-13	Pass

Middle Channel – 1880 MHz

Frequency MHz	Antenna Polarization	Level dBm	Limit dBm	Result
1880	Horizontal	27.9	33.0	Pass
3760	Horizontal	-45.2	-13	Pass
9400	Vertical	-43.3	-13	Pass

High Channel – 1909.8 MHz

Frequency MHz	Antenna Polarization	Level dBm	Limit dBm	Result
1909.8	Horizontal	28.7	33.0	Pass
3819.6	Horizontal	-43.8	-13	Pass
9549.0	Vertical	-43.0	-13	Pass
1910 Band Edge	Horizontal	-19.4	-13	Pass

4.2.1.6 1900 MHz EGPRS**Low Channel – 1850.2 MHz**

Frequency MHz	Antenna Polarization	Level dBm	Limit dBm	Result
1850.2	Horizontal	26.5	33.0	Pass
3700.4	Horizontal	-48.8	-13	Pass
9251.0	Vertical	-48.3	-13	Pass
1850 Band Edge	Horizontal	-20.1	-13	Pass

Middle Channel – 1880 MHz

Frequency MHz	Antenna Polarization	Level dBm	Limit dBm	Result
1880	Horizontal	27.1	33.0	Pass
3760	Horizontal	-47.6	-13	Pass
9400	Vertical	-47.9	-13	Pass

High Channel – 1909.8 MHz

Frequency MHz	Antenna Polarization	Level dBm	Limit dBm	Result
1909.8	Horizontal	27.4	33.0	Pass
3819.6	Horizontal	-46.1	-13	Pass
9549.0	Vertical	-47.5	-13	Pass
1910 Band Edge	Horizontal	-19.2	-13	Pass

4.2.1.7 1900 MHz WCDMA**Low Channel – 1852.4 MHz**

Frequency MHz	Antenna Polarization	Level dBm	Limit dBm	Result
1852.4	Horizontal	22.4	33.0	Pass
3704.8	Horizontal	-53.0	-13	Pass
1850 Band Edge	Horizontal	-26.5	-13	Pass

Middle Channel – 1880 MHz

Frequency MHz	Antenna Polarization	Level dBm	Limit dBm	Result
1880	Horizontal	22.8	33.0	Pass
3760	Horizontal	-49.1	-13	Pass

High Channel – 1907.6 MHz

Frequency MHz	Antenna Polarization	Level dBm	Limit dBm	Result
1907.6	Horizontal	23.7	33.0	Pass
3815.2	Horizontal	-35.9	-13	Pass
1910 Band Edge	Horizontal	-24.0	-13	Pass

4.2.1.8 1900 MHz HSDPA**Low Channel – 1852.4 MHz**

Frequency MHz	Antenna Polarization	Level dBm	Limit dBm	Result
1852.4	Horizontal	23.5	33.0	Pass
3704.8	Horizontal	-53.7	-13	Pass
1850 Band Edge	Horizontal	-21.2	-13	Pass

Middle Channel – 1880 MHz

Frequency MHz	Antenna Polarization	Level dBm	Limit dBm	Result
1880	Horizontal	23.2	33.0	Pass
3760	Horizontal	-50.3	-13	Pass

High Channel – 1907.6 MHz

Frequency MHz	Antenna Polarization	Level dBm	Limit dBm	Result
1907.6	Horizontal	23.3	33.0	Pass
3815.2	Horizontal	-38.7	-13	Pass
1910 Band Edge	Horizontal	-21.9	-13	Pass

4.2.2 Frequency Band: 30 - 1000 MHz

A calibrated Biconical antenna was used for measurements between 30 MHz to 232 MHz and a calibrated Logperiodic antenna used for measurements between 230 MHz to 1000 MHz.

Testing was performed at 3m distance. The resolution bandwidth of 1 MHz and the video bandwidth of 1 MHz were utilised.

No spurious emissions were recorded within 30 dB of the FCC limit (the limit is -13dBm). Refer to Appendix F (graphs 3 to 4) for plots.

Result: Complies.

4.3 Band Edge Measurements

Refer to the manufacturer's (Sierra Wireless) FCC Part 22 and 24 test report. Report dated: 18, April 2007, tested by Sierra Wireless INC, Canada.

Complied – refer to attachment 1 (Sierra Wireless FCC Part 22 and 24 Test Report).

4.4 Antenna Conducted RF Measurements

Refer to the manufacturer's (Sierra Wireless) FCC Part 22 and 24 test report. Report dated: 18, April 2007, tested by Sierra Wireless INC, Canada.

Complied – refer to attachment 1 (Sierra Wireless FCC Part 22 and 24 Test Report).

5.0 FREQUENCY STABILITY

Refer to the manufacturer's (Sierra Wireless) FCC Part 22 and 24 test report. Report dated: 18, April 2007, tested by Sierra Wireless INC, Canada.

Complied – refer to attachment 1 (Sierra Wireless FCC Part 22 and 24 Test Report).

6.0 CHANNEL BANDWIDTH

Refer to the manufacturer's (Sierra Wireless) FCC Part 22 and 24 test report. Report dated: 18, April 2007, tested by Sierra Wireless INC, Canada.

Complied – refer to attachment 1 (Sierra Wireless FCC Part 22 and 24 Test Report).

7.0 CONDUCTED EMISSION MEASUREMENTS

7.1 Test Procedure

The arrangement specified in ANSI/TIA/EIA-603 and ANSI C63.4-2003 was adhered to for the conducted EMI measurements. The EUT was placed in the RF screened enclosure and a CISPR EMI Receiver as defined in ANSI C63.2-1996 was used to perform the measurements.

The EMI Receiver was operated under program control using the Max-Hold function and automatic frequency scanning, measurement and data logging techniques. The specified 0.15 MHz to 30 MHz frequency range was sub-divided into sub-ranges to ensure that all short duration peaks were captured.

7.2 Peak Maximising Procedure

The various operating modes of the system were investigated. For each of the sub-ranges, the EMI receiver was set to continuous scan with the Peak detector set to Max-Hold mode. The Quasi-Peak detector and the Average detector were then invoked to measure the actual Quasi-Peak and Average level of the most significant peaks, which were detected.

7.3 Calculation of Voltage Levels

The voltage levels were automatically measured in software and compared to the test limit. The method of calculation was as follows:

$$VEMI = VRx + LBPF$$

Where:

- VEMI** = the Measured EMI voltage in dB μ V to be compared to the limit.
- VRx** = the Voltage in dB μ V read directly at the EMI receiver.
- LBPF** = the loss in dB of the cables and the Limiter and Pass Filter.

7.4 Plotting of Conducted Emission Measurement Data

The measurement data pertaining to each frequency sub-range were then concatenated to form a single graph of (peak) amplitude versus frequency. This was performed for both Active and Neutral lines and the composite graph were subsequently plotted. A list of the highest relevant peaks and the respective Quasi-Peak and Average values were also plotted on the graph.

7.5 Results of Conducted Emission Measurements (AC Mains Ports)

The worst case conducted EMI complied with both quasi peak and average limits by margins of 3.5 dB and 23.9 dB respectively. Refer to Appendix F (graphs 1 & 2) for plots.

Result: Complies

8.0 RADIO FREQUENCY EXPOSURE (HAZARD) INFORMATION

The Personal Communications Services operating in the 824 – 849 MHz and 1850 - 1910 MHz bands are required to be operated in a manner that ensures that the public is not exposed to RF energy levels in accordance with CFR 47, Section 1.1307(b)(1).

In accordance with this section and also section 2.1091 this device has been defined as a portable device and SAR testing was performed in accordance with OET Bulletin 65 and reported under EMC Technologies M071033_Cert_MC8781_SAR_GSM-UMTS. The highest SAR value measured 0.968 mW/g complies with the FCC human exposure requirements of 47 CFR 2.1093(d).

9.0 COMPLIANCE STATEMENT

The UMTS module, model: MC8781 installed in Fujitsu notebook PC, Model: T2010, **complied** with the requirements of 47 CFR, Part 24 Subpart E – Broadband PCS and Part 22 Subpart H - Cellular Radiotelephone Service. The test sample also complied with the Industry Canada RSS-132 and RSS-133 and the RF exposure requirements of RSS-102.

Results were as follows:

FCC Part 24 Subpart E Clauses	FCC Part 22 Subpart H Clauses	IC RSS-132 Clauses	IC RSS-133 Clauses	Test Performed	Result
24.232	22.913	4.4	6.4	Power Limits	Complies (1)*
24.235	22.355	4.3	6.3	Frequency Stability	Complies (1)*
24.238	22.917	4.5.1	6.5.1	Emission Limits	Complies

(1)* Refer to the manufacturer's (Sierra Wireless) FCC Part 22 and 24 test report. Report dated: 18, April 2007, tested by Sierra Wireless INC, Canada.

Note: Refer to M071033_Cert_MC8781_SAR_GSM-UMTS (FCC SAR Report) for details of SAR Compliance.

10.0 UNCERTAINTIES

EMC Technologies has evaluated the equipment and the methods used to perform the emissions testing. The estimated measurement uncertainties for emissions tests shown within this report are as follows:

Conducted Emissions:	9 kHz to 30 MHz	±3.2 dB
Radiated Emissions:	30 MHz to 300 MHz	±5.1 dB
	300 MHz to 1000 MHz	±4.7 dB
	1 GHz to 18 GHz	±4.6 dB

The above expanded uncertainties are based on standard uncertainties multiplied by a coverage factor of k=2, providing a level of confidence of approximately 95%.

11.0 APPENDICES

- APPENDIX A: MEASUREMENT INSTRUMENT DETAILS**
- APPENDIX B: PHOTOGRAPHS**
- APPENDIX C: ANTENNA INFORMATION**
- APPENDIX D: FCC LABELLING DETAILS**
- APPENDIX E: USER MANUAL**
- APPENDIX F: CONDUCTED AND RADIATED EMISSIONS PLOTS**

Attachment 1: Sierra Wireless FCC Part 22 and 24 Test Report