



FCC LTE NB1 Test Report

CUSTOMER : Sierra Wireless Inc.
EQUIPMENT : Radio Module
MODEL NAME : WP7702
FCC ID : N7NWP77B
STANDARD : FCC 47 CFR Part 2, and 90(S)
CLASSIFICATION : PCS Licensed Transmitter (PCB)

This is a partial report. The product was received on Dec. 05, 2017 and testing was completed on Apr. 13, 2018. We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI / TIA / EIA-603-E and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.

Reviewed by: Joseph Lin / Supervisor

Approved by: Jones Tsai / Manager



SPORTON INTERNATIONAL INC.

No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan District, Tao Yuan City, Taiwan, R.O.C.



TABLE OF CONTENTS

REVISION HISTORY..... 3

SUMMARY OF TEST RESULT 4

1 GENERAL DESCRIPTION 5

 1.1 Customer 5

 1.2 Manufacturer 5

 1.3 Feature of Equipment Under Test..... 5

 1.4 Product Specification of Equipment Under Test 5

 1.5 Modification of EUT 5

 1.6 Testing Site..... 6

 1.7 Applied Standards 6

2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST 7

 2.1 Test Mode..... 7

 2.2 Connection Diagram of Test System 8

 2.3 Support Unit used in test configuration and system..... 8

 2.4 Measurement Results Explanation Example 8

 2.5 Frequency List of Low/Middle/High Channels..... 9

3 TEST RESULT..... 10

 3.1 Conducted Output Power Measurement..... 10

 3.2 99% Occupied Bandwidth and 26dB Bandwidth Measurement..... 11

 3.3 Emissions Mask Measurement 12

 3.4 Emissions Mask – Out Of Band Emissions Measurement..... 14

 3.5 Field Strength of Spurious Radiation Measurement 15

 3.6 Frequency Stability Measurement..... 17

4 LIST OF MEASURING EQUIPMENT 19

5 UNCERTAINTY OF EVALUATION 20

APPENDIX A. TEST RESULTS OF CONDUCTED TEST

APPENDIX B. TEST RESULTS OF RADIATED TEST



SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	§2.1046	Conducted Output Power	Reporting only	PASS	-
3.2	§2.1049 §90.209	Occupied Bandwidth and 26dB Bandwidth	Reporting only	PASS	-
3.3	§2.1051 §90.691	Emission masks – In-band emissions	$< 50+10\log_{10}(P[\text{Watts}])$	PASS	-
3.4	§2.1051 §90.691	Emission masks – Out of band emissions	$< 43+10\log_{10}(P[\text{Watts}])$	PASS	-
3.5	§2.1053 §90.691	Field Strength of Spurious Radiation	$< 43+10\log_{10}(P[\text{Watts}])$	PASS	Under limit 22.33 dB at 1632.000 MHz
3.6	§2.1055 §90.213	Frequency Stability for Temperature & Voltage	$< 2.5 \text{ ppm}$	PASS	-



1 General Description

1.1 Customer

Sierra Wireless Inc.
13811 Wireless Way Richmond, BC Canada V6V 3A4

1.2 Manufacturer

Sierra Wireless Inc.
13811 Wireless Way Richmond, BC Canada V6V 3A4

1.3 Feature of Equipment Under Test

WP7702 is an IOT module supporting multiband LTE CATM1/NB1 and 2G operation.

1.4 Product Specification of Equipment Under Test

Product Specification subjective to this standard	
Tx Frequency	814.1 ~ 823.9 MHz
Rx Frequency	859.1 ~ 868.9 MHz
Maximum Output Power to Antenna	23.22 dBm
Type of Modulation	BPSK / QPSK

Remark: This test report recorded

1.5 Modification of EUT

No modifications are made to the EUT during all test items.



1.6 Testing Site

Sporton Lab is accredited to ISO 17025 by Taiwan Accreditation Foundation (TAF code : 1190) and the FCC designation No. TW1190 and TW0007 under the FCC 2.948(e) by Mutual Recognition Agreement (MRA) in FCC Test.

Test Site	SPORTON INTERNATIONAL INC.	
Test Site Location	No. 52, Hwa Ya 1 st Rd., Hwa Ya Technology Park, Kwei-Shan District, Tao Yuan City, Taiwan, R.O.C. TEL: +886-3-327-3456 FAX: +886-3-328-4978	
Test Site No.	Sporton Site No.	
	TH05-HY	03CH07-HY

1.7 Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- FCC 47 CFR Part 2, 90
- ANSI / TIA / EIA-603-E
- FCC KDB 971168 D01 Power Meas. License Digital Systems v03r01
- Interim Guidance for Equipment Authorization of Devices with Channel Bandwidths Combined Across Two Contiguous Service Rule Allocations OET/Lab/EACB, June 6, 2013

Remark: All test items were verified and recorded according to the standards and without any deviation during the test.



2 Test Configuration of Equipment Under Test


2.1 Test Mode

During all testing, EUT is in link mode with base station emulator at maximum power level. The spurious emission measurements were carried out in semi-anechoic chamber with 3-meter test range, and EUT is rotated on three test planes to find out the worst emission.

Frequency range investigated for radiated emission is 30 MHz to 9000 MHz.

Test Items	LTE -NB1	Subcarrier (kHz)		Modulation		Tone@		Test Channel		
	Band	3.75	15	BPSK	QPSK	1	Full	L	M	H
Max. Output Power	26	v	v	v	v	v	v	v	v	v
26dB and 99% Bandwidth	26		v	v	v		v	v	v	v
Emission masks In-band emissions	26	v	v	v	v	v	v	v		v
Emission masks – Out of band emissions	26	v	v	v	v	v		v	v	v
Frequency Stability	26		v	v			v		v	
Radiated Spurious Emission	26	Worst Case						v	v	v
Note	1. The mark “v” means that this configuration is chosen for testing 2. The mark “-“ means that this bandwidth is not supported.									

2.2 Connection Diagram of Test System



2.3 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord
1.	LTE-NB1 Base Station	Anritsu	MT8821C	N/A	N/A	Unshielded, 1.8 m
2.	Base Station	Kaysight	UXM	N/A	N/A	Unshielded, 1.8 m

2.4 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between RF conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level will be exactly the RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

The following shows an offset computation example with RF cable loss 4.2 dB and a 10dB attenuator.

Example :

$$\begin{aligned} \text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)}. \\ &= 4.2 + 10 = 14.2 \text{ (dB)} \end{aligned}$$



2.5 Frequency List of Low/Middle/High Channels

LTE-NB1 Band 26 Channel and Frequency List			
Channel/Frequency(MHz)	Lowest	Middle	Highest
Channel	26691	26740	26789
Frequency	814.1	819.0	823.9

3 Test Result

3.1 Conducted Output Power Measurement

3.1.1 Description of the Conducted Output Power Measurement

A system simulator was used to establish communication with the EUT. Its parameters were set to enforce EUT transmitting at the maximum power. The measured power in the radio frequency on the transmitter output terminals shall be reported.


3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedures

1. The transmitter output port was connected to the system simulator.
2. Set EUT at maximum power through system simulator.
3. Select lowest, middle, and highest channels for each band and different modulation.
4. Measure and record the power level from the system simulator.

3.1.4 Test Setup



3.1.5 Test Result of Conducted Output Power

Please refer to Appendix A.

3.2 99% Occupied Bandwidth and 26dB Bandwidth Measurement

3.2.1 Description of (Occupied) Bandwidth Limitations Measurement

The 99% occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The emission bandwidth is defined as the width of the signal between two points, located at the 2 sides of the carrier frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.


3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.2.3 Test Procedures

1. The EUT was connected to spectrum analyzer and system simulator via a power divider.
2. The 26dB and 99% occupied bandwidth (BW) of the middle channel for the highest RF power with full RB sizes were measured.

3.2.4 Test Setup



3.2.5 Test Result of 99% Occupied Bandwidth and 26dB Bandwidth

Please refer to Appendix A.



3.3 Emissions Mask Measurement

3.3.1 Description of Emissions Mask Measurement

Equipment used in this licensed to EA or non-EA systems shall comply with the emission mask provisions of FCC Part 90.691.(a)

(a) Out-of-band emission requirement shall apply only to the "outer" channels included in an EA license and to spectrum adjacent to interior channels used by incumbent licensees. The emission limits are as follows:

(1) For any frequency removed from the EA licensee's frequency block by up to and including 37.5 kHz, the power of any emission shall be attenuated below the transmitter power (P) in watts by at least $116 \text{ Log}_{10}(f/6.1)$ decibels or $50 + 10 \text{ Log}_{10}(P)$ decibels or 80 decibels, whichever is the lesser attenuation, where f is the frequency removed from the center of the outer channel in the block in kilohertz and where f is greater than 12.5 kHz.

(2) For any frequency removed from the EA licensee's frequency block greater than 37.5 kHz, the power of any emission shall be attenuated below the transmitter power (P) in watts by at least $43 + 10\text{Log}_{10}(P)$ decibels or 80 decibels, whichever is the lesser attenuation, where f is the frequency removed from the center of the outer channel in the block in kilohertz and where f is greater than 37.5 kHz.


3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.3.3 Test Procedures

1. The EUT was connected to spectrum analyzer and base station via power divider.
2. The emissions mask of low and high channels for the highest RF powers were measured.
3. The measured RBW and the VBW set 3 times of RBW are then set in spectrum analyzer, and the RBW correction factor $10\log(1\% \text{ of OBW/measured RBW})(\text{dB})$ was compensated, if required.
4. The test results were shown below plots with a correction offset factor including cable loss, insertion loss of power divider.

3.3.4 Test Setup



3.3.5 Test Result (Plots) of Conducted Emissions Mask

Please refer to Appendix A.

3.4 Emissions Mask – Out Of Band Emissions Measurement

3.4.1 Description of Conducted Emissions Out of band emissions measurement

The power of any emission FCC Part 90.691 (a)(2) on any frequency removed from the assigned frequency by out of the authorized bandwidth at least $43 + 10 \log (P)$ dB. It is measured by means of a calibrated spectrum analyzer and scanned from 30 MHz up to a frequency including its 10th harmonic.


3.4.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.4.3 Test Procedures

1. The EUT was connected to spectrum analyzer and system simulator via a power divider.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. The middle channel for the highest RF power within the transmitting frequency was measured.
4. The conducted spurious emission for the whole frequency range was taken.
5. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking the record of maximum spurious emission.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
7. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)

3.4.4 Test Setup



3.4.5 Test Result (Plots) of Conducted Emission

Please refer to Appendix A.



3.5 Field Strength of Spurious Radiation Measurement

3.5.1 Description of Field Strength of Spurious Radiated Measurement

The radiated spurious emission was measured by substitution method according to ANSI / TIA / EIA-603-C-2004. The power of any emission FCC Part 90.691 on any frequency removed from the assigned frequency by more than 250 percent of the authorized bandwidth at least $43 + 10 \log (P)$ dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least $43 + 10 \log_{10}(P[\text{Watts}])$ dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

3.5.2 Measuring Instruments


The measuring equipment is listed in the section 4 of this test report.

3.5.3 Test Procedures


1. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
2. The EUT was set 3 meters from the receiving antenna, which was mounted on the antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest spurious emission.
4. The height of the receiving antenna is varied between one meter and four meters to search the maximum spurious emission for both horizontal and vertical polarizations.
5. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, Sweep = 500ms, Taking the record of maximum spurious emission.
6. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
7. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
8. Taking the record of output power at antenna port.
9. Repeat step 7 to step 8 for another polarization.
10. $\text{EIRP (dBm)} = \text{S.G. Power} - \text{Tx Cable Loss} + \text{Tx Antenna Gain}$
11. $\text{ERP (dBm)} = \text{EIRP} - 2.15$
12. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
13. The limit line is derived from $43 + 10 \log(P)$ dB below the transmitter power P(Watts)

3.5.4 Test Setup

For radiated test from 30MHz to 1GHz



For radiated test above 1GHz



3.5.5 Test Result of Field Strength of Spurious Radiated

Please refer to Appendix B.



3.6 Frequency Stability Measurement

3.6.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within $\pm 0.00025\%$ ($\pm 2.5\text{ppm}$) of the center frequency according to FCC Part 90.213.

3.6.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.


3.6.3 Test Procedures for Temperature Variation

1. The EUT was set up in the thermal chamber and connected with the base station.
2. With power OFF, the temperature was decreased to -30°C and the EUT was stabilized for three hours. Power was applied and the maximum change in frequency was recorded within one minute.
3. With power OFF, the temperature was raised in 10°C step up to 50°C . The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

3.6.4 Test Procedures for Voltage Variation

1. The EUT was placed in a temperature chamber at $20\pm 5^{\circ}\text{C}$ and connected with the base station.
2. The power supply voltage to the EUT was varied from BEP to 115% of the nominal value measured at the input to the EUT.
3. The variation in frequency was measured for the worst case.

3.6.5 Test Setup



3.6.6 Test Result of Temperature Variation

Please refer to Appendix A.



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Base Station (Measure)	Anritsu	MT8821C	620166475 5	GSM / GPRS /WCDMA / LTE FDD/TDD	Mar. 26, 2018	Apr. 03, 2018~ Apr. 13, 2018	Mar. 25, 2019	Conducted (TH05-HY)
Spectrum Analyzer	Rohde & Schwarz	FSV40	101397	10Hz~40GHz	Nov. 07, 2017	Apr. 03, 2018~ Apr. 13, 2018	Nov. 06, 2018	Conducted (TH05-HY)
Temperature Chamber	ESPEC	SH-641	92013720	-30℃~70℃	Aug. 28, 2017	Apr. 03, 2018~ Apr. 13, 2018	Aug. 27, 2018	Conducted (TH05-HY)
Programmable Power Supply	GW Instek	PSS-2005	EL890001	1V~20V 0.5A~5A	Oct. 06, 2017	Apr. 03, 2018~ Apr. 13, 2018	Oct. 05, 2018	Conducted (TH05-HY)
Coupler	Warison	1-18GHz 20dB	#B	1G~18GHz	Dec. 04, 2017	Apr. 03, 2018~ Apr. 13, 2018	Dec. 03, 2018	Conducted (TH05-HY)
Bilog Antenna	TESEQ	CBL 6111D&00800 N1D01N-06	35419&03	30MHz to 1GHz	Jan. 07, 2017	Dec. 12, 2017~ Dec. 19, 2017	Jan. 06, 2018	Radiation (03CH07-HY)
Double Ridge Horn Antenna	ESCO	3117	00075962	1GHz ~ 18GHz	Aug. 23, 2017	Dec. 12, 2017~ Dec. 19, 2017	Aug. 22, 2018	Radiation (03CH07-HY)
Horn Antenna	ESCO	3117	00066584	1GHz~18GHz	Sep. 06, 2017	Dec. 12, 2017~ Dec. 19, 2017	Sep. 05, 2018	Radiation (03CH07-HY)
SHF-EHF Horn Antenna	SCHWARZBE CK	BBHA 9170	BBHA9170 251	18GHz- 40GHz	Nov. 10, 2017	Dec. 12, 2017~ Dec. 19, 2017	Nov. 09, 2018	Radiation (03CH07-HY)
SHF-EHF Horn Antenna	SCHWARZBE CK	BBHA 9170	BBHA9170 584	18GHz- 40GHz	Nov. 27, 2017	Dec. 12, 2017~ Dec. 19, 2017	Nov. 26, 2018	Radiation (03CH07-HY)
Preamplifier	COM-POWER	PA-103A	161241	10MHz-1GHz	Mar. 14, 2017	Dec. 12, 2017~ Dec. 19, 2017	Mar. 13, 2018	Radiation (03CH07-HY)
Preamplifier	Agilent	8449B	3008A023 62	1GHz~ 26.5GHz	Oct. 30, 2017	Dec. 12, 2017~ Dec. 19, 2017	Oct. 29, 2018	Radiation (03CH07-HY)
Amplifier	MITEQ	TTA1840-35- HG	1871923	18GHz~40GHz, VSWR : 2.5:1 max	Jul. 18, 2017	Dec. 12, 2017~ Dec. 19, 2017	Jul. 17, 2018	Radiation (03CH07-HY)
Spectrum Analyzer	Agilent	N9010A	MY534701 18	10Hz~44GHz	Apr. 17, 2017	Dec. 12, 2017~ Dec. 19, 2017	Apr. 16, 2018	Radiation (03CH07-HY)
Antenna Mast	Max-Full	MFA520BS	N/A	1m~4m	N/A	Dec. 12, 2017~ Dec. 19, 2017	N/A	Radiation (03CH07-HY)
Turn Table	ChainTek	Chaintek 3000	N/A	0~360 Degree	N/A	Dec. 12, 2017~ Dec. 19, 2017	N/A	Radiation (03CH07-HY)



5 Uncertainty of Evaluation

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	3.05
---	------

Uncertainty of Radiated Emission Measurement (1 GHz ~ 9 GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	3.44
---	------



Appendix A. Test Results of Conducted Test

Conducted Output Power(Average power)

LTE-NB1 Band 26 Maximum Average Power [dBm]					
Sub-carrier Spacing [kHz]	Mod	Number of Tones	Lowest	Middle	Highest
3.75	BPSK	1T0	15.99	23.05	16.87
3.75		1T47	16.03	23.05	16.83
3.75	QPSK	1T0	16.02	23.06	16.86
3.75		1T47	16.01	23.03	16.82
15	BPSK	1T0	19.95	23.21	16.99
15		1T11	19.91	23.18	17.01
15	QPSK	1T0	19.96	23.22	17.01
15		1T11	19.93	23.19	17.02
15		12T0	18.48	21.52	17.46



LTE NB1 Band 26-90S


Peak-to-Average Ratio

Mode	LTE NB1 Band 26-90S / 15kHz			
Mod.	BPSK	QPSK		Limit: 13dB
T Size	1T	1T	Full T	Result
Lowest CH	2.70	2.26	3.65	PASS
Middle CH	2.75	2.32	3.74	
Highest CH	2.78	2.32	4.43	




LTE NB1 Band 26-90S / 15kHz / BPSK

Lowest Channel / 1T




Date: 4 APR 2018 05:08:53

Middle Channel / 1T



Date: 4 APR 2018 05:29:34

Highest Channel / 1T



Date: 4 APR 2018 06:02:03




LTE NB1 Band 26-90S / 10MHz / QPSK

Lowest Channel / 1T



Date: 4 APR 2018 05:10:04

Lowest Channel / Full T




Date: 4 APR 2018 05:12:21

Middle Channel / 1T



Date: 4 APR 2018 05:30:41

Middle Channel / Full T



Date: 4 APR 2018 05:28:33

Highest Channel / 1T



Date: 4 APR 2018 05:44:34

Highest Channel / Full T



Date: 4 APR 2018 06:03:34




26dB Bandwidth

Mode	LTE NB1 Band 26-90S : 26dB(kHz)
Subcarrier Spacing	15k
Mod.	QPSK
Lowest CH	210.59
Middle CH	200.60
Highest CH	210.19




LTE NB1 Band 26-90S

Lowest Channel / 15kHz / QPSK



Middle Channel / 15kHz / QPSK



Highest Channel / 15kHz / QPSK






Occupied Bandwidth

Mode	LTE NB1 Band 26-90S : OB(kHz)
Subcarrier Spacing	15k
Mod.	QPSK
Lowest CH	182.62
Middle CH	188.21
Highest CH	183.02



LTE NB1 Band 26-90S

Lowest Channel / 15kHz / QPSK




Date: 4 APR 2018 04:59:30

Middle Channel / 15kHz / QPSK



Date: 13 APR 2018 11:55:07



Highest Channel / 15kHz / QPSK



Date: 4 APR 2018 05:37:13



Conducted Band Edge







LTE NB1 Band 26-90S / 15kHz / BPSK

Lowest Band Edge / 1 T

Highest Band Edge / 1 T




Date: 13.APR.2018 11:34:19

Date: 13.APR.2018 11:50:59




LTE NB1 Band 26-90S / 15kHz / QPSK

Lowest Band Edge / 1 T




Date: 13 APR 2018 11:33:39

Lowest Band Edge / 1 T




Date: 13 APR 2018 11:49:20

Lowest Band Edge / Full T



Date: 13 APR 2018 11:37:44


Lowest Band Edge / Full T




Date: 13 APR 2018 11:47:25



Conducted Spurious Emission









LTE NB1 Band 26-90S / 15kHz

Lowest Channel / BPSK

Lowest Channel / QPSK





Date: 3.APR.2018 09:12:15

Date: 3.APR.2018 09:13:07


Middle Channel / BPSK

Middle Channel / QPSK



Date: 3.APR.2018 09:23:49

Date: 3.APR.2018 09:24:55





Frequency Stability

Test Conditions		LTE NB1 Band 26-90S (BPSK) / Middle Channel	Limit
Temperature (°C)	Voltage (Volt)	BW 10MHz	Note 2.
		Deviation (ppm)	Result
50	Normal Voltage	0.0018	PASS
40	Normal Voltage	0.0013	
30	Normal Voltage	0.0005	
20(Ref.)	Normal Voltage	0.0000	
10	Normal Voltage	0.0012	
0	Normal Voltage	0.0004	
-10	Normal Voltage	0.0029	
-20	Normal Voltage	0.0001	
-30	Normal Voltage	0.0057	
20	Maximum Voltage	0.0059	
20	Normal Voltage	0.0000	
20	Battery End Point	0.0037	

Note:

1. Normal Voltage =3.7 V. ; Battery End Point (BEP) =3.4 V. ; Maximum Voltage =4.3 V.
2. Note: The frequency fundamental emissions stay within the authorized frequency block.



Appendix B. Test Results of Radiated Test

Part 90S LTE-NB1 Band 26

LTE-NB1 Band 26 Sub-carrier Spacing: 3.75kHz									
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Lowest	1632	-49.75	-13	-36.75	-61.62	-51.56	0.97	4.93	H
	2440	-49.68	-13	-36.68	-66.83	-51.48	1.27	5.22	H
	3256	-56.53	-13	-43.53	-75.77	-59.78	1.53	6.93	H
									H
									H
									H
	1632	-35.33	-13	-22.33	-47.68	-37.14	0.97	4.93	V
	2440	-41.96	-13	-28.96	-59.55	-43.76	1.27	5.22	V
	3256	-49.89	-13	-36.89	-69.53	-53.14	1.53	6.93	V
									V
									V
									V
Middle	1640	-35.90	-13	-22.90	-47.91	-37.68	0.97	4.91	H
	2456	-43.13	-13	-30.13	-60.36	-44.97	1.28	5.27	H
	3280	-48.86	-13	-35.86	-68.18	-52.21	1.54	7.03	H
									H
									H
									H
	1640	-35.63	-13	-22.63	-48.11	-37.41	0.97	4.91	V
	2456	-42.46	-13	-29.46	-60.13	-44.3	1.28	5.27	V
	3280	-48.61	-13	-35.61	-68.3	-51.96	1.54	7.03	V
									V
									V
									V



Highest	1648	-47.56	-13	-34.56	-59.57	-49.32	0.98	4.89	H
	2472	-47.68	-13	-34.68	-64.99	-49.56	1.28	5.32	H
	3296	-55.61	-13	-42.61	-75.01	-59.02	1.54	7.10	H
									H
									H
									H
									H
	1648	-35.98	-13	-22.98	-48.46	-37.74	0.98	4.89	V
	2472	-43.41	-13	-30.41	-61.16	-45.29	1.28	5.32	V
	3296	-47.50	-13	-34.50	-67.23	-50.91	1.54	7.10	V
									V
									V
									V
									V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.



LTE-NB1 Band 26 Sub-carrier Spacing: 15kHz									
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Lowest	1632	-50.47	-13	-37.47	-62.13	-52.28	0.97	4.93	H
	2440	-52.66	-13	-39.66	-69.51	-54.46	1.27	5.22	H
	3256	-58.38	-13	-45.38	-77.37	-61.63	1.53	6.93	H
									H
									H
									H
									H
	1632	-36.74	-13	-23.74	-48.83	-38.55	0.97	4.93	V
	2440	-44.36	-13	-31.36	-61.74	-46.16	1.27	5.22	V
	3256	-54.88	-13	-41.88	-74.2	-58.13	1.53	6.93	V
									V
									V
									V
									V
Middle	1640	-38.25	-13	-25.25	-49.98	-40.03	0.97	4.91	H
	2456	-45.37	-13	-32.37	-62.33	-47.21	1.28	5.27	H
	3280	-53.77	-13	-40.77	-72.85	-57.12	1.54	7.03	H
									H
									H
									H
									H
	1640	-37.74	-13	-24.74	-49.97	-39.52	0.97	4.91	V
	2456	-44.12	-13	-31.12	-61.53	-45.96	1.28	5.27	V
	3280	-53.36	-13	-40.36	-72.78	-56.71	1.54	7.03	V
									V
									V
									V
									V



Highest	1648	-50.88	-13	-37.88	-62.65	-52.64	0.98	4.89	H
	2472	-50.76	-13	-37.76	-67.76	-52.64	1.28	5.32	H
	3296	-57.67	-13	-44.67	-76.79	-61.08	1.54	7.10	H
									H
									H
									H
									H
	1648	-36.96	-13	-23.96	-49.22	-38.72	0.98	4.89	V
	2472	-44.26	-13	-31.26	-61.85	-46.14	1.28	5.32	V
	3296	-52.27	-13	-39.27	-71.73	-55.68	1.54	7.10	V
									V
									V
									V
									V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.