

A
1239277

SYM	DESCRIPTION	PCI	DATE	DRAWN	CHECKED	APPROVE
-	SEE PCI	C	2014.06.26	WUQIHU	WYH	ZJ

KOHLER
 MODEL : K-4026-0
 120V, 60Hz, 1/8 HP, 11A
 1-800-4-KOHLER

SER. NO. :

This device complies with Part 15 of FCC Rules. Operation is subject to the following two conditions:
 (1) This device may not cause harmful interference, and (2) This device must accept interference received, including interference that may cause undesired operations.
 CAN ICES-3(B)/NMB-3(B) CRAFTED IN CHINA

WARNING
 RISK OF ELECTRICAL SHOCK, DO NOT REMOVE COVER, REFER SERVICING TO QUALIFIED SERVICE PERSONNEL
 RISK OF ELECTRICAL SHOCK, CONNECT ONLY TO A GROUNDING TYPE RECEPTACLE PROTECTED BY A GROUND-FAULT CIRCUIT-INTERRUPTER(GFCI)

INTEGRATED TOILET
 40/PC
 E321009

UL US LISTED

UPC

FCC ID: N82-KOHLER014 IC: 4554A-KOHLER014

技术要求:

- 尺寸: 115*60mm
- 印刷颜色: C: 0 M: 0 Y: 0 K: 100
- 材料: 特多龙(不变色), 需通过高低温测试(需粘贴在PP材料上, 在70°、-20°、70° 温度下各测试24H观察标签是否卷曲, 起泡。卷曲、起泡视为不合格)及擦拭试验(经过高低温测试的样品, 用手指擦拭标签20次是否掉色, 掉色为不合格)此标签需通过UL&CUL认证
- 来料包装方式: 卷状, 来料包装需要在的外包装箱上贴我们标签的型号, 数量, 已及该公司的UL认证号等信息。
- 生产编号由工厂使用标签打印机自我打印。正式生产时使用下面的编码原则, 例如: KU1003001EC
 第1位: K—表示主机打Kohler logo。如果将来做OEM则打商标字母, 如T—TOTO, R—ROCA...
 第2位: U—表示主机去向, 该位决定了主机内的高压器件。U—美国市场, C—中国市场, K—韩国市场...
 第3, 4位: 10—表示主机生产年份。10—2010, 11—2011...
 第5, 6位: 03—表示主机生产月份。01—第1月...
 第7, 8, 9位: 001—表示主机流水号。001—999...
 第10位: U—表示主机出厂时遥控器默认语言。E—英文, C—中文, F—法文...
 第11位: C—表示主机组装地。U—美国, C—中国...
 打印字体为Helvetica。字体大小为8pt。
 打印部分需要字体清晰可辨, 不易脱落(即用手指擦拭20次不褪色或模糊不清)。
- 供应商: 东灵
- 公差: ±1mm
- 重要尺寸为零
- 需符合欧盟最新的RoHS要求。

APPROVED		DATE	SCALE 1:1
DRAWN	DATE	CHECKED	DATE
DO NOT SCALE DRAWING		THIS DRAWING IN DESIGN AND DETAILS IS THE PROPERTY OF KOHLER CO. AND MAY NOTBE USED EXCEPT IN CONNECTION WITH KOHLER CO. WORK. ALL RIGHTS OF DESIGN OR INVENTION ARE RESEVED.	
KOHLER SHANGHAI KOHLER ELECTRONICS LTD.			
DESCRIPTION Product Label		MATERIAL: 特多龙(不变色)	
DWG. NO. 1239277		P/N: 1239277	
		SHT: 1 OF 1	

1
2
3
4
5
SIZE A4