



FCC PART 15.247


TEST REPORT

For

Lierda Science& Technology Group Co., Ltd

Lierda Building, 425 Dengyun Rd, Hangzhou, China

FCC ID: N8NLSD4WF2MD05106

Report Type: Original Report	Product Type: WIFI Module
Test Engineer: <u>Matt Yao</u> 	
Report Number: <u>RKS151013001-00A</u>	
Report Date: <u>2015-10-29</u>	
Reviewed By: <u>Jesse Huang</u>  Prepared By: EMC Manager Bay Area Compliance Laboratories Corp. (Kunshan) Chenghu Road, Kunshan Development Zone No.248, Kunshan, Jiangsu, China Tel: +86-0512-86175000 Fax: +86-0512-88934268 www.baclcorp.com.cn	



Note: This test report is prepared for the customer shown above and for the equipment described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp.

TABLE OF CONTENTS

GENERAL INFORMATION.....	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
OBJECTIVE	4
RELATED SUBMITTAL(S)/GRANT(S).....	4
TEST METHODOLOGY	4
TEST FACILITY.....	5
SYSTEM TEST CONFIGURATION.....	6
DESCRIPTION OF TEST CONFIGURATION	6
EQUIPMENT MODIFICATIONS	6
EUT EXERCISE SOFTWARE	6
EXTERNAL I/O CABLE.....	7
BLOCK DIAGRAM OF TEST SETUP	7
SUMMARY OF TEST RESULTS	8
FCC§15.247 (i), §1.1310& §2.1091 –MAXIMUM PERMISSIBLE.....	9
EXPOSURE (MPE).....	9
APPLICABLE STANDARD	9
FCC §15.203 - ANTENNA REQUIREMENT.....	10
APPLICABLE STANDARD	10
ANTENNA CONNECTOR CONSTRUCTION	10
FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS	11
APPLICABLE STANDARD	11
MEASUREMENT UNCERTAINTY	11
EUT SETUP	11
EMI TEST RECEIVER SETUP.....	12
TEST PROCEDURE	12
TEST EQUIPMENT LIST AND DETAILS.....	12
CORRECTED FACTOR & MARGIN CALCULATION	12
TEST RESULTS SUMMARY	13
TEST DATA	13
FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS.....	16
APPLICABLE STANDARD	16
MEASUREMENT UNCERTAINTY	16
EUT SETUP	16
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP	17
TEST PROCEDURE	17
TEST EQUIPMENT LIST AND DETAILS.....	18
CORRECTED AMPLITUDE & MARGIN CALCULATION	18
TEST RESULTS SUMMARY	18
TEST DATA	19
FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH.....	32
APPLICABLE STANDARD	32
TEST PROCEDURE	32
TEST EQUIPMENT LIST AND DETAILS.....	32
TEST DATA	32
FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER.....	40

APPLICABLE STANDARD	40
TEST PROCEDURE	40
TEST EQUIPMENT LIST AND DETAILS.....	40
TEST DATA	41
FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE.....	42
APPLICABLE STANDARD	42
TEST PROCEDURE	42
TEST EQUIPMENT LIST AND DETAILS.....	42
TEST DATA	42
FCC §15.247(e) - POWER SPECTRAL DENSITY	47
APPLICABLE STANDARD	47
TEST PROCEDURE	47
TEST EQUIPMENT LIST AND DETAILS.....	47
TEST DATA	48

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

The Lierda Science& Technology Group Co., Ltd.'s product, model number: LSD4WF-2MD05106 (FCC ID: N8NLSD4WF2MD05106) or the "EUT" in this report was a WIFI Module , which was measured approximately: 32 mm (L) x16 mm (W) x 3 mm (H), rated input voltage: DC 3.3 V .

** Note: The product ' s series model number: LSD4WF-2MD05106 (XXXXY). First "XXXX" is customer number,it ranges from "0000" to "9999". Last "Y" is software version number ,it ranges from "A" to "Z". Different "Software" is only to perform different features, RF parameters are not changed.*

**All measurement and test data in this report was gathered from production sample serial number: 20151009001 (Assigned by Bay Area Compliance Laboratories Corp. (Kunshan). The EUT supplied by the applicant was received on 2015-10-09)*

Objective

This report is prepared on behalf of Lierda Science& Technology Group Co., Ltd. in accordance with Part 2-Subpart J, Part 15-Subparts A, B and C of the Federal Communication Commissions rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

Related Submittal(s)/Grant(s)

N/A

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

All emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Kunshan). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Measurement uncertainty with RF radiated emission is 5.91 dB for 30MHz-1GHz.and 4.92 dB for above 1GHz, 1.95dB for conducted measurement.

Test Facility

The test site used by Bay Area Compliance Laboratories Corp. (Kunshan) to collect test data is located on the Chenghu Lake Road, Kunshan Development Zone No.248,Kunshan, Jiangsu, China

Test site at Bay Area Compliance Laboratories Corp. (Kunshan) has been fully described in reports submitted to the Federal Communication Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on November 06, 2014. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 815570. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

For 802.11b, 802.11g and 802.11n-HT20 mode, 11 channels are provided to testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	8	2447
2	2417	9	2452
3	2422	10	2457
4	2427	11	2462
5	2432	/	/
6	2437	/	/
7	2442	/	/

For 802.11b, 802.11g, 802.11n-HT20 mode, EUT was tested with Channel 1, 6 and 11.

For 802.11n-HT40 mode, 7 channels are provided to testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
3	2422	8	2447
4	2427	9	2452
5	2432	/	/
6	2437	/	/
7	2442	/	/

EUT was tested with Channel 3, 6 and 9.

Equipment Modifications

No modification was made to the EUT tested.

EUT Exercise Software

RF test tool built-in the EUT.

The worst case was performed under:

802.11b: Data rate: 1 Mbps, Power level: 26

802.11g: Data rate: 6 Mbps, Power level: 30

802.11n-HT20: Data rate: MCS0, Power level: 30


802.11n-HT40: Data rate: MCS0, Power level: 30

External I/O Cable

Cable Description	Length (m)	From Port	To
USB Cable	0.9	EUT	PC

Block Diagram of Test Setup

For conducted emission



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§15.247 (i), §1.1307 (b) (1)& §2.1091	RF Exposure	Compliance
§15.203	Antenna Requirement	Compliance
§15.207 (a)	AC Line Conducted Emissions	Compliance
§15.247(d)	Spurious Emissions at Antenna Port	Compliance
§15.205, §15.209, §15.247(d)	Spurious Emissions	Compliance
§15.247 (a)(2)	6 dB Emission Bandwidth	Compliance
§15.247(b)(3)	Maximum Conducted Output Power	Compliance
§15.247(d)	100 kHz Bandwidth of Frequency Band Edge	Compliance
§15.247(e)	Power Spectral Density	Compliance

FCC§15.247 (i), §1.1310& §2.1091 –MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Applicable Standard

According to subpart 15.247(i)and subpart §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for Maximum Permissible Exposure (MPE) (§1.1310, §2.1091)

(B) Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (minutes)
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	/		f/1500	30
1500-100,000	/		1.0	30

f = frequency in MHz; * = Plane-wave equivalent power density;

According to §1.1310 and §2.1091 RF exposure is calculated.

Calculated Formulary:

Predication of MPE limit at a given distance

S = PG/4 π R² = power density (in appropriate units, e.g. mW/cm²);

P = power input to the antenna (in appropriate units, e.g., mW);

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain;

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);

Calculated Data:

Mode	Frequency (MHz)	Antenna Gain		Target Power		Evaluation Distance (cm)	Power Density (mW/cm ²)	MPE Limit (mW/cm ²)
		(dBi)	(numeric)	(dBm)	(mW)			
802.11b	2412	2	1.585	17.5	56.23	20	0.018	1.0
802.11g	2412	2	1.585	16.0	39.81	20	0.013	1.0
802.11n HT20	2412	2	1.585	16.0	39.81	20	0.013	1.0
802.11n HT40	2452	2	1.585	16.0	39.81	20	0.013	1.0

Note: The target power :802.11b 17 dBm±0.5
802.11g/n 15.5 dBm±0.5

Please refer to the Technical Specification, which declared by the Manufacturer.

Result: The device meet FCC MPE at 20 cm distance

FCC §15.203 - ANTENNA REQUIREMENT

Applicable Standard

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.

Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

And according to FCC 47 CFR section 15.247 (b), if the transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Antenna Connector Construction

The EUT has one integral antenna arrangement for wifi, which was permanently attached and the antenna gain is 2 dBi, fulfill the requirement of this section. Please refer to the EUT photos.

Result: Compliance.

FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

Applicable Standard

FCC§15.207


Measurement Uncertainty

Input quantities to be considered for conducted disturbance measurements maybe receiver reading, attenuation of the connection between LISN and receiver, LISN voltage division factor, LISN VDF frequency interpolation and receiver related input quantities, etc.

Based on CISPR 16-4-2, the expended combined standard uncertainty of conducted disturbance test at Bay Area Compliance Laboratories Corp. (Kunshan) is shown as below. And the uncertainty will not be taken into consideration for the test data recorded in the report.

Port	Expanded Measurement uncertainty
AC Mains	3.26 dB (k=2, 95% level of confidence)
CAT 3	3.70 dB (k=2, 95% level of confidence)
CAT 5	3.86 dB (k=2, 95% level of confidence)
CAT 6	4.64 dB (k=2, 95% level of confidence)

EUT Setup



- Note: 1. Support units were connected to second LISN.
2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The adapter was connected to a 120 VAC/60 Hz power source.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

During the conducted emission test, the adapter was connected to the outlet of the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and average detection mode.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCS30	934115/007	2014-11-4	2015-11-3
Rohde & Schwarz	LISN	ESH3-Z5	862770/011	2014-11-4	2015-11-3
Rohde & Schwarz	LISN	ESH3-Z5	892239/018	2015-6-23	2016-6-22
Rohde & Schwarz	Pulse limiter	ESH3-Z2	879940/0058	2015-6-19	2016-6-18
HP	Current probe	8710-1744	636	2015-6-19	2016-6-18
FCC	ISN	FCC-TLISN-T8-02	20376	2015-6-23	2016-6-22
Rohde & Schwarz	CE Test software	EMC 32	V 09.10.0	--	--

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Kunshan) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

Corrected Factor & Margin Calculation

The Corrected factor is calculated by adding LISN VDF (Voltage Division Factor), Cable Loss and Transient Limiter Attenuation. The basic equation is as follows:

$$\text{Correction Factor} = \text{LISN VDF} + \text{Cable Loss}$$

The “Margin” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7 dB means the emission is 7 dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Part 15.207, the worst margin reading as below:

12.80 dB at 0.175000MHz in the Line conducted mode

Refer to CISPR16-4-2:2011 and CISPR 16-4-1:2009, the measured level complies with the limit if

$$L_m + U_{(Lm)} \leq L_{lim} + U_{cisp}$$

In BACL, $U_{(Lm)}$ is less than U_{cisp} , if L_m is less than L_{lim} , it implies that the EUT complies with the limit.


Test Data

Environmental Conditions


Temperature:	23 °C
Relative Humidity:	56 %
ATM Pressure:	101.0 kPa

The testing was performed by Matt Yao on 2015-10-22.

EUT operation mode: Transmitting

AC 120V/60 Hz, Line

Frequency (MHz)	QuasiPeak (dB μ V)	Average (dB μ V)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dB μ V)	Comment
0.175000	---	36.57	9.000	L1	11.0	18.15	54.72	Compliance
0.175000	51.92	---	9.000	L1	11.0	12.80	64.72	Compliance
0.200000	---	29.13	9.000	L1	11.0	24.48	53.61	Compliance
0.200000	45.72	---	9.000	L1	11.0	17.89	63.61	Compliance
0.240000	---	25.32	9.000	L1	11.0	26.78	52.10	Compliance
0.240000	40.25	---	9.000	L1	11.0	21.85	62.10	Compliance
0.480000	---	23.86	9.000	L1	11.0	22.48	46.34	Compliance
0.480000	33.69	---	9.000	L1	11.0	22.65	56.34	Compliance
3.770000	---	17.99	9.000	L1	11.3	28.01	46.00	Compliance
3.770000	27.82	---	9.000	L1	11.3	28.18	56.00	Compliance
5.000000	---	25.86	9.000	L1	11.3	20.14	46.00	Compliance
5.000000	30.78	---	9.000	L1	11.3	29.22	60.00	Compliance

AC 120V/60 Hz, Neutral

Frequency (MHz)	QuasiPeak (dB μ V)	Average (dB μ V)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dB μ V)	Comment
0.160000	---	28.53	9.000	N	11.0	26.93	55.46	Compliance
0.160000	50.84	---	9.000	N	11.0	14.62	65.46	Compliance
0.175000	---	30.74	9.000	N	11.0	23.98	54.72	Compliance
0.175000	50.23	---	9.000	N	11.0	14.49	64.72	Compliance
0.200000	---	29.54	9.000	N	11.0	24.07	53.61	Compliance
0.200000	43.95	---	9.000	N	11.0	19.66	63.61	Compliance
0.240000	---	25.72	9.000	N	11.0	26.38	52.10	Compliance
0.240000	38.88	---	9.000	N	11.0	23.22	62.10	Compliance
0.500000	---	26.98	9.000	N	11.0	19.02	46.00	Compliance
0.500000	34.95	---	9.000	N	11.0	21.05	56.00	Compliance
4.850000	---	20.64	9.000	N	11.4	25.36	46.00	Compliance
4.850000	30.88	---	9.000	N	11.4	25.12	56.00	Compliance

Note:

- 1) Corr.=LISN VDF (Voltage Division Factor) + Cable Loss
- 2) Corrected Amplitude = Reading + Corr.
- 3) Margin = Limit -Corrected Amplitude

FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS

Applicable Standard

FCC §15.247 (d); §15.209; §15.205;


Measurement Uncertainty


All measurements involve certain levels of uncertainties, especially in field of EMC. The factors contributing to uncertainties are spectrum analyzer, cable loss, antenna factor calibration, antenna directivity, antenna factor variation with height, antenna phase center variation, antenna factor frequency interpolation, measurement distance variation, site imperfections, mismatch (average), and system repeatability.

Based on CISPR 16-4-2, the expended combined standard uncertainty of radiation emissions at Bay Area Compliance Laboratories Corp. (Kunshan) is 5.91 dB for 30MHz-1GHz and 4.92 dB for above 1GHz, 1.95dB for conducted measurement at antenna port. And the uncertainty will not be taken into consideration for the test data recorded in the report

EUT Setup

Below 1 GHz:



Above 1GHz:

The radiated emission tests were performed in the 3 meters test site, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, and FCC 15.247 limits.

The adapter was connected to a 120 VAC/60 Hz power source.

EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Detector
30 MHz – 1000 MHz	100 kHz	300 kHz	120 kHz	QP
Above 1 GHz	1MHz	3 MHz	/	PK
	1MHz	10 Hz	/	Ave.

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz-1 GHz, peak and Average detection modes for frequencies above 1 GHz.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Sonoma Instrument	Amplifier	330	171377	2015-9-16	2016-9-16
Rohde & Schwarz	EMI Test Receiver	ESCI	100195	2015-5-20	2016-5-19
Sunol Sciences	Broadband Antenna	JB3	A090314-2	2014-11-7	2015-11-6
ETS	Horn Antenna	3115	6229	2014-11-7	2015-11-6
Rohde & Schwarz	Signal Analyzer	FSIQ26	100048	2014-11-4	2015-11-3
Mini	Pre-amplifier	ZVA-183-S+	857001418	2015-9-16	2016-9-16
R&S	Auto test Software	EMC32	V 09.10.0	-	-
BACL	RF cable	KS-LAB-012	KS-LAB-012	2015-06-16	2015-12-15

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Kunshan) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “Margin” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Title 47, Part 15, Subpart C, section 15.205, 15.209 and 15.247.

**7.29dB at 4824 MHz in the Horizontal polarization
for 802.11b mode**

Refer to CISPR16-4-2:2011 and CISPR 16-4-1:2009, the measured level complies with the limit if

$$L_m + U_{(Lm)} \leq L_{\lim} + U_{\text{cispr}}$$

In BACL, $U_{(Lm)}$ is less than U_{cispr} , if L_m is less than L_{\lim} , it implies that the EUT complies with the limit.

Test Data

Environmental Conditions


Temperature:	25 °C
Relative Humidity:	55 %
ATM Pressure:	101.0 kPa

The testing was performed by Matt Yao on 2015-10-22.

EUT operation mode: Transmitting

30 MHz-1 GHz:

The worst case was performed under 802.11b mode



Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB)	Corrected Amplitude (dB μ V/m)	FCC Part 15.247/205/209	
	Reading (dB μ V)	Detector (QP/QP/Ave.)		Height (cm)	Polar (H/V)			Limit (dB μ V/m)	Margin (dB)
44.186250	42.12	QP	143.0	100.0	V	-12.9	29.22	40.00	10.78
86.138750	39.74	QP	331.0	100.0	V	-17.1	22.64	40.00	17.36
147.733750	29.99	QP	99.0	200.0	H	-12.1	17.89	43.50	25.61
283.655000	44.26	QP	355.0	100.0	H	-10.6	33.66	46.00	12.34
558.892500	39.10	QP	0.0	200.0	H	-5.1	34.00	46.00	12.00
818.246250	34.17	QP	146.0	100.0	H	-1.3	32.87	46.00	13.13

1GHz-25GHz**802.11b Mode:**

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB)	Corrected Amplitude (dB μ V/m)	FCC Part 15.247/205/209	
	Reading (dB μ V)	Detector (PK/QP/Ave.)		Height (cm)	Polar (H/V)			Limit (dB μ V/m)	Margin (dB)
Low Channel (2412 MHz)									
2412	96.66	PK	183.0	150.00	V	2.90	99.56	/	/
2412	92.92	Ave	183.0	150.00	V	2.90	95.82	/	/
2412	95.83	PK	91.0	150.00	H	2.90	98.73	/	/
2412	91.41	Ave	91.0	150.00	H	2.90	94.31	/	/
2315	46.26	PK	59.0	200.00	V	1.00	47.26	73.90	26.64
2315	25.18	Ave	59.0	150.00	H	1.00	26.18	53.90	27.72
2341	42.13	PK	74.0	150.00	V	1.70	43.83	73.90	30.07
2341	20.47	Ave	74.0	200.00	H	1.70	22.17	53.90	31.73
4824	50.21	PK	225.0	200.00	V	13.80	64.01	73.90	9.89
4824	32.81	Ave	225.0	150.00	H	13.80	46.61	53.90	7.29
6657	38.00	PK	50.0	200.00	V	17.10	55.10	73.90	18.80
6657	21.56	Ave	50.0	150.00	H	17.10	38.66	53.90	15.24
7236	42.48	PK	127.0	150.00	V	18.80	61.28	73.90	12.62
7236	23.65	Ave	127.0	200.00	H	18.80	42.45	53.90	11.45

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB)	Corrected Amplitude (dB μ V/m)	FCC Part 15.247/205/209	
	Reading (dB μ V)	Detector (PK/QP/Ave.)		Height (cm)	Polar (H/V)			Limit (dB μ V/m)	Margin (dB)
Middle Channel (2437 MHz)									
2437	96.15	PK	234.00	150.00	V	3.10	99.25	/	/
2437	92.07	Ave	234.00	150.00	V	3.10	95.17	/	/
2437	94.96	PK	45.00	200.00	H	3.10	98.06	/	/
2437	90.69	Ave	45.00	200.00	H	3.10	93.79	/	/
1489	44.91	PK	117.00	150.00	V	0.00	44.91	73.90	28.99
1489	24.01	Ave	117.00	150.00	H	0.00	24.01	53.90	29.89
1597	41.61	PK	66.00	200.00	V	0.70	42.31	73.90	31.59
1597	21.35	Ave	66.00	200.00	H	0.70	22.05	53.90	31.85
4874	49.38	PK	86.00	150.00	V	13.90	63.28	73.90	10.62
4874	31.87	Ave	86.00	150.00	H	13.90	45.77	53.90	8.13
6647	34.38	PK	149.00	200.00	V	18.80	53.18	73.90	20.72
6647	18.60	Ave	149.00	200.00	H	18.80	37.40	53.90	16.50
7311	41.69	PK	94.00	150.00	V	18.90	60.59	73.90	13.31
7311	22.81	Ave	94.00	150.00	H	18.90	41.71	53.90	12.19

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB)	Corrected Amplitude (dB μ V/m)	FCC Part 15.247/205/209	
	Reading (dB μ V)	Detector (PK/QP/Ave.)		Height (cm)	Polar (H/V)			Limit (dB μ V/m)	Margin (dB)
High Channel (2462 MHz)									
2462	95.36	PK	163.00	200.00	V	3.10	98.46	/	/
2462	91.83	Ave	163.00	200.00	V	3.10	94.93	/	/
2462	94.17	PK	35.00	150.00	H	3.10	97.27	/	/
2462	89.22	Ave	35.00	150.00	H	3.10	92.32	/	/
2485	41.14	PK	59.00	150.00	V	4.20	45.34	73.90	28.56
2485	19.96	Ave	59.00	150.00	H	4.20	24.16	53.90	29.74
2499	36.82	PK	174.00	200.00	V	4.20	41.02	73.90	32.88
2499	18.58	Ave	174.00	200.00	H	4.20	22.78	53.90	31.12
4924	48.76	PK	89.00	200.00	V	14.00	62.76	73.90	11.14
4924	30.16	Ave	89.00	200.00	H	14.00	44.16	53.90	9.74
6622	33.75	PK	133.00	150.00	V	18.70	52.45	73.90	21.45
6622	18.38	Ave	133.00	150.00	H	18.70	37.08	53.90	16.82
7386	40.33	PK	227.00	200.00	V	19.80	60.13	73.90	13.77
7386	21.68	Ave	227.00	200.00	H	19.80	41.48	53.90	12.42

802.11g Mode:

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB)	Corrected Amplitude (dB μ V/m)	FCC Part 15.247/205/209	
	Reading (dB μ V)	Detector (PK/QP/Ave.)		Height (cm)	Polar (H/V)			Limit (dB μ V/m)	Margin (dB)
Low Channel (2412 MHz)									
2412	93.35	PK	72.0	150.00	V	2.90	99.05	/	/
2412	91.92	Ave	72.0	150.00	V	2.90	95.31	/	/
2412	92.47	PK	38.0	200.00	H	2.90	98.22	/	/
2412	90.66	Ave	38.0	200.00	H	2.90	93.80	/	/
2315	35.20	PK	148.0	200.00	V	1.10	46.77	73.90	27.13
2315	20.11	Ave	148.0	200.00	H	1.10	25.69	53.90	28.21
2382	38.51	PK	63.0	150.00	V	1.80	43.34	73.90	30.56
2382	19.96	Ave	63.0	150.00	H	1.80	21.85	53.90	32.05
4824	37.27	PK	59.0	200.00	V	13.80	63.69	73.90	10.21
4824	25.60	Ave	59.0	200.00	H	13.80	46.29	53.90	7.61
6696	35.97	PK	162.0	150.00	V	17.20	54.78	73.90	19.12
6696	22.81	Ave	162.0	150.00	H	17.20	38.54	53.90	15.36
7236	35.85	PK	78.0	200.00	V	18.80	61.16	73.90	12.74
7236	23.97	Ave	78.0	200.00	H	18.80	42.33	53.90	11.57

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB)	Corrected Amplitude (dB μ V/m)	FCC Part 15.247/205/209	
	Reading (dB μ V)	Detector (PK/QP/Ave.)		Height (cm)	Polar (H/V)			Limit (dB μ V/m)	Margin (dB)
Middle Channel (2437 MHz)									
2437	95.45	PK	82.0	200.0	V	3.10	98.55	/	/
2437	91.71	Ave	82.0	200.0	V	3.10	94.81	/	/
2437	94.62	PK	120.0	200.0	H	3.10	97.72	/	/
2437	90.20	Ave	120.0	150.0	H	3.10	93.30	/	/
1495	47.27	PK	190.0	150.0	V	0.00	47.27	73.90	26.63
1495	25.19	Ave	190.0	150.0	H	0.00	25.19	53.90	28.71
1584	43.14	PK	80.0	150.0	V	0.70	43.84	73.90	30.06
1584	21.65	Ave	80.0	150.0	H	0.70	22.35	53.90	31.55
4874	49.29	PK	115.0	200.0	V	13.90	63.19	73.90	10.71
4874	31.89	Ave	115.0	200.0	H	13.90	45.79	53.90	8.11
6652	35.48	PK	220.0	150.0	V	18.80	54.28	73.90	19.62
6652	19.24	Ave	220.0	150.0	H	18.80	38.04	53.90	15.86
7311	42.76	PK	95.0	150.0	V	18.90	61.66	73.90	12.24
7311	22.93	Ave	95.0	150.0	H	18.90	41.83	53.90	12.07

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB)	Corrected Amplitude (dB μ V/m)	FCC Part 15.247/205/209	
	Reading (dB μ V)	Detector (PK/QP/Ave.)		Height (cm)	Polar (H/V)			Limit (dB μ V/m)	Margin (dB)
High Channel (2462 MHz)									
2462	94.95	PK	96.0	200.0	V	3.10	98.05	/	/
2462	91.21	Ave	96.0	200.0	V	3.10	94.31	/	/
2462	94.12	PK	36.0	150.0	H	3.10	97.22	/	/
2462	89.70	Ave	36.0	150.0	H	3.10	92.80	/	/
2484	42.32	PK	166.0	150.0	V	4.20	46.52	73.90	27.38
2484	20.28	Ave	166.0	150.0	H	4.20	24.48	53.90	29.42
2496	38.93	PK	60.0	150.0	V	4.20	43.13	73.90	30.77
2496	17.40	Ave	60.0	150.0	H	4.20	21.60	53.90	32.30
4924	48.47	PK	20.0	200.0	V	14.00	62.47	73.90	11.43
4924	31.04	Ave	20.0	200.0	H	14.00	45.04	53.90	8.86
6663	34.84	PK	286.0	200.0	V	18.70	53.54	73.90	20.36
6663	18.61	Ave	286.0	200.0	H	18.70	37.31	53.90	16.59
7386	41.14	PK	170.0	200.0	V	19.80	60.94	73.90	12.96
7386	21.28	Ave	170.0	200.0	H	19.80	41.08	53.90	12.82

802.11n-HT20 Mode:

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB)	Corrected Amplitude (dB μ V/m)	FCC Part 15.247/205/209	
	Reading (dB μ V)	Detector (PK/QP/Ave.)		Height (cm)	Polar (H/V)			Limit (dB μ V/m)	Margin (dB)
Low Channel (2412 MHz)									
2412	95.05	PK	96.0	150.0	V	2.90	97.95	/	/
2412	91.31	Ave	96.0	150.0	V	2.90	94.21	/	/
2412	94.22	PK	141.0	200.00	H	2.90	97.12	/	/
2412	89.80	Ave	141.0	200.00	H	2.90	92.70	/	/
2359	45.40	PK	120.0	150.00	V	1.10	46.50	73.90	27.40
2359	20.17	Ave	120.0	150.00	H	1.10	21.27	53.90	32.63
2389	40.86	PK	89.0	150.00	V	1.80	42.66	73.90	31.24
2389	20.66	Ave	89.0	150.00	H	1.80	22.46	53.90	31.44
4824	44.78	PK	66.0	200.00	V	13.80	58.58	73.90	15.32
4824	29.14	Ave	66.0	200.00	H	13.80	42.94	53.90	10.96
6225	33.38	PK	38.0	150.0	V	17.20	50.58	73.90	23.32
6225	20.21	Ave	38.0	150.0	H	17.20	37.41	53.90	16.49
7236	38.33	PK	126.0	200.00	V	18.80	57.13	73.90	16.77
7236	21.25	Ave	126.0	200.00	H	18.80	40.05	53.90	13.85

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB)	Corrected Amplitude (dB μ V/m)	FCC Part 15.247/205/209	
	Reading (dB μ V)	Detector (PK/QP/Ave.)		Height (cm)	Polar (H/V)			Limit (dB μ V/m)	Margin (dB)
Middle Channel (2437 MHz)									
2437	94.35	PK	304.0	150.0	V	3.10	97.45	/	/
2437	90.61	Ave	304.0	150.0	V	3.10	93.71	/	/
2437	93.52	PK	97.0	150.0	H	3.10	96.62	/	/
2437	89.10	Ave	97.0	150.0	H	3.10	92.20	/	/
1495	45.68	PK	192.0	200.0	V	0.00	45.68	73.90	28.22
1495	20.46	Ave	192.0	200.0	H	0.00	20.46	53.90	33.44
1584	41.14	PK	58.0	200.00	V	0.70	41.84	73.90	32.06
1584	20.97	Ave	58.0	200.00	H	0.70	21.67	53.90	32.23
4874	43.86	PK	228.0	200.0	V	13.90	57.76	73.90	16.14
4874	28.19	Ave	228.0	200.0	H	13.90	42.09	53.90	11.81
6227	30.96	PK	146.0	150.0	V	18.80	49.76	73.90	24.14
6227	17.79	Ave	146.0	150.0	H	18.80	36.59	53.90	17.31
7311	37.57	PK	159.0	200.00	V	18.90	56.47	73.90	17.43
7311	20.33	Ave	159.0	200.00	H	18.90	39.23	53.90	14.67



Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB)	Corrected Amplitude (dB μ V/m)	FCC Part 15.247/205/209	
	Reading (dB μ V)	Detector (PK/QP/Ave.)		Height (cm)	Polar (H/V)			Limit (dB μ V/m)	Margin (dB)
High Channel (2462 MHz)									
2462	92.36	PK	112.0	200.0	V	3.10	95.46	/	/
2462	89.90	Ave	112.0	200.0	V	3.10	93.00	/	/
2462	91.60	PK	95.0	150.0	H	3.10	94.70	/	/
2462	89.34	Ave	95.0	150.0	H	3.10	92.44	/	/
2484	41.03	PK	171.0	150.0	V	4.20	45.23	73.90	28.67
2484	15.81	Ave	171.0	150.0	H	4.20	20.01	53.90	33.89
2491	37.19	PK	44.0	150.0	V	4.20	41.39	73.90	32.51
2491	17.02	Ave	44.0	150.0	H	4.20	21.22	53.90	32.68
4924	30.61	PK	321.0	150.0	V	18.70	49.31	73.90	24.59
4924	17.44	Ave	321.0	150.0	H	18.70	36.14	53.90	17.76
6230	43.31	PK	235.0	200.0	V	14.00	57.31	73.90	16.59
6230	27.64	Ave	235.0	200.0	H	14.00	41.64	53.90	12.26
7386	36.22	PK	77.0	200.0	V	19.80	56.02	73.90	17.88
7386	18.98	Ave	77.0	200.0	H	19.80	38.78	53.90	15.12

802.11n-HT40 Mode:


Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB)	Corrected Amplitude (dB μ V/m)	FCC Part 15.247/205/209	
	Reading (dB μ V)	Detector (PK/QP/Ave.)		Height (cm)	Polar (H/V)			Limit (dB μ V/m)	Margin (dB)
Low Channel (2422 MHz)									
2422	92.06	PK	288.0	200.00	V	2.90	94.96	/	/
2422	89.60	Ave	288.0	200.00	V	2.90	92.50	/	/
2422	91.30	PK	89.0	200.00	H	2.90	94.20	/	/
2422	89.04	Ave	89.0	200.00	H	2.90	91.94	/	/
2380	43.88	PK	96.0	150.00	V	1.10	44.98	73.90	28.92
2380	18.66	Ave	96.0	150.00	H	1.10	19.76	53.90	34.14
2390	39.34	PK	343.0	200.00	V	1.80	41.14	73.90	32.76
2390	19.17	Ave	343.0	200.00	H	1.80	20.97	53.90	32.93
4844	35.26	PK	85.0	200.00	V	13.80	49.06	73.90	24.84
4844	22.09	Ave	85.0	200.00	H	13.80	35.89	53.90	18.01
6875	39.86	PK	137.0	150.00	V	17.20	57.06	73.90	16.84
6875	24.19	Ave	137.0	150.00	H	17.20	41.39	53.90	12.51
7266	36.97	PK	113.0	200.00	V	18.80	55.77	73.90	18.13
7266	19.73	Ave	113.0	200.00	H	18.80	38.53	53.90	15.37

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB)	Corrected Amplitude (dB μ V/m)	FCC Part 15.247/205/209	
	Reading (dB μ V)	Detector (PK/QP/Ave.)		Height (cm)	Polar (H/V)			Limit (dB μ V/m)	Margin (dB)
Middle Channel (2437 MHz)									
2437	91.41	PK	305.0	200.0	V	3.10	94.51	/	/
2437	88.95	Ave	305.0	200.0	V	3.10	92.05	/	/
2437	90.65	PK	169.0	150.0	H	3.10	93.75	/	/
2437	88.39	Ave	169.0	150.0	H	3.10	91.49	/	/
1486	44.53	PK	119.0	150.00	V	0.00	44.53	73.90	29.37
1486	19.31	Ave	119.0	150.00	H	0.00	19.31	53.90	34.59
1584	39.99	PK	226.0	200.0	V	0.70	40.69	73.90	33.21
1584	19.82	Ave	226.0	200.0	H	0.70	20.52	53.90	33.38
4874	34.71	PK	77.0	200.0	V	13.90	48.61	73.90	25.29
4874	21.54	Ave	77.0	200.0	H	13.90	35.44	53.90	18.46
6010	37.81	PK	93.0	200.0	V	18.80	56.61	73.90	17.29
6010	22.14	Ave	93.0	200.0	H	18.80	40.94	53.90	12.96
7311	36.42	PK	344.0	200.0	V	18.90	55.32	73.90	18.58
7311	19.18	Ave	344.0	200.0	H	18.90	38.08	53.90	15.82


Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB)	Corrected Amplitude (dB μ V/m)	FCC Part 15.247/205/209	
	Reading (dB μ V)	Detector (PK/QP/Ave.)		Height (cm)	Polar (H/V)			Limit (dB μ V/m)	Margin (dB)
High Channel (2452 MHz)									
2452	91.15	PK	104.0	150.0	V	3.10	94.25	/	/
2452	88.69	Ave	104.0	150.0	V	3.10	91.79	/	/
2452	90.39	PK	74.0	200.0	H	3.10	93.49	/	/
2452	88.13	Ave	74.0	200.0	H	3.10	91.23	/	/
2484	40.07	PK	58.0	200.0	V	4.20	44.27	73.90	29.63
2484	14.85	Ave	58.0	200.0	H	4.20	19.05	53.90	34.85
2496	36.23	PK	277.0	150.0	V	4.20	40.43	73.90	33.47
2496	16.06	Ave	277.0	150.0	H	4.20	20.26	53.90	33.64
4904	37.65	PK	148.0	150.0	V	18.70	56.35	73.90	17.55
4904	21.98	Ave	148.0	150.0	H	18.70	40.68	53.90	13.22
6230	34.35	PK	65.0	200.0	V	14.00	48.35	73.90	25.55
6230	21.18	Ave	65.0	200.0	H	14.00	35.18	53.90	18.72
7356	35.26	PK	66.0	150.0	V	19.80	55.06	73.90	18.84
7356	18.02	Ave	66.0	150.0	H	19.80	37.82	53.90	16.08



Conducted Spurious Emissions at Antenna Port**802.11b Low Channel****802.11b Middle Channel**



802.11b High Channel







802.11g Low Channel



802.11g Middle Channel**802.11g High Channel**

802.11n-HT20 Low Channel**802.11n-HT20 Middle Channel**

802.11n-HT20 High Channel**802.11n-HT40 Low Channel**

802.11n-HT40 Middle Channel**802.11n-HT40 High Channel**


FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH

Applicable Standard

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 6 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.



Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	Signal Analyzer	FSIQ26	100048	2014-11-4	2015-11-3
BACL	RF cable	KS-LAB-012	KS-LAB-012	2015-06-16	2015-12-15

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Kunshan) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	27 °C
Relative Humidity:	55 %
ATM Pressure:	101.0 kPa

The testing was performed by Matt Yao on 2015-10-22.


Test Result: Pass.

Please refer to the following tables and plots.


EUT operation mode: Transmitting

Channel	Frequency (MHz)	6 dB Emission Bandwidth (MHz)	Limit (kHz)
802.11b mode			
Low	2412	8.42	≥500
Middle	2437	8.36	≥500
High	2462	8.36	≥500
802.11g mode			
Low	2412	16.59	≥500
Middle	2437	17.01	≥500
High	2462	16.59	≥500
802.11n-HT20 mode			
Low	2412	17.68	≥500
Middle	2437	17.73	≥500
High	2462	17.68	≥500
802.11n-HT40 mode			
Low	2422	36.31	≥500
Middle	2437	35.95	≥500
High	2452	35.95	≥500


802.11b Low Channel




802.11b Middle Channel




802.11b High Channel




802.11g Low Channel







802.11g Middle Channel




802.11g High Channel




802.11n-HT20 Low Channel**802.11n-HT20 Middle Channel**

802.11n-HT20 High Channel**802.11n-HT40 Low Channel**

802.11n-HT40 Middle Channel



802.11n-HT40 High Channel




FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER

Applicable Standard

According to FCC §15.247(b) (3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

Test Procedure

1. Place the EUT on a bench and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to one test equipment.
3. Add a correction factor to the display.



Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Agilent	Wideband Power Sensor	N1921A	MY54210120	2014-11-03	2015-11-03
Agilent	Wideband Power Sensor	N1921A	MY54210115	2014-11-03	2015-11-03
Agilent	P-Series Power Meter	N1921A	MY5000465	2014-11-03	2015-11-03
BACL	RF cable	KS-LAB-012	KS-LAB-012	2015-06-16	2015-12-15

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Kunshan) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

Test Data**Environmental Conditions**

Temperature:	27 °C
Relative Humidity:	55 %
ATM Pressure:	101.0 kPa

The testing was performed by Matt Yao on 2015-10-23

EUT operation mode: Transmitting

Channel	Frequency (MHz)	Max Conducted Peak Output Power (dBm)	Limit (dBm)
802.11b			
Low	2412	17.37	30
Middle	2437	17.27	30
High	2462	17.18	30
802.11g			
Low	2412	15.93	30
Middle	2437	15.57	30
High	2462	15.29	30
802.11n-HT20			
Low	2412	14.83	30
Middle	2437	14.64	30
High	2462	14.14	30
802.11n-HT40			
Low	2422	14.67	30
Middle	2437	14.31	30
High	2452	14.02	30

FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE

Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	Signal Analyzer	FSIQ26	100048	2014-11-4	2015-11-3
BACL	RF cable	KS-LAB-012	KS-LAB-012	2015-06-16	2015-12-15

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Kunshan) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions


Temperature:	27 °C
Relative Humidity:	55 %
ATM Pressure:	101.0 kPa

The testing was performed by Matt Yao on 2015-10-22.


Test Result: *Compliance*

Please refer to the following table and plots.


802.11b: Band Edge, Left Side




802.11b: Band Edge, Right Side







802.11g: Band Edge, Left Side



802.11g: Band Edge, Right Side



802.11n-HT20: Band Edge, Left Side**802.11n-HT20: Band Edge, Right Side**

802.11n-HT40: Band Edge, Left Side**802.11n-HT40: Band Edge, Right Side**

FCC §15.247(e) - POWER SPECTRAL DENSITY

Applicable Standard

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

Test Procedure

According to KDB558074 D01 DTS Meas Guidance v03r03 sub-clause 10.2

1. Use this procedure when the maximum peak conducted output power in the fundamental emission is used to demonstrate compliance.
2. Set the RBW to: $3\text{kHz} \leq \text{RBW} \leq 100\text{ kHz}$.
3. Set the VBW $\geq 3 \times \text{RBW}$.
4. Set the span to 1.5 times the DTS bandwidth.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level within the RBW.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	Signal Analyzer	FSIQ26	100048	2014-11-4	2015-11-3
BACL	RF cable	KS-LAB-012	KS-LAB-012	2015-06-16	2015-12-15

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Kunshan) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

Test Data**Environmental Conditions**



Temperature:	27 °C
Relative Humidity:	55 %
ATM Pressure:	101.0 kPa

The testing was performed by Matt Yao on 2015-10-22.


EUT operation mode: Transmitting

Test Result: Pass


Channel	Frequency (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)
802.11b mode			
Low	2412	-9.12	≤8
Middle	2437	-9.58	≤8
High	2462	-10.38	≤8
802.11g mode			
Low	2412	-20.27	≤8
Middle	2437	-19.99	≤8
High	2462	-19.47	≤8
802.11n-HT20 mode			
Low	2412	-21.32	≤8
Middle	2437	-20.82	≤8
High	2462	-20.84	≤8
802.11n-HT40 mode			
Low	2422	-22.44	≤8
Middle	2437	-22.29	≤8
High	2452	-22.31	≤8

Power Spectral Density, 802.11b Low Channel**Power Spectral Density, 802.11b Middle Channel**


Power Spectral Density, 802.11b High Channel




Power Spectral Density, 802.11g Low Channel







Power Spectral Density, 802.11g Middle Channel





Power Spectral Density, 802.11g High Channel



Power Spectral Density, 802.11n-HT20 Low Channel**Power Spectral Density, 802.11n-HT20 Middle Channel**

Power Spectral Density, 802.11n-HT20 High Channel**Power Spectral Density, 802.11n-HT40 Low Channel**

Power Spectral Density, 802.11n-HT40 Middle Channel**Power Spectral Density, 802.11n-HT40 High Channel********* END OF REPORT *******