

Date: 2004-04-08 TEST REPORT Page 1 of 24

No.: HM150102

Applicant: Ewig Industries Co., Ltd.

Description of Samples: Model name: Air Quality Sensor

Model no.: 001A21 Brand name: Ewig

FCC ID: N9Z001A21 IC: 4351A-001A21

Date Samples Received: 2004-02-25

Date Tested: 2004-03-10 to 2003-03-11

Investigation Requested: FCC Part 15 Subpart C

Conclusions: See the attached sheets for details

Remarks: ----

Patrick Wong, EMC DAR Approved Signatory

This report shall not be reproduced unless with prior written approval from the Hong Kong Standards and Testing Centre.



No.: HM150102

CONTENT:

	Cover Content Conclusions	Page 1 of 24 Page 2-3 of 24 Page 4 of 24
<u>1.0</u>	General Details	
1.1	Test Laboratory	Page 5 of 24
1.2	Applicant Details Applicant HKSTC Code Number for Applicant Manufacturer	Page 5 of 24
1.3	Equipment Under Test [EUT] Description of EUT operation	Page 6 of 24
1.4	Date of Order	Page 6 of 24
1.5	Submitted Samples	Page 6 of 24
1.6	Test Duration	Page 6 of 24
1.7	Country of Origin	Page 6 of 24
1.8	Additional Information of EUT	Page 7 of 24
2.0	Technical Details	
2.1	Investigations Requested	Page 8 of 24
2.2	Test Standards and Results Summary	Page 8 of 24
<u>3.0</u>	Test Results	
3.1	Emission	Page 9-14 of 24
3.2	Bandwidth Measurement	Page 15-16 of 24



No.: HM150102

Appendix A

List of Measurement Equipment Page 17 of 24

Appendix B

Duty Cycle Correction During 100 msec Page 18-19 of 24

Appendix C

Periodic Operation Page 20-21 of 24

Appendix D

Photographs Page 23-24 of 24



Date: 2004-04-08 TEST REPORT Page 4 of 24

No.: HM150102

CONCLUSIONS

The submitted product was deemed to have <u>COMPLIED</u> with the requirements of Federal Communications Commission [FCC] Rules and Regulations Part 15. The tests were performed in accordance with the standards described above and on Section 2.2 in this Test Report.



No.: HM150102

1.0 General Details

1.1 Test Laboratory

The Hong Kong Standards and Testing Centre Ltd. EMC Laboratory 10 Dai Wang Street, Taipo Industrial Estate New Territories, Hong Kong

Telephone: 852 2666 1888 Fax: 852 2664 4353

1.2 Applicant Details Applicant

EWIG INDUSTRIES CO., LTD. 13/F., Houtex Ind'l Bldg., 16 Hung To Road, Kwun Tong, Kowloon, Hong Kong.

HKSTC Code Number for Applicant

EWI001

Manufacturer

Q & S MANUFACTURING CO., LTD. Yin Shan Industrial District, Fu Gang Village, Xiang Mang West Road, Qing Xi Town, Dongguan City, Guang Dong Province, China



Date: 2004-04-08 TEST REPORT Page 6 of 24

No.: HM150102

1.3 Equipment Under Test [EUT] Description of Sample

Product: Air Quality Sensor

Manufacturer: Q & S Manufacturing Co., Ltd.

Brand Name: Ewig Model Number: 001A21

Input Voltage: 6Vd.c ("AAA" size battery x 4)

1.3.1 Description of EUT Operation

The Equipment Under Test (EUT) is an Ewig Industries Co., Ltd., Air Quality Sensor. The transmitter is an automatic transmitter. The EUT is to transmit RF signal while temperature measurement is changed. The EUT is for data transmission, Modulation by Data Code. Tape is pulses modulation.

1.4 Date of Order

2004-02-25

1.5 Submitted Sample(s):

2 Samples per model

1.6 Test Duration

2004-03-10 to 2003-03-11

1.7 Country of Origin

China



No.: HM150102

1.8 Additional Information of EUT

	Submitted	Not Available
User Manual	\boxtimes	
Part List	\boxtimes	
Circuit Diagram	\boxtimes	
Printed Circuit Board [PCB] Layout	\boxtimes	
Block diagram	\boxtimes	
FCC ID Label	\boxtimes	



Date: 2004-04-08 TEST REPORT Page 8 of 24

No.: HM150102

2.0 <u>Technical Details</u>

2.1 Investigations Requested

Perform ElectroMagnetic Interference measurement in accordance with FCC 47CFR [Codes of Federal Regulations] Part 15 and ANSI C63.4:2003 for FCC Certification.

2.2 Test Standards and Results Summary Tables

EMISSION						
	Resul	Its Summary				
Test Condition	Test Requirement	Test Method	Class /	Т	est Resu	lt
			Severity	Pass	Failed	N/A
Field Strength of Fundamental Emissions & Spurious Emissions	FCC 47CFR 15.231e	ANSI C63.4:2003	N/A			
Radiated Emissions, 30MHz to 1GHz	FCC 47CFR 15.209	ANSI C63.4:2003	Class B			
Conducted Emissions on AC, 0.15MHz to 30MHz	FCC 47CFR 15.207	ANSI C63.4:2003	Class B			

Note: N/A - Not Applicable

Requirement of FCC Part 15 section 15.209 and 15.207 is equivalent to the requirement of RSS-210 (Low Power License-Exempt Radiocommunication Devices (All Frequency Bands)) section 6.2.1 and 9. The tests were performed according to FCC Part 15 which covers the scope of RSS-210.



Date: 2004-04-08 TEST REPORT Page 9 of 24

No.: HM150102

3.0 Test Results

3.1 Emission

3.1.1 Radiated Emissions


Test Requirement: FCC 47CFR 15.231e
Test Method: ANSI C63.4:2003
Test Date: 2004-03-10
Mode of Operation: On mode

Test Method:

The sample was placed 0.8m above the ground plane on the OATS *. Measurements in both horizontal and vertical polarities were performed. During the test, each emission was maximized by: having the EUT continuously working, investigate all operating modes, rotated about all 3 axis (X, Y & Z) to obtain worst position, manipulating interconnecting cables, rotating turntable, varying antenna height from 1m to 4m in both horizontal and vertical polarization. The emissions worst-case are shown in Test Results of the following pages.

*: OATS [Open Area Test Site] located at HKSTC with a metal ground plane on filed with the FCC pursuant to section 2.948 of the FCC rules, with Registration Number: 90657.

Test Setup:





No.: HM150102

Limits for Field Strength of Fundamental Emissions [FCC 47CFR 15.231e]:

Frequency Range of Fundamental	Field Strength of Fundamental Emission	Field Strength of Fundamental Emission
	[Peak]	[Average]
[MHz]	[μV/m]	[μV/m]
40.66-40.70	1,000	100
70-130	500	50
130-174	500 to 1,500 *	50 to 150 *
174-260	1,500	150
260-470	1,500 to 5,000 *	150 to 500 *
Above 470	5,000	500

Where F is the frequency in MHz, the formula for calculating the maximum permitted fundamental field strengths are as follows: for the band 130-174 MHz, μ V/m at meters=22.72727(F)-2454.545; for the band 260-470 MHz, μ V/m at 3 meters =16.6667(F)-2833.3333. The maximum permissible unwanted emission level is 20dB below the maximum fundamental level.

Results:

Field Strength of Fundamental Emissions						
			Peak Value			
Frequency	Measured	Correction	Field	Field	Limit	Antenna
	Level @3m	Factor	Strength	Strength	@3m	Polarity
MHz	dBμV/m	dBμV/m	dBμV/m	μV/m	μV/m	•
433.80	62.5	20.7	83.2	14454.4	43,966.8	Horizontal
867.60	20.7	28.9	49.6	302.0	4,396.7	Horizontal

Field Strength of Fundamental Emissions Average Value						
Frequency	Measured	Correction	Field	Field	Limit **	Antenna
	Level @3m	Factor	Strength	Strength	@3m	Polarity
MHz	dBμV/m	dBμV/m	dB _μ V/m	μV/m	μV/m	
* 433.80	46.4	20.7	67.1	2264.6	4,396.7	Horizontal
867.60	4.6	28.9	33.5	47.3	439.7	Horizontal

According to FCC 47CFR15.35, the limit on the radio frequency emissions as measured using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit for the frequency being investigated unless a different peak emission limit is otherwise specified in the rules.



No.: HM150102

Results:

	Field Strength of Spurious Emissions Average Value									
F	requency	Me	asured	Correction		Field		Field	Limit @3m	Antenna
		Lev	el @3m	Factor	S	trength	S	trength		Polarity
	MHz	dE	3μV/m	dBμV/m	d	BμV/m		μV/m	μV/m	
+	1301.40	<	1.0	29.4	٧	30.4	<	33.1	500.0	Vertical
	1735.20	<	1.0	32.2	٧	33.2	<	45.7	439.7	Vertical
	2169.00	<	1.0	15.9	٧	16.9	<	7.0	439.7	Vertical
	2602.80	<	1.0	17.4	٧	18.4	<	8.3	439.7	Vertical
	3036.60	<	1.0	17.2	٧	18.2	<	8.1	439.7	Vertical
	3470.40	<	1.0	18.8	٧	19.8	<	9.8	439.7	Vertical
+	3904.20	<	1.0	19.7	٧	20.7	<	10.8	500.0	Vertical
+	4338.00	<	1.0	20.6	٧	21.6	<	12.0	500.0	Vertical

Remarks:

- *: Adjusted by Duty Cycle = -16.1dB
- **: According to FCC C47CFR 15.231e,
 - FCC Limit for Average Measurement = 16.6667(433.8MHz)-2883.3333=4,396.68μV/m
- +: Denotes restricted band of operation.

 Measurements were made using a peak detector. Any emission less than 1000 MHz and falling within the restricted bands of FCC Rules Part 15 Section 15.205 were not adjusted for averaging and the limit of FCC Rules Part 15 Section 15.209 were applied

Correction Factor included Antenna Factor and Cable Attenuation.

Calculated measurement uncertainty = 30MHz to 1GHz ±4.1dB



No.: HM150102

Limited for Radiated Emissions [FCC 47 CFR 15.209 Class B]:

Frequency Range [MHz]	Quasi-Peak Limits [μV/m]
30-88	100
88-216	150
216-960	200
Above960	500

The emission limits shown in the above table are based on measurement employing a CISPR quasipeak detector and above 1000MHz are based on measurements employing an average detector.

Results:

Radiated Emissions Quasi-Peak						
Frequency	Measured	Correction	Field	Field	Limit @3m	Antenna
	Level @3m	Factor	Strength	Strength		Polarity
MHz dBμV/m dBμV/m μV/m μV/m						
NO EMISSION DETECTED WITHIN 20dB OF THE FCC LIMITS						

Remarks:

Correction Factor included Antenna Factor and Cable Attenuation.

Calculated measurement uncertainty = 30MHz to 1GHz ±4.1dB



No.: HM150102


3.1.2 Conducted Emissions (0.15MHz to 30MHz)

Test Requirement: FCC 47CFR 15.107
Test Method: ANSI C63.4:2003
Test Date: 2004-03-11
Mode of Operation: On mode

Test Method:

The test was performed in accordance with ANSI C63.4: 2003, with the following: an initial measurement was performed in peak and average detection mode on the live line. Any emissions recorded within 30dB of the relevant limit line were re-measured using quasi-peak and average detection on the live and neutral lines with the worst case recorded in the table of results.

Test Setup:





No.: HM150102


Limit for Conducted Emissions (FCC 47 CFR 15.107):

Frequency Range	Quasi-Peak Limits	Average
[MHz]	[dB _µ V]	[dBµV]
0.15-0.5	66 to 56*	56 to 46*
0.5-5.0	56	46
5.0-30.0	60	50

^{*} Decreases with the logarithm of the frequency.

Limits for Conducted Emissions Test, please refer to limit lines (Quasi-Peak and Average) in the following diagram.

Results: On Mode



		Quasi-peak		Ave	rage	
Conductor	Frequency	Level	Limit	Level	Limit	
Live or Neutral	MHz	dBμV	dBμV	dBμV	dBμV	
NO EMISSION DETECTED WITHIN 20dB OF THE FCC LIMITS						

Remarks:

Calculated measurement uncertainty: ±2.8dB



No.: HM150102

3.2 20dB Bandwidth of Fundamental Emission

Test Requirement: FCC 47 CFR 15.231e

Test Method: ANSI C63.4:2003 (Section 13.1.7)

Test Date: 2004-03-11 Mode of Operation: On mode

Test Method:

The bandwidth is measured at an amplitude level reduced from the reference level by a specified ratio. The reference level is the level of the highest amplitude signal observed from the transmitter at the fundamental frequency. Once the reference level is established, the equipment is conditioned with typical modulating signal to produce the worst-case (i.e. the widest) bandwidth.

Test Setup:

As Test Setup of clause 3.1.1 in this test report.



No.: HM150102

Limits for 20 dB Bandwidth of Fundamental Emission:

Frequency Range	26dB Bandwidth	FCC Limits *
[MHz]	[KHz]	[KHz]
433.8	50	1085


*: FCC Limit for Bandwidth measurement

= (0.25%)(Center Frequency)

=(0.0025)(433.8)

=1085KHz

20dB Bandwidth of Fundamental Emission





No.: HM150102

Appendix A

List of Measurement Equipment

Radiated Emission

EQP NO.	DESCRIPTION	MANUFACTURER	MODEL NO.	SERIAL NO.	LAST CAL
EM007	SPECTRUM ANALYZER	HEWLETT PACKARD	HP85660B	3144A21192	14/03/03
EM008	SPECTRUM ANALYZER DISPLAY	HEWLETT PACKARD	HP85662A	3144A20514	14/03/03
EM009	QUASI PEAK ADAPTOR	HEWLETT PACKARD	HP85650A	3303A01702	14/03/03
EM010	RF PRESELECTOR	HEWLETT PACKARD	HP85685A	3221A01410	14/03/03
EM011	ATTENNUATOR/SWITCH	HEWLETT PACKARD	HP11713A	2508A10595	14/03/03
EM012	PRE-AMPLIFIER	HEWLETT PACKARD	HP8449B	3008A00262	14/03/03
EM013	CONTROLLER (COMPUTER), COLOR MONITOR, KEYBOARD & MOUSE FLOPPY DRIVE	HEWLETT PACKARD HEWLETT PACKARD HEWLETT PACKARD	HP9000 HP A1097C HP9133L	6226A60314 3151J39517 2623A02468	СМ
EM020	HORN ANTENNA	EMCO	3115	4032	19/07/00
EM022	LOOP ANTENNA	EMCO	6502	1189-2424	04/08/00
EM072	SIGNAL GENERATOR	HEWLETT PACKARD	8640B	1948A11892	N/A
EM083	HKSTC OPEN AREA TEST SITE	HKSTC	N/A	N/A	08/11/02
EM131	PORTABLE SPECTRUM ANALYSER	HEWLETT PACKARD	8595EM	3710A00155	18/12/01
EM145	EMI TEST RECEIVER	R&S	ESCS 30	830245/021	02/08/03
EM194	BICONILOG ANTENNA	EMCO	3142B	1795	14/05/02
EM195	ANTENNA POSITIONING MAST	EMCO	2075	2368	N/A
EM196	MULTI-DEVICE CONTROLLER	EMCO	2090	1662	N/A

Conducted Emission

EQP NO.	DESCRIPTION	MANUFACTURER	MODEL NO.	SERIAL NO.	LAST CAL
EM078	VARIAC	SHANGHAI VOLTAGE	TDGC-3/0.5	N/A	CM
EM081	SMALL SCREENED ROOM	MIKO INST HK	N/A	N/A	18/10/02
EM119	LISN	R&S	ESH3-Z5	0831.5518.52	01/10/02
EM127	ISOLATION TRANSFORMER 220 TO 300	WING SUN	N/A	N/A	СМ
EM142	PULES LIMITER	R&S	ESH3Z2	357.8810.52	03/07/02
EM181	EMI TEST RECEIVER	R&S	ESIB7	100072	28/11/01
EM154	SHIELDING ROOM	SIEMENA MATSUSHITA COMPONENTS	N/A	803-740-057- 99A	18/10/02
EM197	LISN	EMCO	4825/2	1193	08/04/03

Remarks:

CM Corrective Maintenance N/A Not Applicable or Not Available

TBD To Be Determined



No.: HM150102

Appendix B

Duty Cycle Correction During 100msec


Each function key sends a different series of characters, but each packet period (59.25msec) never exceeds a series of 37 long (250µsec) or short (200µsec) pulses. Assuming any combination of short and long pulses may be obtained due to encoding the worse case transmit duty cycle would be considered 37x250µsec per 59.25msec=15.6% duty cycle. Figure A through C show the characteristics of the pulse train for one of these functions.

Remarks:

Duty Cycle Correction = 20Log(0.156) =-16.1dB

The following figures [Figure A to Figure C] showed the characteristics of the pulse train for one of these functions.







No.: HM150102

Figure B [Long Pulse]





Figure C [Short Pulse]





No.: HM150102

Appendix C

Periodic Operation [FCC 47CFR 15.231e]


According to FCC 47CFR15.231e. The EUT shall be provided with a means for automatically limiting operation so that the duration of each transmission shall not be greater than one second and the silent period between transmissions shall be at least 30 times the duration of the transmission but in no case less than 10 seconds.

Results:

Since the EUT of each transmission is 750msec, so the silent period must not less than 22.5 seconds (700msec x 30).

The following figures [Figure D to Figure E] showed the duration of each transmission and silent period.


Figure D [Each transmission]





No.: HM150102

Periodic operation [FCC 47CFR15.231e] Figure E [Silent Period]






No.: HM150102

Periodic Operation [FCC 47CFR 15.231a]

According to FCC 47CFR15.231a. A transmitter manually activated must automatically deactivate within not more than 5 seconds of being released. The transmitter is a one button transmitter for registration mode. The EUT to transmit while a button is being pressed. The EUT ceases transmission almost immediately upon being released and appears to finish the current packet being transmitted and it shown in the figure.

Periodic operation [FCC 47CFR15.231a] Figure F





No.: HM150102

Appendix D

Photographs of EUT

Front View of the product



Rear View of the product



Inner Circuit Top View



Inner Circuit Bottom View





No.: HM150102

Photographs of EUT,

Measurement of Radiated Emission Test Set Up

End of Document