

Date:1999-02-26
No.: HM1905/504

TEST REPORT

Page 1 of 4

APPLICANT: (CODE :007802)

EWIG INDUSTRIES CO. LTD.

13/F., HOUTEX INDUSTRIAL BUILDING, 16 HUNG TO ROAD, KWUN TONG, KOWLOON,
HONG KONG.

DATE OF SAMPLES RECEIVED: 1999.02.10

DATE OF TESTING: 1999.02.24

DESCRIPTION OF SAMPLE(S):

A sample of product said to be:

Product: Thermometer
Manufacturer: EWIG INDUSTRIES CO. LTD.
Brand Name: N/A
Model Number: 303
Rating: 3Vd.c. ("AAA" size battery × 2)
Origin: China

INVESTIGATIONS REQUESTED:

Measurement to the relevant clauses of F.C.C. Rules and Regulations Part 15 Subpart B - Unintentional Radiator.

RESULT/ REMARK: Please see attached sheet(s).

CONCLUSION:

From the measurement data obtained, the tested sample was considered to have COMPLIED with the clause 15.109(a) for the Receiver Section of Federal Communication Rules and Regulation Part 15 and ANSI C63.4-1992 Section 12.1.1.1-2.

TEST EQUIPMENT AUDIT: Please see Appendix A

LAW MAN KIT
Testing Engineer

KITTY CHOY
Verify by

PATRICK WONG
Patrick Wong
for Managing Director

Conditions in issuance of Test Report

1. This Report is issued in confidence to the client and it will be strictly treated as such by the Hong Kong Standards and Testing Centre Ltd. It may not be reproduced either in its entirety or in part and it may not be used for advertising. The client to whom the Report is issued may, however, show or send it, or a certified copy thereof prepared by the Hong Kong Standards and Testing Centre Ltd. to his customer, supplier or other persons directly concerned. The Hong Kong Standards and Testing Centre Ltd. will not, without the consent of the client, enter into any discussion or correspondence with any third party concerning the contents of the Report. 2. The report refers only to the sample tested and does not apply to the bulk, unless the sampling has been carried out by the Hong Kong Standards and Testing Centre Ltd. and is stated as such in the Report. 3. In the event of the improper use of the report, the Hong Kong Standards and Testing Centre Ltd. reserves the rights to withdraw it, and to adopt any other remedies which may be appropriate. 4. Samples submitted for testing are accepted on the understanding that the Report issued cannot form the basis of, or be the instrument for, any legal action against the Hong Kong Standards and Testing Centre Ltd. 5. The Hong Kong Standards and Testing Centre Ltd. will not be liable for or accept responsibility for any loss or damage howsoever arising from the use of information contained in any of its Reports or in any communication

Date: 1999-02-26
No.: HM1905/504

TEST REPORT

Page 2 of 4

TEST SUMMARY

- (A) Measurement of Radiated EmissionsSatisfactory
- (B) Line Conducted Voltage Test.Not applicable

TEST DATA

Please refer to the attached result sheets.

Date: 1999-02-26
No.: HM1905/504

TEST REPORT

Page 3 of 4

*** RECEIVER SECTION ***

(A) Measurement of Radiated Interference

TEST REFERENCE: FCC Rules Part 15 Subpart B section 15.109(a)

TEST CONDITION : Normal

TEST DATE : 1999-02-24

Emission Frequency	Meter Reading	Polarization	Antenna Factor	Field Strength (at 3m)	FCC Limit	
MHz	dB(μV)	H-V	dB	dB(μV/m)	μV/m	μV/m
414.8	22.4	H	+	19.5	41.9	124.5
829.6	< 1.0		+	28.5	<29.5	<29.9
1244.4	< 1.0		+	25.8	<26.8	<21.8
1659.2	< 1.0		+	26.2	<27.2	<22.9
2074.0	< 1.0		+	28.0	<29.0	<28.2
2488.8	< 1.0		+	28.5	<29.5	<29.9
2903.6	< 1.0		+	30.6	<31.6	<38.0
3318.4	< 1.0		+	32.0	<33.0	<44.7
3733.2	< 1.0		+	33.2	<34.2	<51.2
4148.0	< 1.0		+	33.3	<34.3	<51.9

=====SUMMARY=====

All data is within limits

Broad-band Antennas were used and both polarizations of emissions were measured

Polarizations at highest reading indicated as:

H -- Horizontal

V -- Vertical

Date: 1999-02-26
No.: HM1905/504

TEST REPORT

Page 4 of 4

NOTES FOR THE RADIATION MEASUREMENT

(1) Test site facility:

Open field test site located at Taipo (Hong Kong) with a metal ground plane on filed with the FCC pursuant to section 2.948 of the FCC Rules.

(2) Distance between the ET and measuring antenna:

3 meters.

(3) Measuring instrumentations:

CISPR Quasi-peak type field strength meter (25 MHz - 1000 MHz and 1GHz-18GHz).6dB bandwidth set at 120KHz. Also, peak level of the fundamental emissions was measured in order to determine compliance with the 20dB peak to verage limit specified in Section 15.231 of the FCC new Rules.

(4) Measuring antenna:

Broad band antenna for the frequency range 25-1000 MHz, connected with 10 meters coaxial cable.Horn antenna for the frequency range 1-18 GHz, connected with high frequency coaxial cable.Cable loss of the coaxial cable. Cable included in the Antenna Factor for measurement data. The antenna are capable of measuring both horizontal and vertical polarizations.

(5) Frequency range scanned:

The frequency range from 25 MHz to 1000 MHz had been searched. Readings of the highest emissions relating to the limit were reported as above.

(6) Arrangement of EUT:

During the test, the sample was operated at rated supply voltage and arranged for maximum emissions.

(7) Measuring Procedure:

In accordance with the relevant clauses of the FCC Rules Part 15 section 15.109(a) and ANSI C63.4:1992 section 12.1.1.1-2.

(8) Measuring Uncertainty:

The calculated uncertainty for measurement performed at 3M test distance are:-

30MHz to 300MHz = $\pm 3.7\text{dB}$, 300MHz to 1000MHz = $+ 3.0\text{dB}/-2.7\text{dB}$.

1GHz to 18GHz = $+3.3\text{dB}/-3.4\text{dB}$.

Remark: Purpose of this test is to provide the Applicant with the necessary test data of their device for the submission to FCC with application for Equipment Authorization under FCC Equipment Authorization Program. This test itself is not an Approval Test.

**** End of document ****