

## **MPE Calculation**

Applicant: Guillemot Corporation S.A.

Address: Place Du Granier - B.P. 97143, 35571 CHANTEPIE CEDEX, FRANCE

Model No.: Y-400Pt

According to subpart 15.247(i)and subpart §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for Maximum Permissible Exposure (MPE) (§1.1310, §2.1091)

| (B) Limits for General Population/Uncontrolled Exposure |                |                |                        |                |  |
|---|----------------|----------------|------------------------|----------------|--|
| Frequency Range   | Electric Field | Magnetic Field | Power Density          | Averaging Time |  |
| (MHz)   | Strength (V/m) | Strength (A/m) | (mW/cm <sup>2</sup> )  | (minutes)      |  |
| 0.3-1.34  | 614            | 1.63           | *(100)                 | 30             |  |
| 1.34-30   | 824/f          | 2.19/f         | *(180/f <sup>2</sup> ) | 30             |  |
| 30–300  | 27.5           | 0.073          | 0.2                    | 30             |  |
| 300–1500  | /              | /              | f/1500                 | 30             |  |
| 1500-100,000  | /              | /              | 1.0                    | 30             |  |

f = frequency in MHz; \* = Plane-wave equivalent power density;

According to §1.1310 and §2.1091 RF exposure is calculated.

## Calculated Formulary:

Predication of MPE limit at a given distance

 $S = PG/4\pi R^2 = power density (in appropriate units, e.g. mW/cm^2);$ 

P = power input to the antenna (in appropriate units, e.g., mW);

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain;

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);

## Calculated Data:

| Maximum peak output power at antenna input terminal (dBm):                               | 0.07 (CC8530)<br>0.12 (CC2533)       |
|--|--------------------------------------|
| Maximum peak output power at antenna input terminal (mW):                                | 1.016 (CC8530)<br>1.028 (CC2533)     |
| Prediction distance (cm):  | 20                                   |
| Antenna Gain, typical (dBi):   | 6.73 (CC8530)<br>2.66 (CC2533)       |
| Maximum Antenna Gain (numeric):  | 4.710(CC8530)<br>1.845(CC2533)       |
| The worst case is power density at predication frequency at 20 cm (mW/cm <sup>2</sup> ): | 0.00095 (CC8530)<br>0.00038 (CC2533) |
| MPE limit for general population exposure at prediction frequency (mW/cm²):              | 1.0                                  |

Result: Compliant

Date: 18<sup>th</sup> July 2013

- TÜV SÜD HONG KONG LTD. -

Prepared by:

Reviewed by:

CHAN Kwong Ngai

Edmond FUNG

Report Number: 60.790.13.023.05A (revision2.0)

TÜV SÜD HONG KONG LTD., 3/F, West Wing, Lakeside 2, 10 Science Park West Avenue, Science Park, Shatin, HK.

Tel: +852-2776 1323 Fax: +852-2776 1206