



FCC 47 CFR PART 15 SUBPART C

TEST REPORT

For

Portable Data Collector

Model: PT-20; PT-2xxx (x= A~Z, a~z, 0~9, or blank, any character)

Trade Name: Argox

Issued to

Argox Information Co., Ltd.

7F, No. 126, Lane 235, Pao-Chiao Rd., Hsin Tien, Taipei, Taiwan, R.O.C.

Issued by

Compliance Certification Services Inc.

No. 81-1, Lane 210, Pa-De 2nd Rd., Luchu Hsiang,

Taoyuan Shien, (338) Taiwan, R.O.C.

TEL: 886-3-324-0332

FAX: 886-3-324-5235

<http://www.ccserf.com>

service@ccsrf.com



Note: This report shall not be reproduced except in full, without the written approval of Compliance Certification Services Inc. This document may be altered or revised by Compliance Certification Services Inc. personnel only, and shall be noted in the revision section of the document.



Revision History

Rev.	Issue Date	Revisions	Effect Page	Revised By
00	March 30, 2009	Initial Issue	ALL	Jill Shiau



TABLE OF CONTENTS

1. TEST RESULT CERTIFICATION.....	4
2. EUT DESCRIPTION.....	5
3. TEST METHODOLOGY.....	6
3.1 EUT CONFIGURATION.....	6
3.2 EUT EXERCISE.....	6
3.3 GENERAL TEST PROCEDURES.....	6
3.4 FCC PART 15.205 RESTRICTED BANDS OF OPERATIONS.....	7
3.5 DESCRIPTION OF TEST MODES.....	8
4. INSTRUMENT CALIBRATION.....	9
4.1 MEASUREMENT EQUIPMENT USED.....	9
4.2 MEASUREMENT UNCERTAINTY.....	11
5. FACILITIES AND ACCREDITATIONS.....	12
5.1 FACILITIES.....	12
5.2 EQUIPMENT.....	12
5.3 TABLE OF ACCREDITATIONS AND LISTINGS.....	13
6. SETUP OF EQUIPMENT UNDER TEST.....	14
6.1 SETUP CONFIGURATION OF EUT.....	14
6.2 SUPPORT EQUIPMENT.....	14
7. FCC PART 15.247 REQUIREMENTS.....	15
7.1 20dB BANDWIDTH.....	15
7.2 PEAK POWER.....	19
7.3 AVERAGE POWER.....	20
7.4 BAND EDGES MEASUREMENT.....	22
7.5 FREQUENCY SEPARATION.....	27
7.6 NUMBER OF HOPPING FREQUENCY.....	34
7.7 TIME OF OCCUPANCY (DWELL TIME).....	37
7.8 SPURIOUS EMISSIONS.....	44
7.9 POWERLINE CONDUCTED EMISSIONS.....	62
APPENDIX I RADIO FREQUENCY EXPOSURE.....	69
APPENDIX II PHOTOGRAPHS OF TEST SETUP.....	70



1. TEST RESULT CERTIFICATION

Applicant: **Argox Information Co., Ltd.**
7F, No. 126, Lane 235, Pao-Chiao Rd., Hsin Tien,
Taipei, Taiwan, R.O.C.

Equipment Under Test: Portable Data Collector

Trade Name: Argox

Model: PT-20; PT-2xxx (x= A~Z, a~z, 0~9, or blank, any character)

Date of Test: February 4 ~ March 18, 2009

APPLICABLE STANDARDS	
STANDARD	TEST RESULT
FCC 47 CFR Part 15 Subpart C	No non-compliance noted

We hereby certify that:

The above equipment was tested by Compliance Certification Services Inc. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.4: 2003 and the energy emitted by the sample EUT tested as described in this report is in compliance with the requirements of FCC Rules Part 15.207, 15.209, 15.247.

The test results of this report relate only to the tested sample EUT identified in this report.

Approved by:

Ethan Huang
Section Manager

Reviewed by:

Julia Wei
Senior Specialist



2. EUT DESCRIPTION

Product	Portable Data Collector	
Trade Name	Argox	
Model Number	PT-20; PT-2xxx (x= A~Z, a~z, 0~9, or blank, any character)	
Model Discrepancy	1. For marketing purpose only, all the model numbers	
	2. The mean of “x (x= A~Z, a~z, 0~9, or blank, any character)” on model number, they are identical just for marketing purpose only.	
	3. The EUT has two type for sales except handle.	
	Type	Handle
	1	X
	2	O
EUT Power Rating	3.7V, 2000mAh	
Frequency Range	2402 ~ 2480 MHz	
Transmit Power	0.67dBm	
Modulation Technique	GFSK; $\pi/4$ -DQPSK; 8-DPSK	
Transmit Data Rate	GFSK for 1Mbps; $\pi/4$ -DQPSK for 2Mbps; 8-DPSK for 3Mbps	
Number of Channels	79 Channels	
Antenna Specification	Chip Antenna / Gain: 4.1dBi	

Remark:

1. The sample selected for test was production product and was provided by manufacturer.
2. This submittal(s) (test report) is intended for FCC ID: **NBF-PT20** filing to comply with Section 15.207, 15.209 and 15.247 of the FCC Part 15, Subpart C Rules.



3. TEST METHODOLOGY

The tests documented in this report were performed in accordance with ANSI C63.4 (2003) and FCC CFR 47 Part 2, Part 15.207, 15.209 and 15.247.

3.1 EUT CONFIGURATION

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner that intends to maximize its emission characteristics in a continuous normal application.

3.2 EUT EXERCISE

The EUT was operated in the engineering mode to fix the TX frequency that was for the purpose of the measurements.

According to its specifications, the EUT must comply with the requirements of the Section 15.207, 15.209 and 15.247 under the FCC Rules Part 15 Subpart C.

3.3 GENERAL TEST PROCEDURES

Conducted Emissions

The EUT is placed on the turntable, which is 0.8 m above ground plane. According to the requirements in Section 13.1.4.1 of ANSI C63.4 (2003) Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using CISPR Quasi-peak and average detector modes.

Radiated Emissions

The EUT is placed on a turn table, which is 0.8 m above ground plane. The turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna, which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the maximum emissions, exploratory radiated emission measurements were made according to the requirements in Section 13.1.4.1 of ANSI C63.4 (2003).



3.4 FCC PART 15.205 RESTRICTED BANDS OF OPERATIONS

- (a) Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
¹ 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 -	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.52525	2655 - 2900	22.01 - 23.12
8.41425 - 8.41475	156.7 - 156.9	3260 - 3267	23.6 - 24.0
12.29 - 12.293	162.0125 - 167.17	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	167.72 - 173.2	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	240 - 285	3600 - 4400	(²)
13.36 - 13.41	322 - 335.4		

¹ Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

² Above 38.6

- (b) Except as provided in paragraphs (d) and (e), the field strength of emissions appearing within these frequency bands shall not exceed the limits shown in Section 15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in Section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000 MHz, compliance with the emission limits in Section 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in Section 15.35 apply to these measurements.



3.5 DESCRIPTION OF TEST MODES

The EUT (model: PT-20 with type 1) had been tested under operating condition.

Test program used to control the EUT for staying in continuous transmitting mode was programmed.

After verification, all tests were carried out with the worst case test modes as shown below except radiated spurious emission below 1GHz, which worst case was in normal link mode only.

Channel Low (2402MHz), Mid (2441MHz) and High (2480MHz) were chosen for full testing.

The field strength of spurious emission was measured in the following position: EUT stand-up position (Z axis), lie-down position (X, Y axis). The worst emission was found in lie-down position (Y axis) and the worst case was recorded.

Following channels were selected for the for radiated emission testing only as listed below:

Tested Channel	Modulation Type	Date Rate
Low, Mid, High	GFSK	1
Low, Mid, High	8DPSK	3



4. INSTRUMENT CALIBRATION

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipment, which is traceable to recognized national standards.

4.1 MEASUREMENT EQUIPMENT USED

Equipment Used for Emissions Measurement

Remark: Each piece of equipment is scheduled for calibration once a year.

Conducted Emissions Test Site				
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	R&S	FSP30	100112	10/16/2009
Spectrum Analyzer	R&S	FSEB	825829/011	10/29/2009
Horn Antenna	EMCO	3115	00022250	05/08/2009
Antenna Tower	HD	AS620E	N/A	N.C.R
Controller	HD	HD100	N/A	N.C.R
Power Meter	Agilent	E4416A	GB41291611	04/06/2009

3M Semi Anechoic Chamber				
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	R&S	FSP30	100112	10/16/2009
Spectrum Analyzer	R&S	FSEB	825829/011	10/29/2009
Pre-Amplifier	Anritsu	MH648A	M89145	07/25/2009
Pre-Amplifier	Agilent	8449B	3008A01738	03/28/2009
Bilog Antenna	FRANKONIA	BTA-M	030003M	04/03/2009
Horn Antenna	EMCO	3115	00022250	05/08/2009
Antenna Tower	HD	AS620E	N/A	N.C.R
Controller	HD	HD100	N/A	N.C.R
Turn Table	HD	DT-K312	N/A	N.C.R
Test S/W	LabVIEW 6.1 (Wugu Chamber EMI Teat V1_4.5.3)			

Power Line Conducted Emission Room #3				
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
EMI Test Receiver	R&S	ESCS30	845552/030	04/08/2009
LISN	R&S	ENV216	100074	12/09/2009
LISN	FCC	FCC-LISN-50/ 250-16-2-07	06013	10/12/2009
Test S/W	LabVIEW 6.1 (CCS Conduction Test SW Version_01)			



4.2 MEASUREMENT UNCERTAINTY

Parameter	Uncertainty
Powerline Conducted Emission	± 1.7806
3M Semi Anechoic Chamber / 30MHz ~ 1GHz	± 3.8856
3M Semi Anechoic Chamber / Above 1GHz	± 3.8721

Remark: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.



4.3 MEASUREMENT UNCERTAINTY

For the test methods, according to the present document, the measurement uncertainty figures shall be calculated in accordance with TR 100 028-1 [2] and shall correspond to an expansion factor (coverage factor) $k = 1,96$ or $k = 2$ (which provide confidence levels of respectively 95 % and 95,45 % in the case where the distributions characterizing the actual measurement uncertainties are normal (Gaussian)).

Table 6 is based on such expansion factors.

Table 6: Maximum measurement uncertainty

Parameter	Uncertainty
RF frequency	$\pm 1 \cdot 10^{-5}$
Total RF power conducted	$\pm 1,5$ dB
RF power density, conducted	± 3 dB
Spurious emissions, conducted	± 3 dB
All emissions, radiated	± 6 dB
Humidity	± 5 %
Temperature	$\pm 1^{\circ}\text{C}$
DC and low frequency voltages	$\pm 3\%$



5. FACILITIES AND ACCREDITATIONS

5.1 FACILITIES

All measurement facilities used to collect the measurement data are located at

☐ No.199, Chunghsen Road, Hsintien City, Taipei Hsien, Taiwan, R.O.C.

Tel: 886-2-2217-0894 / Fax: 886-2-2217-1029

☐ No.11, Wugong 6th Rd., Wugu Industrial Park, Taipei Hsien 248, Taiwan

Tel: 886-2-2299-9720 / Fax: 886-2-2298-4045

☒ No. 81-1, Lane 210, Pa-De 2nd Rd., Luchu Hsiang, Taoyuan Shien, (338) Taiwan, R.O.C.

Tel: 886-3-324-0332 / Fax: 886-3-324-5235

The sites are constructed in conformance with the requirements of ANSI C63.7 (1992), ANSI C63.4 (2003) and CISPR Publication 22.

5.2 EQUIPMENT





Radiated emissions are measured with one or more of the following types of linearly polarized antennas: tuned dipole, biconical, log periodic, bi-log, and/or ridged waveguide, horn. Spectrum analyzers with pre-selectors and quasi-peak detectors are used to perform radiated measurements.

Conducted emissions are measured with Line Impedance Stabilization Networks and EMI Test Receivers.

Calibrated wideband preamplifiers, coaxial cables, and coaxial attenuators are also used for making measurements.

All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

5.3 TABLE OF ACCREDITATIONS AND LISTINGS

Country	Agency	Scope of Accreditation	Logo
USA	A2LA	CFR 47, FCC Part15/18, CISPR 22, EN 55022, ICES-003, AS/NZS CISPR 22, VCCI V-3, EN 55011, CISPR 11, IEC/EN 61000-4-2/3/4/5/6/8/11, EN 61000-6-1/2/3/4, EN 55024, CISPR 24, AS/NZS CISPR 24, AS/NZS 61000.6.2, EN 55014-1/-2, ETSI EN 300 386 v1.3.2/v1.3.3, IEC/EN 61000-3-2, AS/NZS 61000.3.2, IEC/EN 61000-3-3, AS/NZS 61000.3.3	 ACCREDITED No. 0824-01
USA	FCC MRA	3/10 meter Open Area Test Sites to perform FCC Part 15/18 measurements	 TW1026
Japan	VCCI	3/10 meter Open Area Test Sites and conducted test sites to perform radiated/conducted measurements	VCCI R-2882/2541/2798/725/1868 C-402/747/912 T-321/325
Taiwan	TAF	EN 55014-1, CISPR 14, CNS 13781-1, EN 55013, CISPR 13, CNS 13439, EN 55011, CISPR 11, CNS 13803, PLMN09, IS2045-0, LP0002 FCC Part 27/90, Part 15B/C/D/E, RSS-192/193/210/310 ETSI EN 300 328/ 300 220-1/ 300 220-2/ 301 893/ 301 489-01/ 301 489-03/ 301 489-07 / 301 489-17/ 300 440-1/ 300 440-2 AS/NZS 4268, AS/NZS 4771 CISPR 22, EN 55022, CNS 13438, AS/NZS CISPR 22, VCCI, IEC/EN 61000-4-2/3/4/5/6/8/11, CNS 14676-2/3/4/5/6/8, CNS 14934-2/3, CNS 13783-1, CNS 13439, CNS 13803	 Testing Laboratory 0363
Taiwan	BSMI	CNS 13438, CNS 13783-1, CNS 13439, CNS 14115	SL2-IS-E-0014 / IN-E-0014 /A1-E-0014 /R1-E-0014 /R2-E-0014 /L1-E-0014
Canada	Industry Canada	RSS212, Issue 1	 IC 2324C-3 IC 2324C-5

Note: No part of this report may be used to claim or imply product endorsement by A2LA, TAF or other government agency.



6. SETUP OF EQUIPMENT UNDER TEST

6.1 SETUP CONFIGURATION OF EUT

See test photographs attached in Appendix 1 for the actual connections between EUT and support equipment.

6.2 SUPPORT EQUIPMENT

No.	Device Type	Brand	Model	Series No.	FCC ID	Data Cable	Power Cord
1.	Notebook PC	HP	COMPAQ NC 4010	CNU441F8LV	FCC DoC	N/A	AC I/P: Unshielded, 1.8m DC O/P: Unshielded, 1.8m with a core
2.	LCD Monitor	DELL	2407WFPb	CN-0FC255-46633-675-24TKS	FCC DoC	D-SUB Cable; Shielded, 1.8m with two cores	Unshielded, 1.8m
3.	USB Mouse	DELL	MO56UOA	F0Q01BKU	FCC DoC	Unshielded, 1.8m	N/A
4.	Cradle	Argox	CRD-20	N/A	FCC DoC	RS-232 Cable Unshielded, 1.8m USB Cable: Unshielded, 1.8m	DC O/P: Unshielded, 1.8m with a core

Remark: Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.




7. FCC PART 15.247 REQUIREMENTS

7.1 20dB BANDWIDTH

LIMIT

None; for reporting purposes only.

TEST CONFIGURATION



TEST PROCEDURE

1. Place the EUT on the table and set it in the transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. Set the spectrum analyzer as RBW=10kHz, VBW = 30kHz, Span = 2.5MHz, Sweep = auto.
4. Mark the peak frequency and 20dB (upper and lower) frequency.
5. Repeat until all the rest channels are investigated.

TEST RESULTS


No non-compliance noted



Test Plot


GFSK

20dB Bandwidth (CH Low)



Date: 17.MAR.2009 14:11:48


20dB Bandwidth (CH Mid)



Date: 17.MAR.2009 14:14:40




20dB Bandwidth (CH High)



Date: 17.MAR.2009 14:18:10

8DPSK


20dB Bandwidth (CH Low)



Date: 17.MAR.2009 14:55:38




20dB Bandwidth (CH Mid)



Date: 17.MAR.2009 14:56:54

20dB Bandwidth (CH High)



Date: 17.MAR.2009 14:52:43




7.2 PEAK POWER

LIMIT

According to §15.247, the maximum peak output power of the intentional radiator shall not exceed the following:

1. According to §15.247(a)(1), Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.
2. According to §15.247(b)(3), for systems using digital modulation in the bands of 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz: 1 watt.
3. According to §15.247(b) (4), the conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

TEST CONFIGURATION



TEST PROCEDURE

The transmitter output is connected to the Power Meter. The Power Meter is set to the peak power detection.

TEST RESULTS

No non-compliance noted

**TEST DATA****GFSK MODE**

Channel	Frequency (MHz)	Output Power (dBm)	Output Power (W)	Limit (W)	Result
Low	2402	-2.40	0.00058	0.125	PASS
Mid	2441	-0.49	0.00089		PASS
High	2480	0.67	0.00117		PASS

8DPSK MODE

Channel	Frequency (MHz)	Output Power (dBm)	Output Power (W)	Limit (W)	Result
Low	2402	-4.38	0.00036	0.125	PASS
Mid	2441	-2.82	0.00052		PASS
High	2480	-1.74	0.00067		PASS




7.3 AVERAGE POWER

LIMIT

None; for reporting purposes only.

TEST CONFIGURATION



TEST PROCEDURE

The transmitter output is connected to the Power Meter. The Power Meter is set to the average power detection.

TEST RESULTS

No non-compliance noted

TEST DATA

GFSK MODE

Channel	Frequency (MHz)	Output Power (dBm)	Output Power (W)
Low	2402	-3.68	0.00043
Mid	2441	-1.53	0.00070
High	2480	-0.15	0.00097

8DPSK MODE


Channel	Frequency (MHz)	Output Power (dBm)	Output Power (W)
Low	2402	-6.51	0.00022
Mid	2441	-5.59	0.00028
High	2480	-3.91	0.00041

7.4 BAND EDGES MEASUREMENT

LIMIT

According to §15.247(d), in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

TEST CONFIGURATION



TEST PROCEDURE

1. The EUT is placed on a turntable, which is 0.8m above the ground plane.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emission.
4. Set the spectrum analyzer in the following setting in order to capture the lower and upper band-edges of the emission:
 - (a) PEAK: RBW=VBW=1MHz / Sweep=AUTO
 - (b) AVERAGE: RBW=1MHz / VBW=10Hz / Sweep=AUTO
5. Repeat the procedures until all the PEAK and AVERAGE versus POLARIZATION are measured.

TEST RESULTS

No non-compliance noted



TEST DATA


Refer to attach spectrum analyzer data chart.

GFSK Mode

Band Edges (CH Low)

Detector mode: Peak


Polarity: Vertical



Date: 4.FEB.2009 15:42:13

Detector mode: Average

Polarity: Vertical




Date: 4.FEB.2009 15:42:57



Detector mode: Peak


Polarity: Horizontal



Date: 4.FEB.2009 15:45:13

Detector mode: Average

Polarity: Horizontal




Date: 4.FEB.2009 15:46:07



Band Edges (CH High)

Detector mode: Peak


Polarity: Vertical



Date: 4.FEB.2009 14:09:02

Detector mode: Average

Polarity: Vertical




Date: 4.FEB.2009 14:10:02



Detector mode: Peak


Polarity: Horizontal



Date: 4.FEB.2009 14:12:16

Detector mode: Average

Polarity: Horizontal




Date: 4.FEB.2009 14:13:13



8DPSK Mode
Band Edges (CH Low)


Detector mode: Peak

Polarity: Vertical



Date: 4.FEB.2009 15:35:39

Detector mode: Average **Polarity: Vertical**




Date: 4.FEB.2009 15:36:23



Detector mode: Peak


Polarity: Horizontal



Date: 4.FEB.2009 15:32:50

Detector mode: Average

Polarity: Horizontal




Date: 4.FEB.2009 15:33:44



Band Edges (CH High)

Detector mode: Peak


Polarity: Vertical



Date: 4.FEB.2009 14:24:43

Detector mode: Average

Polarity: Vertical




Date: 4.FEB.2009 14:25:16



Detector mode: Peak


Polarity: Horizontal



Date: 4.FEB.2009 14:21:06

Detector mode: Average

Polarity: Horizontal



Date: 4.FEB.2009 14:21:55




7.5 FREQUENCY SEPARATION

LIMIT

According to §15.247(a)(1), Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

TEST CONFIGURATION



TEST PROCEDURE

1. Place the EUT on the table and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. Set center frequency of spectrum analyzer = middle of hopping channel.
4. Set the spectrum analyzer as RBW = 30kHz, VBW = 100kHz, Span = 3MHz, Sweep = auto.
5. Max hold, mark 3 peaks of hopping channel and record the 3 peaks frequency.

TEST RESULTS

No non-compliance noted

**TEST DATA****GFSK Mode**

Channel Separation (MHz)	two-thirds of the 20 dB bandwidth (kHz)	Channel Separation Limit	Result
1.00	626	> 20dB Bandwidth or two-thirds of the 20 dB bandwidth	Pass

8DPSK Mode


Channel Separation (MHz)	two-thirds of the 20 dB bandwidth (kHz)	Channel Separation Limit	Result
1.00	852	> 20dB Bandwidth or two-thirds of the 20 dB bandwidth	Pass




Test Plot

Measurement of Channel Separation

GFSK Mode



8DPSK Mode






7.6 NUMBER OF HOPPING FREQUENCY

LIMIT

According to §15.247(a)(1)(iii), Frequency hopping systems operating in the 2400MHz-2483.5 MHz bands shall use at least 15 hopping frequencies.

TEST CONFIGURATION



TEST PROCEDURE

1. Place the EUT on the table and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. Set spectrum analyzer Start=2400MHz, Stop = 2441.5MHz, Sweep = auto and Start=2441.5MHz, Stop = 2483.5MHz, Sweep = auto.
4. Set the spectrum analyzer as RBW, VBW=500kHz.
5. Max hold, view and count how many channel in the band.

TEST RESULTS

No non-compliance noted

TEST DATA

Result (No. of CH)	Limit (No. of CH)	Result
79	>15	PASS




Test Plot

Channel Number


GFSK Mode

2.4 GHz – 2.4415 GHz



Date: 17.MAR.2009 16:51:53

2.4415 GHz – 2.4835 GHz




Date: 17.MAR.2009 16:50:35




8DPSK Mode

2.4 GHz – 2.4415 GHz



Date: 17.MAR.2009 16:39:13

2.4415 GHz – 2.4835 GHz



Date: 17.MAR.2009 16:47:14




7.7 TIME OF OCCUPANCY (DWEELL TIME)

LIMIT

According to §15.247(a)(1)(iii), Frequency hopping systems operating in the 2400MHz-2483.5 MHz bands. The average time of occupancy on any channels shall not greater than 0.4 s within a period 0.4 s multiplied by the number of hopping channels employed.

TEST CONFIGURATION



TEST PROCEDURE

1. Place the EUT on the table and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. Set center frequency of spectrum analyzer = operating frequency.
4. Set the spectrum analyzer as RBW, VBW=1MHz, Span = 0Hz, Sweep = auto.
5. Repeat above procedures until all frequency measured were complete.

TEST RESULTS

No non-compliance noted

**TEST DATA****GFSK Mode****DH 1**CH Low: $0.399 * (1600/2)/79 * 31.6 = 127.68$ (ms)CH Mid: $0.399 * (1600/2)/79 * 31.6 = 127.68$ (ms)CH High: $0.399 * (1600/2)/79 * 31.6 = 127.68$ (ms)

CH	Pulse Time (ms)	Total of Dwell (ms)	Period Time (s)	Limit (ms)	Result
Low	0.399	127.68	31.60	400.00	PASS
Mid	0.399	127.68	31.60		PASS
High	0.399	127.68	31.60		PASS

DH 3CH Low: $1.661 * (1600/4)/79 * 31.6 = 265.76$ (ms)CH Mid: $1.661 * (1600/4)/79 * 31.6 = 265.76$ (ms)CH High: $1.661 * (1600/4)/79 * 31.6 = 265.76$ (ms)

CH	Pulse Time (ms)	Total of Dwell (ms)	Period Time (s)	Limit (ms)	Result
Low	1.661	265.76	31.60	400.00	PASS
Mid	1.661	265.76	31.60		PASS
High	1.661	265.76	31.60		PASS


DH 5CH Low: $2.922 * (1600/6)/79 * 31.6 = 311.68$ (ms)CH Mid: $2.902 * (1600/6)/79 * 31.6 = 309.55$ (ms)CH High: $2.902 * (1600/6)/79 * 31.6 = 309.55$ (ms)

CH	Pulse Time (ms)	Total of Dwell (ms)	Period Time (s)	Limit (ms)	Result
Low	2.922	311.68	31.60	400.00	PASS
Mid	2.902	309.55	31.60		PASS
High	2.902	309.55	31.60		PASS


Test Plot

DH 1

(CH Low)




(CH Mid)






(CH High)




DH 3

(CH Low)






(CH Mid)




(CH High)






DH 5

(CH Low)




(CH Mid)





CH High)



**8DPSK Mode****DH 1**CH Low: $0.403 * (1600/2)/79 * 31.6 = 128.90$ (ms)CH Mid: $0.403 * (1600/2)/79 * 31.6 = 128.90$ (ms)CH High: $0.403 * (1600/2)/79 * 31.6 = 128.90$ (ms)

CH	Pulse Time (ms)	Total of Dwell (ms)	Period Time (s)	Limit (ms)	Result
Low	0.403	128.90	31.60	400.00	PASS
Mid	0.403	128.90	31.60		PASS
High	0.403	128.90	31.60		PASS

DH 3CH Low: $1.661 * (1600/4)/79 * 31.6 = 265.76$ (ms)CH Mid: $1.661 * (1600/4)/79 * 31.6 = 265.76$ (ms)CH High: $1.661 * (1600/4)/79 * 31.6 = 265.76$ (ms)

CH	Pulse Time (ms)	Total of Dwell (ms)	Period Time (s)	Limit (ms)	Result
Low	1.661	265.76	31.60	400.00	PASS
Mid	1.661	265.76	31.60		PASS
High	1.661	265.76	31.60		PASS

DH 5CH Low: $2.926 * (1600/6)/79 * 31.6 = 312.11$ (ms)CH Mid: $2.904 * (1600/6)/79 * 31.6 = 309.76$ (ms)CH High: $2.924 * (1600/6)/79 * 31.6 = 311.89$ (ms)


CH	Pulse Time (ms)	Total of Dwell (ms)	Period Time (s)	Limit (ms)	Result
Low	2.926	312.11	31.60	400.00	PASS
Mid	2.904	309.76	31.60		PASS
High	2.924	311.89	31.60		PASS




Test Plot

DH 1


(CH Low)



(CH Mid)




(CH High)




DH 3

(CH Low)






(CH Mid)




(CH High)




DH 5

(CH Low)




(CH Mid)





(CH High)



Date: 17.MAR.2009 16:18:23




7.8 SPURIOUS EMISSIONS

7.8.1 Conducted Measurement

LIMIT

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

TEST CONFIGURATION



TEST PROCEDURE

Conducted RF measurements of the transmitter output were made to confirm that the EUT antenna port conducted emissions meet the specified limit and to identify any spurious signals that require further investigation or measurements on the radiated emissions site.

The transmitter output is connected to the spectrum analyzer. The resolution bandwidth is set to 100 kHz. The video bandwidth is set to 100 kHz.

Measurements are made over the 30MHz to 26GHz range with the transmitter set to the lowest, middle, and highest channels.

TEST RESULTS

No non-compliance noted




TEST DATA

Refer to attach spectrum analyzer data chart.

Test Plot


GFSK Mode

CH Low



Date: 18.MAR.2009 16:12:56


CH Mid



Date: 18.MAR.2009 16:14:01




CH High



Date: 18.MAR.2009 16:14:56

8DPSK Mode


CH Low



Date: 18.MAR.2009 16:23:31




CH Mid



Date: 18.MAR.2009 16:21:45

CH High



Date: 18.MAR.2009 16:16:42



7.8.2 RADIATED EMISSIONS

LIMIT

1. According to §15.209(a), except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength ($\mu\text{V/m}$)	Measurement Distance (m)
30-88	100*	3
88-216	150*	3
216-960	200*	3
Above 960	500	3


Remark: Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.

2. In the emission table above, the tighter limit applies at the band edges.


Frequency (Hz)	Field Strength ($\mu\text{V/m}$ at 3-meter)	Field Strength (dB $\mu\text{V/m}$ at 3-meter)
30-88	100	40
88-216	150	43.5
216-960	200	46
Above 960	500	54

TEST CONFIGURATION

Below 1 GHz



Above 1 GHz





TEST PROCEDURE

1. The EUT is placed on a turntable, which is 0.8m above ground plane.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
6. Set the spectrum analyzer in the following setting as:
Below 1GHz:
RBW=100kHz / VBW=300kHz / Sweep=AUTO
Above 1GHz:
(a) PEAK: RBW=VBW=1MHz / Sweep=AUTO
(b) AVERAGE: RBW=1MHz / VBW=10Hz / Sweep=AUTO
7. Repeat above procedures until the measurements for all frequencies are complete.

TEST RESULTS

No non-compliance noted



TEST DATA

Below 1 GHz

Operation Mode: Normal Link**Test Date:** March 21, 2009**Temperature:** 18°C**Tested by:** Stan Lin**Humidity:** 60 % RH**Polarity:** Ver. / Hor.

Freq. (MHz)	Ant.Pol. H/V	Detector Mode (PK/QP)	Reading (dBuV)	Factor (dB)	Actual FS (dBuV/m)	Limit 3m (dBuV/m)	Safe Margin (dB)
34.8500	V	Peak	46.50	-15.15	31.35	40.00	-8.65
42.1250	V	Peak	44.05	-14.76	29.29	40.00	-10.71
54.2500	V	Peak	42.63	-14.37	28.26	40.00	-11.74
61.5250	V	Peak	44.06	-14.92	29.14	40.00	-10.86
78.5000	V	Peak	49.59	-17.83	31.76	40.00	-8.24
207.0250	V	Peak	37.79	-14.51	23.28	43.50	-20.22
956.3500	V	Peak	32.83	0.04	32.87	46.00	-13.13
66.3750	H	Peak	38.95	-15.77	23.18	40.00	-16.82
78.5000	H	Peak	42.44	-17.83	24.61	40.00	-15.39
105.1749	H	Peak	39.30	-16.18	23.12	43.50	-20.38
131.8499	H	Peak	36.22	-13.62	22.60	43.50	-20.90
214.3000	H	Peak	35.80	-14.37	21.43	43.50	-22.07
459.2250	H	Peak	34.04	-8.43	25.61	46.00	-20.39
898.1499	H	Peak	38.65	-1.11	37.54	46.00	-8.46

Remark:

1. No emission found between lowest internal used / generated frequency to 30 MHz. (9kHz ~ 30MHz)
2. Measuring frequencies from 9 kHz to the 1GHz.
3. Radiated emissions measured in the measured frequency range were made with an instrument using peak detector mode.
4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. The IF bandwidth of SPA between 30MHz to 1GHz was 100kHz.

**Above 1 GHz****Operation Mode:** TX / GFSK / CH Low**Test Date:** March 21, 2009**Temperature:** 16°C**Tested by:** Alonso Lu**Humidity:** 48 % RH**Polarity:** Ver. / Hor.

Freq. (MHz)	Ant. Pol H/V	Peak Reading (dBuV)	AV Reading (dBuV)	Ant. / CL CF (dB)	Actual Fs		Peak Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Remark
					Peak (dBuV/m)	AV (dBuV/m)				
1600.00	V	60.66	58.93	-7.82	52.85	51.11	74.00	54.00	-2.89	Peak
4800.00	V	51.08	44.81	1.81	52.89	46.62	74.00	54.00	-7.38	AVG
N/A										
1600.00	H	60.74	58.75	-7.82	52.92	50.93	74.00	54.00	-3.07	AVG
2352.00	H	58.37	51.29	-4.73	53.64	46.56	74.00	54.00	-7.44	AVG
2376.00	H	58.87	52.67	-4.68	54.19	47.99	74.00	54.00	-6.01	AVG
4800.00	H	52.82	46.21	1.81	54.63	48.02	74.00	54.00	-5.98	AVG
N/A										

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. $\text{Margin (dB)} = \text{Result (Peak or Average) (dBuV/m)} - \text{Limit (Peak or Average) (dBuV/m)}$.



Operation Mode: TX / GFSK / CH Mid

Test Date: March 21, 2009

Temperature: 16°C

Tested by: Alonso Lu

Humidity: 48 % RH

Polarity: Ver. / Hor.

Freq. (MHz)	Ant. Pol H/V	Peak Reading (dBuV)	AV Reading (dBuV)	Ant. / CL CF (dB)	Actual Fs		Peak Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Remark
					Peak (dBuV/m)	AV (dBuV/m)				
1628.00	V	57.01	---	-7.66	49.35	---	74.00	54.00	-4.65	Peak
2416.00	V	56.30	---	-4.59	51.71	---	74.00	54.00	-2.29	Peak
4880.00	V	50.54	43.95	2.05	52.58	46.00	74.00	54.00	-8.00	AVG
N/A										
1628.00	H	62.33	60.16	-7.66	54.68	52.50	74.00	54.00	-1.50	AVG
2416.00	H	60.24	54.46	-4.59	55.65	49.87	74.00	54.00	-4.13	AVG
4880.00	H	49.04	---	2.05	51.09	---	74.00	54.00	-2.91	Peak
N/A										

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Result (Peak or Average) (dBuV/m) (Peak or Average) – Limit (Peak or Average) (dBuV/m).



Operation Mode: TX / GFSK / CH High

Test Date: March 21, 2009

Temperature: 16°C

Tested by: Alonso Lu

Humidity: 48 % RH

Polarity: Ver. / Hor.

Freq. (MHz)	Ant. Pol H/V	Peak Reading (dBuV)	AV Reading (dBuV)	Ant. / CL CF (dB)	Actual Fs		Peak Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Remark
					Peak (dBuV/m)	AV (dBuV/m)				
1656.00	V	60.25	57.78	-7.50	52.76	50.28	74.00	54.00	-3.72	AVG
2712.00	V	55.00	---	-3.42	51.57	---	74.00	54.00	-2.43	Peak
4960.00	V	49.50	---	2.28	51.79	---	74.00	54.00	-2.21	Peak
N/A										
1656.00	H	61.20	58.04	-7.50	53.70	50.54	74.00	54.00	-3.46	AVG
2404.00	H	58.60	52.58	-4.62	53.98	47.96	74.00	54.00	-6.04	AVG
2428.00	H	58.72	52.97	-4.56	54.16	48.41	74.00	54.00	-5.59	AVG
2456.00	H	60.94	54.51	-4.50	56.44	50.01	74.00	54.00	-3.99	AVG
4960.00	H	52.88	45.03	2.28	55.16	47.31	74.00	54.00	-6.69	AVG
N/A										

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Result (Peak or Average) (dBuV/m) (Peak or Average) – Limit (Peak or Average) (dBuV/m).



Operation Mode: RX / GFSK / CH Mid

Test Date: March 21, 2009

Temperature: 16°C

Tested by: Alonso Lu

Humidity: 48 % RH

Polarity: Ver. / Hor.

Freq. (MHz)	Ant. Pol H/V	Peak Reading (dBuV)	AV Reading (dBuV)	Ant. / CL CF (dB)	Actual Fs		Peak Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Remark
					Peak (dBuV/m)	AV (dBuV/m)				
1628.00	V	57.42	---	-7.66	49.76	---	74.00	54.00	-4.24	Peak
2440.00	V	49.50	---	-4.54	44.96	---	74.00	54.00	-9.04	Peak
N/A										
1016.00	H	50.45	---	-10.63	39.82	---	74.00	54.00	-14.18	Peak
1328.00	H	47.18	---	-9.18	38.00	---	74.00	54.00	-16.00	Peak
1628.00	H	56.80	---	-7.66	49.14	---	74.00	54.00	-4.86	Peak
2440.00	H	50.95	---	-4.54	46.41	---	74.00	54.00	-7.59	Peak
N/A										

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Result (Peak or Average) (dBuV/m) (Peak or Average) – Limit (Peak or Average) (dBuV/m).



Operation Mode: TX / 8DPSK / CH Low

Test Date: March 21, 2009

Temperature: 16°C

Tested by: Alonso Lu

Humidity: 48 % RH

Polarity: Ver. / Hor.

Freq. (MHz)	Ant. Pol H/V	Peak Reading (dBuV)	AV Reading (dBuV)	Ant. / CL CF (dB)	Actual Fs		Peak Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Remark
					Peak (dBuV/m)	AV (dBuV/m)				
1600.00	V	59.52	---	-7.82	51.70	---	74.00	54.00	-2.30	Peak
6070.00	V	42.37	---	4.26	46.63	---	74.00	54.00	-7.37	Peak
N/A										
1600.00	H	59.07	---	-7.82	51.25	---	74.00	54.00	-2.75	Peak
2376.00	H	58.41	51.30	-4.68	53.73	46.62	74.00	54.00	-7.38	AVG
4940.00	H	43.55	---	2.22	45.77	---	74.00	54.00	-8.23	Peak
N/A										

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Result (Peak or Average) (dBuV/m) (Peak or Average) – Limit (Peak or Average) (dBuV/m).



Operation Mode: TX / 8DPSK / CH Mid

Test Date: March 21, 2009

Temperature: 16°C

Tested by: Alonso Lu

Humidity: 48 % RH

Polarity: Ver. / Hor.

Freq. (MHz)	Ant. Pol H/V	Peak Reading (dBuV)	AV Reading (dBuV)	Ant. / CL CF (dB)	Actual Fs		Peak Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Remark
					Peak (dBuV/m)	AV (dBuV/m)				
1628.00	V	59.56	---	-7.66	51.90	---	74.00	54.00	-2.10	Peak
4390.00	V	43.86	---	1.00	44.85	---	74.00	54.00	-9.15	Peak
N/A										
1628.00	H	58.40	---	-7.66	50.74	---	74.00	54.00	-3.26	Peak
2392.00	H	56.44	---	-4.64	51.80	---	74.00	54.00	-2.20	Peak
2416.00	2416.00	59.49	52.47	-4.59	54.90	47.88	74.00	54.00	-6.12	AVG
5610.00	5610.00	42.62	---	3.56	46.18	---	74.00	54.00	-7.82	Peak
N/A										

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Result (Peak or Average) (dBuV/m) (Peak or Average) – Limit (Peak or Average) (dBuV/m).



Operation Mode: TX / 8DPSK / CH High

Test Date: March 21, 2009

Temperature: 16°C

Tested by: Alonso Lu

Humidity: 48 % RH

Polarity: Ver. / Hor.

Freq. (MHz)	Ant. Pol H/V	Peak Reading (dBuV)	AV Reading (dBuV)	Ant. / CL CF (dB)	Actual Fs		Peak Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Remark
					Peak (dBuV/m)	AV (dBuV/m)				
1656.00	V	57.96	---	-7.50	50.46	---	74.00	54.00	-3.54	Peak
4960.00	V	43.38	---	2.28	45.67	---	74.00	54.00	-8.33	Peak
N/A										
1656.00	H	60.86	58.04	-7.50	53.36	50.54	74.00	54.00	-3.46	AVG
2456.00	H	58.18	50.82	-4.50	53.68	46.32	74.00	54.00	-7.68	AVG
6290.00	H	41.90	---	4.31	46.21	---	74.00	54.00	-7.79	Peak
N/A										

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Result (Peak or Average) (dBuV/m) (Peak or Average) – Limit (Peak or Average) (dBuV/m).



Operation Mode: RX / 8DPSK / CH Mid

Test Date: March 21, 2009

Temperature: 16°C

Tested by: Alonso Lu

Humidity: 48 % RH

Polarity: Ver. / Hor.

Freq. (MHz)	Ant. Pol H/V	Peak Reading (dBuV)	AV Reading (dBuV)	Ant. / CL CF (dB)	Actual Fs		Peak Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Remark
					Peak (dBuV/m)	AV (dBuV/m)				
1628.00	V	54.02	---	-7.66	46.37	---	74.00	54.00	-7.63	Peak
2440.00	V	49.93	---	-4.54	45.39	---	74.00	54.00	-8.61	Peak
5310.00	V	41.96	---	3.00	44.96	---	74.00	54.00	-9.04	Peak
N/A										
1016.00	H	50.11	---	-10.63	39.49	---	74.00	54.00	-14.51	Peak
1220.00	H	46.86	---	-9.68	37.18	---	74.00	54.00	-16.82	Peak
1328.00	H	47.88	---	-9.18	38.69	---	74.00	54.00	-15.31	Peak
1380.00	H	46.66	---	-8.94	37.72	---	74.00	54.00	-16.28	Peak
1628.00	H	57.42	---	-7.66	49.76	---	74.00	54.00	-4.24	Peak
2444.00	H	50.07	---	-4.53	45.54	---	74.00	54.00	-8.46	Peak

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Result (Peak or Average) (dBuV/m) (Peak or Average) – Limit (Peak or Average) (dBuV/m).



7.9 POWERLINE CONDUCTED EMISSIONS

LIMIT

For an intentional radiator which is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed 250 microvolts (The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz). The limits at specific frequency range is listed as follows:

Frequency Range (MHz)	Limits (dB μ V)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56	56 to 46
0.50 to 5	56	46
5 to 30	60	50

Compliance with this provision shall be based on the measurement of the radio frequency voltage between each power line (LINE and NEUTRAL) and ground at the power terminals.

TEST CONFIGURATION

See test photographs attached in Appendix 1 for the actual connections between EUT and support equipment.

TEST PROCEDURE

1. The EUT was placed on a table, which is 0.8m above ground plane.
2. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
3. Repeat above procedures until all frequency measured were complete.

TEST RESULTS

The initial step in collecting conducted data is a spectrum analyzer peak scan of the measurement range. Significant peaks are then marked as shown on the following data page, and these signals are then quasi-peaked.

**TEST DATA****Operation Mode:** Charging with
Normal Link**Test Date:** February 19, 2009**Temperature:** 25°C**Tested by:** Stan Lin**Humidity:** 57% RH

Freq. (MHz)	QP Reading	AV Reading	Corr. factor	QP Result	AV Result	QP Limit	AV Limit	QP Margin	AV Margin	Note
0.1734	26.42	19.02	9.68	36.10	28.70	64.79	54.80	-28.69	-26.10	L1
0.3375	26.22	24.82	9.68	35.90	34.50	59.26	49.26	-23.36	-14.76	L1
2.7984	20.90	15.10	9.70	30.60	24.80	56.00	46.00	-25.40	-21.20	L1
6.7633	26.37	21.97	9.83	36.20	31.80	60.00	50.00	-23.80	-18.20	L1
8.1031	21.65	17.55	9.95	31.60	27.50	60.00	50.00	-28.40	-22.50	L1
17.6617	19.18	14.58	10.32	29.50	24.90	60.00	50.00	-30.50	-25.10	L1
0.1655	29.62	22.12	9.68	39.30	31.80	65.18	55.18	-25.88	-23.38	L2
0.3336	27.32	23.32	9.68	37.00	33.00	59.36	49.36	-22.36	-16.36	L2
2.9117	20.20	13.70	9.70	29.90	23.40	56.00	46.00	-26.10	-22.60	L2
6.5289	26.07	21.37	9.83	35.90	31.20	60.00	50.00	-24.10	-18.80	L2
7.0563	25.35	20.05	9.85	35.20	29.90	60.00	50.00	-24.80	-20.10	L2
16.7281	18.39	13.89	10.31	28.70	24.20	60.00	50.00	-31.30	-25.80	L2

Remark:

1. Measuring frequencies from 0.15 MHz to 30MHz.
2. The emissions measured in frequency range from 0.15 MHz to 30MHz were made with an instrument using Quasi-peak detector and average detector.
3. "---" denotes the emission level was or more than 2dB below the Average limit
4. The IF bandwidth of SPA between 0.15MHz to 30MHz was 10kHz; the IF bandwidth of Test Receiver between 0.15MHz to 30MHz was 9kHz;
5. L1 = Line One (Live Line) / L2 = Line Two (Neutral Line)




Test Plots

Conducted emissions (Line 1)



Conducted emissions (Line 2)





APPENDIX I

RADIO FREQUENCY EXPOSURE

LIMIT

According to §15.247(i), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines. See § 1.1307(b)(1) of this chapter.

EUT SPECIFICATION

EUT	Portable Data Collector
Frequency band (Operating)	<input type="checkbox"/> WLAN: 2.412GHz ~ 2.462GHz <input type="checkbox"/> WLAN: 5.18GHz ~ 5.32GHz / 5.50GHz ~ 5.70GHz <input type="checkbox"/> WLAN: 5.745GHz ~ 5.825GHz <input checked="" type="checkbox"/> Others: <u>Bluetooth: 2.402GHz ~ 2.480GHz</u>
Device category	<input checked="" type="checkbox"/> Portable (<20cm separation) <input type="checkbox"/> Mobile (>20cm separation) <input type="checkbox"/> Others
Exposure classification	<input type="checkbox"/> Occupational/Controlled exposure ($S = 5mW/cm^2$) <input checked="" type="checkbox"/> General Population/Uncontrolled exposure ($S=1mW/cm^2$)
Antenna diversity	<input checked="" type="checkbox"/> Single antenna <input type="checkbox"/> Multiple antennas <input type="checkbox"/> Tx diversity <input type="checkbox"/> Rx diversity <input type="checkbox"/> Tx/Rx diversity
Max. output power	0.67 dBm (1.17mW)
Antenna gain (Max)	4.1dBi (Numeric gain: 2.95)
Evaluation applied	<input type="checkbox"/> MPE Evaluation <input type="checkbox"/> SAR Evaluation <input checked="" type="checkbox"/> N/A

Remark:

1. The maximum output power is 0.67dBm (1.117mW) at 2480MHz (with 2.95 numeric antenna gain.)
2. For mobile or fixed location transmitters, no SAR consideration applied. The minimum separation generally be used is at least 20 cm, even if the calculations indicate that the MPE distance would be lesser.

TEST RESULTS

No non-compliance noted.

(SAR evaluation is not required for the PORTABLE device while its maximum output power is lower than the general population low threshold: $60/f_{(GHz)}=60/2.441=24.58mW$) even if the calculation indicates that the power density would be larger.)

APPENDIX II

BLUETOOTH DECLARATION PER FCC 15.247

REQUIREMENTS

1 Output power and channel separation of a Bluetooth device in the different operating modes:

The different operating modes (data-mode, acquisition-mode) of a Bluetooth device don't influence the output power and the channel spacing. There is only one transmitter which is driven by identical input parameters concerning these two parameters. Only a different hopping sequence will be used.

For this reason the check of these RF parameters in one op-mode is sufficient.

2 Frequency range of a Bluetooth device:

Hereby we declare that the maximum frequency of this device is: **2402 – 2480 MHz**.

This is according the Bluetooth Core Specification V 1.0B (+ critical errata) for devices which will be operated in the USA.

This was checked during the Bluetooth Qualification tests (Test Case: TRM/CA/04-E).

Other frequency ranges (e.g. for Spain, France, Japan) which are allowed according the Core Specification are **not** supported by this device.

3 Co-ordination of the hopping sequence in data mode to avoid simultaneous occupancy by multiple transmitters:

Bluetooth units which want to communicate with other units must be organized in a structure called piconet. This piconet consist of max. 8 Bluetooth units. One unit is the master the other seven are the slaves. The master co-ordinates frequency occupation in this piconet for all units. As the master hop sequence is derived from it's BD address which is unique for every Bluetooth device, additional masters intending to establish new piconets will always use different hop sequences.

4 Example of a hopping sequence in data mode:

Example of a 79 hopping sequence in data mode:

40, 21, 44, 23, 42, 53, 46, 55, 48, 33, 52, 35, 50, 65, 54, 67,
56, 37, 60, 39, 58, 69, 62, 71, 64, 25, 68, 27, 66, 57, 70, 59,
72, 29, 76, 31, 74, 61, 78, 63, 01, 41, 05, 43, 03, 73, 07, 75,
09, 45, 13, 47, 11, 77, 15, 00, 64, 49, 66, 53, 68, 02, 70, 06,
01, 51, 03, 55, 05, 04

5 Equally average use of frequencies in data mode and behaviour for short transmissions:

The generation of the hopping sequence in connection mode depends essentially on two input values:

1. LAP/UAP of the master of the connection
2. Internal master clock The LAP (lower address part) are the 24 LSB's of the 48 BD_ADDRESS. The BD_ADDRESS is an unambiguous number of every Bluetooth unit. The UAP (upper address part) are the 24 MSB's of the 48 BD_ADDRESS.
The internal clock of a Bluetooth unit is derived from a free running clock which is never adjusted and is never turned off. For synchronisation with other units only offset are used. It has no relation to the time of the day. Its resolution is at least half the RX/TX slot length of 312.5 μ s. The clock has a cycle of about one day (23h30). In most case it is implemented as 28 bit counter. For the deriving of the hopping sequence the entire LAP (24 bits), 4 LSB's (4 bits) (Input 1) and the 27 MSB's of the clock (Input 2) are used.
With this input values different mathematical procedures (permutations, additions, XOR-operations) are performed to generate the sequence. This will be done at the beginning of every new transmission.
Regarding short transmissions the Bluetooth system has the following behaviors:



The first connection between the two devices is established, a hopping sequence was generated. For transmitting the wanted data the complete hopping sequence was not used. The connection ended.

The second connection will be established. A new hopping sequence is generated. Due to the fact that the Bluetooth clock has a different value, because the period between the two transmission is longer (and it cannot be shorter) than the minimum resolution of the clock (312.5 μ s). The hopping sequence will always differ from the first one.

6 Receiver input bandwidth and behaviors for repeated single or multiple packets:

The input bandwidth of the receiver is 1 MHz.

In every connection one Bluetooth device is the master and the other one is the slave.

The master determines the hopping sequence (see chapter 5). The slave follows this sequence. Both devices shift between RX and TX time slot according to the clock of the master. Additionally the type of connection (e.g. single or multislot packet) is set up at the beginning of the connection. The master adapts its hopping frequency and its TX/RX timing according to the packet type of the connection. Also the slave of the connection will use these settings.

Repeating of a packet has no influence on the hopping sequence. The hopping sequence generated by the master of the connection will be followed in any case. That means, a repeated packet will not be send on the same frequency, it is send on the next frequency of the hopping sequence.

7 Dwell time in data mode

The dwell time of 0.3797s within a 30 second period in data mode is independent from the packet type (packet length). The calculation for a 30 second period is a follows:

Dwell time = time slot length * hop rate / number of hopping channels * 30s

Example for a DH1 packet (with a maximum length of one time slot)

Dwell time = $625 \mu\text{s} * 1600 \text{ 1/s} / 79 * 30\text{s} = 0.3797\text{s}$ (in a 30s period)

For multislot packet the hopping is reduced according to the length of the packet.

Example for a DH5 packet (with a maximum length of five time slots)

Dwell time = $5 * 625 \mu\text{s} * 1600 * 1/5 * 1/s / 79 * 30\text{s} = 0.3797\text{s}$ (in a 30s period)

This is according the Bluetooth Core Specification V 1.0B (+ critical errata) for all Bluetooth devices. There for all Bluetooth devices **comply** with the FCC dwell time requirement in data mode.

This was checked during the Bluetooth Qualification tests.

The Dwell time in hybrid mode is measured and stated in the test report.

8 Channel Separation in hybrid mode

The nominal channel spacing of the Bluetooth system is 1Mhz independent of the operating mode.

The maximum "initial carrier frequency tolerance" which is allowed for Bluetooth is $f_{\text{center}} = 75 \text{ kHz}$.

This was checked during the Bluetooth Qualification tests (Test Case: TRM/CA/07-E) for three frequencies (2402, 2441, 2480 MHz).

Additionally an example for the channel separation is given in the test report

9 Derivation and examples for a hopping sequence in hybrid mode

For the generation of the inquiry and page hop sequences the same procedures as described for the data mode are used (see chapter 5), but this time with different input vectors:

- For the inquiry hop sequence, a predefined fixed address is always used. This results in the same 32 frequencies used by all devices doing an inquiry but every time with a different start frequency and phase in this sequence.
- For the page hop sequence, the device address of the paged unit is used as input vector. This results in the use of a subset of 32 frequencies which is specific for that initial state of the connection establishment between the two units. A page to



different devices would result in a different subset of 32 frequencies.

So it is ensured that also in hybrid mode the frequency use equally averaged.

Example of a hopping sequence in inquiry mode:

48, 50, 09, 13, 52, 54, 41, 45, 56, 58, 11, 15, 60, 62, 43, 47, 00, 02, 64, 68, 04, 06,
17, 21, 08, 10, 66, 70, 12, 14, 19, 23

Example of a hopping sequence in paging mode:

08, 57, 68, 70, 51, 02, 42, 40, 04, 61, 44, 46, 63, 14, 50, 48, 16, 65, 52, 54, 67, 18, 58, 56,
20, 53, 60, 62, 55, 06, 66, 64

10 Receiver input bandwidth and synchronisation in hybrid mode:

The receiver input bandwidth is the same as in the data mode (1 MHz). When two Bluetooth devices establish contact for the first time, one device sends an inquiry access code, the other device is scanning for this inquiry access code. If two devices have been connected previously and want to start a new transmission, a similar procedure takes place. The only difference is, instead of the inquiry access code, an special access code, derived from the BD_ADDRESS of the paged device will be, will be sent by the master of this connection.

Due to the fact that both units have been connected before (in the inquiry procedure) the paging unit has timing and frequency information about the page scan of the paged unit. For this reason the time to establish the connection is reduced considerable.

11 Spread rate / data rate of the direct sequence signal

The Spread rate / Data rate in inquiry and paging mode can be defined via the access code. The access code is the only criterion for the system to check if there is a valid transmission or not. If you regard the presence of a valid access code as one bit of information, and compare it with the length of the access code of 68 bits, the Spread rate / Data rate will be 68/1.

12 Spurious emission in hybrid mode

The Dwell in hybrid mode is shorter than in data mode. For this reason the spurious emissions average level in data mode is worst case. The spurious emissions peak level is the same for both modes.