

TEST REPORT No.: 02001415

Date : 2002.09.12

EQUIPMENT UNDER TEST:

Trade Name: HELLA
Model: 5FA 008 750-50
Serial No: none
Equipment Category: Transmitter
Manufacturer: HELLA KG Hueck & Co.
Address: Rixbecker Straße 75
D-59552 Lippstadt
Germany
Phone: +49 2941 38 8392
Fax: +49 2941 38 8074
E-mail: Heinz-Theo.Holle@hella.de
RELEVANT STANDARD: 47 CFR Part 15C - Intentional Radiators
USED: ANSI C63.4-1992

TEST REPORT PREPARED

BY:

Ralf Trepper
m.dudde hochfrequenz-technik
Rottland 5a
D-51429 Bergisch Gladbach
Germany
Phone: +49 2207 96890
Fax : +49 2207 968920
E-mail: manfred.dudde@t-online.de

TEST PERSONNEL:

Ralf Trepper



SIGNATURE OF THE COMPANY OFFICIAL:

Manfried Dudde



CONTENTS

1 GENERAL INFORMATION	4
1.1 Purpose	4
1.2 Limits and Reservations	4
1.3 Test Location	4
1.4 Manufacturer	4
1.5 Dates	4
2 PRODUCT DESCRIPTION	5
2.1 Equipment Under Test (EUT)	5
2.2 EUT Peripherals	5
2.4 Modifications Required for Compliance	5
4 ANTENNA REQUIREMENT	7
4.1 Regulation	7
4.2 Result	7
5 RADIATED EMISSIONS	8
5.1 Regulation	8
5.2 Test Equipment	9
5.3 Test Procedures	9
5.4 Calculation of Field Strength Limits	10
5.5 Calculation of Average Correction Factor	10
5.6 Field Strength Calculation	10
5.7 Test Results	11
5.7.1 Model 5 FA 008 750-50	11
6 CONDUCTED EMISSIONS TESTS	12
6.1 Regulation	12
6.2 Test Equipment	12
6.3 Test Procedures	12
6.4 Test Results	12
7 PERIODIC OPERATION CHARACTERISTICS	13
7.1 Periodic Operation	13
7.1.1 Regulation	13
7.1.2 Result	13
7.2 Manually Operated Transmitter Deactivation	13
7.2.1 Regulation	13
7.2.2 Result	13
7.3 Automatically Operated Transmitter Deactivation	14
7.3.1 Regulation	14
7.3.2 Result	14
7.4 Prohibition of Periodic Transmission	14
7.4.1 Regulation	14
7.4.2 Result	14
7.5 Continuous Transmission During an Alarm Condition	14
7.5.1 Regulation	14
7.5.2 Result	14
8.1 Regulation	15
8.2 Calculation of 20 dB Bandwidth Limit	15
8.3 Test Equipment	15
8.4 Test Procedure	15
8.5 Test Result	16
8.5.1 Model : 5 FA 008 750-50	16
9 PHOTOGRAHPS OF THE TEST SETUP	17
9.1 Radiated Emissions Tests	17
9.1.2 Photograph: EUT in horizontal polarization on the turntable	17
9.2 Conducted Emission Tests	18
not applicable10 MISCELLANEOUS COMMENTS AND NOTES	18

10	MISCELLANEOUS COMMENTS AND NOTES	19
11	LIST OF ANNEXES.....	20

1 GENERAL INFORMATION

1.1 Purpose

The purpose of this report is to show compliance to the FCC regulations for unlicensed devices operating under section 15.231 of the Code of Federal Regulations title 47.

1.2 Limits and Reservations

The test results in this report apply only to the particular Equipment Under Test (EUT) as declared in this report. This test report shall not be reproduced except in full without the written permission of m.dudde hochfrequenz-technik.

1.3 Test Location

Company Name: m.dudde high frequency technology
Street: Rottland 5a
City: 51429 Bergisch Gladbach
Country: Germany
Laboratory: FCC Registration Number: 699717
This site has been fully described in a report submitted to the FCC, and
accepted in the letter dated Registration Number 699717.
Phone: +49-2207-9689-0
Fax: +49-2207-9689-20
Mail: manfred.dudde@t-online.de
Web: <http://www.dudde.com>

1.4 Manufacturer

Company Name: HELLA KG Hueck & Co.
Street: Rixbecker Straße 75
City: D-59552 Lippstadt
Country: Germany

Name for contact purposes: Heinz-Theo Holle

Phone: +49 2941 38 8392
Fax: +49 2941 38 8074
Mail: Heinz-Theo.Holle@hella.de

1.5 Dates

Date of receipt of EUT: 2002 08 05
Test date: 2002 09 03

2 PRODUCT DESCRIPTION

2.1 Equipment Under Test (EUT)

Device:	Transmitter
Trade Name:	HELLA
Model:	5FA 008 750-50
Serial Number:	none (Prototype)
FCC ID:	NBG008750T
Power:	3.0 V DC
Transmit Frequency:	315 MHz
Type of modulation:	A1D
Interface:	none
Variants:	none
Highest frequency generated or used in the device:	9.84375 MHz

2.2 EUT Peripherals

The EUT were tested as stand-alone device.

2.3 Mode of Operation During Testing

The transmitter were tested in a typical fashion. During preliminary emission tests all 3 transmitter codes activated by the 3 different buttons ("Lock", "Release" and "Tailgate remote release") were investigated for worst case emission mode. Pressing the "Lock" button was found to be the worst case emission mode. Therefore, final qualification testing was completed with transmitters activated with the "Lock" button.

2.4 Modifications Required for Compliance

None.

3 TEST RESULTS SUMMARY

Summary of Test Results Transmitter

Requirement	CFR Section	Report Section	Test Result
Antenna Requirement	15.203	4	Pass
Radiated Spurious Emissions	15.209, 15.205(b)	5	Pass
Conducted Emissions	15.207	6	*
Periodic Operation Characteristics	15.231 (a)	7	Pass
Field Strength Limits (Fundamental)	15.231 (b)	5	Pass
20 dB Bandwidth	15.231 (c)	9	Pass

* Not required, the EUT is battery powered.

The client has made the determination that EUT Condition, Characterization, and Mode of Operation are representative of production units, and meet the requirements of the specifications referenced herein.

Consistent with Industry practice, measurement and test equipment not directly involved in obtaining measurement results but having an impact on measurements (such as cable loss, antenna factors, etc.) are factored into the "Correction Factor" documented in certain test results. Instrumentation employed for testing meets tolerances consistent with known Industry Standards and Regulations.

The measurements contained in this report were made in accordance with the procedure ANSI C63.4 1992 and all applicable Public Notices received prior to the date of testing. All emissions from the device were found to be within the limits outlined in this report. The test results in this report apply only to the particular Equipment Under Test (EUT) as declared in this report.

Test Personnel: Ralf Trepper

Issuance Date: 2002 09 03

4 ANTENNA REQUIREMENT

Test Requirement: FCC CFR47, Part 15C

4.1 Regulation

15.203 An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of Part 15C. The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of Sections 15.211, 15.213, 15.217, 15.219, or 15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with Section 15.31 (d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this Part are not exceeded.

4.2 Result

Device: Remote Control (RF) for Car Locking / Unlocking

Transmitter Model:

Antenna is a trace on the PCB.

The EUT meets the requirements of this section.

5 RADIATED EMISSIONS

Test Requirement: FCC CFR47, Part 15C Test Procedure: ANSI C63.4:1992

5.1 Regulation

15.231 (b) In addition to the provisions of Section 15.205, the field strength of emissions from intentional radiators operated under this Section shall not exceed the following:

Fundamental Frequency (MHz)	Field Strength of Fundamental (microvolts/meter)	Field Strength of Spurious Emissions (microvolts/meter)
40.66 - 40.70	2,250	225
70-130	1,250	125
130-174	1,250 to 3,750	125 to 375
174-260	3,750	375
260-470	3,750 to 12,500	375 to 1,250
Above 470	12,500	1,250

** Linear interpolations

[Where F is the frequency in MHz, the formulas for calculating the maximum permitted fundamental field strengths are as follows: for the band 130-174 MHz, $\mu\text{V/m}$ at 3 meters = $56.81818(F) - 6136.3636$; for the band 260-470 MHz, $\mu\text{V/m}$ at 3 meters = $41.6667(F) - 7083.3333$. The maximum permitted unwanted emission level is 20 dB below the maximum permitted fundamental level.]

(1) The above field strength limits are specified at a distance of 3 meters. The tighter limits apply at the band edges.

(2) Intentional radiators operating under the provisions of this Section shall demonstrate compliance with the limits on the field strength of emissions, as shown in the above table, based on the average value of the measured emissions. As an alternative, compliance with the limits in the above table may be based on the use of measurement instrumentation with a CISPR quasi-peak detector. The specific method of measurement employed shall be specified in the application for equipment authorization. If average emission measurements are employed, the provisions in Section 15.35 for averaging pulsed emissions and for limiting peak emissions apply. Further, compliance with the provisions of Section 15.205 shall be demonstrated using the measurement instrumentation specified in that section.

(3) The limits on the field strength of the spurious emissions in the above table are based on the fundamental frequency of the intentional radiator. Spurious emissions shall be attenuated to the average (or, alternatively, CISPR quasi-peak) limits shown in this table or to the general limits shown in Section 15.209, whichever limit permits a higher field strength

Section 15.33 Frequency range of radiated measurements: (a) Unless otherwise noted in the specific rule section under which the equipment operates for an intentional radiator the spectrum shall be investigated from the lowest radio frequency signal generated in the device, without going below 9 kHz, up to at least the frequency shown in this paragraph: (1) If the intentional radiator operates below 10 GHz: to the tenth harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower.

5.2 Test Equipment

Type	Manufacturer/ Model No.	Serial No.	Last Calibration	Next Calibration
Receiver (9 kHz –30 MHz)	Anritzu Spectrum Analyzer MS 2601 (2)	MT74457	03/2002	03/2005
Receiver (9 kHz –30 MHz)	Rohde & Schwarz ESH2 (22)	882902/007	01/2002	01/2005
Loop Antenna	Schwarzbeck FMZB 1516			

5.3 Test Procedures

For tabletop equipment, the EUT is placed on a 1 meter by 1.5 meters wide and 0.8 meter high nonconductive table that sits on a flush mounted metal turntable. Floor standing equipment is placed directly on the flush mounted metal turntable [*Remark: Not applicable*]. The EUT is connected to its associated peripherals with any excess I/O cabling bundled to approximately 1 meter [*Remark: Not applicable*].

Preview tests are performed to determine the "worst case" mode of operation. With the EUT operating in "worst case" mode, emissions from the unit are maximized by adjusting the polarization and height of the receive antenna and rotating the EUT on the turntable. Manipulating the system cables also maximizes EUT emissions [*Remark: Not applicable*]. All tests performed with the EUT placed in two polarizations on the nonconductive table: horizontal and vertical. Refer to the photographs' section.

Please note that in order to establish the "worst case" planes of testing sample, all three orthogonal planes had been examined in a pretest. The final measurement had been carried out only in the two orthogonal planes with the highest emissions.

Radiated Emissions Test Characteristics	
Frequency range	30 MHz - 4,000 MHz
Test distance	3 m*
Test instrumentation resolution bandwidth	120 kHz (30 MHz - 1,000 MHz) 1 MHz (1000 MHz - 4,000 MHz)
Receive antenna scan height	1 m - 4 m
Receive antenna polarization	Vertical/Horizontal

* According to Section 15.31 (f)(1): At frequencies at or above 30 MHz, measurements may be performed at a distance other than what is specified provided: measurements are not made in the near field except where it can be shown that near field measurements are appropriate due to the characteristics of the device; and it can be demonstrated that the signal levels needed to be measured at the distance employed can be detected by the measurement equipment. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade (inverse linear-distance for field strength measurements; inverse-linear-distance-squared for power density measurements).

5.4 Calculation of Field Strength Limits

Fundamental field strength limits for the band 260 - 470 MHz: $\mu\text{V/m}$ at 3 meters = 41.6667(F[MHz]) - 7083.3333 = 41.6667 * 315 - 7083.3333 = 6,041.68 $\mu\text{V/m}$ corresponds with 75.6 dB $\mu\text{V/m}$. The maximum permitted unwanted emission level is 20 dB below the maximum permitted fundamental level, i.e. 55.6 dB $\mu\text{V/m}$.

5.5 Calculation of Average Correction Factor

The average correction factor is computed by analyzing the "worst case" on time in any 100 msec time period and using the formula: Corrections Factor (c113) + 20*Log (worst case on time/100 msec) Analysis of the remote transmitter worst case on time in any 100 msec time period is an on time of 50 msec, therefor the correction factor is 20*Log (50/100) = - 6 dB. The maximum correction factor to be applied is 20 dB per section 15.35 of the FCC rules. *The relationship between average and peak mode reading has been confirmed also by direct measurement using the receiver's average and peak detectors. All emission measurements performed using the test receiver's average detector and the max. hold facility.*

5.6 Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor. The basic equation with a sample calculation is as follows:

FS=RA+ AF+CF where FS Field Strength in dB $\mu\text{V/m}$ RA Receiver Amplitude in dB μV AF Antenna Factor in dB(1/m) CF Cable Attenuation Factor in dB

Assume a receiver reading of 23.5 dB μV is obtained. The Antenna Factor of 7.4 dB(1/m) and a Cable Factor of 1.1 dB are added, giving a field strength of 32 dB $\mu\text{V/m}$. The 32 dB $\mu\text{V/m}$ value can be mathematically converted to its corresponding level in $\mu\text{V/m}$.

$$\text{FS} = 23.5 + 7.4 + 1.1 = 32 \text{ [dB}\mu\text{V/m]}$$

$$\text{Level in } \mu\text{V/m} = \text{Common Antilogarithm } (32/20) = 39.8$$

For test distance other than what is specified, but fulfilling the requirements of Section 15.31 (f)(1) the field strength is calculated by adding additionally an extrapolation factor of 20 dB/decade (inverse linear distance for field strength measurements). The basic equation with a sample calculation is as follows:

$$\text{FS=RA+ AF+CF+DF where}$$

FS Field Strength in dB $\mu\text{V/m}$

RA Receiver Amplitude in dB μV **AF** Antenna Factor in dB(1/m) **CF** Cable Attenuation Factor in dB **DF** Distance Extrapolation Factor in dB, where $DF = 20 \log (D_{\text{test}}/D_{\text{spec}})$ where D_{test} = Test Distance and D_{spec} = Specified Distance

Assume the tests performed at a reduced Test Distance of 1,5 m instead of the Specified Distance of 3 m giving a Distance Extrapolation Factor of $DF = 20 \log(1.5m/3m) = -6$ dB. Assuming a receiver reading of 23.5 dB μ V is obtained. The Antenna Factor of 7.4 dB(1/m), the Cable Factor of 1.1 dB and the Distance Factor of -6 dB are added, giving a field strength of 26 dB μ V/m. The 26 dB μ V/m value can be mathematically converted to its corresponding level in μ V/m.

$$FS = 23.5 + 7.4 + 1.1 - 6 = 26 \text{ [dB}\mu\text{V/m]}$$

Level in μ V/m = Common Antilogarithm (26/20) = 20

5.7 Test Results

5.7.1 Model 5 FA 008 750-50

PRODUCT EMISSIONS PEAK DATA 15.231 BANDS											
No	Emission Frequency [MHz]	Receiver Mode and Bandwidth [kHz]	Test Distance [m]	Receiver Reading RA [dB μ V]	Correction Factor AF+CF [dB(1/m)]	Distance Extrapolation Factor DF [dB]	Result = Corrected Reading FS [dB μ V/m]	Spec Limit [dB μ V/m]	Antenna Height [m]	Polarization Eut/Ant	Margin [dB]
1	315.0048	120, QPK	3	51.49	+16	0	67.49	75.6	180	H/V	8.11
		120, AV	3	48.25	+16	0	64.25	75.6	180	H/V	11.35
2	630.0096	120, QPK	3	28.99	+2	0	30.99	55.6	200	H/V	24.61
		120, AV	3	26.40	+2	0	28.40	55.6	200	H/V	27.20
3	945.0144	120, QPK	3	29.80	+6	0	35.80	55.6	380	H/V	19.80
		120, AV	3	27.55	+6	0	33.55	55.6	380	H/V	22.05
3	1260.0192	1000, AV	3	< 10	+28.5	0	38.5* ²	55.6	100-400	H, V/H, V	17.10
4	1575.0240	1000, AV	3	< 10	+28.6	0	38.6* ²	55.6	100-400	H, V/H, V	17.00
5	1890.0288	1000, AV	3	< 10	+29.0	0	39.0* ²	55.6	100-400	H, V/H, V	16.60
6	2205.0336	1000, AV	3	< 17	+29.3	0	46.3* ³	55.6	100-400	H, V/H, V	9.30
7	2520.0384	1000, AV	3	< 17	+30.6	0	47.6* ³	55.6	100-400	H, V/H, V	8.00
8	2835.0432	1000, AV	3	< 17	+31.4	0	48.4* ³	55.6	100-400	H, V/H, V	7.20
9	3150.0480	1000, AV	3	< 17	+31.6	0	48.6* ³	55.6	100-400	H, V/H, V	7.00
10	3465.0528	1000, AV	3	< 17	+32.5	0	49.5* ³	55.6	100-400	H, V/H, V	6.10

PRODUCT EMISSIONS PEAK DATA 15.205 BANDS											
No	Emission Frequency [MHz]	Receiver Mode and Bandwidth [kHz]	Test Distance [m]	Receiver Reading RA [dB μ V]	Correction Factor AF+CF [dB(1/m)]	Distance Extrapolation Factor DF [dB]	Result = Con-ected Reading FS [dB μ V/m]	Spec Limit [dB μ V/m]	Antenna Height [m]	Polarization Eut/Ant	Margin [dB]
1	In this band no emissions detected *¹										
2											
3											

Remark: *¹ noise floor noise level of the measuring instrument ≤ 6.5 dB μ V @ 3m distance (30 – 1000 MHz)

Remark: *² noise floor noise level of the measuring instrument ≤ 10 dB μ V @ 3m distance (1000 – 2000 MHz)

Remark: *³ noise floor noise level of the measuring instrument ≤ 17 dB μ V @ 3m distance (2000 – 5500 MHz)

The EUT meets the requirements of this section.

Test Personnel: Ralf Trepper

Issuance Date: 2002 09 03

6 CONDUCTED EMISSIONS TESTS

Test Requirement: FCC CFR47, Part 15C

Test Procedure: ANSI C63.4:1992

6.1 Regulation

Section 15.207 (a) For an intentional radiator which is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 450 kHz to 30 MHz shall not exceed 250 microvolts. Compliance with this provision shall be based on the measurement of the radio frequency voltage between each power line

and ground at the power terminals.

Section 15.207 (d) Measurements to demonstrate compliance with the conducted limits are not required for devices which only employ battery power for operation and which do not operate from the AC power lines or contain provisions for operation while connected to the AC power lines. Devices that include, or make provision for, the use of battery chargers which permit operating while charging, AC adaptors or

battery eliminators or that connect to the AC power lines indirectly, obtaining their power through another device which is connected to the AC power lines, shall be tested to demonstrate compliance with the

conducted limits.

6.2 Test Equipment

Not applicable.

6.3 Test Procedures

Not applicable.

6.4 Test Results

Device: Remote Control (RF) for Car Locking / Unlocking Transmitter Model: 5 FA 008 750-50

The EUT is battery powered only. Therefore - according to Section 15.207

(d) - conducted emissions measurements to demonstrate compliance with the conducted limits are not required.

7 PERIODIC OPERATION CHARACTERISTICS

Test Requirement: FCC CFR47, Part 15C

7.1 Periodic Operation

7.1.1 Regulation

15.231 (a) The provisions of this Section are restricted to periodic operation within the band 40.66 40.70 MHz and above 70 MHz. Except as shown in paragraph (e) of this Section, the intentional radiator is restricted to the transmission of a control signal such as those used with alarm systems, door openers, remote switches, etc. Radio control of toys is not permitted. Continuous transmissions, such as voice or video, and data transmissions are not permitted. The prohibition against data transmissions does not preclude the use of recognition codes. Those codes are used to identify the sensor that is activated or to identify the particular component as being part of the system.

7.1.2 Result

Device: Remote Control (RF) for Car Locking / Unlocking

Transmitter Model: 5 FA 008 750-50

The EUT meets the requirements of this section.

7.2 Manually Operated Transmitter Deactivation

7.2.1 Regulation

15.231 (a1) A manually operated transmitter shall employ a switch that will automatically deactivate the transmitter within not more than 5 seconds of being released.

7.2.2 Result

Device: Remote Control (RF) for Car Locking / Unlocking

Transmitter Model: 5 FA 008 750-50

Transmitter ceases immediately after being released.

The EUT meets the requirements of this section.

7.3 Automatically Operated Transmitter Deactivation

7.3.1 Regulation

15.231 (a2) A transmitter activated automatically shall cease transmission within 5 seconds after activation.

7.3.2 Result

Device: Remote Control (RF) for Car Locking / Unlocking

Transmitter Model: 5 FA 008 750-50

The EUT does not have automatic transmission.

7.4 Prohibition of Periodic Transmission

7.4.1 Regulation

15.231 (a3) Periodic transmissions at regular predetermined intervals are not permitted. However, polling or supervision transmissions to determine system integrity of transmitters used in security or safety applications are allowed if the periodic rate of transmission does not exceed one transmission of not more than one second duration per hour for each transmitter.

7.4.2 Result

Device: Remote Control (RF) for Car Locking / Unlocking

Transmitter Model: 5 FA 008 750-50

The EUT does not employ periodic transmission.

7.5 Continuous Transmission During an Alarm Condition

7.5.1 Regulation

15.231 (a4) Intentional radiators which are employed for radio control purposes during emergencies involving fire, security, and safety of life, when activated to signal an alarm, may operate during the pendency of the alarm condition.

7.5.2 Result

Device: Remote Control (RF) for Car Locking / Unlocking

Transmitter Model: 5 FA 008 750-50

This section is not applicable to the EUT.

8 BANDWIDTH

Test Requirement: FCC CFR47, Part 15C

Test Procedure: ANSI C63.4:1992 Section 13.1.7

8.1 Regulation

15.231 (c) The bandwidth of the emission shall be no wider than 0.25% of the center frequency for devices operating above 70 MHz and below 900 MHz. For devices operating above 900 MHz, the emission shall be no wider than 0.5% of the center frequency. Bandwidth is determined at the points 20 dB down from the modulated carrier.

8.2 Calculation of 20 dB Bandwidth Limit

The 20 dB bandwidth limit = $0.0025 * 315 \text{ MHz} = 0.7875 \text{ MHz} = 787.5 \text{ kHz}$

8.3 Test Equipment

Type	Manufacturer/ Model No.	Serial No.	Last Calibration	Next Calibration
Receiver (30MHz - 1GHz)	Hewlett Packard Spectrum Analyzer (171)	3528U00990	02/2002	02/2004
(30MHz - 1GHz)	8593 E			
Pre-Amplifier	Hewlett Packard			
(30MHz - 1GHz)	8447 E (166a)	1726°00705	04/2002	04/2006
Antenna	Chase (Bilog)	1517	04/2002	04/2008
(30 MHz - 1 GHz)	CBL 611A			
Receiver (1 GHz - 26.5 GHz) Antenna	Hewlett Packard Spectrum Analyzer (171) 8593 E Schwarzbeck	3528U00990	02/2002	02/2004

8.4 Test Procedure

ANSI C63.4-1992 Section 13.1.7 Occupied Bandwidth Measurements. The bandwidth is measured at an amplitude level reduced from the reference level by a specified ratio. The reference level is the level of the highest amplitude signal observed from the transmitter at either the fundamental frequency or first-order modulation products in all typical modes of operation, including the unmodulated carrier, even if atypical. Once the reference level is established, the equipment is conditioned with typical modulating signals to produce worst-case (i.e., the widest) bandwidth. In order to measure the modulated signal properly, a resolution bandwidth that is small compared to the bandwidth required by the procuring or regulatory agency shall be used on the measuring instrument. However, the 6 dB resolution bandwidth of the measuring instrument shall be set to a value greater than 5% of the bandwidth requirements.

8.5 Test Result

8.5.1 Model : 5 FA 008 750-50

Bandwidth setting of the analyzer: 30 kHz [3 dB] corresponds with 46 kHz [6 dB]

The measured 20 dB bandwidth is: **190 kHz**

The EUT meets the requirements of this section.


Test Personnel: Ralf Trepper

Issuance Date: 2002 09 03

9 PHOTOGRAPHS OF THE TEST SETUP

9.1 Radiated Emissions Tests

9.1.2 Photograph: EUT in horizontal polarization on the turntable



9.2 Conducted Emission Tests

not applicable

10 MISCELLANEOUS COMMENTS AND NOTES

None.

11 LIST OF ANNEXES

The following Exhibits are separated annexes to this test report.

Annex No.	Exhibit	Pages
1	External Photographs of the Equipment Under Test	2
2	Internal Photographs of the Equipment Under Test	2
3	Occupied Bandwidth Plot	1
4	FCC ID Label Sample	1
5	Technical Description /Operational Description	4
6	Test Setup Foto	1
7	Block Diagram	1
8	Schematics	5