

FCC Test Report

Product Name	Radio Identification device
Model No.	FS09P03
FCC ID.	NBGFS09P03

Applicant	Hella KGaA Hueck & Co.
Address	Rixbecker Strasse 75, 59552 Lippstadt, Germany

Date of Receipt	Mar. 10, 2016
Issued Date	Mar. 18, 2016
Report No.	1630219R-RFUSP14V00
Report Version	V1.0



The test results relate only to the samples tested.

The test results shown in the test report are traceable to the national/international standard through the calibration of the equipment and evaluated measurement uncertainty herein.

This report must not be used to claim product endorsement by TAF or any agency of the government.

The test report shall not be reproduced without the written approval of QuieTek Corporation.

Test Report

Issued Date : Mar. 18, 2016

Report No. : 1630219R-RFUSP14V00



Product Name	Radio Identification device
Applicant	Hella KGaA Hueck & Co.
Address	Rixbecker Strasse 75, 59552 Lippstadt, Germany
Manufacturer	1. Hella KGaA Hueck & Co. 2. Hella Shanghai Electronics Co. Ltd (HSE)
Model No.	FS09P03
FCC ID.	NBGFS09P03
EUT Rated Voltage	DC 3V(Power by Battery)
EUT Test Voltage	DC 3V(Power by Battery)
Trade Name	HELLA
Applicable Standard	FCC CFR Title 47 Part 15 Subpart C: 2014 ANSI C63.4: 2014, ANSI C63.10: 2013
Test Result	Complied

Documented By :

Leven Huang

(Senior Adm. Specialist / Leven Huang)

Tested By :

Ken chen

(Engineer / Ken Chen)

Approved By :

Vincent Lin

(Director / Vincent Lin)

TABLE OF CONTENTS

Description	Page
1. General Information	4
1.1. EUT Description.....	4
1.2. Operation Description	5
1.3. Tested System Details.....	6
1.4. Configuration of tested System	6
1.5. EUT Exercise Software	6
1.6. Test Facility	7
2. Conducted Emission.....	8
2.1. Test Equipment.....	8
2.2. Test Setup	8
2.3. Limits	9
2.4. Test Procedure	9
2.5. Test Specification	9
2.6. Uncertainty	9
2.7. Test Result	10
3. Radiated Emission.....	11
3.1. Test Equipment.....	11
3.2. Test Setup	12
3.3. Limits	13
3.4. Test Procedure	14
3.5. Test Specification	14
3.6. Uncertainty	14
3.7. Test Result	15
4. Transmit time.....	21
4.1. Test Equipment.....	21
4.2. Test Setup	21
4.3. Limits	21
4.4. Test Specification	21
4.5. Uncertainty	21
4.6. Test Result	22
5. Occupied Bandwidth.....	23
5.1. Test Equipment.....	23
5.2. Test Setup	23
5.3. Limits	23
5.4. Test Specification	23
5.5. Uncertainty	23
5.6. Test Result	24

Attachment 1: EUT Test Photographs

Attachment 2: EUT Detailed Photographs

1. General Information

1.1. EUT Description

Product Name	Radio Identification device
Trade Name	HELLA
Model No.	FS09P03
FCC ID	NBGFS09P03
Frequency Range	315MHz
Number of Channels	1
Type of Modulation	A1D (OOK)
Antenna Type	Loop antenna on PCB

Frequency of Each Channel:

Channel	Frequency
Channel 1:	315 MHz

Note:

1. The EUT is a Radio Identification device with a built-in 315 MHz transmitter.
2. The antenna of EUT is conform to FCC 15.203
3. These tests are conducted on a sample for the purpose of demonstrating compliance with Part 15 Subpart C Paragraph 15.231.
4. The radiation measurements are performed in X, Y, Z axis positioning. Only the worst case is shown in the report.

Test Mode	Mode 1: Transmit
-----------	------------------


1.3. Tested System Details

The types for all equipments, plus descriptions of all cables used in the tested system (including inserted cards) are:

Product	Manufacturer	Model No.	Serial No.	FCC ID	Power Cord
N/A					

Signal Cable Type	Signal cable Description
N/A	

1.4. Configuration of tested System



1.5. EUT Exercise Software

1	Setup the EUT as shown in section 1.4.
2	Install the battery.
3	Press the test button of the EUT.
4	Verify that the EUT works properly.

1.6. Test Facility

Ambient conditions in the laboratory:

Items	Required (IEC 68-1)	Actual
Temperature (°C)	15-35	20-35
Humidity (%RH)	25-75	30-65
Barometric pressure (mbar)	860-1060	950-1000

The related certificate for our laboratories about the test site and management system can be downloaded from
QuieTek Corporation's Web Site: <http://www.quietek.com/chinese/about/certificates.aspx?bval=5>

The address and introduction of QuieTek Corporation's laboratories can be founded in our Web site:
<http://www.quietek.com/>

Site Description: File on
Federal Communications Commission
FCC Engineering Laboratory
7435 Oakland Mills Road
Columbia, MD 21046
Registration Number: 92195

Site Name: Quietek Corporation
Site Address: No.5-22, Ruishukeng,
Linkou Dist. New Taipei City 24451,
Taiwan, R.O.C.
TEL: 886-2-8601-3788 / FAX : 886-2-8601-3789
E-Mail : service@quietek.com

FCC Accreditation Number: TW1014

2. Conducted Emission


2.1. Test Equipment

	Equipment	Manufacturer	Model No. / Serial No.	Last Cal.	Remark
X	Test Receiver	R & S	ESCS 30 / 825442/018	Sep., 2015	
X	Artificial Mains Network	R & S	ENV4200 / 848411/10	Feb., 2016	Peripherals
X	LISN	R & S	ESH3-Z5 / 825562/002	Feb., 2016	EUT
	DC LISN	Schwarzbeck	8226 / 176	Mar, 2016	EUT
X	Pulse Limiter	R & S	ESH3-Z2 / 357.8810.52	Feb., 2016	
	No.1 Shielded Room				

Note:

1. All equipments are calibrated every one year.
2. The test instruments marked by "X" are used to measure the final test results.

2.2. Test Setup



2.3. Limits

FCC Part 15 Subpart C Paragraph 15.207 Limits (dBμV)		
Frequency MHz	QP	AV
0.15 - 0.50	66-56	56-46
0.50-5.0	56	46
5.0 - 30	60	50

Remarks : In the above table, the tighter limit applies at the band edges.

2.4. Test Procedure

The EUT and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50 ohm /50uH coupling impedance for the measuring equipment. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refers to the block diagram of the test setup and photographs.)

Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10: 2013 on conducted measurement.

Conducted emissions were investigated over the frequency range from 0.15MHz to 30MHz using a receiver bandwidth of 9kHz.

2.5. Test Specification

According to FCC Part 15 Subpart C Paragraph 15.231

2.6. Uncertainty

± 2.26 dB

2.7. Test Result

Owing to the DC operation of EUT, this test item is not performed.

3. Radiated Emission

3.1. Test Equipment

The following test equipments are used during the radiated emission test:


Test Site		Equipment	Manufacturer	Model No./Serial No.	Last Cal.
☒ Site # 3	X	Magnetic Loop Antenna	Teseq	HLA6121/ 37133	Sep, 2015
	X	Bilog Antenna	Schaffner Chase	CBL6112B/ 2707	Jun, 2015
	X	EMI Test Receiver	R&S	ESCS 30/838251/ 001	Jun, 2015
	X	Coaxial Cable	QTK(Arnist)	RG 214/ LC003-RG	Jun, 2015
	X	Coaxial signal switch	Arnist	MP59B/ 6200798682	Jun, 2015

Test Site		Equipment	Manufacturer	Model No./Serial No.	Last Cal.
☒ CB # 8	X	Spectrum Analyzer	R&S	FSP40/ 100339	Oct, 2015
	X	Horn Antenna	ETS-Lindgren	3117/ 35205	Mar, 2016
	X	Horn Antenna	Schwarzbeck	BBHA9170/209	Jan, 2016
	X	Horn Antenna	TRC	AH-0801/95051	Aug, 2015
	X	Pre-Amplifier	EMCI	EMC012630SE/980210	Jan, 2016
	X	Pre-Amplifier	MITEQ	JS41-001040000-58-5P/153945	Jul, 2015
	X	Pre-Amplifier	NARDA	DBL-1840N506/013	Jul, 2015


- Note:
1. All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.
 2. The test instruments marked with "X" are used to measure the final test results.

3.2. Test Setup

Radiated Emission Below 1GHz



Radiated Emission Above 1GHz



3.3. Limits

➤ Fundamental and Harmonics Emission Limits

Fundamental Frequency MHz	Field Strength of Fundamental	Field Strength of Spurious Emission
40.66-40.70	2250	225
70-130	1250	125
130-174	1250-3750	125-375
174-260	3750	375
260-470	3750-12500	375-1250
above 470	12500	1250

Remarks :

1. RF Voltage (dBμV) = 20 log RF Voltage (uV)
2. Distance refers to the distance in meters between the measuring instrument antenna and the closed point of any part of the device or system.
3. The emission limit in this paragraph is based on measurement instrumentation employing an average detector.

➤ Spurious electric field strength limits

FCC Part 15 Subpart C Paragraph 15.209 Limits			
Frequency MHz	uV/m	dBμV/m	Measurement distance (meter)
0.009-0.490	2400/F(kHz)	See Remark ¹	300
0.490-1.705	24000/F(kHz)	See Remark ¹	30
1.705-30	30	29.5	30
30-88	100	40	3
88-216	150	43.5	3
216-960	200	46	3
Above 960	500	54	3

Remarks :

1. RF Voltage (dBμV) = 20 log RF Voltage (uV)
2. In the Above Table, the tighter limit applies at the band edges.
3. Distance refers to the distance in meters between the measuring instrument antenna and the closed point of any part of the device or system.

3.4. Test Procedure

Measuring the frequency range below 1GHz, the EUT is placed on a turn table which is 0.8 meter above ground, when measuring the frequency range above 1GHz, the EUT is placed on a turn table which is 1.5 meter above ground. The turn table can rotate 360 degrees to determine the position of the maximum emission level.

The antenna can move up and down between 1 meter and 4 meters to find out the maximum emission level.

Both horizontal and vertical polarization of the antenna are set on measurement. In order to find the maximum emission, all of the interface cables must be manipulated according to ANSI C63.10, 2013 on radiated measurement.

On the field strength of fundamental and harmonics, the limits shown are based on measuring equipment employing a average detector function. As an alternative, compliance with the limits may be based on the use of measurement instrumentation with a CISPR quasi-peak detector.

On the field strength of spurious electric, on any frequency or frequencies below or equal to 1000 MHz, the limits shown are based on measuring equipment employing a quasi-peak detector function and on any frequency or frequencies above 1000 MHz the radiated limits shown are based upon the use of measurement instrumentation employing an average detector function.

When average radiated emission measurement are included emission measurement below 1000 MHz, there also is a limit on the radio frequency emissions, as measured using instrumentation with a peak detector function, corresponding to 20 dB above the maximum permitted average limit.

The bandwidth The resolution bandwidth below 30MHz setting on the field strength meter is 9kHz and below 1GHz setting on the field strength meter is 120 kHz and above 1GHz is 1MHz.

3.5. Test Specification

According to FCC Part 15 Subpart C Paragraph 15.231

3.6. Uncertainty

± 3.8 dB below 1GHz

± 3.9 dB above 1GHz

3.7. Test Result

Product	Radio Identification device		
Test Item	Fundamental Radiated Emission		
Test Mode	Mode 1: Transmit		
Date of Test	2016/03/16	Test Site	No.3 OATS

Fundamental Power (X-Line)

Peak Detector:

Frequency MHz	Correct Factor dB	Reading Level dB μ V	Measurement Level dB μ V/m	Margin dB	Limit dB μ V/m
------------------	-------------------------	--------------------------------	--------------------------------------	--------------	-----------------------

Horizontal

315.000	-17.333	91.260	73.926	-21.697	95.623
---------	---------	--------	--------	---------	--------

Vertical

315.000	-18.535	82.720	64.185	-31.438	95.623
---------	---------	--------	--------	---------	--------

Average Detector:

Frequency MHz	Correct Factor dB	Reading Level dB μ V	Measurement Level dB μ V/m	Margin dB	Limit dB μ V/m
------------------	-------------------------	--------------------------------	--------------------------------------	--------------	-----------------------

Horizontal

315.000	-17.333	83.140	65.806	-9.817	75.623
---------	---------	--------	--------	--------	--------

Vertical

315.000	-18.535	74.560	56.025	-19.598	75.623
---------	---------	--------	--------	---------	--------

Note:

1. Correct factor = Antenna Factor + Cable Loss – Pre-amplifier Gain
2. The average measurement was not performed when the peak measured data under the limit of average detection. If the readings given are average, peak measurement should also be supplied.
3. Limit=20dB+(20log(41.667(315)-7083.333))

Product	Radio Identification device		
Test Item	Fundamental Radiated Emission		
Test Mode	Mode 1: Transmit		
Date of Test	2016/03/16	Test Site	No.3 OATS

Fundamental Power (Y-Line)

Peak Detector:

Frequency MHz	Correct Factor dB	Reading Level dB μ V	Measurement Level dB μ V/m	Margin dB	Limit dB μ V/m
------------------	-------------------------	--------------------------------	--------------------------------------	--------------	-----------------------

Horizontal

315.000	-17.333	91.860	74.526	-21.097	95.623
---------	---------	--------	--------	---------	--------

Vertical

315.000	-18.535	90.880	72.345	-23.278	95.623
---------	---------	--------	--------	---------	--------

Average Detector:

Frequency MHz	Correct Factor dB	Reading Level dB μ V	Measurement Level dB μ V/m	Margin dB	Limit dB μ V/m
------------------	-------------------------	--------------------------------	--------------------------------------	--------------	-----------------------

Horizontal

315.000	-17.333	84.120	66.786	-8.837	75.623
---------	---------	--------	--------	--------	--------

Vertical

315.000	-18.535	83.140	64.605	-11.018	75.623
---------	---------	--------	--------	---------	--------

Note:

1. Correct factor = Antenna Factor + Cable Loss – Pre-amplifier Gain
2. The average measurement was not performed when the peak measured data under the limit of average detection. If the readings given are average, peak measurement should also be supplied.
3. Limit=20dB+(20log(41.667(315)-7083.333))

Product	Radio Identification device		
Test Item	Fundamental Radiated Emission		
Test Mode	Mode 1: Transmit		
Date of Test	2016/03/16	Test Site	No.3 OATS

Fundamental Power (Z-Line)

Peak Detector:

Frequency MHz	Correct Factor dB	Reading Level dB μ V	Measurement Level dB μ V/m	Margin dB	Limit dB μ V/m
------------------	-------------------------	--------------------------------	--------------------------------------	--------------	-----------------------

Horizontal

315.000	-17.333	86.180	68.846	-26.777	95.623
---------	---------	--------	--------	---------	--------

Vertical

315.000	-18.535	94.820	76.285	-19.338	95.623
---------	---------	--------	--------	---------	--------

Average Detector:

Frequency MHz	Correct Factor dB	Reading Level dB μ V	Measurement Level dB μ V/m	Margin dB	Limit dB μ V/m
------------------	-------------------------	--------------------------------	--------------------------------------	--------------	-----------------------

Horizontal

315.000	-17.333	78.500	61.166	-14.457	75.623
---------	---------	--------	--------	---------	--------

Vertical

315.000	-18.535	87.090	68.555	-7.068	75.623
---------	---------	--------	--------	--------	--------

Note:

1. Correct factor = Antenna Factor + Cable Loss – Pre-amplifier Gain
2. The average measurement was not performed when the peak measured data under the limit of average detection. If the readings given are average, peak measurement should also be supplied.
3. Limit=20dB+(20log(41.667(315)-7083.333))

Product	Radio Identification device		
Test Item	Harmonic Radiated Emission		
Test Mode	Mode 1: Transmit		
Date of Test	2016/03/17	Test Site	No.3 OATS

Frequency	Correct	Reading	Measurement	Margin	Peak	Average
MHz	Factor	Level	Level		Limit	Limit
	dB	dB μ V	dB μ V/m	dB	dB μ V/m	dB μ V/m

Harmonic Radiated Emission

Horizontal

Peak

1260.000	-4.305	41.480	37.175	-36.825	74.000	54.000
1575.000	-3.683	42.881	39.198	-34.802	74.000	54.000
1890.000	-3.988	42.016	38.028	-35.972	74.000	54.000
2205.000	-1.857	38.199	36.343	-37.657	74.000	54.000
2520.000	-0.569	43.945	43.376	-30.624	74.000	54.000
2835.000	-0.411	39.145	38.734	-35.266	74.000	54.000
3150.000	-1.109	38.099	36.990	-37.010	74.000	54.000
3465.000	-0.953	41.940	40.987	-33.013	74.000	54.000
3780.000	-0.110	38.556	38.446	-35.554	74.000	54.000
4095.000	1.515	40.930	42.446	-31.554	74.000	54.000
4410.000	1.856	38.195	40.051	-33.949	74.000	54.000
4725.000	2.606	37.477	40.083	-33.917	74.000	54.000

Horizontal

Average

--

Note:

1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. Measurement Level = Reading Level + Correct Factor.
5. Correct Factor = Antenna factor + Cable loss – Amplifier gain.
6. The average measurement was not performed when the peak measured data under the limit of average detection.
7. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product	Radio Identification device		
Test Item	Harmonic Radiated Emission		
Test Mode	Mode 1: Transmit		
Date of Test	2016/03/17	Test Site	No.3 OATS

Frequency	Correct	Reading	Measurement	Margin	Peak	Average
MHz	Factor	Level	Level		Limit	Limit
	dB	dB μ V	dB μ V/m	dB	dB μ V/m	dB μ V/m

Harmonic Radiated Emission

Vertical

Peak

1260.000	-3.699	41.744	38.045	-35.955	74.000	54.000
1575.000	-1.948	49.910	47.962	-26.038	74.000	54.000
1890.000	-3.425	51.250	47.825	-26.175	74.000	54.000
2205.000	-1.874	41.088	39.214	-34.786	74.000	54.000
2520.000	-1.229	43.480	42.252	-31.748	74.000	54.000
2835.000	-0.571	43.500	42.929	-31.071	74.000	54.000
3150.000	-0.634	38.077	37.443	-36.557	74.000	54.000
3465.000	-0.262	43.940	43.678	-30.322	74.000	54.000
3780.000	0.973	42.999	43.972	-30.028	74.000	54.000
4095.000	2.241	41.390	43.631	-30.369	74.000	54.000
4410.000	4.070	37.480	41.550	-32.450	74.000	54.000
4725.000	6.379	38.056	44.434	-29.566	74.000	54.000

Vertical

Average

--

Note:

1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. Measurement Level = Reading Level + Correct Factor.
5. Correct Factor = Antenna factor + Cable loss – Amplifier gain.
6. The average measurement was not performed when the peak measured data under the limit of average detection.
7. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product	Radio Identification device		
Test Item	General Radiated Emission		
Test Mode	Mode 1: Transmit		
Date of Test	2016/03/16	Test Site	No.3 OATS

Frequency MHz	Correct Factor dB	Reading Level dBμV	Measurement Level dBμV/m	Margin dB	Limit dBμV/m
Horizontal					
Quasi-Peak					
99.840	-15.568	39.313	23.745	-19.755	43.500
205.880	-21.517	39.588	18.071	-25.429	43.500
322.945	-16.806	45.088	28.282	-17.718	46.000
544.122	-9.375	35.644	26.269	-19.731	46.000
630.000	-7.258	39.000	31.742	-14.258	46.000
945.000	-6.682	46.000	39.318	-6.682	46.000
Vertical					
Quasi-Peak					
99.840	-15.568	43.955	28.387	-15.113	43.500
255.930	-14.178	41.770	27.592	-18.408	46.000
289.991	-18.376	38.150	19.774	-26.226	46.000
408.117	-12.451	41.422	28.971	-17.029	46.000
630.112	-10.115	45.200	35.085	-10.915	46.000
945.000	-5.815	50.200	44.385	-1.615	46.000

Note:

1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
2. Peak measurements: RBW = 1MHz, VBW = 3 MHz, Sweep: Auto.
3. Average measurements: RBW = 1MHz, VBW = 10 Hz, Sweep: Auto.
4. Measurement Level = Reading Level + Correct Factor.
5. Correct Factor = Antenna factor + Cable loss – Amplifier gain.
6. The average measurement was not performed when the peak measured data under the limit of average detection.
7. The emission levels of other frequencies are very lower than the limit and not show in test report.
8. No emission found between lowest internal used/generated frequency to 30MHz.

4. Transmit time


4.1. Test Equipment

The following test equipment are used during the test:

	Equipment	Manufacturer	Model No./Serial No.	Last Cal.
	Spectrum Analyzer	R&S	FSP40 / 100170	Jun, 2015
	Spectrum Analyzer	Agilent	E4407B / US39440758	Jun, 2015
X	Spectrum Analyzer	Agilent	N9010A / MY48030495	Apr., 2015

Note: 1. All equipments are calibrated every one year.
2. The test instruments marked by “X” are used to measure the final test results.

4.2. Test Setup



4.3. Limits

A manually operated transmitter shall employ a switch that will automatically deactivate the transmitter within not more than 5 seconds of being released.

A transmitter activated automatically shall cease transmission within 5 seconds after activation.

4.4. Test Specification

According to FCC Part 15 Subpart C Paragraph 15.231


4.5. Uncertainty

± 25ms

4.6. Test Result

Product	Radio Identification device		
Test Item	Transmit time		
Test Mode	Mode 1: Transmit		
Date of Test	2016/03/16	Test Site	No.3 OATS

Channel No.	Frequency (MHz)	Measurement Value (Sec)	Limit (Sec)	Result
1	315	0.380	< 5	Pass



5. Occupied Bandwidth


5.1. Test Equipment

The following test equipment are used during the test:

	Equipment	Manufacturer	Model No./Serial No.	Last Cal.
	Spectrum Analyzer	R&S	FSP40 / 100170	Jun, 2015
	Spectrum Analyzer	Agilent	E4407B / US39440758	Jun, 2015
X	Spectrum Analyzer	Agilent	N9010A / MY48030495	Apr., 2015

Note: 1. All equipments are calibrated every one year.
2. The test instruments marked by “X” are used to measure the final test results.

5.2. Test Setup



5.3. Limits

The bandwidth of the emission shall be no wider than 0.25% of the center frequency for devices operating above 70MHz and below 900MHz. For devices operating above 900MHz, the emission shall be no wider than 0.5% of the center frequency. Bandwidth is determined at the points 20 dB down from the modulated carrier

5.4. Test Specification

According to FCC Part 15 Subpart C Paragraph 15.231

5.5. Uncertainty

± 150Hz

5.6. Test Result

Product	Radio Identification device		
Test Item	Occupied Bandwidth		
Test Mode	Mode 1: Transmit		
Date of Test	2016/03/18	Test Site	No.3 OATS

Channel No.	Frequency (MHz)	Measurement Value (MHz)	Limit (MHz)	Result
1	315	0.051	0.7875	Pass

Note: Limit = 315MHz * 0.25%= 0.7875MHz

Figure Channel 1:

