

PGDQ2

June 17, 1993

Component - Marking and Labeling Systems

CHUNG TAI PRINTING CO LTD

CHUNG TAI PRINTING GROUP BLDG 11 YIP
CHEONG ST ON LOK TSUEN, FANLING HONG

KONG

MH13653 (N)

Pressure-sensitive systems:

"300" removable intact. Affixed to aluminum, galvanized steel, stainless steel, porcelain, alkyd enamel and acrylonitrile butadiene styrene (ABS) plastic, maximum temperature 80 C (176 F), minimum temperature -40 C (-40 F). Suitable where exposed indoors or outdoors to high humidity or occasional exposure to water.

"1002" removable intact. Affixed to aluminum, galvanized steel, stainless steel, porcelain and alkyd enamel maximum temperature 125 C (257 F), minimum temperature -40 C (-40 F); phenolic, nylon polycarbonate and acrylonitrile butadiene styrene (ABS) plastic, maximum temperature 60 C (140 F), minimum temperature -40 C (-40 F). Suitable where exposed indoors or outdoors to high humidity or occasional exposure to water.

Marking: Company trade mark "CTP", factory identification and label designation on label or on label packages.

See General Information Preceding These Recognitions.

For use only in equipment where the acceptability of the combination is determined by Underwriters Laboratories Inc.

Report: May 30, 1985; April 18, 1985.

Replaces MH13653 dated January 10, 1991.

Underwriters Laboratories Inc.®

823333002

DIU0116431