






# TEST REPORT

**Report Reference No.**..... : **TRE1803010601** R/C.....: 98148  
**FCC ID**..... : **NCI-VH810-M01**  
**Applicant's name**..... : **VIA Technologies, Inc.**  
Address.....: 8F,533 Zhongzheng Rd, Xindian Dist, New Taipei City, Taiwan  
Manufacturer.....: VIA Technologies(Shenzhen)Co.,Ltd.  
Address.....: 4F, VIA Building, NO. 9966, Shennan Avenue,  
Nanshan District, Shenzhen, China  
**Test item description** ..... : **Full HD Battery IP Camera**  
Trade Mark .....: VIA  
Model/Type reference.....: VH810 M01  
Listed Model(s) .....: VH810 MXX(XX represent 01,02.....99)  
**Standard** ..... : **FCC CFR Title 47 Part 15 Subpart C Section 15.247**  
Date of receipt of test sample.....: Mar. 14, 2018  
Date of testing.....: Mar. 15, 2018 - Mar. 21, 2018  
Date of issue.....: Mar. 22, 2018  
**Result**.....: **PASS**

Compiled by  
(position+printedname+signature)....: File administrators Fanghui Zhu   
Supervised by  
(position+printedname+signature)....: Project Engineer John Qiao   
Approved by  
(position+printedname+signature)....: RF Manager Hans Hu 

**Testing Laboratory Name** ..... : **Shenzhen Huatongwei International Inspection Co., Ltd.**  
Address.....: 1/F, Bldg 3, Hongfa Hi-tech Industrial Park, Genyu Road,  
Tianliao, Gongming, Shenzhen, China

**Shenzhen Huatongwei International Inspection Co., Ltd. All rights reserved.**

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen Huatongwei International Inspection Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen Huatongwei International Inspection Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

*The test report merely correspond to the test sample.*

## Contents

<b>1.</b>	<b><u>TEST STANDARDS AND REPORT VERSION</u></b>	<b>3</b>
1.1.	Test Standards	3
1.2.	Report version	3
<b>2.</b>	<b><u>TEST DESCRIPTION</u></b>	<b>4</b>
<b>3.</b>	<b><u>SUMMARY</u></b>	<b>5</b>
3.1.	Client Information	5
3.2.	Product Description	5
3.3.	Operation state	6
3.4.	EUT configuration	6
3.5.	Modifications	6
<b>4.</b>	<b><u>TEST ENVIRONMENT</u></b>	<b>7</b>
4.1.	Address of the test laboratory	7
4.2.	Test Facility	7
4.3.	Environmental conditions	8
4.4.	Statement of the measurement uncertainty	8
4.5.	Equipments Used during the Test	9
<b>5.</b>	<b><u>TEST CONDITIONS AND RESULTS</u></b>	<b>11</b>
5.1.	Antenna requirement	11
5.2.	Conducted Emissions (AC Main)	12
5.3.	Conducted Peak Output Power	15
5.4.	Power Spectral Density	16
5.5.	6dB bandwidth	22
5.6.	Restricted band	28
5.7.	Band edge and Spurious Emissions (conducted)	33
5.8.	Spurious Emissions (radiated)	50
<b>6.</b>	<b><u>TEST SETUP PHOTOS</u></b>	<b>57</b>
<b>7.</b>	<b><u>EXTERANAL AND INTERNAL PHOTOS</u></b>	<b>59</b>

# **1. TEST STANDARDS AND REPORT VERSION**

## **1.1. Test Standards**

The tests were performed according to following standards:

[FCC Rules Part 15.247](#): Frequency Hopping, Direct Spread Spectrum and Hybrid Systems that are in operation within the bands of 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz.

[ANSI C63.10:2013](#): American National Standard for Testing Unlicensed Wireless Devices

[KDB 558074 D01 DTS Meas Guidance v04](#): Guidance for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating under §15.247

## **1.2. Report version**

Revision No.	Date of issue	Description
N/A	Mar. 22, 2018	Original

## **2. TEST DESCRIPTION**

<b>Test Item</b>	<b>FCC Rule</b>	<b>Result</b>	<b>Test Engineer</b>
Antenna requirement	15.203/15.247(c)	PASS	John Qiao
Line Conducted Emissions (AC Main)	15.207	PASS	Alex Guo
Conducted Peak Output Power	15.247(b)(3)	PASS	Baozhu hu
Power Spectral Density	15.247(e)	PASS	Baozhu hu
6dB Bandwidth	15.247(a)(2)	PASS	Baozhu hu
Restricted band	15.247(d)/15.205	PASS	Baozhu hu
Spurious Emissions	15.247(d)/15.209	PASS	Baozhu hu

Note: The measurement uncertainty is not included in the test result.

### 3. SUMMARY

#### 3.1. Client Information

Applicant:	VIA Technologies, Inc.
Address:	8F,533 Zhongzheng Rd, Xindian Dist, New Taipei City, Taiwan
Manufacturer:	VIA Technologies(Shenzhen)Co.,Ltd.
Address:	4F, VIA Building, NO. 9966, Shennan Avenue, Nanshan District, Shenzhen, China

#### 3.2. Product Description

Name of EUT:	Full HD Battery IP Camera
Trade Mark:	VIA
Model No.:	VH810 M01
Listed Model(s):	VH810 MXX(XX represent 01,02.....99)
IMEI:	-
Power supply:	DC 5V
Adapter information:	Input: 100-240Va.c., 50/60Hz, 0.3A Output: 5Vd.c., 2A
Hardware version:	VTS8707C
Software version:	V0.1.1
<b>WIFI</b>	
Supported type:	802.11b/802.11g/802.11n(HT20)/802.11n(HT40)
Modulation:	DSSS for 802.11b OFDM for 802.11g/802.11n(HT20)/802.11n(HT40)
Operation frequency:	2412MHz~2462MHz for 802.11b/802.11g/802.11n(HT20) 2422MHz~2452MHz for 802.11n(HT40)
Channel number:	11 for 802.11b/802.11g/802.11n(HT20) 7 for 802.11n(HT40)
Channel separation:	5MHz
Antenna type:	Integral Antenna
Antenna gain:	2 dbi

### 3.3. Operation state

➤ **Test frequency list**

According to section 15.31(m), regards to the operating frequency range over 10 MHz, must select three channel which were tested. the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, please see the above gray bottom.

802.11b/g/n(HT20)		802.11n(HT40)	
Channel	Frequency (MHz)	Channel	Frequency (MHz)
01	2412	01	-
02	2417	02	-
03	2422	03	2422
04	2427	04	2427
05	2432	05	2432
06	2437	06	2437
07	2442	07	2442
08	2447	08	2447
09	2452	09	2452
10	2457	10	-
11	2462	11	-

➤ **Test mode**

For RF test items
The engineering test program was provided and enabled to make EUT continuous transmit (duty cycle>98%).
For AC power line conducted emissions:
The EUT was set to connect with the WLAN AP under large package sizes transmission.
For Radiated suprious emissions test item:
The engineering test program was provided and enabled to make EUT continuous transmit(duty cycle>98%). The EUT in each of three orthogonal axis emissions had been tested ,but only the worst case (X axis) data Recorded in the report.

### 3.4. EUT configuration

The following peripheral devices and interface cables were connected during the measurement:

- - supplied by the manufacturer
- - supplied by the lab

○ /	Manufacturer:	/
	Model No.:	/
○ /	Manufacturer:	/
	Model No.:	/

### 3.5. Modifications

No modifications were implemented to meet testing criteria.

## **4. TEST ENVIRONMENT**

### **4.1. Address of the test laboratory**

Laboratory: Shenzhen Huatongwei International Inspection Co., Ltd.

Address: 1/F, Bldg 3, Hongfa Hi-tech Industrial Park, Genyu Road, Tianliao, Gongming, Shenzhen, China

### **4.2. Test Facility**

#### **CNAS-Lab Code: L1225**

Shenzhen Huatongwei International Inspection Co., Ltd. has been assessed and proved to be in compliance with CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC17025: 2005 General Requirements) for the Competence of Testing and Calibration Laboratories.

#### **A2LA-Lab Cert. No.: 3902.01**

Shenzhen Huatongwei International Inspection Co., Ltd. EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025: 2005 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

#### **FCC-Registration No.: 762235**

Shenzhen Huatongwei International Inspection Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files.

#### **IC-Registration No.:5377B-1**

Two 3m Alternate Test Site of Shenzhen Huatongwei International Inspection Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for the performance of radiated measurements with Registration No.: 5377B-1.

#### **ACA**

Shenzhen Huatongwei International Inspection Co., Ltd. EMC Laboratory can also perform testing for the Australian C-Tick mark as a result of our A2LA accreditation.

### 4.3. Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature:	15~35°C
Relative Humidity:	30~60 %
Air Pressure:	950~1050mba

### 4.4. Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors in calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report according to TR-100028-01 "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics; Part 1" and TR-100028-02 "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics; Part 2" and is documented in the Shenzhen Huatongwei International Inspection Co., Ltd. quality system according to ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Here after the best measurement capability for Shenzhen Huatongwei International Inspection Co., Ltd. is reported:

Test Items	Measurement Uncertainty	Notes
Transmitter power conducted	0.57 dB	(1)
Transmitter power Radiated	2.20 dB	(1)
Conducted spurious emissions 9kHz~40GHz	1.60 dB	(1)
Radiated spurious emissions 9kHz~40GHz	2.20 dB	(1)
Conducted Emissions 9kHz~30MHz	3.39 dB	(1)
Radiated Emissions 30~1000MHz	4.24 dB	(1)
Radiated Emissions 1~18GHz	5.16 dB	(1)
Radiated Emissions 18~40GHz	5.54 dB	(1)

(1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=1.96.



**4.5. Equipments Used during the Test**

<b>Conducted Emissions</b>						
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal. (mm-dd-yy)	Next Cal. (mm-dd-yy)
1	EMI Test Receiver	R&S	ESCI	101247	11/11/2017	11/10/2018
2	Artificial Mains	SCHWARZBECK	NNLK 8121	573	11/11/2017	11/10/2018
3	2-Line V-Network	R&S	ESH3-Z5	100049	11/11/2017	11/10/2018
4	Pulse Limiter	R&S	ESH3-Z2	101488	11/11/2017	11/10/2018
5	RF Connection Cable	HUBER+SUHNER	EF400	N/A	11/21/2017	11/20/2018
6	Test Software	R&S	ES-K1	N/A	N/A	N/A

<b>Radiated Emissions</b>						
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal. (mm-dd-yy)	Next Cal. (mm-dd-yy)
1	EMI Test Receiver	R&S	ESCI	101247	11/11/2017	11/10/2018
2	Loop Antenna	R&S	HFH2-Z2	100020	11/20/2017	11/19/2018
3	Ultra-Broadband Antenna	SCHWARZBECK	VULB9163	538	4/5/2017	4/4/2018
4	Preamplifier	SCHWARZBECK	BBV 9743	9743-0022	10/18/2017	10/17/2018
5	RF Connection Cable	HUBER+SUHNER	RE-7-FL	N/A	11/21/2017	11/20/2018
6	EMI Test Software	R&S	ESK1	N/A	N/A	N/A
7	Spectrum Analyzer	R&S	FSP40	100597	11/11/2017	11/10/2018
8	Horn Antenna	SCHWARZBECK	9120D	1011	3/27/2017	3/26/2018
9	Horn Antenna	SCHWARZBECK	BBHA9170	25841	3/27/2017	3/26/2018
10	Broadband Preamplifier	SCHWARZBECK	BBV 9718	9718-248	10/18/2017	10/17/2018
11	High pass filter	Compliance Direction systems	BSU-6	34202	11/11/2017	11/10/2018
12	RF Connection Cable	HUBER+SUHNER	RE-7-FH	N/A	11/21/2017	11/20/2018
13	EMI Test Software	Audix	E3	N/A	N/A	N/A
14	Turntable	MATURO	TT2.0	/	N/A	N/A
15	Antenna Mast	MATURO	TAM-4.0-P	/	N/A	N/A

<b>RF Conducted Test</b>						
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal. (mm-dd-yy)	Next Cal. (mm-dd-yy)
1	Spectrum Analyzer	R&S	FSV40	100048	11/11/2017	11/10/2018
2	EXA Signal Analyzer	Agilent	N9020A	184247	9/22/2017	9/21/2018
3	Power Meter	Agilent	U2021XA	178231	9/22/2017	9/21/2018
4	OSP	R&S	OSP120	101317	N/A	N/A

The Cal.Interval was one year.

## 5. TEST CONDITIONS AND RESULTS

### 5.1. Antenna requirement

#### REQUIREMENT:

#### **FCC CFR Title 47 Part 15 Subpart C Section 15.203:**

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.


#### **FCC CFR Title 47 Part 15 Subpart C Section 15.247(c) (1)(i):**

(i) Systems operating in the 2400~2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6 dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.

#### TEST RESULTS

**Passed**       **Not Applicable**

The directional gain of the antenna less than 6 dBi, please refer to the below antenna photo.



## 5.2. Conducted Emissions (AC Main)


### LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.207:

Frequency range (MHz)	Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

\* Decreases with the logarithm of the frequency.

### TEST CONFIGURATION



### TEST PROCEDURE

1. The EUT was setup according to ANSI C63.10:2013 requirements.
2. The EUT was placed on a platform of nominal size, 1 m by 1.5 m, raised 80 cm above the conducting ground plane. The vertical conducting plane was located 40 cm to the rear of the EUT. All other surfaces of EUT were at least 80 cm from any other grounded conducting surface.
3. The EUT and simulators are connected to the main power through a line impedances stabilization network (LISN). The LISN provides a 50 ohm /50uH coupling impedance for the measuring equipment.
4. The peripheral devices are also connected to the main power through a LISN. (Please refer to the block diagram of the test setup and photographs)
5. Each current-carrying conductor of the EUT power cord, except the ground (safety) conductor, was individually connected through a LISN to the input power source.
6. The excess length of the power cord between the EUT and the LISN receptacle were folded back and forth at the center of the lead to form a bundle not exceeding 40 cm in length.
7. Conducted Emissions were investigated over the frequency range from 0.15MHz to 30MHz using a receiver bandwidth of 9 kHz.
8. During the above scans, the emissions were maximized by cable manipulation.

### TEST MODE:

Please refer to the clause 3.3

### TEST RESULTS


Passed       Not Applicable

Note:

- 1) Transd=Cable lose+ Pulse Limiter Factor + Artificial Mains Factor
- 2) Margin= Limit -Level

Test Line:

L



**MEASUREMENT RESULT: "GM1803155125\_fin"**

3/15/2018 7:04PM

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.361500	45.00	9.9	59	13.7	QP	L1	GND
0.366000	44.20	9.9	59	14.4	QP	L1	GND
0.717000	34.60	10.0	56	21.4	QP	L1	GND
1.567500	32.10	10.1	56	23.9	QP	L1	GND
3.808500	28.20	10.1	56	27.8	QP	L1	GND
6.990000	28.30	10.2	60	31.7	QP	L1	GND
23.527500	15.70	10.7	60	44.3	QP	L1	GND


**MEASUREMENT RESULT: "GM1803155125\_fin2"**

3/15/2018 7:04PM

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.343500	28.00	9.9	49	21.1	AV	L1	GND
0.370500	32.00	9.9	49	16.5	AV	L1	GND
0.717000	19.30	10.0	46	26.7	AV	L1	GND
1.648500	20.50	10.1	46	25.5	AV	L1	GND
3.534000	18.30	10.1	46	27.7	AV	L1	GND
6.783000	17.10	10.2	50	32.9	AV	L1	GND
23.127000	20.00	10.7	50	30.0	AV	L1	GND

Test Line:

N



**MEASUREMENT RESULT: "GM1803155124\_fin"**

3/15/2018 6:58PM

Frequency MHz	Level dBuV	Transd dB	Limit dBuV	Margin dB	Detector	Line	PE
0.361500	35.50	9.9	59	23.2	QP	N	GND
0.370500	34.60	9.9	59	23.9	QP	N	GND
0.937500	20.80	10.0	56	35.2	QP	N	GND
2.256000	18.20	10.1	56	37.8	QP	N	GND
5.410500	15.90	10.2	60	44.1	QP	N	GND
15.967500	17.50	10.5	60	42.5	QP	N	GND

**MEASUREMENT RESULT: "GM1803155124\_fin2"**

3/15/2018 6:58PM


Frequency MHz	Level dBuV	Transd dB	Limit dBuV	Margin dB	Detector	Line	PE
0.357000	23.10	9.9	49	25.7	AV	N	GND
0.370500	24.10	9.9	49	24.4	AV	N	GND
1.279500	13.20	10.1	46	32.8	AV	N	GND
2.224500	11.20	10.1	46	34.8	AV	N	GND
6.657000	8.70	10.2	50	41.3	AV	N	GND
16.480500	9.40	10.5	50	40.6	AV	N	GND

### 5.3. Conducted Peak Output Power

#### LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (b)(3): 30dBm

#### TEST CONFIGURATION



#### TEST PROCEDURE

1. The EUT was tested according to ANSI C63.10: 2013 and KDB 558074 D01 for compliance to FCC 47 CFR 15.247 requirements.
2. The maximum peak conducted output power may be measured using a broadband peak RF power meter.
3. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall utilize a fast-responding diode detector
4. Record the measurement data.

#### TEST MODE:

Please refer to the clause 3.3

#### TEST RESULTS

Passed       Not Applicable


Type	Channel	Output power (dBm)	Limit (dBm)	Result
802.11b	01	16.27	≤30.00	Pass
	06	16.27		
	11	16.20		
802.11g	01	15.43	≤30.00	Pass
	06	15.77		
	11	15.51		
802.11n(HT20)	01	14.04	≤30.00	Pass
	06	14.41		
	11	14.22		
802.11n(HT40)	03	13.13	≤30.00	Pass
	06	13.41		
	09	13.30		

## 5.4. Power Spectral Density

### LIMIT

**FCC CFR Title 47 Part 15 Subpart C Section 15.247 (e):**For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

### TEST CONFIGURATION



### TEST PROCEDURE

1. Connect the antenna port(s) to the spectrum analyzer input,
2. Configure the spectrum analyzer as shown below:  
Center frequency=DTS channel center frequency  
Span =1.5 times the DTS bandwidth  
RBW = 3 kHz ≤ RBW ≤ 100 kHz, VBW ≥ 3 × RBW  
Sweep time = auto couple  
Detector = peak  
Trace mode = max hold
3. Place the radio in continuous transmit mode, allow the trace to stabilize, view the transmitter wave form on the spectrum analyzer.
4. Use the peak marker function to determine the maximum amplitude level within the RBW.
5. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

### TEST MODE:

Please refer to the clause 3.3




### TEST RESULTS




Passed       Not Applicable









Type	Channel	Power Spectral Density (dBm/30KHz)	Limit (dBm/3KHz)	Result
802.11b	01	0.37	≤8.00	Pass
	06	-0.53		
	11	1.35		
802.11g	01	-8.54	≤8.00	Pass
	06	-8.57		
	11	-8.69		
802.11n(HT20)	01	-10.43	≤8.00	Pass
	06	-10.18		
	11	-10.33		
802.11n(HT40)	03	-13.76	≤8.00	Pass
	06	-13.86		
	09	-13.92		

Test plot as follows:

Type:		802.11b
CH01		
CH06		
CH11		

Type:		802.11g
CH01		
CH06		
CH11		

Type:		802.11n(HT20)
CH01		
CH06		
CH11		

Type:		802.11n(HT40)
CH03		
CH06		
CH09		


## 5.5. 6dB bandwidth

### LIMIT

#### **FCC CFR Title 47 Part 15 Subpart C Section 15.247 (a)(2):**

For digital modulation systems, the minimum 6 dB bandwidth shall be at least 500 kHz.

### TEST CONFIGURATION



### TEST PROCEDURE

1. Connect the antenna port(s) to the spectrum analyzer input.
2. Configure the spectrum analyzer as shown below (enter all losses between the transmitter output and the spectrum analyzer).  
Center Frequency =DTS channel center frequency  
Span=2 x DTS bandwidth  
RBW = 100 kHz, VBW  $\geq$  3 x RBW  
Sweep time= auto couple  
Detector = Peak  
Trace mode = max hold
3. Place the radio in continuous transmit mode, allow the trace to stabilize, view the transmitter wave form on the spectrum analyzer.
4. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission, and record the pertinent measurements.

### TEST MODE:


Please refer to the clause 3.3

### TEST RESULTS


Passed       Not Applicable


Type	Channel	6dB Bandwidth (MHz)	Limit (kHz)	Result
802.11b	01	10.14	≥500	Pass
	06	10.14		
	11	10.14		
802.11g	01	16.38	≥500	Pass
	06	16.38		
	11	16.38		
802.11n(HT20)	01	17.61	≥500	Pass
	06	17.64		
	11	17.34		
802.11n(HT40)	03	35.28	≥500	Pass
	06	35.64		
	09	35.28		


Test plot as follows:












**5.6. Restricted band**

**LIMIT**

**FCC CFR Title 47 Part 15 Subpart C Section 15.247 (d):**

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, Radiated Emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the Radiated Emissions limits specified in §15.209(a) (see §15.205(c)).

**TEST CONFIGURATION**



**TEST PROCEDURE**

- 1) The EUT was setup and tested according to ANSI C63.10:2013 for compliance to FCC 47CFR 15.247 requirements.
- 2) The EUT is placed on a turn table which is 1.5 meter above ground. The turn table is rotated 360 degrees to determine the position of the maximum emission level.
- 3) The EUT was positioned such that the distance from antenna to the EUT was 3 meters.
- 4) The antenna is scanned from 1 meter to 4 meters to find out the maximum emission level. This is repeated for both horizontal and vertical polarization of the antenna. In order to find the maximum emission, all of the interface cables were manipulated according to ANSI C63.10:2013 on radiated measurement.
- 5) The receiver set as follow:  
 RBW=1MHz, VBW=3MHz PEAK detector for Peak value.  
 RBW=1MHz, VBW=3MHz RMS detector for Average value.

**TEST MODE:**

Please refer to the clause 3.3

**TEST RESULTS**

Passed       Not Applicable

Note:

- 1) Final level= Read level + Antenna Factor+ Cable Loss- Preamp Factor

802.11b					CH01				
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	Test value
2310.00	12.54	28.05	6.62	0.00	47.21	74.00	-26.79	Vertical	Peak
2390.01	14.19	27.65	6.75	0.00	48.59	74.00	-25.41	Vertical	Peak
2310.00	13.96	28.05	6.62	0.00	48.63	74.00	-25.37	Horizontal	Peak
2390.01	13.43	27.65	6.75	0.00	47.83	74.00	-26.17	Horizontal	Peak
2310.00	10.79	28.05	6.62	0.00	45.46	54.00	-8.54	Vertical	Average
2390.01	10.36	27.65	6.75	0.00	44.76	54.00	-9.24	Vertical	Average
2310.00	10.81	28.05	6.62	0.00	45.48	54.00	-8.52	Horizontal	Average
2390.01	10.35	27.65	6.75	0.00	44.75	54.00	-9.25	Horizontal	Average

802.11b					CH11				
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	Test value
2483.49	12.52	27.26	6.83	0.00	46.61	74.00	-27.39	Vertical	Peak
2500.00	15.45	27.20	6.84	0.00	49.49	74.00	-24.51	Vertical	Peak
2483.49	13.48	27.26	6.83	0.00	47.57	74.00	-26.43	Horizontal	Peak
2500.00	13.20	27.20	6.84	0.00	47.24	74.00	-26.76	Horizontal	Peak
2483.49	10.36	27.26	6.83	0.00	44.45	54.00	-9.55	Vertical	Average
2500.00	10.39	27.20	6.84	0.00	44.43	54.00	-9.57	Vertical	Average
2483.49	10.46	27.26	6.83	0.00	44.55	54.00	-9.45	Horizontal	Average
2500.00	10.54	27.20	6.84	0.00	44.58	54.00	-9.42	Horizontal	Average

802.11g					CH01				
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	Test value
2310.00	12.29	28.05	6.62	0.00	46.96	74.00	-27.04	Vertical	Peak
2390.01	12.13	27.65	6.75	0.00	46.53	74.00	-27.47	Vertical	Peak
2310.00	14.65	28.05	6.62	0.00	49.32	74.00	-24.68	Horizontal	Peak
2390.01	13.91	27.65	6.75	0.00	48.31	74.00	-25.69	Horizontal	Peak
2310.00	10.79	28.05	6.62	0.00	45.46	54.00	-8.54	Vertical	Average
2390.01	10.35	27.65	6.75	0.00	44.75	54.00	-9.25	Vertical	Average
2310.00	10.79	28.05	6.62	0.00	45.46	54.00	-8.54	Horizontal	Average
2390.01	10.59	27.65	6.75	0.00	44.99	54.00	-9.01	Horizontal	Average

802.11g					CH11				
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	Test value
2483.49	14.28	27.26	6.83	0.00	48.37	74.00	-25.63	Vertical	Peak
2500.00	13.50	27.20	6.84	0.00	47.54	74.00	-26.46	Vertical	Peak
2483.49	13.00	27.26	6.83	0.00	47.09	74.00	-26.91	Horizontal	Peak
2500.00	12.91	27.20	6.84	0.00	46.95	74.00	-27.05	Horizontal	Peak
2483.49	10.37	27.26	6.83	0.00	44.46	54.00	-9.54	Vertical	Average
2500.00	10.37	27.20	6.84	0.00	44.41	54.00	-9.59	Vertical	Average
2483.49	10.45	27.26	6.83	0.00	44.54	54.00	-9.46	Horizontal	Average
2500.00	10.36	27.20	6.84	0.00	44.40	54.00	-9.60	Horizontal	Average

802.11n(HT20)					CH01				
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	Test value
2310.00	13.25	28.05	6.62	0.00	47.92	74.00	-26.08	Vertical	Peak
2390.01	11.97	27.65	6.75	0.00	46.37	74.00	-27.63	Vertical	Peak
2310.00	12.56	28.05	6.62	0.00	47.23	74.00	-26.77	Horizontal	Peak
2390.01	13.33	27.65	6.75	0.00	47.73	74.00	-26.27	Horizontal	Peak
2310.00	10.82	28.05	6.62	0.00	45.49	54.00	-8.51	Vertical	Average
2390.01	10.37	27.65	6.75	0.00	44.77	54.00	-9.23	Vertical	Average
2310.00	10.80	28.05	6.62	0.00	45.47	54.00	-8.53	Horizontal	Average
2390.01	10.50	27.65	6.75	0.00	44.90	54.00	-9.10	Horizontal	Average

802.11n(HT20)					CH11				
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	Test value
2483.49	14.21	27.26	6.83	0.00	48.30	74.00	-25.70	Vertical	Peak
2500.00	14.09	27.20	6.84	0.00	48.13	74.00	-25.87	Vertical	Peak
2483.49	12.08	27.26	6.83	0.00	46.17	74.00	-27.83	Horizontal	Peak
2500.00	12.65	27.20	6.84	0.00	46.69	74.00	-27.31	Horizontal	Peak
2483.49	10.34	27.26	6.83	0.00	44.43	54.00	-9.57	Vertical	Average
2500.00	10.33	27.20	6.84	0.00	44.37	54.00	-9.63	Vertical	Average
2483.49	10.67	27.26	6.83	0.00	44.76	54.00	-9.24	Horizontal	Average
2500.00	10.49	27.20	6.84	0.00	44.53	54.00	-9.47	Horizontal	Average

802.11n(HT40)					CH03				
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	Test value
2310.00	15.16	28.05	6.62	0.00	49.83	74.00	-24.17	Vertical	Peak
2389.99	13.17	27.65	6.75	0.00	47.57	74.00	-26.43	Vertical	Peak
2310.00	12.75	28.05	6.62	0.00	47.42	74.00	-26.58	Horizontal	Peak
2389.99	13.13	27.65	6.75	0.00	47.53	74.00	-26.47	Horizontal	Peak
2310.00	10.82	28.05	6.62	0.00	45.49	54.00	-8.51	Vertical	Average
2390.23	10.39	27.65	6.75	0.00	44.79	54.00	-9.21	Vertical	Average
2310.00	10.81	28.05	6.62	0.00	45.48	54.00	-8.52	Horizontal	Average
2389.99	10.45	27.65	6.75	0.00	44.85	54.00	-9.15	Horizontal	Average

802.11n(HT40)					CH09				
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	Test value
2483.50	12.97	27.26	6.83	0.00	47.06	74.00	-26.94	Vertical	Peak
2500.00	13.20	27.20	6.84	0.00	47.24	74.00	-26.76	Vertical	Peak
2483.50	13.69	27.26	6.83	0.00	47.78	74.00	-26.22	Horizontal	Peak
2500.00	14.48	27.20	6.84	0.00	48.52	74.00	-25.48	Horizontal	Peak
2483.50	10.55	27.26	6.83	0.00	44.64	54.00	-9.36	Vertical	Average
2500.00	10.46	27.20	6.84	0.00	44.50	54.00	-9.50	Vertical	Average
2483.50	11.26	27.26	6.83	0.00	45.35	54.00	-8.65	Horizontal	Average
2500.00	10.57	27.20	6.84	0.00	44.61	54.00	-9.39	Horizontal	Average




## 5.7. Band edge and Spurious Emissions (conducted)

### LIMIT

#### **FCC CFR Title 47 Part 15 Subpart C Section 15.247 (d):**

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

### TEST CONFIGURATION



### TEST PROCEDURE



1. Connect the antenna port(s) to the spectrum analyzer input.
2. Establish a reference level by using the following procedure  
Center frequency=DTS channel center frequency  
The span = 1.5 times the DTS bandwidth.  
RBW = 100 kHz, VBW  $\geq$  3 x RBW  
Detector = peak, Sweep time = auto couple, Trace mode = max hold  
Allow trace to fully stabilize  
Use the peak marker function to determine the maximum PSD level  
  
Note: the channel found to contain the maximum PSD level can be used to establish the reference level.
3. Emission level measurement  
Set the center frequency and span to encompass frequency range to be measured  
RBW = 100 kHz, VBW  $\geq$  3 x RBW  
Detector = peak, Sweep time = auto couple, Trace mode = max hold  
Allow trace to fully stabilize  
Use the peak marker function to determine the maximum amplitude level.
4. Place the radio in continuous transmit mode, allow the trace to stabilize, view the transmitter waveform on the spectrum analyzer.
5. Ensure that the amplitude of all unwanted emission outside of the authorized frequency band excluding restricted frequency bands) are attenuated by at least the minimum requirements specified (at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz). Report the three highest emission relative to the limit.



### TEST MODE:



Please refer to the clause 3.3

### TEST RESULTS




Passed       Not Applicable

Test Item:	Bandedge	Type:	802.11b																																										
CH01	 <p><b>Spectrum</b>                  Ref Level 20.00 dBm Offset 1.00 dB RBW 100 kHz                  Att 30 dB SWT 246.5 μs VBW 300 kHz Mode Auto FFT</p> <p>1Pk Max</p> <p>M1[1] 3.67 dBm                  2.413980 GHz                  M2[1] -37.59 dBm                  2.413980 GHz</p> <p>D1 -16.330 dBm</p> <p>Start 2.31 GHz 691 pts Stop 2.422 GHz</p> <table border="1"> <thead> <tr> <th>Type</th> <th>Ref</th> <th>Trc</th> <th>X-value</th> <th>Y-value</th> <th>Function</th> <th>Function Result</th> </tr> </thead> <tbody> <tr> <td>M1</td> <td>1</td> <td></td> <td>2.41398 GHz</td> <td>3.67 dBm</td> <td></td> <td></td> </tr> <tr> <td>M2</td> <td>1</td> <td></td> <td>2.4 GHz</td> <td>-37.59 dBm</td> <td></td> <td></td> </tr> <tr> <td>M3</td> <td>1</td> <td></td> <td>2.39 GHz</td> <td>-52.00 dBm</td> <td></td> <td></td> </tr> <tr> <td>M4</td> <td>1</td> <td></td> <td>2.31 GHz</td> <td>-55.34 dBm</td> <td></td> <td></td> </tr> <tr> <td>M5</td> <td>1</td> <td></td> <td>2.397977 GHz</td> <td>-37.30 dBm</td> <td></td> <td></td> </tr> </tbody> </table>			Type	Ref	Trc	X-value	Y-value	Function	Function Result	M1	1		2.41398 GHz	3.67 dBm			M2	1		2.4 GHz	-37.59 dBm			M3	1		2.39 GHz	-52.00 dBm			M4	1		2.31 GHz	-55.34 dBm			M5	1		2.397977 GHz	-37.30 dBm		
Type	Ref	Trc	X-value	Y-value	Function	Function Result																																							
M1	1		2.41398 GHz	3.67 dBm																																									
M2	1		2.4 GHz	-37.59 dBm																																									
M3	1		2.39 GHz	-52.00 dBm																																									
M4	1		2.31 GHz	-55.34 dBm																																									
M5	1		2.397977 GHz	-37.30 dBm																																									
CH11	 <p><b>Spectrum</b>                  Ref Level 20.00 dBm Offset 1.00 dB RBW 100 kHz                  Att 30 dB SWT 113.8 μs VBW 300 kHz Mode Auto FFT</p> <p>1Pk Max</p> <p>M1[1] 3.42 dBm                  2.4594670 GHz                  M2[1] -50.81 dBm                  2.4835000 GHz</p> <p>D1 -16.580 dBm</p> <p>Start 2.452 GHz 691 pts Stop 2.5 GHz</p> <table border="1"> <thead> <tr> <th>Type</th> <th>Ref</th> <th>Trc</th> <th>X-value</th> <th>Y-value</th> <th>Function</th> <th>Function Result</th> </tr> </thead> <tbody> <tr> <td>M1</td> <td>1</td> <td></td> <td>2.459467 GHz</td> <td>3.42 dBm</td> <td></td> <td></td> </tr> <tr> <td>M2</td> <td>1</td> <td></td> <td>2.4835 GHz</td> <td>-50.81 dBm</td> <td></td> <td></td> </tr> <tr> <td>M3</td> <td>1</td> <td></td> <td>2.5 GHz</td> <td>-50.06 dBm</td> <td></td> <td></td> </tr> <tr> <td>M4</td> <td>1</td> <td></td> <td>2.4999304 GHz</td> <td>-49.49 dBm</td> <td></td> <td></td> </tr> </tbody> </table>			Type	Ref	Trc	X-value	Y-value	Function	Function Result	M1	1		2.459467 GHz	3.42 dBm			M2	1		2.4835 GHz	-50.81 dBm			M3	1		2.5 GHz	-50.06 dBm			M4	1		2.4999304 GHz	-49.49 dBm									
Type	Ref	Trc	X-value	Y-value	Function	Function Result																																							
M1	1		2.459467 GHz	3.42 dBm																																									
M2	1		2.4835 GHz	-50.81 dBm																																									
M3	1		2.5 GHz	-50.06 dBm																																									
M4	1		2.4999304 GHz	-49.49 dBm																																									


Test Item:	Bandedge	Type:	802.11g																																										
CH01	 <p><b>Spectrum</b>                  Ref Level 20.00 dBm Offset 1.00 dB RBW 100 kHz                  Att 30 dB SWT 246.5 <math>\mu</math>s VBW 300 kHz Mode Auto FFT</p> <p>1Pk Max</p> <p>M1[1] -4.40 dBm                  2.410740 GHz                  M2[1] -45.35 dBm                  2.4090000 GHz</p> <p>D1 -24.400 dBm</p> <p>Start 2.31 GHz 691 pts Stop 2.422 GHz</p> <table border="1"> <thead> <tr> <th>Type</th> <th>Ref</th> <th>Trc</th> <th>X-value</th> <th>Y-value</th> <th>Function</th> <th>Function Result</th> </tr> </thead> <tbody> <tr> <td>M1</td> <td>1</td> <td></td> <td>2.41074 GHz</td> <td>-4.40 dBm</td> <td></td> <td></td> </tr> <tr> <td>M2</td> <td>1</td> <td></td> <td>2.4 GHz</td> <td>-45.35 dBm</td> <td></td> <td></td> </tr> <tr> <td>M3</td> <td>1</td> <td></td> <td>2.39 GHz</td> <td>-48.72 dBm</td> <td></td> <td></td> </tr> <tr> <td>M4</td> <td>1</td> <td></td> <td>2.31 GHz</td> <td>-53.49 dBm</td> <td></td> <td></td> </tr> <tr> <td>M5</td> <td>1</td> <td></td> <td>2.3996 GHz</td> <td>-44.62 dBm</td> <td></td> <td></td> </tr> </tbody> </table>			Type	Ref	Trc	X-value	Y-value	Function	Function Result	M1	1		2.41074 GHz	-4.40 dBm			M2	1		2.4 GHz	-45.35 dBm			M3	1		2.39 GHz	-48.72 dBm			M4	1		2.31 GHz	-53.49 dBm			M5	1		2.3996 GHz	-44.62 dBm		
Type	Ref	Trc	X-value	Y-value	Function	Function Result																																							
M1	1		2.41074 GHz	-4.40 dBm																																									
M2	1		2.4 GHz	-45.35 dBm																																									
M3	1		2.39 GHz	-48.72 dBm																																									
M4	1		2.31 GHz	-53.49 dBm																																									
M5	1		2.3996 GHz	-44.62 dBm																																									
CH11	 <p><b>Spectrum</b>                  Ref Level 20.00 dBm Offset 1.00 dB RBW 100 kHz                  Att 30 dB SWT 113.8 <math>\mu</math>s VBW 300 kHz Mode Auto FFT</p> <p>1Pk Max</p> <p>M1[1] -4.21 dBm                  2.4644690 GHz                  M2[1] -49.83 dBm                  2.4835000 GHz</p> <p>D1 -24.210 dBm</p> <p>Start 2.452 GHz 691 pts Stop 2.5 GHz</p> <table border="1"> <thead> <tr> <th>Type</th> <th>Ref</th> <th>Trc</th> <th>X-value</th> <th>Y-value</th> <th>Function</th> <th>Function Result</th> </tr> </thead> <tbody> <tr> <td>M1</td> <td>1</td> <td></td> <td>2.464469 GHz</td> <td>-4.21 dBm</td> <td></td> <td></td> </tr> <tr> <td>M2</td> <td>1</td> <td></td> <td>2.4835 GHz</td> <td>-49.83 dBm</td> <td></td> <td></td> </tr> <tr> <td>M3</td> <td>1</td> <td></td> <td>2.5 GHz</td> <td>-49.00 dBm</td> <td></td> <td></td> </tr> <tr> <td>M4</td> <td>1</td> <td></td> <td>2.4897739 GHz</td> <td>-48.91 dBm</td> <td></td> <td></td> </tr> </tbody> </table>			Type	Ref	Trc	X-value	Y-value	Function	Function Result	M1	1		2.464469 GHz	-4.21 dBm			M2	1		2.4835 GHz	-49.83 dBm			M3	1		2.5 GHz	-49.00 dBm			M4	1		2.4897739 GHz	-48.91 dBm									
Type	Ref	Trc	X-value	Y-value	Function	Function Result																																							
M1	1		2.464469 GHz	-4.21 dBm																																									
M2	1		2.4835 GHz	-49.83 dBm																																									
M3	1		2.5 GHz	-49.00 dBm																																									
M4	1		2.4897739 GHz	-48.91 dBm																																									

Test Item:	Bandedge	Type:	802.11n(HT20)																																										
CH01	 <p><b>Spectrum</b>                  Ref Level 20.00 dBm Offset 1.00 dB RBW 100 kHz                  Att 30 dB SWT 246.5 μs VBW 300 kHz Mode Auto FFT</p> <p>1Pk Max</p> <p>M1[1] -5.14 dBm 2.414460 GHz                  M2[1] -46.51 dBm 2.400000 GHz</p> <p>D1 -25.140 dBm</p> <p>M3 M4 M5</p> <p>Start 2.31 GHz 691 pts Stop 2.422 GHz</p> <table border="1"> <thead> <tr> <th>Type</th> <th>Ref</th> <th>Trc</th> <th>X-value</th> <th>Y-value</th> <th>Function</th> <th>Function Result</th> </tr> </thead> <tbody> <tr> <td>M1</td> <td>1</td> <td></td> <td>2.41446 GHz</td> <td>-5.14 dBm</td> <td></td> <td></td> </tr> <tr> <td>M2</td> <td>1</td> <td></td> <td>2.4 GHz</td> <td>-46.51 dBm</td> <td></td> <td></td> </tr> <tr> <td>M3</td> <td>1</td> <td></td> <td>2.39 GHz</td> <td>-52.49 dBm</td> <td></td> <td></td> </tr> <tr> <td>M4</td> <td>1</td> <td></td> <td>2.31 GHz</td> <td>-54.92 dBm</td> <td></td> <td></td> </tr> <tr> <td>M5</td> <td>1</td> <td></td> <td>2.396841 GHz</td> <td>-46.61 dBm</td> <td></td> <td></td> </tr> </tbody> </table>			Type	Ref	Trc	X-value	Y-value	Function	Function Result	M1	1		2.41446 GHz	-5.14 dBm			M2	1		2.4 GHz	-46.51 dBm			M3	1		2.39 GHz	-52.49 dBm			M4	1		2.31 GHz	-54.92 dBm			M5	1		2.396841 GHz	-46.61 dBm		
Type	Ref	Trc	X-value	Y-value	Function	Function Result																																							
M1	1		2.41446 GHz	-5.14 dBm																																									
M2	1		2.4 GHz	-46.51 dBm																																									
M3	1		2.39 GHz	-52.49 dBm																																									
M4	1		2.31 GHz	-54.92 dBm																																									
M5	1		2.396841 GHz	-46.61 dBm																																									
CH11	 <p><b>Spectrum</b>                  Ref Level 20.00 dBm Offset 1.00 dB RBW 100 kHz                  Att 30 dB SWT 113.8 μs VBW 300 kHz Mode Auto FFT</p> <p>1Pk Max</p> <p>M1[1] -5.58 dBm 2.4644690 GHz                  M2[1] -50.59 dBm 2.4835000 GHz</p> <p>D1 -25.580 dBm</p> <p>M2 M3 M4</p> <p>Start 2.452 GHz 691 pts Stop 2.5 GHz</p> <table border="1"> <thead> <tr> <th>Type</th> <th>Ref</th> <th>Trc</th> <th>X-value</th> <th>Y-value</th> <th>Function</th> <th>Function Result</th> </tr> </thead> <tbody> <tr> <td>M1</td> <td>1</td> <td></td> <td>2.464469 GHz</td> <td>-5.58 dBm</td> <td></td> <td></td> </tr> <tr> <td>M2</td> <td>1</td> <td></td> <td>2.4835 GHz</td> <td>-50.59 dBm</td> <td></td> <td></td> </tr> <tr> <td>M3</td> <td>1</td> <td></td> <td>2.5 GHz</td> <td>-51.76 dBm</td> <td></td> <td></td> </tr> <tr> <td>M4</td> <td>1</td> <td></td> <td>2.4948522 GHz</td> <td>-49.53 dBm</td> <td></td> <td></td> </tr> </tbody> </table>			Type	Ref	Trc	X-value	Y-value	Function	Function Result	M1	1		2.464469 GHz	-5.58 dBm			M2	1		2.4835 GHz	-50.59 dBm			M3	1		2.5 GHz	-51.76 dBm			M4	1		2.4948522 GHz	-49.53 dBm									
Type	Ref	Trc	X-value	Y-value	Function	Function Result																																							
M1	1		2.464469 GHz	-5.58 dBm																																									
M2	1		2.4835 GHz	-50.59 dBm																																									
M3	1		2.5 GHz	-51.76 dBm																																									
M4	1		2.4948522 GHz	-49.53 dBm																																									


Test Item:	Bandedge	Type:	802.11n(HT40)																																										
CH03	 <p><b>Spectrum</b>                  Ref Level 20.00 dBm Offset 1.00 dB RBW 100 kHz                  Att 30 dB SWT 303.4 <math>\mu</math>s VBW 300 kHz Mode Auto FFT</p> <p>1Pk Max</p> <p>M1[1] -9.04 dBm                  2.419550 GHz                  M2[1] -48.31 dBm                  2.400000 GHz</p> <p>D1 -29.040 dBm</p> <p>Start 2.31 GHz 691 pts Stop 2.442 GHz</p> <table border="1"> <thead> <tr> <th>Type</th> <th>Ref</th> <th>Trc</th> <th>X-value</th> <th>Y-value</th> <th>Function</th> <th>Function Result</th> </tr> </thead> <tbody> <tr> <td>M1</td> <td>1</td> <td></td> <td>2.41955 GHz</td> <td>-9.04 dBm</td> <td></td> <td></td> </tr> <tr> <td>M2</td> <td>1</td> <td></td> <td>2.4 GHz</td> <td>-48.31 dBm</td> <td></td> <td></td> </tr> <tr> <td>M3</td> <td>1</td> <td></td> <td>2.39 GHz</td> <td>-51.98 dBm</td> <td></td> <td></td> </tr> <tr> <td>M4</td> <td>1</td> <td></td> <td>2.31 GHz</td> <td>-55.30 dBm</td> <td></td> <td></td> </tr> <tr> <td>M5</td> <td>1</td> <td></td> <td>2.393409 GHz</td> <td>-47.78 dBm</td> <td></td> <td></td> </tr> </tbody> </table>			Type	Ref	Trc	X-value	Y-value	Function	Function Result	M1	1		2.41955 GHz	-9.04 dBm			M2	1		2.4 GHz	-48.31 dBm			M3	1		2.39 GHz	-51.98 dBm			M4	1		2.31 GHz	-55.30 dBm			M5	1		2.393409 GHz	-47.78 dBm		
Type	Ref	Trc	X-value	Y-value	Function	Function Result																																							
M1	1		2.41955 GHz	-9.04 dBm																																									
M2	1		2.4 GHz	-48.31 dBm																																									
M3	1		2.39 GHz	-51.98 dBm																																									
M4	1		2.31 GHz	-55.30 dBm																																									
M5	1		2.393409 GHz	-47.78 dBm																																									
CH09	 <p><b>Spectrum</b>                  Ref Level 20.00 dBm Offset 1.00 dB RBW 100 kHz                  Att 30 dB SWT 1.1 ms VBW 300 kHz Mode Auto Sweep</p> <p>1Pk Max</p> <p>M1[1] -8.84 dBm                  2.4570450 GHz                  M2[1] -50.40 dBm                  2.4835000 GHz</p> <p>D1 -28.840 dBm</p> <p>Start 2.432 GHz 691 pts Stop 2.5 GHz</p> <table border="1"> <thead> <tr> <th>Type</th> <th>Ref</th> <th>Trc</th> <th>X-value</th> <th>Y-value</th> <th>Function</th> <th>Function Result</th> </tr> </thead> <tbody> <tr> <td>M1</td> <td>1</td> <td></td> <td>2.457045 GHz</td> <td>-8.84 dBm</td> <td></td> <td></td> </tr> <tr> <td>M2</td> <td>1</td> <td></td> <td>2.4835 GHz</td> <td>-50.40 dBm</td> <td></td> <td></td> </tr> <tr> <td>M3</td> <td>1</td> <td></td> <td>2.5 GHz</td> <td>-50.96 dBm</td> <td></td> <td></td> </tr> <tr> <td>M4</td> <td>1</td> <td></td> <td>2.4858087 GHz</td> <td>-48.84 dBm</td> <td></td> <td></td> </tr> </tbody> </table>			Type	Ref	Trc	X-value	Y-value	Function	Function Result	M1	1		2.457045 GHz	-8.84 dBm			M2	1		2.4835 GHz	-50.40 dBm			M3	1		2.5 GHz	-50.96 dBm			M4	1		2.4858087 GHz	-48.84 dBm									
Type	Ref	Trc	X-value	Y-value	Function	Function Result																																							
M1	1		2.457045 GHz	-8.84 dBm																																									
M2	1		2.4835 GHz	-50.40 dBm																																									
M3	1		2.5 GHz	-50.96 dBm																																									
M4	1		2.4858087 GHz	-48.84 dBm																																									

Test Item:	SE	Type:	802.11b
CH01 Reference level			
CH01 30MHz~1000MHz			
CH01 1GHz~26GHz			


CH06  
Reference level




CH06  
30MHz~1000MHz




CH06  
1GHz~26GHz




CH11  
Reference level






CH11  
30MHz~1000MHz




CH11  
1GHz~26GHz






Test Item:	SE	Type:	802.11g
CH01 Reference level			
CH01 30MHz~1000MHz			
CH01 1GHz~26GHz			


CH06  
Reference level




CH06  
30MHz~1000MHz




CH06  
1GHz~26GHz




CH11  
Reference level






CH11  
30MHz~1000MHz




CH11  
1GHz~26GHz




Test Item:	SE	Type:	802.11n(HT20)
<p>CH01 Reference level</p>			
<p>CH01 30MHz~1000MHz</p>			
<p>CH01 1GHz~26GHz</p>			


CH06  
Reference level




CH06  
30MHz~1000MHz




CH06  
1GHz~26GHz




CH11  
Reference level






CH11  
30MHz~1000MHz




CH11  
1GHz~26GHz




Test Item:	SE	Type:	802.11n(HT40)
<p>CH03 Reference level</p>			
<p>CH03 30MHz~1000MHz</p>			
<p>CH03 1GHz~26GHz</p>			


CH06  
Reference level



CH06  
30MHz~1000MHz




CH06  
1GHz~26GHz







CH09  
Reference level



CH09  
30MHz~1000MHz



CH09  
1GHz~26GHz



### 5.8. Spurious Emissions (radiated)


#### LIMIT

#### FCC CFR Title 47 Part 15 Subpart C Section 15.209


Frequency	Limit (dBuV/m @3m)	Value
30MHz-88MHz	40.00	Quasi-peak
88MHz-216MHz	43.50	Quasi-peak
216MHz-960MHz	46.00	Quasi-peak
960MHz-1GHz	54.00	Quasi-peak
Above 1GHz	54.00	Average
	74.00	Peak

#### TEST CONFIGURATION


➤ 9kHz ~30MHz



➤ 30MHz ~ 1GHz



➤ Above 1GHz



**TEST PROCEDURE**

1. The EUT was setup and tested according to ANSI C63.10:2013 for compliance to FCC 47CFR 15.247 requirements.
2. The EUT is placed on a turn table which is 0.8 meter above ground for below 1 GHz, and 1.5 m for above 1 GHz. The turn table is rotated 360 degrees to determine the position of the maximum emission level.
3. The EUT was set 3 meters from the receiving antenna, which was mounted on the top of a variable height antenna tower.
4. For each suspected emission, the EUT was arranged to its worst case and then tune the Antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level to comply with the guidelines.
5. Set to the maximum power setting and enable the EUT transmit continuously.
6. Use the following spectrum analyzer settings
  - (1) Span shall wide enough to fully capture the emission being measured;
  - (2) Below 1 GHz:  
RBW=120 kHz, VBW=300 kHz, Sweep=auto, Detector function=peak, Trace=max hold;  
If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
  - (3) From 1 GHz to 10<sup>th</sup> harmonic:  
RBW=1MHz, VBW=3MHz Peak detector for Peak value.  
RBW=1MHz, VBW=3MHz RMS detector for Average value.

**TEST MODE:**

Please refer to the clause 3.3

**TEST RESULTS**

**Passed**       **Not Applicable**

**Note:**

- 1) Final Level =Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
- 2) The emission levels of other frequencies are very lower than the limit and not show in test report.

**➤ 9kHz ~ 30MHz**


The EUT was pre-scanned the frequency band (9kHz~30MHz), found the radiated level lower than the limit, so don't show on the report.

**➤ 30MHz ~1000MHz**

Have pre-scan all modulation mode, found the 802.11b mode CH01 which it was worst case, so only the worst case's data on the test report.

➤ 30MHz ~ 1GHz

Polarization: Vertical




**MEASUREMENT RESULT: "GM180319614\_red"**

3/19/2018 2:52PM

Frequency MHz	Level dBµV/m	Transd dB	Limit dBµV/m	Margin dB	Det.	Height cm	Azimuth deg	Polarization
31.940000	23.60	-13.2	40.0	16.4	QP	100.0	277.00	VERTICAL
59.100000	22.90	-9.8	40.0	17.1	QP	100.0	0.00	VERTICAL
103.720000	19.50	-10.5	43.5	24.0	QP	100.0	0.00	VERTICAL
297.720000	23.10	-7.3	46.0	22.9	QP	100.0	78.00	VERTICAL
549.920000	28.50	-0.8	46.0	17.5	QP	100.0	90.00	VERTICAL
955.380000	41.00	7.3	46.0	5.0	QP	100.0	261.00	VERTICAL

Polarization: Horizontal



**MEASUREMENT RESULT: "GM180319613\_red"**

3/19/2018 2:50PM

Frequency MHz	Level dBµV/m	Transd dB	Limit dBµV/m	Margin dB	Det.	Height cm	Azimuth deg	Polarization
49.400000	20.80	-8.7	40.0	19.2	QP	100.0	96.00	HORIZONTAL
55.220000	20.40	-9.2	40.0	19.6	QP	100.0	0.00	HORIZONTAL
111.480000	19.10	-11.0	43.5	24.4	QP	100.0	84.00	HORIZONTAL
303.540000	23.10	-7.2	46.0	22.9	QP	100.0	125.00	HORIZONTAL
553.800000	28.90	-0.7	46.0	17.1	QP	100.0	315.00	HORIZONTAL
955.380000	40.30	7.3	46.0	5.7	QP	300.0	224.00	HORIZONTAL

## ➤ 1 GHz ~ 25 GHz

802.11b					CH01				
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	Test value
2564.71	42.28	27.59	6.89	37.85	38.91	74.00	-35.09	Vertical	Peak
3216.84	44.07	28.70	7.74	38.23	42.28	74.00	-31.72	Vertical	Peak
4821.76	38.99	31.56	9.55	36.90	43.20	74.00	-30.80	Vertical	Peak
7394.88	33.48	36.30	12.06	34.83	47.01	74.00	-26.99	Vertical	Peak
1805.01	32.67	25.39	5.97	37.14	26.89	74.00	-47.11	Horizontal	Peak
3216.84	44.64	28.70	7.74	38.23	42.85	74.00	-31.15	Horizontal	Peak
4821.76	45.61	31.56	9.55	36.90	49.82	74.00	-24.18	Horizontal	Peak
7264.28	31.62	36.26	11.93	35.00	44.81	74.00	-29.19	Horizontal	Peak

802.11b					CH06				
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	Test value
2564.71	36.27	27.59	6.89	37.85	32.90	74.00	-41.10	Vertical	Peak
3249.76	42.77	28.50	7.78	38.29	40.76	74.00	-33.24	Vertical	Peak
4871.10	34.51	31.46	9.59	36.76	38.80	74.00	-35.20	Vertical	Peak
5009.43	35.84	31.54	9.68	36.39	40.67	74.00	-33.33	Vertical	Peak
2564.71	35.62	27.59	6.89	37.85	32.25	74.00	-41.75	Horizontal	Peak
3249.76	47.61	28.50	7.78	38.29	45.60	74.00	-28.40	Horizontal	Peak
4871.10	45.70	31.46	9.59	36.76	49.99	74.00	-24.01	Horizontal	Peak
7451.57	31.70	36.20	12.24	34.86	45.28	74.00	-28.72	Horizontal	Peak

802.11b					CH11				
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	Test value
1889.63	34.81	25.31	6.10	37.21	29.01	74.00	-44.99	Vertical	Peak
2564.71	40.65	27.59	6.89	37.85	37.28	74.00	-36.72	Vertical	Peak
3283.02	44.83	28.30	7.82	38.35	42.60	74.00	-31.40	Vertical	Peak
4920.96	39.84	31.42	9.62	36.62	44.26	74.00	-29.74	Vertical	Peak
2564.71	44.64	27.59	6.89	37.85	41.27	74.00	-32.73	Horizontal	Peak
3283.02	38.99	28.30	7.82	38.35	36.76	74.00	-37.24	Horizontal	Peak
4821.76	37.41	31.56	9.55	36.90	41.62	74.00	-32.38	Horizontal	Peak
5138.58	44.28	31.74	9.78	36.26	49.54	74.00	-24.46	Horizontal	Peak

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. The peak level is lower than average limit(54 dBuV/m), this data is the too weak instrument of signal is unable to test.
3. The emission levels of other frequencies(test frequency band is 1GHz to 25GHz) are very lower than the limit and not show in test report.

802.11g					CH01				
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	Test value
1680.83	32.91	25.14	5.73	36.89	26.89	74.00	-47.11	Vertical	Peak
3216.84	37.53	28.70	7.74	38.23	35.74	74.00	-38.26	Vertical	Peak
4834.05	39.72	31.53	9.56	36.86	43.95	74.00	-30.05	Vertical	Peak
8527.85	30.22	37.01	12.88	34.43	45.68	74.00	-28.32	Vertical	Peak
1759.64	35.63	25.32	5.88	37.06	29.77	74.00	-44.23	Horizontal	Peak
3216.84	39.29	28.70	7.74	38.23	37.50	74.00	-36.50	Horizontal	Peak
4821.76	35.66	31.56	9.55	36.90	39.87	74.00	-34.13	Horizontal	Peak
6428.77	35.36	33.50	11.04	35.32	44.58	74.00	-29.42	Horizontal	Peak

802.11g					CH06				
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	Test value
1642.76	34.17	25.03	5.65	36.81	28.04	74.00	-45.96	Vertical	Peak
3249.76	39.39	28.50	7.78	38.29	37.38	74.00	-36.62	Vertical	Peak
4883.52	39.70	31.43	9.59	36.73	43.99	74.00	-30.01	Vertical	Peak
7413.73	31.37	36.27	12.11	34.83	44.92	74.00	-29.08	Vertical	Peak
1795.84	32.23	25.39	5.95	37.13	26.44	74.00	-47.56	Horizontal	Peak
3249.76	38.58	28.50	7.78	38.29	36.57	74.00	-37.43	Horizontal	Peak
4883.52	37.90	31.43	9.59	36.73	42.19	74.00	-31.81	Horizontal	Peak
6921.30	29.61	34.83	11.75	34.87	41.32	74.00	-32.68	Horizontal	Peak

802.11g					CH11				
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	Test value
1777.65	32.98	25.36	5.92	37.09	27.17	74.00	-46.83	Vertical	Peak
3283.02	38.69	28.30	7.82	38.35	36.46	74.00	-37.54	Vertical	Peak
4809.50	39.48	31.58	9.55	36.93	43.68	74.00	-30.32	Vertical	Peak
7209.02	30.31	36.21	11.87	35.07	43.32	74.00	-30.68	Vertical	Peak
1728.56	34.36	25.26	5.82	36.99	28.45	74.00	-45.55	Horizontal	Peak
3283.02	39.16	28.30	7.82	38.35	36.93	74.00	-37.07	Horizontal	Peak
4933.50	39.84	31.43	9.63	36.59	44.31	74.00	-29.69	Horizontal	Peak
7961.43	30.97	36.95	12.49	34.63	45.78	74.00	-28.22	Horizontal	Peak

## Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. The peak level is lower than average limit(54 dBuV/m), this data is the too weak instrument of signal is unable to test.
3. The emission levels of other frequencies(test frequency band is 1GHz to 25GHz) are very lower than the limit and not show in test report.

802.11n(HT20)					CH01				
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	Test value
1715.41	38.98	25.23	5.80	36.96	33.05	74.00	-40.95	Vertical	Peak
3216.84	39.29	28.70	7.74	38.23	37.50	74.00	-36.50	Vertical	Peak
4821.76	34.66	31.56	9.55	36.90	38.87	74.00	-35.13	Vertical	Peak
6428.77	34.36	33.50	11.04	35.32	43.58	74.00	-30.42	Vertical	Peak
1680.83	32.91	25.14	5.73	36.89	26.89	74.00	-47.11	Horizontal	Peak
3216.84	44.53	28.70	7.74	38.23	42.74	74.00	-31.26	Horizontal	Peak
4821.76	43.71	31.56	9.55	36.90	47.92	74.00	-26.08	Horizontal	Peak
8022.46	30.70	37.08	12.35	34.53	45.60	74.00	-28.40	Horizontal	Peak

802.11n(HT20)					CH06				
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	Test value
1417.28	33.77	25.88	5.05	36.48	28.22	74.00	-45.78	Vertical	Peak
2281.32	32.36	27.99	6.57	37.57	29.35	74.00	-44.65	Vertical	Peak
3249.76	39.39	28.50	7.78	38.29	37.38	74.00	-36.62	Vertical	Peak
4871.10	35.56	31.46	9.59	36.76	39.85	74.00	-34.15	Vertical	Peak
1446.44	31.83	25.85	5.13	36.52	26.29	74.00	-47.71	Horizontal	Peak
3249.76	47.58	28.50	7.78	38.29	45.57	74.00	-28.43	Horizontal	Peak
4871.10	46.59	31.46	9.59	36.76	50.88	74.00	-23.12	Horizontal	Peak
7319.96	31.55	36.30	11.99	34.92	44.92	74.00	-29.08	Horizontal	Peak

802.11n(HT20)					CH11				
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	Test value
1213.44	34.50	26.29	4.68	36.56	28.91	74.00	-45.09	Vertical	Peak
2281.32	32.64	27.99	6.57	37.57	29.63	74.00	-44.37	Vertical	Peak
3283.02	39.69	28.30	7.82	38.35	37.46	74.00	-36.54	Vertical	Peak
4933.50	34.48	31.43	9.63	36.59	38.95	74.00	-35.05	Vertical	Peak
1728.56	34.36	25.26	5.82	36.99	28.45	74.00	-45.55	Horizontal	Peak
3283.02	46.16	28.30	7.82	38.35	43.93	74.00	-30.07	Horizontal	Peak
4920.96	46.22	31.42	9.62	36.62	50.64	74.00	-23.36	Horizontal	Peak
7227.39	30.30	36.23	11.89	35.04	43.38	74.00	-30.62	Horizontal	Peak

## Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. The peak level is lower than average limit(54 dBuV/m), this data is the too weak instrument of signal is unable to test.
3. The emission levels of other frequencies(test frequency band is 1GHz to 25GHz) are very lower than the limit and not show in test report.

802.11n(HT40)					CH03				
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	Test value
1943.29	38.79	25.74	6.18	37.25	33.46	74.00	-40.54	Vertical	Peak
3233.26	49.28	28.60	7.76	38.26	47.38	74.00	-26.62	Vertical	Peak
4846.37	40.94	31.51	9.57	36.83	45.19	74.00	-28.81	Vertical	Peak
7172.41	31.55	36.04	11.86	35.04	44.41	74.00	-29.59	Vertical	Peak
1943.29	46.37	25.74	6.18	37.25	41.04	74.00	-32.96	Horizontal	Peak
3233.26	43.14	28.60	7.76	38.26	41.24	74.00	-32.76	Horizontal	Peak
4846.37	46.07	31.51	9.57	36.83	50.32	74.00	-23.68	Horizontal	Peak
7081.70	30.31	35.55	11.85	34.91	42.80	74.00	-31.20	Horizontal	Peak

802.11n(HT40)					CH06				
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	Test value
1759.64	34.80	25.32	5.88	37.06	28.94	74.00	-45.06	Vertical	Peak
3233.26	38.97	28.60	7.76	38.26	37.07	74.00	-36.93	Vertical	Peak
4858.72	40.94	31.48	9.58	36.80	45.20	74.00	-28.80	Vertical	Peak
7981.72	31.12	37.03	12.39	34.58	45.96	74.00	-28.04	Vertical	Peak
1741.81	33.73	25.29	5.85	37.02	27.85	74.00	-46.15	Horizontal	Peak
3233.26	47.02	28.60	7.76	38.26	45.12	74.00	-28.88	Horizontal	Peak
4871.10	41.61	31.46	9.59	36.76	45.90	74.00	-28.10	Horizontal	Peak
7338.62	31.08	36.30	12.01	34.90	44.49	74.00	-29.51	Horizontal	Peak

802.11n(HT40)					CH09				
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	Test value
1791.27	40.10	25.38	5.94	37.12	34.30	74.00	-39.70	Vertical	Peak
3266.35	40.91	28.40	7.80	38.32	38.79	74.00	-35.21	Vertical	Peak
4895.97	43.07	31.41	9.60	36.69	47.39	74.00	-26.61	Vertical	Peak
7451.57	31.41	36.20	12.24	34.86	44.99	74.00	-29.01	Vertical	Peak
1805.01	32.64	25.39	5.97	37.14	26.86	74.00	-47.14	Horizontal	Peak
3266.35	40.09	28.40	7.80	38.32	37.97	74.00	-36.03	Horizontal	Peak
4895.97	41.80	31.41	9.60	36.69	46.12	74.00	-27.88	Horizontal	Peak
7840.75	29.88	36.35	13.06	34.96	44.33	74.00	-29.67	Horizontal	Peak

## Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. The peak level is lower than average limit(54 dBuV/m), this data is the too weak instrument of signal is unable to test.
3. The emission levels of other frequencies(test frequency band is 1GHz to 25GHz) are very lower than the limit and not show in test report.




## 6. TEST SETUP PHOTOS

### Conducted Emissions




### Radiated Emissions








## 7. EXTERANAL AND INTERNAL PHOTOS

### External Photos















**Internal Photos**



















.....**End of Report**.....