





- 1. Overall dimensions: 62,4mm x 40,6mm / Radius Corners: 1,6mm Same outline as CL1LBL-20037 2
- 2. To be supplied in the format shown, on reels, copy position 2, internal core dia 38mm
- 3. Quantity per roll: 1000 or max o/d 4"
- 4. Each roll to be packed in bubble wrap and sealed in a polythene bag containing no other shedding material.

Reels then to be packed in a box, each box to contain 4 reels.

The outside of the box to be clearly labelled with the following information:

- Option Part number
- Quantity in box
- Date produced
- 5. Liner to be 44mm wide. Vertical gap between labels 4.275mm.
- 6. Label thickness: 50µm max.
- 7. Label to be silver and suitable for thermal transfer printing.
- 8. Label to be printed with artwork 2001423\_2\_2001501\_art.\*
- 9. Printing be resistant to rubbing and alcohol cleaning.
- 10. Raw material:

FLEXcon THERMLfilm MM 200 satin silver TC-715 L-344 40 White Glassine

- 11. Artwork use black 32364
- 12. To be used with print ribbon: Armor AXR7+ or equivalent.

2	4702	Included FCC and CE / Changed to black on white / Release for mass production				TS	26/09/06		
1		Derived from NL1LBL-21793_2				TS	11/08/06		
REV	ECP	DESCRIPTION				ISSUED	DATE	APPROVED	
WIRELESS TECHNOLOGY Kol. Benguitlaan 45 - R3012 Leuven Belnium			Top Mat Nr: 2001423	Rev:	Sap	Sap Mat NR : 2001501			
			Project: FUJI	Part Name: Manufacturing Label Fuji Lite Generic					
			Drawn: Thomas STEVENS	Date: 11/08/06		Scale: 1:1	Size: A4	Page: 1/1	