RF Technical Brief Cover Sheet (for FCB – Industry Canada approval):

All Fields must be completed with the requested	N/A for Not Applicable	
information or the following codes:	the following codes: N/P for Not Performed	
·	N/V for Not Available	
	Where applicable, check appropriate box.	

1	COMPANY NUMBER:	2945A	
2	MODEL NUMBER:	SP24	
3	MANUFACTURER:	Trango Systems, Inc.	
4	TYPE OF EVALUATION:		
	(a) SAR Evaluation: Device Used in the Vicinity of the Human Head		
	(b) SAR Evaluation: Body-worn Device		
	(c) RF Evaluation		
	Note : The worst-case scenario (i.e. highest measured value obtained) should be reported.		l.
	(a) SAR Evaluation: Device used in the Vicinity of the Hu	uman Head	
	Multiple transmitters:	Yes [No [
	Evaluated against exposure limits:	General public	
		Controlled use	
	Duty cycle used in evaluation:	%	
	Standard used for evaluation:		
	SAR value	W/kg.	
		Measured [
		Computed	
		Calculated	
	(b) SAR Evaluation: Body-worn Device and Body Suppo	orted Device	
	Multiple transmitters:	Yes	
	·	No [
	Evaluated against exposure limits:	General public	
	•	Controlled use	
	Duty cycle used in evaluation:		
	Standard used for evaluation:		
	SAR value	W/kg.	
		Measured [
		Computed [
		Calculated [
	(c) SAR Evaluation: Limb-Worn Device		
	Multiple transmitters:	Yes	
		No [
	Evaluated against exposure limits:	General public [Controlled use	
	Duty cycle used in evaluation:		
	Standard used for evaluation:		
	SAR value	W/kg.	
	Of the value	Measured [7
		Computed	_
		Calculated [_
	(d) RF Exposure Evaluation		
	Evaluated against exposure limits:	General Public Use	\overline{A}
	Evaluated against exposure illines.	Controlled Use	7
Ī			

Duty cycle used in evaluation:	100 %
Standard used for evaluation:	RSS-102
Measurement distance:	0.178 m
RF value:	10.0 W/m ²
	Measured
	Computed
	Calculated 🖂