

Nemko Test Report: 1L0374RUS2

Applicant: Trango Systems

**Equipment Under Test:
(E.U.T.)** M5800S Subscriber Unit

In Accordance With: **FCC Part 15, Subpart C, 15.247**
Direct Sequence Spread Spectrum Transmitters

Tested By: Nemko Dallas Inc.
802 N. Kealy
Lewisville, Texas 75057-3136

Authorized By:



Tom Tidwell, RF Group Manager

Date: 12/13/01

Total Number of Pages: 41

DIRECT SEQUENCE SPREAD SPECTRUM TRANSMITTER

EQUIPMENT: M5800S Subscriber Unit

PROJECT NO.: 1L0374RUS2

Table of Contents

Section 1. Summary of Test Results	3
Section 2. Equipment Under Test (E.U.T.)	5
Section 3. Powerline Conducted Emissions	7
Section 4. Minimum 6 dB Bandwidth.....	8
Section 5. Maximum Peak Output Power	12
Section 6. RF Exposure.....	13
Section 7. Spurious Emissions (conducted)	14
Section 8. Spurious Emissions (radiated).....	17
Section 9. Peak Power Spectral Density	25
Section 10. Minimum Processing Gain	26
Section 11. Test Equipment List	27
ANNEX A - TEST DETAILS	28
ANNEX B - TEST DIAGRAMS.....	38

DIRECT SEQUENCE SPREAD SPECTRUM TRANSMITTER

EQUIPMENT: M5800S Subscriber Unit

PROJECT NO.: 1L0374RUS2

Section 1. Summary of Test Results

Manufacturer: Sunstream (Trango) Systems

Model No.: M5800S

Serial No.: S01

General: **All measurements are traceable to national standards.**

These tests were conducted on a sample of the equipment for the purpose of demonstrating compliance with Part 15, Subpart C, Paragraph 15.247 for Direct Sequence Spread Spectrum devices. Radiated tests were conducted in accordance with ANSI C63.4-1992. Radiated emissions are made on an open area test site. A description of the test facility is on file with the FCC.

☐

New Submission

☒

Production Unit

☒

Class II Permissive Change

☐

Pre-Production Unit

THIS TEST REPORT RELATES ONLY TO THE ITEM(S) TESTED.

THE FOLLOWING DEVIATIONS FROM, ADDITIONS TO, OR EXCLUSIONS FROM THE TEST SPECIFICATIONS HAVE BEEN MADE.

See " Summary of Test Data".



NVLAP LAB CODE: 100426-0

Nemko Dallas Inc. authorizes the above named company to reproduce this report provided it is reproduced in its entirety and for use by the company's employees only.

Any use which a third party makes of this report, or any reliance on or decisions to be made based on it, are the responsibility of such third parties. Nemko Dallas Inc. accepts no responsibility for damages, if any, suffered by any third party as a result of decisions made or actions based on this report. This report applies only to the items tested.

DIRECT SEQUENCE SPREAD SPECTRUM TRANSMITTER

EQUIPMENT: M5800S Subscriber Unit

PROJECT NO.: 1L0374RUS2

Summary Of Test Data

NAME OF TEST	PARA. NO.	SPEC.	RESULT
Powerline Conducted Emissions	15.207(a)	48 dB μ V	N/A
Minimum 6 dB Bandwidth	15.247(a)(2)	>500 kHz	Complies
Maximum Peak Power Output	15.247(b)(1)	<1 Watt	Complies
Spurious Emissions (Antenna Conducted)	15.247(c)	-20 dBc/100kHz	N/A
Spurious Emissions (Restricted Bands)	15.247(c)	< 74 dBuV/m Peak < 54 dBuV/m Avg	Complies
Peak Power Spectral Density	15.247(d)	+8 dBm/3kHz	N/A
Processing Gain	15.247(e)	10 dB	N/A

Footnotes:

Due to the Class II Permissive Change not changing any of the radio equipment the Powerline Conducted, Spurious Emissions (Conducted), Peak Power Spectral Density, and Processing Gain portions of the test were not examined. Although the bandedge plots are placed in the Spurious Emissions Conducted portion of this report.

DIRECT SEQUENCE SPREAD SPECTRUM TRANSMITTER

EQUIPMENT: M5800S Subscriber Unit

PROJECT NO.: 1L0374RUS2

Section 2. Equipment Under Test (E.U.T.)

General Equipment Information

Frequency Band:

- ☐ 902 – 928 MHz
☐ 2400 – 2483.5 MHz
☒ 5725 – 5850 MHz

Tuning Range:

5736 - 5836 MHz

User Frequency Adjustment:

Software controlled

DIRECT SEQUENCE SPREAD SPECTRUM TRANSMITTER

EQUIPMENT: M5800S Subscriber Unit

PROJECT NO.: 1L0374RUS2

Description of Modification for Modification Filing

1. Changed RF filters to ceramic type and added one more on transmit side to increase LO and harmonic attenuation.
2. Replaced SAW filters with SMT type.
3. Combined to switches on RF output into a single switch.
4. Replace discrete VCO with a PLL module.
5. Replaced and consolidated IF strip amplifiers.
6. Moved RF connector locations.
7. Replaced Metal shield with copper coated plastic shield.
8. Added resistive heater to heat Ethernet chip at low temperatures.
9. Added temperature sensor.
10. Added EMI filter on 44 MHz clock.
11. Added lightning protection to Ethernet lines.

DIRECT SEQUENCE SPREAD SPECTRUM TRANSMITTER

EQUIPMENT: M5800S Subscriber Unit

PROJECT NO.: 1L0374RUS2

Section 3. Powerline Conducted Emissions

NAME OF TEST: Powerline Conducted Emissions

PARA. NO.: 15.207(a)

TESTED BY:

Test Results:

Not Applicable

complies.

Measurement Data: See attached plots.

Measurement Uncertainty: +/- 1.7 dB

DIRECT SEQUENCE SPREAD SPECTRUM TRANSMITTER

EQUIPMENT: M5800S Subscriber Unit

PROJECT NO.: 1L0374RUS2

Section 4. Minimum 6 dB Bandwidth

NAME OF TEST: Minimum 6 dB Bandwidth	PARA. NO.: 15.247(a)(2)
TESTED BY: Lance Walker	DATE: 12/6/2001

Test Results: Complies.

Measurement Data: See 6 dB BW plot
Measured 6 dB bandwidth:

DIRECT SEQUENCE SPREAD SPECTRUM TRANSMITTER

EQUIPMENT: M5800S Subscriber Unit


PROJECT NO.: 1L0374RUS2



Nemko Dallas, Inc.

Dallas Headquarters:
802 N. Kealy
Lewisville, TX 75057
Tel: (972) 436-9600
Fax: (972) 436-2667

Data Plot		6 dB BW			
Page 1 of 3				Complete <u>X</u>	
Job No.:	1L0374R	Date:	12/6/2001	Preliminary: _____	
Specification:	FCC15247	Temperature(°C):	22		
Tested By:	Lance Walker	Relative Humidity(%)	50		
E.U.T.:	Access Point				
Configuration:	Tx with antenna removed				
Sample Number:					
Location:	Lab 2	RBW:	Refer to plots	Measurement	
Detector Type:	Peak	VBW:	Refer to plots	Distance:	N/A m
Test Equipment Used					
Antenna:	_____	Directional Coupler:	_____		
Pre-Amp:	_____	Cable #1:	1627		
Filter:	_____	Cable #2:	_____		
Receiver:	1464	Cable #3:	_____		
Attenuator #1:	1469	Cable #4:	_____		
Attenuator #2:	1465	Mixer:	_____		
Additional equipment used:	_____				
Measurement Uncertainty:	+/-1.7 dB				



Notes: 6 dB BW mid channel

DIRECT SEQUENCE SPREAD SPECTRUM TRANSMITTER

EQUIPMENT: M5800S Subscriber Unit


PROJECT NO.: 1L0374RUS2



Nemko Dallas, Inc.

Dallas Headquarters:

802 N. Kealy
Lewisville, TX 75057
Tel: (972) 436-9600
Fax: (972) 436-2667



DIRECT SEQUENCE SPREAD SPECTRUM TRANSMITTER

EQUIPMENT: M5800S Subscriber Unit


PROJECT NO.: 1L0374RUS2



Nemko Dallas, Inc.

Dallas Headquarters:

802 N. Kealy
Lewisville, TX 75057
Tel: (972) 436-9600
Fax: (972) 436-2667



DIRECT SEQUENCE SPREAD SPECTRUM TRANSMITTER

EQUIPMENT: M5800S Subscriber Unit

PROJECT NO.: 1L0374RUS2

Section 5. Maximum Peak Output Power

NAME OF TEST: Maximum Peak Output power	PARA. NO.: 15.247(b)(1)
TESTED BY: Lance Walker	DATE: 12/6/01

Test Results: Complies.

Measurement Data:

Antennas: Integral Patch Antenna 17.9 dB
gain

Channel	Limit	Measured at Ant Terminal (mW)	Converted Measurement (dBm)	EIRP (dBm)
Low	18.0 dBm	57.5	17.6	35.5
Mid	18.0 dBm	60.1	17.8	35.7
High	18.0 dBm	61.0	17.9	35.8

Equipment Used: 1029,1030,1626,1469,1465,1470

Measurement Uncertainty: +/- 0.7 dB

Temperature: 22 °C

Relative Humidity: 50 %

Nemko
Dallas

FCC PART 15, SUBPART C

DIRECT SEQUENCE SPREAD SPECTRUM TRANSMITTER

EQUIPMENT: M5800S Subscriber Unit

PROJECT NO.: 1L0374RUS2

Section 6. RF Exposure

NAME OF TEST: RF Exposure

PARA. NO.: 15.247(b)(4)

TESTED BY:

DATE

Test Results:

completes

Measurement Data:

Not Applicable

Nemko
Dallas

FCC PART 15, SUBPART C

DIRECT SEQUENCE SPREAD SPECTRUM TRANSMITTER

EQUIPMENT: M5800S Subscriber Unit

PROJECT NO.: 1L0374RUS2

Section 7. Spurious Emissions (conducted)

NAME OF TEST: Spurious Emissions (conducted)	PARA. NO.: 15.247(c)
TESTED BY: N/A	DATE: N/A

Test Results: N/A

Measurement Data: See attached plots.

DIRECT SEQUENCE SPREAD SPECTRUM TRANSMITTER

EQUIPMENT: M5800S Subscriber Unit


PROJECT NO.: 1L0374RUS2



Nemko Dallas, Inc.

Dallas Headquarters:
802 N. Kealy
Lewisville, TX 75057
Tel: (972) 436-9600
Fax: (972) 436-2667

Data Plot		Bandedges			
Page 1 of 2				Complete <u>X</u>	
Job No.:	1L0374R	Date:	12/6/2001	Preliminary: _____	
Specification:	FCC15247	Temperature(°C):	22		
Tested By:	Lance Walker	Relative Humidity(%)	50		
E.U.T.:	Access Point				
Configuration:	Tx with antenna removed				
Sample Number:					
Location:	Lab 2	RBW:	Refer to plots	Measurement	
Detector Type:	Peak	VBW:	Refer to plots	Distance: N/A m	
Test Equipment Used					
Antenna:	_____	Directional Coupler:	_____		
Pre-Amp:	_____	Cable #1:	1627		
Filter:	_____	Cable #2:	_____		
Receiver:	1464	Cable #3:	_____		
Attenuator #1:	1469	Cable #4:	_____		
Attenuator #2:	1465	Mixer:	_____		
Additional equipment used:	_____				
Measurement Uncertainty:	+/-1.7 dB				



Notes: Low bandedge with signal being more than 20 dBc less than carrier.

DIRECT SEQUENCE SPREAD SPECTRUM TRANSMITTER


EQUIPMENT: M5800S Subscriber Unit

PROJECT NO.: 1L0374RUS2



Dallas Headquarters:
802 N. Kealy
Lewisville, TX 75057
Tel: (972) 436-9600
Fax: (972) 436-2667

Nemko Dallas, Inc.



DIRECT SEQUENCE SPREAD SPECTRUM TRANSMITTER

EQUIPMENT: M5800S Subscriber Unit

PROJECT NO.: 1L0374RUS2

Section 8. Spurious Emissions (radiated)

NAME OF TEST: Peak Power Output	PARA. NO.: 15.247 (c)
TESTED BY: Lance Walker	DATE: 12/6/2001

Test Results: Complies.

Measurement Data: See attached table.

Duty Cycle Calculation:

Duty Cycle correction factor(dB) = $20 \log (rf_{ON} \text{ in ms}/100\text{ms})$

Please note that the SPD4-58 model is the four-foot diameter model of a family that has a 1 foot, 2 foot, and 3 foot model in the same family that will be used with this device.

DIRECT SEQUENCE SPREAD SPECTRUM TRANSMITTER

EQUIPMENT: M5800S Subscriber Unit

PROJECT NO.: 1L0374RUS2



Nemko Dallas, Inc.

Dallas Headquarters:

802 N. Kealy
Lewisville, TX 75057
Tel: (972) 436-9600
Fax: (972) 436-2667


Page <u>1</u> of <u>2</u>		<u>Radiated Emissions</u>	
Job No.:	1L0374R	Date:	12/6/01
Specification:	CFR 47, Part 15	Temperature(°C):	<u>22</u>
Tested By:	<u>Lance Walker</u>	Relative Humidity(%):	<u>50</u>
E.U.T.:	Subscriber Unit with Integral Patch Antenna		
Configuration:	Normal Tx		
Sample Number:			
Location:	<u>AC 3</u>	RBW:	<u>1 MHz</u>
Detector Type:	<u>Average</u>	VBW:	<u>300Hz</u>
<u>Test Equipment Used</u>			
Antenna:	<u>1304</u>	Directional Coupler:	<u>#N/A</u>
Pre-Amp:	<u>#N/A</u>	Cable #1:	<u>1484</u>
Filter:	<u>#N/A</u>	Cable #2:	<u>1485</u>
Receiver:	<u>1464</u>	Cable #3:	<u>1626</u>
Attenuator #1:	<u>#N/A</u>	Cable #4:	<u>#N/A</u>
Attenuator #2:	<u>#N/A</u>	Mixer:	<u>989</u>
Additional equipment used: <u>990</u>			
Measurement Uncertainty: <u>+/- .7 dB</u>			

Frequency (GHz)	Meter Reading (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Pre-Amp Gain (dB)	Corrected Reading (dBuV/m)	Limit (dBuV/m)	Delta (dB)	Comment
11.472	46.7	41.1	7.4	35.5	59.7	74	-14.3	Low Ch V NF
11.472	35.2	41.1	7.4	35.5	48.2	54	-5.8	Noise Floor
40.152	29.6	39.6	0	0	69.2	78	-8.3	at 20 cm
45.888	28.8	40.2	0	0	69.0	78	-8.5	at 20 cm
51.624	28.5	41.0	0	0	69.5	78	-8.0	at 20 cm
57.36	28.1	41.7	0	0	69.8	78	-7.7	at 20 cm
11.472	36.8	41.1	7.4	35.5	49.8	54	-4.2	Low Ch H
40.152	29.6	39.6	0	0	69.2	78	-8.3	at 20 cm
45.888	28.8	40.2	0	0	69.0	78	-8.5	at 20 cm
51.624	28.5	41.0	0	0	69.5	78	-8.0	at 20 cm
57.36	28.1	41.7	0	0	69.8	78	-7.7	at 20 cm
11.672	39	41.1	7.4	35.5	52.0	54	-2.0	High Ch H
11.672	52	41.1	7.4	35.5	65.0	74	-9.0	High Ch H Pk
40.852	28.8	39.7	0	0	68.5	78	-9.0	at 20 cm
46.688	27.8	40.4	0	0	68.2	78	-9.3	at 20 cm
52.524	27.6	41.1	0	0	68.7	78	-8.8	at 20 cm
58.36	27.9	41.8	0	0	69.7	78	-7.8	at 20 cm
11.672	35.5	41.1	7.4	35.5	48.5	54	-5.5	High Ch V
40.852	28.8	39.7	0	0	68.5	78	-9.0	at 20 cm
46.688	27.8	40.4	0	0	68.2	78	-9.3	at 20 cm
52.524	27.6	41.1	0	0	68.7	78	-8.8	at 20 cm
58.36	27.9	41.8	0	0	69.7	78	-7.8	at 20 cm

Notes: All measurements taken in worst case scenario Tx all time in normal there will be bursts.

EQUIPMENT: M5800S Subscriber Unit

PROJECT NO.: 1L0374RUS2



Radiated Spurious Emissions

Continuation Page

Date: 12/10/01

Temperature(°F): 72

Relative Humidity(%) 50

Subscriber Unit with Integral Patch Antenna

Normal Tx

Notes: All measurements above 40GHz were Noise Floor to include peak measurements.

DIRECT SEQUENCE SPREAD SPECTRUM TRANSMITTER

EQUIPMENT: M5800S Subscriber Unit

PROJECT NO.: 1L0374RUS2



Nemko Dallas, Inc.

Dallas Headquarters:

802 N. Kealy
Lewisville, TX 75057
Tel: (972) 436-9600
Fax: (972) 436-2667


Page 1 of 2		Radiated Emissions	
Job No.:	1L0374R	Date:	12/6/01
Specification:	CFR 47, Part 15	Temperature(°C):	22
Tested By:	Lance Walker	Relative Humidity(%)	50
E.U.T.:	Subscriber w/AD5800-27-D		
Configuration:	Normal Tx		
Sample Number:			
Location:	AC 3	RBW:	1 MHz
Detector Type:	Average	VBW:	300Hz
Test Equipment Used			
Antenna:	984	Directional Coupler:	#N/A
Pre-Amp:	1016	Cable #1:	1626
Filter:	#N/A	Cable #2:	1485
Receiver:	1464	Cable #3:	1486
Attenuator #1	#N/A	Cable #4:	#N/A
Attenuator #2:	#N/A	Mixer:	989
Additional equipment used: 1650, 1304			
Measurement Uncertainty: +/- .7 dB			

Frequency (GHz)	Meter Reading (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Pre-Amp Gain (dB)	Corrected Reading (dBuV/m)	Limit (dBuV/m)	Delta (dB)	Comment
11.472	48.2	41.1	7.4	35.5	61.2	74	-12.8	Low Ch V NF
11.472	35.0	41.1	7.4	35.5	48.0	54	-6.0	Noise Floor
40.152	29.8	39.6	0.0	0.0	69.4	78	-8.1	at 20 cm
45.888	28.5	40.2	0.0	0.0	68.7	78	-8.8	
51.624	28.3	41.0	0.0	0.0	69.3	78	-8.2	
57.360	27.9	41.7	0.0	0.0	69.6	78	-7.9	
11.472	34.8	41.1	7.4	35.5	47.8	54	-6.2	Low Ch H
11.472	47.7	41.1	7.4	35.5	60.7	74	-13.3	
40.152	29.8	39.6	0.0	0.0	69.4	78	-8.1	
45.888	28.5	40.2	0.0	0.0	68.7	78	-8.8	
51.624	28.3	41.0	0.0	0.0	69.3	78	-8.2	
57.360	27.9	41.7	0.0	0.0	69.6	78	-7.9	
11.672	34.5	41.1	7.4	35.5	47.5	54	-6.5	High Ch H
11.672	49.3	41.1	7.4	35.5	62.3	74	-11.7	
40.852	28.8	39.7	0.0	0.0	68.5	78	-9.0	
46.688	27.9	40.4	0.0	0.0	68.3	78	-9.2	
52.524	28.3	41.1	0.0	0.0	69.4	78	-8.1	
58.360	28.5	41.8	0.0	0.0	70.3	78	-7.2	
11.672	36.7	41.1	7.4	35.5	49.7	54	-4.3	High Ch V
11.672	50.5	41.1	7.4	35.5	63.5	74	-10.5	
40.852	28.8	39.7	0.0	0.0	68.5	78	-9.0	
46.688	27.9	40.4	0.0	0.0	68.3	78	-9.2	
52.524	28.3	41.1	0.0	0.0	69.4	78	-8.1	

Notes: Noise Floor seen at everything over 40GHz.

EQUIPMENT: M5800S Subscriber Unit

PROJECT NO.: 1L0374RUS2

[illegible]

DIRECT SEQUENCE SPREAD SPECTRUM TRANSMITTER

EQUIPMENT: M5800S Subscriber Unit

PROJECT NO.: 1L0374RUS2



Nemko Dallas, Inc.


Dallas Headquarters:

802 N. Kealy
Lewisville, TX 75057
Tel: (972) 436-9600
Fax: (972) 436-2667

Radiated Emissions								
Page 1 of 2								
Job No.:	1L0374R	Date:	12/6/01					
Specification:	CFR 47, Part 15	Temperature(°C):	22					
Tested By:	Lance Walker	Relative Humidity(%)	50					
E.U.T.:	Subscriber w/SPD4-58							
Configuration:	Normal Tx							
Sample Number:								
Location:	AC 3	RBW:	1 MHz					
Detector Type:	Average	VBW:	300Hz					
Test Equipment Used								
Antenna:	984	Directional Coupler:	#N/A					
Pre-Amp:	1016	Cable #1:	1626					
Filter:	#N/A	Cable #2:	1485					
Receiver:	1464	Cable #3:	1486					
Attenuator #1	#N/A	Cable #4:	#N/A					
Attenuator #2:	#N/A	Mixer:	989					
Additional equipment used: 1650, 1304								
Measurement Uncertainty: +/- .7 dB								
Frequency (GHz)	Meter Reading (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Pre-Amp Gain (dB)	Corrected Reading (dBuV/m)	Limit (dBuV/m)	Delta (dB)	Comment
11.472	48.2	41.1	7.4	35.5	61.2	74	-12.8	Low Ch V NF
11.472	35.0	41.1	7.4	35.5	48.0	54	-6.0	Noise Floor
40.152	29.8	39.6	0.0	0.0	69.4	78	-8.1	at 20 cm
45.888	28.5	40.2	0.0	0.0	68.7	78	-8.8	
51.624	28.3	41.0	0.0	0.0	69.3	78	-8.2	
57.360	27.9	41.7	0.0	0.0	69.6	78	-7.9	
11.472	36.7	41.1	7.4	35.5	49.7	54	-4.3	Low Ch H
11.472	60.7	41.1	7.4	35.5	73.7	74	-0.3	worst case scenario full Tx
40.152	29.8	39.6	0.0	0.0	69.4	78	-8.1	
45.888	28.5	40.2	0.0	0.0	68.7	78	-8.8	
51.624	28.3	41.0	0.0	0.0	69.3	78	-8.2	
57.360	27.9	41.7	0.0	0.0	69.6	78	-7.9	
11.672	35.5	41.1	7.4	35.5	48.5	54	-5.5	High Ch H
11.672	58.3	41.1	7.4	35.5	71.3	74	-2.7	
40.852	28.8	39.7	0.0	0.0	68.5	78	-9.0	
46.688	27.9	40.4	0.0	0.0	68.3	78	-9.2	
52.524	28.3	41.1	0.0	0.0	69.4	78	-8.1	
58.360	28.5	41.8	0.0	0.0	70.3	78	-7.2	
11.672	36.7	41.1	7.4	35.5	49.7	54	-4.3	High Ch V
11.672	50.5	41.1	7.4	35.5	63.5	74	-10.5	
40.852	28.8	39.7	0.0	0.0	68.5	78	-9.0	
46.688	27.9	40.4	0.0	0.0	68.3	78	-9.2	
52.524	28.3	41.1	0.0	0.0	69.4	78	-8.1	
Notes:	Noise Floor seen at everything over 40GHz.							

EQUIPMENT: M5800S Subscriber Unit

PROJECT NO.: 1L0374RUS2


[illegible]

DIRECT SEQUENCE SPREAD SPECTRUM TRANSMITTER

EQUIPMENT: M5800S Subscriber Unit

PROJECT NO.: 1L0374RUS2

Radiated Photographs (Worst Case Configuration)



Nemko
Dallas

FCC PART 15, SUBPART C

DIRECT SEQUENCE SPREAD SPECTRUM TRANSMITTER

EQUIPMENT: M5800S Subscriber Unit

PROJECT NO.: 1L0374RUS2

Section 9. Peak Power Spectral Density

NAME OF TEST: Peak Power Spectral Density

PARA. NO.: 15.247(d)

TESTED BY:

DATE:

Test Results: Complies.

Measurement Data: See attached plots

Equipment Used:

Measurement Uncertainty: +/- 0.7 dB

Temperature: °C

Relative Humidity: %

Not Applicable

DIRECT SEQUENCE SPREAD SPECTRUM TRANSMITTER

EQUIPMENT: M5800S Subscriber Unit

PROJECT NO.: 1L0374RUS2

Section 10. Minimum Processing Gain

NAME OF TEST: Minimum Processing Gain

PARA. NO.: 15.247(e)

TESTED BY:

DATE:

Test Results:

Complies. The minimum processing gain of the system is ____ dB.

Measurement Data: See attached data.

BER:

S/N_{out}:

J/S Ratio:

L_{sys}:

Equipment Used:

Measurement Uncertainty: +/- 0.7 dB

Temperature: °C

Relative Humidity: %

DIRECT SEQUENCE SPREAD SPECTRUM TRANSMITTER

EQUIPMENT: M5800S Subscriber Unit

PROJECT NO.: 1L0374RUS2

Section 11. Test Equipment List

Nemko ID	Description	Manufacturer Model Number	Serial Number	Calibration Date
1016	Pre-Amp	HEWLETT PACKARD 8449A	2749A00159	05/30/01
1464	Spectrum analyzer	Hewlett Packard 8563E	3551A04428	01/02/01
1626	CABLE, 5 ft	MEGAPHASE 10311 1GVT4	N/A	CBU
1484	Cable 2.0-18.0 Ghz	Storm PR90-010-072	N/A	06/01/01
1485	Cable 2.0-18.0 Ghz	Storm PR90-010-216	N/A	06/01/01
1650	12-18 GHz BP Filter	#N/A #N/A	#N/A	12/06/01
1029	PEAK POWER METER	HP 8900D	3303U0012	03/12/01
1030	PEAK POWER SENSOR	HP 84811A	2539A03573	03/12/01
1465	10 db Attenuator DC 8.0 Ghz	Midwest Microwave 292/10db	NONE	CBU
1469	10 db Attenuator DC 18 Ghz	MCL Inc. BW-S10W2 10db-2WDC	NONE	CBU
1470	10 db Attenuator DC 18 Ghz	MCL Inc. BW-S10W2 10db-2WDC	NONE	CBU
984	HORN ANTENNA	MILLITECH NONE	NONE	CNR
989	HARMONIC MIXER	Hewlett Packard 11970U	2332A00116	01/00/00

Nemko
Dallas

FCC PART 15, SUBPART C

DIRECT SEQUENCE SPREAD SPECTRUM TRANSMITTER

EQUIPMENT: M5800S Subscriber Unit

PROJECT NO.: 1L0374RUS2

ANNEX A - TEST DETAILS

Nemko
Dallas

FCC PART 15, SUBPART C

DIRECT SEQUENCE SPREAD SPECTRUM TRANSMITTER

EQUIPMENT: M5800S Subscriber Unit

PROJECT NO.: 1L0374RUS2

NAME OF TEST: Powerline Conducted Emissions	PARA. NO.: 15.207(a)
---	----------------------

Minimum Standard:

The R.F. that is conducted back onto the AC power line on any frequency within the band 0.45 to 30 MHz shall not exceed 250 μ V (48 dB μ V) across 50 ohms.

Nemko
Dallas

FCC PART 15, SUBPART C

DIRECT SEQUENCE SPREAD SPECTRUM TRANSMITTER

EQUIPMENT: M5800S Subscriber Unit

PROJECT NO.: 1L0374RUS2

NAME OF TEST: Minimum 6 dB bandwidth	PARA. NO.: 15.247(a)(2)
--------------------------------------	-------------------------

Minimum Standard:

The minimum 6 dB bandwidth shall be at least 500 kHz

DIRECT SEQUENCE SPREAD SPECTRUM TRANSMITTER

EQUIPMENT: M5800S Subscriber Unit

PROJECT NO.: 1L0374RUS2

NAME OF TEST: Maximum Peak Output Power

PARA. NO.: 15.247(b)(1)

Minimum Standard:

The maximum peak output power shall not exceed 1 watt.

If transmitting antennas of directional gain greater than 6 dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Systems operating in the 2400-2483.5 MHz band that are used exclusively for fixed, point to point operation may employ transmitting antennas with directional gain greater than 6 dBi provided the maximum peak output power is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceed 6 dBi.

Systems operating in the 5725 – 5850 MHz band that are used exclusively for fixed, point-to-point operation may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter peak output power.

Direct Measurement Method For Detachable Antennas:

If the antenna is detachable, a peak power meter is used to measure the power output with the transmitter operating into a 50 ohm load. The dBi gain of the antenna(s) employed shall be reported.

Calculation Of EIRP For Integral Antenna:

If the antenna is not detachable from the circuit then the Peak Power Output is derived from the peak radiated field strength of the fundamental emission by using the plane wave relation $GP/4\pi R^2 = E^2/120\pi$ and proceeding as follows:

$$P = \frac{E^2 R^2}{30G} = \frac{E^2 3^2}{30G}$$

where,

P = the equivalent isotropic radiated power in watts

E = the maximum measured field strength in V/m

R = the measurement range (3 meters)

G = the numeric gain of the transmit antenna in relation to an isotropic radiator

DIRECT SEQUENCE SPREAD SPECTRUM TRANSMITTER

EQUIPMENT: M5800S Subscriber Unit

PROJECT NO.: 1L0374RUS2

The RBW of the spectrum analyzer shall be set to a value greater than the measured 6 dB occupied bandwidth of the E.U.T.

Number of channels tested:

Tuning range	Number of channels tested	Channel location in band
1 MHz or less	1	middle
1 to 10 MHz	2	top and bottom
more than 10 MHz	3	top, middle, bottom

Nemko
Dallas

FCC PART 15, SUBPART C

DIRECT SEQUENCE SPREAD SPECTRUM TRANSMITTER

EQUIPMENT: M5800S Subscriber Unit

PROJECT NO.: 1L0374RUS2

NAME OF TEST: RF Exposure	PARA. NO.: 15.247(b)(4)
---------------------------	-------------------------

Minimum Standard:

Systems operating under the provisions of this section shall be operated in a manner that ensures the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines stipulated in 1.1307(b)(1) of CFR 47.

DIRECT SEQUENCE SPREAD SPECTRUM TRANSMITTER

EQUIPMENT: M5800S Subscriber Unit

PROJECT NO.: 1L0374RUS2

NAME OF TEST: Spurious Emissions(conducted)	PARA. NO.: 15.247(c)
--	-----------------------------

Minimum Standard:

In any 100kHz bandwidth outside the frequency band in which the transmitter is operating, emissions shall be at least 20 dB below the fundamental emission or shall not exceed the following field strength limits. Emissions falling in the restricted bands of 15.205 shall not exceed the following field strength limits:

Frequency (MHz)	Field Strength (mV/m @ 3m)	Field Strength (dB @ 3m)
30 - 88	100	40.0
88 - 216	150	43.5
216 - 960	200	46.0
Above 960	500	54.0

THE SPECTRUM IS SEARCHED TO THE 10th HARMONIC OF THE HIGHEST FREQUENCY GENERATED IN THE EUT.

Method Of Measurement:

30 MHz - 10th harmonic plot

RBW: 100 kHz

VBW: 300 kHz

Sweep: Auto

Display line: -20 dBc

Lower Band Edge

RBW: At least 1% of span/div.

VBW: >RBW

Span: As necessary to display any spurious at band edge.

Sweep: Auto

Center Frequency: 902 MHz, 2400 MHz, or 5725 MHz

Marker: Peak of fundamental emission

Marker Δ: Peak of highest spurious level below center frequency.

Upper Band Edge

RBW: At least 1% of span/div.

VBW: >RBW

Span: As necessary to display any spurious at band edge.

Sweep: Auto

Center Frequency: 928 MHz, 2483.5 MHz, or 5850 MHz

Marker: Peak of fundamental emission

Marker Δ: Peak of highest spurious level above center frequency.

Number of channels tested:

Tuning range	Number of channels tested	Channel location in band
1 MHz or less	1	middle
1 to 10 MHz	2	top and bottom
more than 10 MHz	3	top, middle, bottom

DIRECT SEQUENCE SPREAD SPECTRUM TRANSMITTER

EQUIPMENT: M5800S Subscriber Unit

PROJECT NO.: 1L0374RUS2

NAME OF TEST: Radiated Spurious Emissions	PARA. NO.: 15.247(c)
--	-----------------------------

Minimum Standard: In any 100kHz bandwidth outside the frequency band in which the transmitter is operating, emissions shall be at least 20 dB below the fundamental emission or shall not exceed the following field strength limits:

Emissions falling in the restricted bands of 15.205 shall not exceed the following field strength limits:

Frequency (MHz)	Field Strength (mV/m @ 3m)	Field Strength (dB @ 3m)
30 - 88	100	40.0
88 - 216	150	43.5
216 - 960	200	46.0
Above 960	500	54.0

THE SPECTRUM WAS SEARCHED TO THE 10th HARMONIC

15.205 Restricted Bands

MHz	MHz	MHz	GHz
0.09-0.11	16.42-16.423	399.9-410	4.5-5.25
0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.125-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2655-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	Above 38.6
13.36-13.41	1718		

Number of channels tested:

Tuning range	Number of channels tested	Channel location in band
1 MHz or less	1	middle
1 to 10 MHz	2	top and bottom
more than 10 MHz	3	top, middle, bottom

DIRECT SEQUENCE SPREAD SPECTRUM TRANSMITTER

EQUIPMENT: M5800S Subscriber Unit

PROJECT NO.: 1L0374RUS2

NAME OF TEST: Transmitter Power Density

PARA. NO.: 15.247(d)

Minimum Standard: The transmitted power density averaged over any 1 second interval shall not be greater than +8 dBm in any 3 kHz bandwidth.

Method Of Measurement: The spectrum analyzer is set as follows:

RBW: 3 kHz

VBW: >3 kHz

Span: => measured 6 dB bandwidth

Sweep: Span(kHz)/3 (i.e. for a span of 1.5 MHz the sweep rate is $1500/3 = 500$ sec.

LOG dB/div.: 2 dB

Note: For devices with spectrum line spacing ≤ 3 kHz, the RBW of the analyzer is reduced until the spectral lines are resolved. The measurement data is normalized to 3 kHz by summing the power of all the individual spectral lines within a 3 kHz band in linear power units.

For Devices With Integral Antenna:

For devices with non-detachable antennas, the received field strength is peaked and the spectrum analyzer is set as above. The peak emission level is then measured and converted to a field strength by adding the appropriate antenna factor and cable loss. This field strength is then converted to an equivalent isotropic radiated power using the same method as described for Peak Power output.

Number of channels tested:

Tuning Range	Number Of Channels Tested	Channel Location In Band
1 MHz or Less	1	Middle
1 to 10 MHz	2	Top And Bottom
More Than 10 MHz	3	Top, Middle, Bottom

DIRECT SEQUENCE SPREAD SPECTRUM TRANSMITTER

EQUIPMENT: M5800S Subscriber Unit

PROJECT NO.: 1L0374RUS2

NAME OF TEST: Processing Gain	PARA. NO.: 15.247(e)
-------------------------------	----------------------

Minimum Standard: The processing gain shall be at least 10 dB.

Method Of Measurement: The CW jamming margin method was used to determine the processing gain. A CW signal generator is stepped across the passband of the receiver in 50 kHz increments. At each point the signal generator level required to obtain the recommended bit error rate is recorded. The jammer to signal ratio (J/S) is then calculated. The worst 20% of the J/S points is discarded. The lowest remaining J/S ratio is used to calculate the processing gain.

Calculation Of Processing Gain:

The processing gain was determined by measuring the jamming margin of the E.U.T. and using the following formula:

$$\text{Jamming Margin} = G_p - (S/N)_{\text{out}} - L_{\text{sys}}$$

For a receiver using non-coherent detection the value $(S/N)_{\text{out}}$ is calculated using the formula:

$P_e = (1/2)\text{EXP}\{-E/2N_o\}$ where P_e is the probability of error (minimum Bit Error Rate required for proper operation).

E/N_o is $(S/N)_{\text{out}}$

for example, for a bit error rate of 10^{-4} a S/N ratio of 12.3 dB is required.

L_{sys} (system losses) is assumed to be 2 dB.

$$\text{Therefore } G_p = M_j + (S/N)_{\text{out}} + L_{\text{sys}}$$

Measurement performed at a channel in the center of the operating band of the EUT.

Nemko
Dallas

FCC PART 15, SUBPART C

DIRECT SEQUENCE SPREAD SPECTRUM TRANSMITTER

EQUIPMENT: M5800S Subscriber Unit

PROJECT NO.: 1L0374RUS2


ANNEX B - TEST DIAGRAMS

DIRECT SEQUENCE SPREAD SPECTRUM TRANSMITTER


EQUIPMENT: M5800S Subscriber Unit

PROJECT NO.: 1L0374RUS2

Test Site For Radiated Emissions



Conducted Emissions




DIRECT SEQUENCE SPREAD SPECTRUM TRANSMITTER


EQUIPMENT: M5800S Subscriber Unit

PROJECT NO.: 1L0374RUS2

Peak Power At Antenna Terminals



**Minimum 6 dB Bandwidth
Peak Power Spectral Density
Spurious Emissions (conducted)**




DIRECT SEQUENCE SPREAD SPECTRUM TRANSMITTER

EQUIPMENT: M5800S Subscriber Unit

PROJECT NO.: 1L0374RUS2

Processing Gain



NOTE: This is a typical setup. The setup may vary slightly since many devices have BER test functions built into the device.