

# 1 Human Exposure Assessment

## 1.1 Maximum Permissible Exposure

### 1.1.1 Limit of Maximum Permissible Exposure

Limits for Occupational / Controlled Exposure				
Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm <sup>2</sup> )	Averaging Time  E  <sup>2</sup> , H  <sup>2</sup> or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842 / f	4.89 / f	(900 / f)*	6
30-300	61.4	0.163	1.0	6
300-1500	-	-	F/300	6
1500-100,000	-	-	5	6
Limits for General Population / Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm <sup>2</sup> )	Averaging Time  E  <sup>2</sup> , H  <sup>2</sup> or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500	-	-	F/1500	30
1500-100,000	-	-	1.0	30
Note 1: f = frequency in MHz ; *Plane-wave equivalent power density				
Note 2: For the applicable limit, see FCC 1.1310				

RF Field Strength Limits for Controlled Use Devices (Controlled Environment)				
Frequency Range (MHz)	Electric Field (V/m rms)	Magnetic Field (A/m rms)	Power Density (W/m <sup>2</sup> )	Averaging Time (minutes)
0.003-1	600	4.9	-	6
1-10	600/f	4.9/f	-	6
10-30	60	4.9/f	-	6
30-300	60	0.163	10*	6
300-1500	3.54 f <sup>0.5</sup>	0.0094 f <sup>0.5</sup>	f/30	6
1500-15000	137	0.364	50	6
15000-150000	137	0.364	50	616000/f <sup>1.2</sup>
150000-300000	0.354 f <sup>0.5</sup>	9.4 x 10 <sup>-4</sup> f <sup>0.5</sup>	3.33 x 10 <sup>-4</sup> f	616000/f <sup>1.2</sup>
RF Field Strength Limits for Devices Used by the General Public (Uncontrolled Environment)				
Frequency Range (MHz)	Electric Field (V/m rms)	Magnetic Field (A/m rms)	Power Density (W/m <sup>2</sup> )	Averaging Time (minutes)
0.003-1	280	2.19	-	6
1-10	280/f	2.19/f	-	6
10-30	28	2.19/f	-	6
30-300	28	0.073	2*	6
300-1500	1.585 f <sup>0.5</sup>	0.0042 f <sup>0.5</sup>	f/150	6
1500-15000	61.4	0.163	10	6
15000-150000	61.4	0.163	10	616000/f <sup>1.2</sup>
150000-300000	0.158 f <sup>0.5</sup>	4.21 x 10 <sup>-4</sup> f <sup>0.5</sup>	6.67 x 10 <sup>-5</sup> f	616000/f <sup>1.2</sup>
Note 1: f is frequency in MHz.				
Note 2: For the applicable limit, see IC RSS-102				

### 1.1.2 MPE Calculation Method

$$E \text{ (V/m)} = \frac{\sqrt{30 \times P \times G}}{d}$$

**E** = Electric field (V/m)

**G** = EUT Antenna numeric gain (numeric)

The formula can be changed to

$$Pd = \frac{30 \times P \times G}{377 \times d^2}$$

$$\text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

**P** = RF output power (W)

**d** = Separation distance between radiator and human body (m)



1.1.3 Result of Maximum Permissible Exposure

Transmitter Chains & Receiver Chains Information				
IEEE Std. 802.11 Protocol	Number of Transmit Chains (N <sub>TX</sub> )	Number of Receive Chains (N <sub>RX</sub> )	Correlation Signals with Multiple N <sub>TX</sub>	RF Output Power (dBm)
b	1	1	Correlated	15.81
g	1	1	Correlated	15.44
n (HT20)	1	1	Correlated	15.43
n (HT40)	1	1	Correlated	14.24

Note 1: RF output power specifies that Maximum Conducted (Average) Output Power.

Worst Maximum RF Output Power Result					
Exposure Environment		RTL819x_2.2.4			
Separation Distance (cm)		20			
Power Level	1	RF Output Power (dBm)			
Modulation Mode	N <sub>TX</sub>	RF Output Power (dBm)	Gain (dBi)	EIRP Power	PD (S) (mW/cm <sup>2</sup> )
11B-20M	1	15.81	3.71	19.52	0.01781
11G-20M	1	15.44	3.71	19.15	0.01636
11N2.4G-20M	1	15.43	3.71	19.14	0.01632
11N2.4G-40M	1	14.24	3.71	17.95	0.01241
Maximum Permissible Exposure Limit (mW/cm <sup>2</sup> )					1

Note 1: N<sub>TX</sub> = Number of Transmit Chains