	BUREAU VERITAS	
	RF Exposure Report	
Report No.:	SA190614C18	
FCC ID:	NDD9532311904	
Test Model:	IC-3231GOP	
Series Model:	IC-S200WD	
Received Date:	Jun. 21, 2019	
Test Date:	Jul. 10, 2019 ~ Jun. 17, 2020	
Issued Date:	Jun. 18, 2020	
Applicant:	EDIMAX TECHNOLOGY CO., LTD.	
Address:	No. 3, Wuquan 3rd Rd., Wugu Dist., New Taipei City 248, Taiwan (R.O.C.)	
Issued By:	Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch Lin Kou Laboratories	
Lab Address:	No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan	
Test Location:	No. 19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City 33383, TAIWAN	
FCC Registration / Designation Number:	788550 / TW0003	
	BICC-MRA Testing Laboratory 2021	
This report is for your exclusive use Apy	conving or replication of this report to or for any other person or entity or use of our name or trademark is permitted	

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth ourfindings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specification, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.



Table of Contents

Rele	ase Control Record	3
1	Certificate of Conformity	4
2	RF Exposure	5
2.2	 Limits for Maximum Permissible Exposure (MPE) MPE Calculation Formula Classification 	5
3	Calculation Result of Maximum Conducted Power	5



Release Control Record

Issue No.	Description	Date Issued
SA190614C18	Original release	Jun. 18, 2020



1 **Certificate of Conformity**

Product:	2MP WI-FI Bullet Cammera		
Brand:	EDIMAX		
Test Model:	IC-3231GOP		
Series Model:	IC-S200WD		
Sample Status:	Engineering sample		
Applicant:	EDIMAX TECHNOLOGY CO., LTD.		
Test Date:	Jul. 10, 2019 ~ Jun. 17, 2020		
Standards:	FCC Part 2 (Section 2.1091)		
	KDB 447498 D01 General RF Exposure Guidance v06		
Guidance:	IEEE C95.3 -2002		

The above equipment has been tested by Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

Prepared by :

Polly Chien / Specialist , Date: Jun. 18, 2020

Approved by :

ne Chen , Date: Jun. 18, 2020

Bruce Chen / Senior Project Engineer



2 RF Exposure

2.1 Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	g		Average Time (minutes)	
Limits For General Population / Uncontrolled Exposure					
300-1500			F/1500	30	
1500-100,000			1.0	30	

F = Frequency in MHz

2.2 MPE Calculation Formula

 $\begin{array}{l} \mathsf{Pd}=(\mathsf{Pout}^*G) \ / \ (4^*pi^*r^2) \\ \text{where} \\ \mathsf{Pd}=\mathsf{power} \ \mathsf{density} \ in \ mW/cm^2 \\ \mathsf{Pout}=\mathsf{output} \ \mathsf{power} \ \mathsf{to} \ \mathsf{antenna} \ in \ mW \\ \mathsf{G}=\mathsf{gain} \ \mathsf{of} \ \mathsf{antenna} \ in \ \mathsf{linear} \ \mathsf{scale} \\ \mathsf{pi}=3.1416 \\ \mathsf{r}=\mathsf{distance} \ \mathsf{between} \ \mathsf{observation} \ \mathsf{point} \ \mathsf{and} \ \mathsf{center} \ \mathsf{of} \ \mathsf{the} \ \mathsf{radiator} \ \mathsf{in} \ \mathsf{cm} \end{array}$

2.3 Classification

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as **Mobile Device**.

3 Calculation Result of Maximum Conducted Power

Frequency Band (MHz)	Max Power (dBm)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm²)	
WLAN						
2412-2462	24.96	2	20	0.099	1	
BT LE						
2402-2480	3.59	2	20	0.001	1	

Note:

1. Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

2. WLAN and BT LE technology cannot transmit simultaneously.

----END----