

EDIMAX TECHNOLOGY CO., LTD.

No.3,Wu-Chuan 3rd Road,Wu-Ku Industrial Park, New Taipei City, Taiwan

Tune up procedure

2.4G

B	Power Target (dBm)	Tolerance (dBm)	Max. Tune-up Power(dBm)	Avg.Pwr (dBm)
2412	18.00	+/-1	19.00	18.66
2437	17.50	+/-1	18.50	18.23
2462	17.00	+/-1	18.00	17.89

G	Power Target (dBm)	Tolerance (dBm)	Max. Tune-up Power(dBm)	Avg.Pwr (dBm)
2412	15.50	+/-1	16.50	16.09
2437	15.50	+/-1	16.50	16.38
2462	15.50	+/-1	16.50	16.04

N20	Power Target (dBm)	Tolerance (dBm)	Max. Tune-up Power(dBm)	Avg.Pwr (dBm)
2412	16.50	+/-1	17.50	17.36
2437	16.00	+/-1	17.00	16.88
2462	16.00	+/-1	17.00	16.80

N40	Power Target (dBm)	Tolerance (dBm)	Max. Tune-up Power(dBm)	Avg.Pwr (dBm)
2422	13.00	+/-1	14.00	13.71
2437	16.00	+/-1	17.00	16.84
2452	15.00	+/-1	16.00	15.97

5G

A	Power Target (dBm)	Tolerance (dBm)	Max. Tune-up Power(dBm)	Avg.Pwr (dBm)
5180	16.00	+/-1	17.00	16.95
5220	16.00	+/-1	17.00	16.6
5240	16.00	+/-1	17.00	16.5
5745	18.00	+/-1	19.00	18.68
5785	18.00	+/-1	19.00	18.42
5825	17.50	+/-1	18.50	18.33

EDIMAX TECHNOLOGY CO., LTD.

No.3,Wu-Chuan 3rd Road,Wu-Ku Industrial Park, New Taipei City, Taiwan

N20	Power Target (dBm)	Tolerance (dBm)	Max. Tune-up Power(dBm)	Avg.Pwr (dBm)
5180	16.50	+/-1	17.50	17.07
5220	17.00	+/-1	18.00	17.68
5240	17.00	+/-1	18.00	17.79
5745	18.00	+/-1	19.00	18.67
5785	18.00	+/-1	19.00	18.09
5825	17.00	+/-1	18.00	17.49

N40	Power Target (dBm)	Tolerance (dBm)	Max. Tune-up Power(dBm)	Avg.Pwr (dBm)
5190	16.00	+/-1	17.00	16.87
5230	16.00	+/-1	17.00	16.82
5755	18.00	+/-1	19.00	18.66
5795	17.50	+/-1	18.50	18.14

AC80	Power Target (dBm)	Tolerance (dBm)	Max. Tune-up Power(dBm)	Avg.Pwr (dBm)
5210	17.50	+/-1	18.50	18.01
5775	17.50	+/-1	18.50	18.30