

IEEE C95.1

KDB 447498 D01 General RF Exposure Guidance v06

47 C.F.R. Part 1, Subpart I, Section 1.1310

47 C.F.R. Part 2, Subpart J, Section 2.1091

RF EXPOSURE REPORT

For

AC1200 Wireless LAN Concurrent Dual Band Gigabit Router

Model: BR-6485AC

Trade Name: EDIMAX

Issued to

EDIMAX TECHNOLOGY CO., LTD.

No.3,Wu-Chuan 3rd Road,Wu-Ku Industrial Park, New Taipei City, Taiwan

Issued by

Compliance Certification Services Inc.

**No.11, Wugong 6th Rd., Wugu Dist.,
New Taipei City 24891, Taiwan. (R.O.C.)**

<http://www.ccsrf.com>

service@ccsrf.com

Issued Date: December 18, 2015



**Testing Laboratory
1309**

Revision History

Rev.	Issue Date	Revisions	Effect Page	Revised By
00	2015//12/18	Initial Issue	ALL	Kelly Cheng

TABLE OF CONTENTS

1. LIMIT 4

2. EUT SPECIFICATION 4

3. TEST RESULTS 6

4. MAXIMUM PERMISSIBLE EXPOSURE 7

1. LIMIT

According to §15.247(i), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines. See § 1.1307(b)(1) of this chapter.

2. EUT SPECIFICATION

EUT	AC1200 Wireless LAN Concurrent Dual Band Gigabit Router		
Model	BR-6485AC		
RF Module(2.4G)	MEDIATEK	Model:	MT7603EN
RF Module(5G)	MEDIATEK	Model:	MT7612EN
Frequency band (Operating)	<input checked="" type="checkbox"/> 802.11b/g/n HT20: 2.412GHz ~ 2.462GHz 802.11n HT40: 2.422GHz ~ 2.452GHz 802.11a/n HT20: 5.180GHz ~ 5.240GHz / 5.745 ~ 5.825GHz 802.11n HT40: 5.190GHz ~ 5.230GHz / 5.755~ 5.795GHz 802.11ac VHT80: 5.210GHz / 5.775GHz <input type="checkbox"/> Others		
Device category	<input type="checkbox"/> Portable (<20cm separation) <input checked="" type="checkbox"/> Mobile (>20cm separation) <input type="checkbox"/> Others		
Exposure classification	<input type="checkbox"/> Occupational/Controlled exposure (S = 5mW/cm ²) <input checked="" type="checkbox"/> General Population/Uncontrolled exposure (S=1mW/cm ²)		
Antenna Specification	Dipole Antenna : GORTEC 2.4GHz: AN2450-1711WBO Antenna Gain : 2.73 dBi (Numeric gain: 1.87) AN2450-1712WGO Antenna Gain : 2.73 dBi (Numeric gain: 1.87) 5GHz: AN2450-1711WBO Antenna Gain : 4.30 dBi (Numeric gain: 2.69) AN2450-1712WGO Antenna Gain : 4.30 dBi (Numeric gain: 2.69) 2.4GHz: Directional gain = 2.73 dBi +10log (2) = 5.74 dBi (Numeric gain 3.75) 5GHz: Directional gain = 4.30 dBi +10log (2) = 7.31 dBi (Numeric gain 5.38)		
Maximum Average output power	IEEE 802.11b Mode: 22.31 dBm (170.216 mW) IEEE 802.11g Mode: 21.10 dBm (128.825 mW) IEEE 802.11n HT 20 Mode: 19.12 dBm (81.658 mW) IEEE 802.11n HT 40 Mode: 18.86 dBm (76.913 mW) IEEE 802.11a Mode: 24.05 dBm (254.097 mW) IEEE 802.11n HT 20 Mode: 22.11 dBm (162.555 mW) IEEE 802.11n HT 40 Mode: 18.28 dBm (67.298 mW) IEEE 802.11ac VHT80 Mode: 23.81 dBm (240.436 mW)		

<p>Maximum Tune up Power</p>	<p>IEEE 802.11b Mode: 22.50 dBm (177.828 mW) IEEE 802.11g Mode: 22.50 dBm (177.828 mW) IEEE 802.11n HT 20 Mode: 19.50 dBm (89.125 mW) IEEE 802.11n HT 40 Mode: 19.00 dBm (79.433 mW) IEEE 802.11a Mode: 24.50 dBm (281.838 mW) IEEE 802.11n HT 20 Mode: 22.50 dBm (177.828 mW) IEEE 802.11n HT 40 Mode: 18.50 dBm (70.795 mW) IEEE 802.11ac VHT80 Mode: 24.00 dBm (251.189 mW)</p>
<p>Evaluation applied</p>	<p><input checked="" type="checkbox"/> MPE Evaluation* <input type="checkbox"/> SAR Evaluation <input type="checkbox"/> N/A</p>

3. TEST RESULTS

No non-compliance noted.

Calculation

$$\text{Given } E = \frac{\sqrt{30 \times P \times G}}{d} \quad \& \quad S = \frac{E^2}{377}$$

Where E = Field strength in Volts / meter

P = Power in Watts

G = Numeric antenna gain

d = Distance in meters

S = Power density in milliwatts / square centimeter

Combining equations and re-arranging the terms to express the distance as a function of the remaining variables yields:

$$S = \frac{30 \times P \times G}{377d^2}$$

Changing to units of mW and cm, using:

$$P \text{ (mW)} = P \text{ (W)} / 1000 \text{ and}$$

$$d \text{ (cm)} = d \text{ (m)} / 100$$

Yields

$$S = \frac{30 \times (P/1000) \times G}{377 \times (d/100)^2} = 0.0796 \times \frac{P \times G}{d^2} \quad \text{Equation 1}$$

Where d = Distance in cm

P = Power in mW

G = Numeric antenna gain

S = Power density in mW / cm²

4. MAXIMUM PERMISSIBLE EXPOSURE

Substituting the MPE safe distance using $d = 20$ cm into Equation 1:

$$S = 0.000199 \times P \times G$$

Where $P =$ Power in mW

$G =$ Numeric antenna gain

$S =$ Power density in mW / cm²

IEEE 802.11b mode:

Ch.	Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm2)
6	2437	177.828	3.75	20	0.1327	1

IEEE 802.11g mode:

Ch.	Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm2)
6	2437	177.828	3.75	20	0.1327	1

IEEE 802.11n HT20 mode:

Ch.	Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm2)
6	2437	89.125	3.75	20	0.0665	1

IEEE 802.11n HT40 mode:

Ch.	Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm2)
6	2437	79.433	3.75	20	0.0593	1

IEEE 802.11a mode:

Ch.	Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm2)
36	5180	281.838	5.38	20	0.3017	1

IEEE 802.11a HT20 mode:

Ch.	Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm2)
44	5220	177.828	5.38	20	0.1904	1

IEEE 802.11a HT40 mode:

Ch.	Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm2)
46	5230	70.795	5.38	20	0.0758	1

IEEE 802.11ac VHT80 mode:

Ch.	Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm2)
42	5210	251.189	5.38	20	0.2689	1