

EXHIBIT C

PRODUCT SPECIFICATIONS

Name: Manual Type Smart Card Reader/Writer

Model: M-360M

Hitachi, Ltd.

Hitachi Maxell, Ltd.

Contents

	page
1. Outline -----	2
2. General Specifications -----	2
3. Composition -----	2
4. Interface -----	3
5. Device Dimensions -----	4

Specifications will be changed without notice for improvement of the product.

1. Outline


This product is a manual insertion/ejection smart card reader/writer(R/W) to organize smart card system with PC.

2. General Specifications

Name	Manual Type Smart Card Reader/Writer	
Model	M-360M	
Card insertion/ejection	manual insertion/manual ejection	
Applicable smart card	Smart card conforming to ISO7816 with "T=0" and "T=1" protocol. But, use it after you confirm conformity with a smart card to use, and this product. Note: No Vpp control. And maximum value for card warp 2.0mm.	
Applicable PC	DOS/V PC (IBM A/T compatible)	
Applicable OS	Windows95/98	
Interface	Serial interface (conforming RS-232C D-sub 9pin)	
Power supply	DC5V $\pm$ 5%, 110mA max. (Supplied from PC PS/2 port)	
Durability	Smart card insertion/ejection 100,000passes(number of insertion/ejection times, warranty for 6 months after supply)	
Outer dimensions	76mm(W) $\times$ 105mm(D) $\times$ 23mm(H) (cable is not included)	
Weight	about 160g (cable is included)	
Operating conditions	0 ~ 50	10 ~ 85%RH (No condensation)
Storage conditions	-10 ~ 60	10 ~ 90%RH (No condensation)

3. Composition

Following figure shows block diagram of R/W.



4. Interface

4.1 PC interface

Following table shows data transmission specification between PC and R/W.

Table. Data transmission specifications between PC-R/W

#	Item	Specifications
1	Transmission method	half duplex transmission method
2	Character format	ST + Data + P + SP ST : start bit 1 bit Data : data bit 8 bit P : parity bit 1 bit SP : stop bit 1 bit
3	Synchronous method	Asynchronous method(RS-232C,non-procedural)
4	Transfer rate	9600bps, 19200bps, 38400bps
5	Error detection	vertical parity(even number) horizontal parity(exclusive OR)
6	Bit detection	LSB first positive logic

Table. Pin assaign of RS-232C connector (D-sub 9pin)

Pin No.	Pin Name	Signal direction	
		R/W	PC
1			
2	RD	→	
3	SD	←	
4			
5	SG	-	
6	DR	→	
7			
8	CS	→	
9			


4.2 Smart card interface

Following table shows data transmission specification between R/W and smart card.


Table. Data transmission specifications between R/W-Smart card

#	Item	Specifications
1	Transmission method	half duplex transmission method
2	Character format	ST + Data + P + GT ST : start bit 1 bit Data: data bit 8 bit P : parity bit 1 bit GT : guard time variable
3	Synchronous method	Asynchronous method
4	Transfer rate	9600bps, 19200bps, 38400bps
5	Error detection	vertical parity LSB first: even number MSB first: odd number horizontal parity(exclusive OR)
6	Bit detection	LSB first positive logic or MSB first negative logic
7	Card power supply	5V ± 10%
8	Card supply clock	3.55MHz ± 3%, 7.10MHz ± 3%

5.Device Dimensions



unit: mm



FCC ID : NEE03		
Title	M-360M Circuit Diagram	
Size	Document Number	Rev
B		
Date:	Tuesday, May 23, 2000	Sheet 1 of 1