



TEST REPORT NO: RU1063/4785
COPY NO:
ISSUE NO: 1
FCC ID: NEO50-0606Series

**REPORT ON THE CERTIFICATION TESTING OF A
Aerial Facilities Limited
5 CHANNEL UHF Signal Enhancer
WITH RESPECT TO
THE FCC RULES CFR 47, PART 90 Subpart I
PRIVATE LAND MOBLIE REPEATER.**

TEST DATE: 1st August – 10th September 2003

TESTED BY: J CHARTERS
APPROVED BY: P GREEN
PRODUCT MANAGER
EMC
DATE:

Distribution:

- Copy Nos:
1. Aerial Facilities Limited
 2. TCB: TRL Compliance Services Limited
 3. TRL EMC

THIS DOCUMENT MAY BE REPRODUCED ONLY IN ITS ENTIRETY AND WITHOUT CHANGE



CONTENTS

	PAGE	
CERTIFICATE OF CONFORMITY & COMPLIANCE	3	
APPLICANT'S SUMMARY	4	
EQUIPMENT TEST CONDITIONS	5	
TESTS REQUIRED	5	
TEST RESULTS	6-65	
		ANNEX
PHOTOGRAPHS	A	
PHOTOGRAPH No. 1: Test setup		
PHOTOGRAPH No. 2: Test setup		
APPLICANT'S SUBMISSION OF DOCUMENTATION LIST	B	
 Notes:		
1. Component failure during test	YES	<input type="checkbox"/>
	NO	<input checked="" type="checkbox"/>
2. If Yes, details of failure:		
3. The facilities used for the testing of the product contain in this report are FCC Listed.		



CERTIFICATE OF CONFORMITY & COMPLIANCE

FCC IDENTITY: NEO50-0606Series
PURPOSE OF TEST: CERTIFICATION
TEST SPECIFICATION: FCC RULES CFR 47, Part 90 Subpart I
TEST RESULT: Compliant to Specification
EQUIPMENT UNDER TEST: 5 CHANNEL UHF Signal Enhancer
EQUIPMENT TYPE: Private Land Mobile Repeater
MAXIMUM GAIN: +98.03dBm
MAXIMUM INPUT: -77.0dBm
MAXIMUM OUTPUT: +23.0dBm
ANTENNA TYPE: Not applicable
CHANNEL SPACING: 12.5kHz

NUMBER OF CHANNELS:

Channel No.	Uplink	Downlink
1	453.300MHz	458.300MHz
2	453.600MHz	458.600MHz
3	453.500MHz	458.500MHz
4	453.200MHz	458.200MHz
5	453.750MHz	458.750MHz

FREQUENCY GENERATION: N/A
MODULATION TYPE: F3E
POWER SOURCE(s): 24Vdc
TEST DATE(s): 1st August – 10th September 2003
ORDER No(s): 19800
APPLICANT: Aerial Facilities Limited
ADDRESS: Aerial House
Latimer Park, Latimer
Chesham
Buckinghamshire
HP5 1TU
United Kingdom

TESTED BY: _____ J CHARTERS

APPROVED BY: _____ P GREEN
PRODUCT
MANAGER EMC

APPLICANT'S SUMMARY

EQUIPMENT UNDER TEST (EUT): 5 CHANNEL UHF Signal Enhancer

EQUIPMENT TYPE: 50-0606063

PURPOSE OF TEST: CERTIFICATION

TEST SPECIFICATION(s): FCC RULES CFR 47, Part 90 Subpart I

TEST RESULT: COMPLIANT Yes
No

APPLICANT'S CATEGORY: MANUFACTURER
IMPORTER
DISTRIBUTOR
TEST HOUSE
AGENT

APPLICANT'S ORDER No(s): 19801

APPLICANT'S CONTACT PERSON(s): Mr Peter Bradfield

E-mail address: Peterb@aerial.co.uk

APPLICANT: Aerial Facilities Limited

ADDRESS: Aerial House
Latimer Park, Latimer
Chesham
Buckinghamshire
HP5 1TU
United Kingdom

TEL: +44 (0)1494777020

FAX: +44 (0)149477020

MANUFACTURER: Aerial Facilities Limited

EUT(s) COUNTRY OF ORIGIN: United Kingdom

TEST LABORATORY: TRL EMC

UKAS ACCREDITATION No: 0728

TEST DATE(s) 1st August – 10th September 2003

TEST REPORT No: RU1063/4785

EQUIPMENT TEST / EXAMINATIONS REQUIRED

1.	TEST/EXAMINATION	RULE PART	APPLICABILITY	RESULT
	RF Power Output	90.205	Yes	Complies
	Audio Frequency Response	TIA EIA-603.3.2.6	N/A	N/A
	Audio Low-Pass Filter Response	TIA EIA-603.3.2.6	N/A	N/A
	Modulation Limiting	TIA EIA-603.3.2.6	N/A	N/A
	Occupied Bandwidth	90.210	Yes	Complies
	Spurious Emissions at Antenna Terminals	90.210	Yes	Complies
	Field Strength of Spurious Emissions	90.210	Yes	Complies
	Frequency Stability	90.213	N/A(note 1)	N/A
	Transient behaviour	90.214	N/A(note 2)	N/A

Notes:

1 The EUT does not contain modulation circuitry, therefore the test was not performed.

2 The EUT is not a keyed carrier system, therefore the test was not performed.


- | | | | |
|--|--|----------------------------------|---|
| 2. | Product Use: | Private Land Mobile Repeater | |
| 3. | Emission Designator: | F3E | |
| 4. | Temperatures: | Ambient (Tnom) | 24°C |
| 5. | Supply Voltages: | Vnom | 24Vac |
| Note: Vnom voltages are as stated above unless otherwise shown on the test report page | | | |
| 6. | Equipment Category: | Single channel | <input type="checkbox"/> |
| | | Two channel | <input type="checkbox"/> |
| | | Multi-channel | <input checked="" type="checkbox"/> |
| 7. | Channel spacing: | Narrowband | <input checked="" type="checkbox"/> 12.5kHz |
| | | Wideband | <input type="checkbox"/> |
| 8. | Test Location | TRL Compliance Services | |
| | | Up Holland | <input checked="" type="checkbox"/> |
| | | Long Green | <input type="checkbox"/> |
| 9. | Modifications made during test program | No modifications were performed. | |

COMPLIANCE TESTS

AMPLIFIER GAIN – CONDUCTED – PART 2.1046 – UPLINK

Ambient temperature = 27°C
 Relative humidity = 45%
 Supply voltage = 24Vdc
 Channel number = See test results

Radio Laboratory



Frequency MHz	Signal Generator input level dBm	Cable & Attenuator loss dB	Level at Spectrum Analyser dBm	Gain dB	Gain after 20dB input level increase dBm
453.20	-73.4	26.72	-3.5	96.66	96.66
453.50	-73.4	26.72	-3.5	96.66	96.66
453.75	-73.4	26.72	-3.4	96.75	96.75

Notes:


1. The level of the signal generator takes into consideration the loss from the cable.
2. The signal generator input was increased by 20dBs and the level of the output signal remeasured

TYPE OF EQUIPMENT	MAKER/SUPPLIER	MODEL No	SERIAL No	TRL No	ACTUAL EQUIPMENT USED
SPECTRUM ANALYSER	ANRITSU	MS2665C	MT26089	479	X
ATTENUATOR	BIRD	8304-300-N	N/A	220	X
CABLE	ROSENBERGER	MICRO COAX	N/A	279	X
SIGNAL GENERATOR	MARCON	2042	119388/080	179	X

AMPLIFIER INTERMODULATION SPURIOUS EMISSIONS – CONDUCTED – PART 2.1053– UPLINK

Ambient temperature = 27°C
 Relative humidity = 45%
 Supply voltage = 24Vdc


Radio Laboratory



The Intermodulation and spurious products were measured with the amplifier operating at maximum gain. A three tone test was conducted using the equipment as above. The input power level was adjusted so the level at point D was the maximum input of -73.4dBm. The cable and attenuator loss between the EUT and the spectrum analyser was 26.7 dB.


Sweep data is shown on the next page:

Intermodulation Inband



The above plot shows that all products (designated by ☆) are at least 40dB below the fundamentals.

Intermodulation Wideband



The above plot shows that there are no products outside the bands.

Test equipment used for intermodulation test


TYPE OF EQUIPMENT	MAKER/SUPPLIER	MODEL No	SERIAL No	TRL No	ACTUAL EQUIPMENT USED
SPECTRUM ANALYSER	ANRITSU	MS2665C	MT26089	479	X
SIGNAL GENERATOR	MARCON	2042	119562/02	254	X
CMTA	ROHDE & SCHWARZ	CMTA52	894715/033	05	X
SIGNAL GENERATOR	MARCON	2042	119388/080	179	X
COMBINER	ELCOM	RC-4-50	N/A	170	X

TRANSMITTER TESTS

AMPLIFIER MODULATED CHANNEL TEST – CONDUCTED – Part 2.1049– UPLINK

Ambient temperature = 24°C
Relative humidity = 46%
Supply voltage = 24Vdc
Channel number = See test results

Radio Laboratory




This test was performed to show that the amplifier does not alter the input signal in any way. The input signal was set to the maximum input level (-73.4dBm) and modulated with a 2500Hz tone. The plots show the signal measured at the signal generator and the signal measured at the output of the EUT.


Note: The cables and attenuators had the following losses.

1. Cable TRL279 and attenuator TRL220 26.7dB
2. Cable between signal generator and EUT 0.4dB

453.2MHz Signal Generator deviation set to 5kHz




453.2MHz Signal Generator and EUT deviation set to 5kHz




The above plots depicting the output waveshape show no measurable distortion visible. When compared to the input signal.

453.5MHz Signal Generator deviation set to 5kHz




453.5MHz Signal Generator and amplifier deviation set to 5kHz




The above plots depicting the output waveshape show no measurable distortion visible. When compared to the input signal.

453.75MHz Signal Generator deviation set to 5kHz



453.75MHz Signal Generator deviation set to 5kHz



The above plots depicting the output waveshape show no measurable distortion visible. When compared to the input signal.


The test equipment used for the Transmitter Modulated Channel tests is shown overleaf:

TYPE OF EQUIPMENT	MAKER/SUPPLIER	MODEL No	SERIAL No	TRL No	ACTUAL EQUIPMENT USED
SPECTRUM ANALYSER	ANRITSU	MS2665C	MT26089	479	X
ATTENUATOR	BIRD	8304-300-N	N/A	220	X
CABLE	ROSENBERGER	MICRO COAX	N/A	279	X
SIGNAL GENERATOR	MARCON	2042	119388/080	179	X

TRANSMITTER TESTS

AMPLIFIER SPURIOUS EMISSIONS – CONDUCTED – Part 2.1051– UPLINK

Ambient temperature = 24°C
 Relative humidity = 46%
 Supply voltage = 24Vdc
 Radio Laboratory Test Signal = F3E



The test was set up as per the diagram. The level at the input was adjusted to compensate for the loss of the interconnecting cable. The unit was tested operating at maximum power and on three test frequencies.

The Spurious limit was calculated as follows:

On any frequency removed from the assigned frequency by more that 250% of the authorised bandwidth


At least 43 + 10 log PdB

$$(10\log P_{\text{watts}}) - (43 + 10\log (P_{\text{watts}} * 1000)) = \text{LIMIT } = -13 \text{ dBm}$$


The test equipment used for the Transmitter Conducted Emissions:

TYPE OF EQUIPMENT	MAKER/SUPPLIER	MODEL No	SERIAL No	TRL No	ACTUAL EQUIPMENT USED
SPECTRUM ANALYSER	ANRITSU	MS2665C	MT26089	479	X
ATTENUATOR	BIRD	8304-300-N	N/A	220	X
CABLE	ROSENBERGER	MICRO COAX	N/A	279	X
SIGNAL GENERATOR	MARCON	2042	119388/080	179	X

Conducted emissions 453.2MHz 0 - 3GHz



Conducted emissions 453.5MHz 0 - 3GHz



Conducted emissions 453.75MHz 0 - 3GHz

MKR: 464MHz

-2.85dBm

RB 1MHz#


AT 10dB#

Band auto

RLV: 0.00dBm

VB 1MHz#


ST 50ms



ST:30MHz

SP:3.000GHz

Conducted emissions 453.75MHz 2.9 - 6GHz




TRANSMITTER TESTS

AMPLIFIER SPURIOUS EMISSIONS – RADIATED – Part 2.1053– UPLINK

Ambient temperature = 25°C
Relative humidity = 50%
Conditions = OATS
Supply voltage = 24Vdc
Supply Frequency = N/A

Test Signal = F3E



The test was set up as per the diagram. The level at the input was adjusted to compensate for the loss of the interconnecting cable. The unit was tested operating maximum power on three test frequencies with a 50 ohm load on the output. The unit was also tested with the signal generator replaced by another 50ohm load.


The Spurious limit was calculated as follows:

On any frequency removed from the assigned frequency by more that 250% of the authorised bandwidth

At least $43 + 10 \log P_{dB}$


$$(10\log P_{\text{watts}}) - (43 + 10\log (P_{\text{watts}} * 1000)) = \text{LIMIT} = -13 \text{ dBm}$$

Radiated emissions 453.2MHz 0-3GHz




The above test results show that there were no emissions within 20dBs of the -13dBm limit.

Radiated emissions 453.5MHz 0-3GHz




The above test results show that there were no emissions within 20dBs of the -13dBm limit.

Radiated emissions 453.75MHz 0-3GHz



The above test results show that there were no emissions within 20dBs of the -13dBm limit.

Radiated emissions no input signal 0-3GHz



The above test results show that there were no emissions within 20dBs of the -13dBm limit.


The test equipment used for the Transmitter Spurious Emissions:

TYPE OF EQUIPMENT	MAKER/SUPPLIER	MODEL No	SERIAL No	TRL No	ACTUAL EQUIPMENT USED
SPECTRUM ANALYSER	ANRITSU	MS2665C	MT26089	479	X
HORN	EMCO	3115	9010-3581	139	X
ATTENUATOR	BIRD	8304-300-N	N/A	220	X
CABLE	ROSENBERGER	MICRO COAX	N/A	279	X
SIGNAL GENERATOR	MARCON	2042	119388/080	179	X

AMPLIFIER GAIN – CONDUCTED – PART 2.1046 – DOWNLINK

Ambient temperature = 24°C
 Relative humidity = 43%
 Supply voltage = 24Vdc
 Channel number = See test results

Radio Laboratory



Frequency MHz	Signal Generator input level dBm	Cable & Attenuator loss dB	Level at Spectrum Analyser dBm	Gain dB	Gain after 20dB input level increase dBm
458.2	-77.0	26.5	-5.87	97.63	97.63
458.5	-77.0	26.5	-5.49	98.01	98.01
458.75	-77.0	26.5	-5.54	98.25	98.25

Notes:


1. The level of the signal generator takes into consideration the loss from the cable.
2. The signal generator input was increased by 20dBs and the level of the output signal remeasured

TYPE OF EQUIPMENT	MAKER/SUPPLIER	MODEL No	SERIAL No	TRL No	ACTUAL EQUIPMENT USED
SPECTRUM ANALYSER	ANRITSU	MS2665C	MT26089	479	X
ATTENUATOR	BIRD	8304-200	N/A	103	X
ATTENUATOR	BIRD	8304-300-N	N/A	220	X
CABLE	ROSENBERGER	MICRO COAX	N/A	279	X
SIGNAL GENERATOR	MARCON	2042	119388/080	179	X

AMPLIFIER INTERMODULATION SPURIOUS EMISSIONS – CONDUCTED – PART 2.1053– DOWNLINK

Ambient temperature = 26°C
 Relative humidity = 40%
 Supply voltage = 24Vdc


Radio Laboratory



The Intermodulation and spurious products were measured with the amplifier operating at maximum gain. A three tone test was conducted using the equipment as above. The input power level was adjusted so the level at point D was the maximum input of -77.0dBm. The cable and attenuators loss between the EUT and the spectrum analyser was 26.5 dB.


Sweep data is shown on the next page:

Intermodulation Inband



The above plot shows that all products (designated by ☆) are at least 50dB below the fundamentals.

Intermodulation Wideband



The above plot shows that there are no products outside the bands.

Test equipment used for intermodulation test


TYPE OF EQUIPMENT	MAKER/SUPPLIER	MODEL No	SERIAL No	TRL No	ACTUAL EQUIPMENT USED
SPECTRUM ANALYSER	ANRITSU	MS2665C	MT26089	479	X
SIGNAL GENERATOR	MARCON	2042	119562/02	254	X
CMTA	ROHDE & SCHWARZ	CMTA52	894715/033	05	X
SIGNAL GENERATOR	MARCON	2042	119388/080	179	X
COMBINER	ELCOM	RC-4-50	N/A	170	x

TRANSMITTER TESTS

AMPLIFIER MODULATED CHANNEL TEST – CONDUCTED – Part 2.1049– DOWNLINK

Ambient temperature = 24°C
Relative humidity = 43%
Supply voltage = 24Vdc
Channel number = See test results

Radio Laboratory




This test was performed to show that the amplifier does not alter the input signal in any way. The input signal was set to the maximum input level (-77.0dBm) and modulated with a 2500Hz tone. The plots show the signal measured at the signal generator and the signal measured at the output of the EUT.


Note: The cables and attenuators had the following losses.

1. Cable TRL279 and attenuators TRL220 = 26.5dB
2. Cable between signal generator and EUT = 0.4dB

458.2MHz Signal Generator deviation set to 5kHz




458.2MHz Signal Generator and EUT deviation set to 5kHz




The above plots depicting the output waveshape show no measurable distortion visible. When compared to the input signal.

458.5MHz Signal Generator deviation set to 5kHz




458.5MHz Signal Generator and amplifier deviation set to 5kHz




The above plots depicting the output waveshape show no measurable distortion visible. When compared to the input signal.

458.75MHz Signal Generator deviation set to 5kHz



458.75MHz Signal Generator deviation set to 5kHz



The above plots depicting the output waveshape show no measurable distortion visible. When compared to the input signal.

The test equipment used for the Transmitter modulated channel tests is shown overleaf:


TYPE OF EQUIPMENT	MAKER/SUPPLIER	MODEL No	SERIAL No	TRL No	ACTUAL EQUIPMENT USED
SPECTRUM ANALYSER	ANRITSU	MS2665C	MT26089	479	X
ATTENUATOR	BIRD	8304-200	N/A	103	
ATTENUATOR	BIRD	8304-300-N	N/A	220	X
CABLE	ROSENBERGER	MICRO COAX	N/A	279	X
SIGNAL GENERATOR	MARCON	2042	119388/080	179	X

TRANSMITTER TESTS

AMPLIFIER SPURIOUS EMISSIONS – CONDUCTED – Part 2.1051– DOWNLINK

Ambient temperature = 24°C
 Relative humidity = 43%
 Supply voltage = 24Vdc

Radio Laboratory Test Signal = F3E



The test was set up as per the diagram. The level at the input was adjusted to compensate for the loss of the interconnecting cable. The unit was tested operating at maximum power and on three test frequencies.

The Spurious limit was calculated as follows:

On any frequency removed from the assigned frequency by more that 250% of the authorised bandwidth


At least 43 + 10 log PdB

$$(10\log P_{\text{watts}}) - (43+10\log (P_{\text{watts}} * 1000)) = \text{LIMIT} = -13 \text{ dBm}$$


The test equipment used for the Transmitter Conducted Emissions:

TYPE OF EQUIPMENT	MAKER/ SUPPLIER	MODEL No	SERIAL No	TRL No	ACTUAL EQUIPMENT USED
SPECTRUM ANALYSER	ANRITSU	MS2665C	MT26089	479	X
ATTENUATOR	BIRD	8304-200	N/A	103	
ATTENUATOR	BIRD	8304-300-N	N/A	220	X
CABLE	ROSENBERGER	MICRO COAX	N/A	279	X
SIGNAL GENERATOR	MARCON	2042	119388/080	179	X


Conducted emissions 458.2MHz 0-3GHz




Conducted emissions 458.2MHz 2.9-10GHz




Conducted emissions 458.5MHz 0-3GHz



Conducted emissions 458.5MHz 2.9-10GHz



Conducted emissions 458.75MHz 0-3GHz




TRANSMITTER TESTS

AMPLIFIER SPURIOUS EMISSIONS – RADIATED – Part 2.1053– DOWNLINK

Ambient temperature = 24°C
Relative humidity = 43%
Conditions = OATS
Supply voltage = 24Vdc
Supply Frequency = N/A

Test Signal = F3E



The test was set up as per the diagram. The level at the input was adjusted to compensate for the loss of the interconnecting cable. The unit was tested operating maximum power on three test frequencies with a 50 ohm load on the output. The unit was also tested with the signal generator replaced by another 50ohm load.


The Spurious limit was calculated as follows:

On any frequency removed from the assigned frequency by more that 250% of the authorised bandwidth

At least $43 + 10 \log P_{dB}$


$$(10\log P_{watts}) - (43 + 10\log (P_{watts} * 1000)) = \text{LIMIT } = -13 \text{ dBm}$$

Radiated emissions 458.2MHz 0-3GHz




The above test results show that there were no emissions within 20dBs of the -13dBm limit.

Radiated emissions 458.2MHz 2.9-10GHz




The above test results show that there were no emissions within 20dBs of the -13dBm limit.

Radiated emissions 458.5MHz 0-3GHz




The above test results show that there were no emissions within 20dBs of the -13dBm limit.

Radiated emissions 458.75MHz 0-3GHz




The above test results show that there were no emissions within 20dBs of the -13dBm limit.

Radiated emissions no input signal 0-3GHz



The above test results show that there were no emissions within 20dBs of the -13dBm limit.

Radiated emissions no input signal 2.9-10GHz




The above test results show that there were no emissions within 20dBs of the -13dBm limit.

The test equipment used for the Transmitter Spurious Emissions:

TYPE OF EQUIPMENT	MAKER/SUPPLIER	MODEL No	SERIAL No	TRL No	ACTUAL EQUIPMENT USED
SPECTRUM ANALYSER	ANRITSU	MS2665C	MT26089	479	X
HORN	EMCO	3115	9010-3581	139	X
ATTENUATOR	BIRD	8304-300-N	N/A	220	X
ATTENUATOR	BIRD	8308-100	N/A	112	X
CABLE	ROSENBERGER	MICRO COAX	N/A	279	X
SIGNAL GENERATOR	MARCON	2042	119388/080	179	X

ANNEX A
PHOTOGRAPHS





ANNEX B
APPLICANT'S SUBMISSION OF DOCUMENTATION LIST

APPLICANT'S SUBMISSION OF DOCUMENTATION LIST

a.	TCB	-	APPLICATION	<input checked="" type="checkbox"/>
		-	FEE	<input checked="" type="checkbox"/>
b.	AGENT'S LETTER OF AUTHORISATION	-		<input checked="" type="checkbox"/>
c.	MODEL(s) vs IDENTITY	-		<input type="checkbox"/>
d.	ALTERNATIVE TRADE NAME DECLARATION(s)	-		<input type="checkbox"/>
e.	LABELLING	-	PHOTOGRAPHS	<input type="checkbox"/>
		-	DECLARATION	<input type="checkbox"/>
		-	DRAWINGS	<input type="checkbox"/>
f.	TECHNICAL DESCRIPTION	-		<input checked="" type="checkbox"/>
g.	BLOCK DIAGRAMS	-	Tx	<input checked="" type="checkbox"/>
		-	Rx	<input type="checkbox"/>
		-	PSU	<input type="checkbox"/>
		-	AUX	<input type="checkbox"/>
h.	CIRCUIT DIAGRAMS	-	Tx	<input type="checkbox"/>
		-	Rx	<input type="checkbox"/>
		-	PSU	<input type="checkbox"/>
		-	AUX	<input type="checkbox"/>
i.	COMPONENT LOCATION	-	Tx	<input type="checkbox"/>
		-	Rx	<input type="checkbox"/>
		-	PSU	<input type="checkbox"/>
		-	AUX	<input type="checkbox"/>
j.	PCB TRACK LAYOUT	-	Tx	<input type="checkbox"/>
		-	Rx	<input type="checkbox"/>
		-	PSU	<input type="checkbox"/>
		-	AUX	<input type="checkbox"/>
k.	BILL OF MATERIALS	-	Tx	<input type="checkbox"/>
		-	Rx	<input type="checkbox"/>
		-	PSU	<input type="checkbox"/>
		-	AUX	<input type="checkbox"/>
l.	USER INSTALLATION / OPERATING INSTRUCTIONS	-		<input checked="" type="checkbox"/>