



TEST REPORT NO: RU1193/6623
COPY NO: .1.....
ISSUE NO: 1
FCC ID: NEO55-1547VHF

**REPORT ON THE CERTIFICATION TESTING OF A
AERIAL FACILITIES LIMITED
OFF AIR BI-DIRECTION AMPLIFIER SYSTEM (VHF)
WITH RESPECT TO
THE FCC RULES CFR 47, PART 90 Subpart I
PRIVATE LAND MOBILE REPEATER.**

TEST DATE: 22nd August 2005 – 25th August 2005

TESTED BY: J CHARTERS
APPROVED BY: P GREEN
PRODUCT MANAGER
EMC
DATE: 11th November 2005

Distribution:

- Copy Nos:
1. Aerial Facilities Limited
 2. TCB: TRL Compliance Limited
 3. TRL EMC

THIS DOCUMENT MAY BE REPRODUCED ONLY IN ITS ENTIRETY AND WITHOUT CHANGE



CONTENTS

	PAGE	
CERTIFICATE OF CONFORMITY & COMPLIANCE	3	
APPLICANT'S SUMMARY	4	
EQUIPMENT TEST CONDITIONS	5	
TESTS REQUIRED	5	
TEST RESULTS	6-48	
		ANNEX
PHOTOGRAPHS	A	
PHOTOGRAPH No. 1: Test setup		
PHOTOGRAPH No. 2: Test setup		
APPLICANT'S SUBMISSION OF DOCUMENTATION LIST	B	
EQUIPMENT CALIBRATION	C	
Notes:		
1. Component failure during test	YES	<input type="checkbox"/>
	NO	<input checked="" type="checkbox"/>
2. If Yes, details of failure:		
3. The facilities used for the testing of the product contain in this report are FCC Listed.		



CERTIFICATE OF CONFORMITY & COMPLIANCE

FCC IDENTITY: NEO55-1547VHF

PURPOSE OF TEST: Certification

TEST SPECIFICATION: FCC RULES CFR 47, Part 90 Subpart I

TEST RESULT: Compliant to Specification

EQUIPMENT UNDER TEST: OFF AIR BI-DIRECTION AMPLIFIER SYSTEM (VHF)

EQUIPMENT TYPE: Private Land Mobile Repeater

MAXIMUM GAIN: Uplink 109.94dB
Downlink 96.24dB

MAXIMUM INPUT: Uplink -82 dBm
Downlink -64 dBm

MAXIMUM OUTPUT: Uplink 27.94dBm
Downlink 32.24dBm

ANTENNA TYPE: Not applicable

CHANNEL SPACING: 15kHz

NUMBER OF CHANNELS: Uplink 11
Downlink 11

FREQUENCY GENERATION: N/A

MODULATION TYPE: F3E

POWER SOURCE(s): +110Vac

TEST DATE(s): 22nd August 2005 – 25th August 2005

ORDER No(s): 32001

APPLICANT: Aerial Facilities Limited

ADDRESS: Aerial House
Asheridge Road
Chesham
Buckinghamshire
HP5 1TU
United Kingdom

TESTED BY: ----- J CHARTERS

APPROVED BY: ----- P GREEN
PRODUCT
MANAGER EMC

EQUIPMENT TEST / EXAMINATIONS REQUIRED

1.	TEST/EXAMINATION	RULE PART	APPLICABILITY	RESULT
	RF Power Output	90.205	Yes	Complies
	Audio Frequency Response	TIA EIA-603.3.2.6	N/A	N/A
	Audio Low-Pass Filter Response	TIA EIA-603.3.2.6	N/A	N/A
	Modulation Limiting	TIA EIA-603.3.2.6	N/A	N/A
	Occupied Bandwidth	90.210	Yes	Complies
	Spurious Emissions at Antenna Terminals	90.210	Yes	Complies
	Field Strength of Spurious Emissions	90.210	Yes	Complies
	Frequency Stability	90.213	N/A(note 1)	N/A
	Transient behaviour	90.214	N/A(note 2)	N/A

Notes:

1 The EUT does not contain modulation circuitry, therefore the test was not performed.

2 The EUT is not a keyed carrier system, therefore the test was not performed.


2. Product Use: Private Land Mobile Repeater
3. Emission Designator: F3E
4. Temperatures: Ambient (Tnom) 21°C
5. Supply Voltages: Vnom +110Vac
- Note: Vnom voltages are as stated above unless otherwise shown on the test report page
6. Equipment Category: Single channel
 Two channel
 Multi-channel
7. Channel spacing: Narrowband 15kHz
 Wideband
8. Test Location TRL Compliance Limited
 Up Holland
 Long Green
9. Modifications made during test program No modifications were performed.

COMPLIANCE TESTS

AMPLIFIER GAIN – CONDUCTED – PART 2.1046 – UPLINK

Ambient temperature = 26°C
 Relative humidity = 54%
 Supply voltage = +110Vac
 Channel number = See test results

Radio Laboratory



Frequency MHz	Signal Generator input level dBm	Cable & Attenuator loss dB	Level at Spectrum Analyser dBm	Gain dB	Gain after 10dB input level increase dBm
153.785 MHz	-80	27.36	-9.68	98.68	90.37
155.280 MHz	-77	27.36	-2.84	102.52	92.85
158.865 MHz	-75	27.36	-4.94	98.58	88.72
159.210 MHz	-80	27.36	-1.78	106.58	97.06
161.520 MHz	-82	27.36	-0.42	109.94	100.48

Notes:


- The signal generator input was increased by 20dBs and the level of the output signal remeasured.
- Antenna Port input split into 2 channelised amplifiers.

TYPE OF EQUIPMENT	MAKER/SUPPLIER	MODEL No	SERIAL No	TRL No	ACTUAL EQUIPMENT USED
SPECTRUM ANALYSER	ANRITSU	MS2665C	MT26089	479	X
ATTENUATOR	BIRD	8304-300-N	N/A	220	X
CABLE	ROSENBERGER	MICRO COAX	N/A	280	X
SIGNAL GENERATOR	MARCONI	2042	119388/080	176	X

AMPLIFIER INTERMODULATION SPURIOUS EMISSIONS – CONDUCTED – PART 2.1053– UPLINK

Ambient temperature = 26°C
 Relative humidity = 53%
 Supply voltage = +110Vac

Radio Laboratory




The Intermodulation and spurious products were measured with the amplifier operating at maximum gain. A three tone test was conducted using the equipment as above. The input power level was adjusted so the level at point D was 10dB above the maximum input of -75dBm. The cable and attenuator loss between the EUT and the spectrum analyser was 26.89dB. The Uplink input is split into two frequency ranges, 153.75-155.3MHz and 159-161MHz. This test was performed with 3 carriers on the frequencies listed in the table below. Sweep data is shown on the next pages for scan with the highest intermodulation product.

RF Input Frequency (MHz)			Highest Intermodulation Product Level (dBm)	Limit (dBm)
153.785	155.280	154.325	No intermodulation products within 20 dBs of the limit	-13
159.210	159.090	158.865	No intermodulation products within 20 dBs of the limit	-13
153.785	161.520	154.680	No intermodulation products within 20 dBs of the limit	-13

Test equipment used for intermodulation test


TYPE OF EQUIPMENT	MAKER/SUPPLIER	MODEL No	SERIAL No	TRL No	ACTUAL EQUIPMENT USED
SPECTRUM ANALYSER	ANRITSU	MS2665C	MT26089	479	X
SIGNAL GENERATOR	MARCONI	2042	119388/080	176	X
SIGNAL GENERATOR	MARCONI	2023	112224/040	UH105	X
SIGNAL GENERATOR	MARCONI	2022D	119224/035	UH89	X
COMBINER	ELCOM	RC-4-50	N/A	170	X

All Channels on no RF inputs




Scan plot showing amplifiers channels

Intermodulation Inband



The above plot shows that all products (designated by ☆) are at least 20dB below the spurious limit.

Intermodulation Wideband




The above plot shows that there are no products outside the bands.

TRANSMITTER TESTS

AMPLIFIER MODULATED CHANNEL TEST – CONDUCTED – Part 2.1049– UPLINK

Ambient temperature = 26°C Radio Laboratory
 Relative humidity = 53%
 Supply voltage = +110Vac
 Channel number = See test results



This test was performed to show that the amplifier does not alter the input signal in any way. The input signal was set to the maximum input level (-75dBm) and modulated with a 2500Hz tone. The plots show the signal measured at the signal generator without any attenuators in line and the signal measured at the output of the EUT.


Note: The cables and attenuators had the following losses.

1. Cable and attenuators between EUT and spectrum analyser 26.89dB
2. Cable between signal generator and EUT 0.47dB


Cable and attenuator between EUT and spectrum analyser removed to show signal measured at the signal generator.

TYPE OF EQUIPMENT	MAKER/SUPPLIER	MODEL No	SERIAL No	TRL No	ACTUAL EQUIPMENT USED
SPECTRUM ANALYSER	ANRITSU	MS2665C	MT26089	479	X
ATTENUATOR	BIRD	8304-300-N	N/A	220	X
ATTENUATOR	BIRD	8308-100	N/A	112	X
CABLE	ROSENBERGER	MICRO COAX	N/A	280	X
SIGNAL GENERATOR	MARCONI	2042	119388/080	176	X

153.785 MHz Signal Generator deviation set to 2.5kHz




153.785 MHz Signal Generator and EUT deviation set to 2.5kHz




The above plots depicting the output waveshape show no measurable distortion visible when compared to the input signal.

155.280 MHz Signal Generator deviation set to 2.5kHz




155.280 MHz Signal Generator and EUT deviation set to 2.5kHz




The above plots depicting the output waveshape show no measurable distortion visible when compared to the input signal.

158.865 MHz Signal Generator deviation set to 2.5kHz




158.865 MHz Signal Generator and EUT deviation set to 2.5kHz




The above plots depicting the output waveshape show no measurable distortion visible when compared to the input signal.

159.210 MHz Signal Generator deviation set to 2.5kHz




159.210 MHz Signal Generator and EUT deviation set to 2.5kHz




The above plots depicting the output waveshape show no measurable distortion visible when compared to the input signal.

161.520 MHz Signal Generator deviation set to 2.5kHz



161.520 MHz Signal Generator and EUT deviation set to 2.5kHz




The above plots depicting the output waveshape show no measurable distortion visible when compared to the input signal.

TRANSMITTER TESTS

AMPLIFIER SPURIOUS EMISSIONS – CONDUCTED – Part 2.10 – UPLINK

Ambient temperature = 26°C
 Relative humidity = 53%
 Supply voltage = +110Vac

Radio Laboratory
 Test Signal = F3E



The test was set up as per the diagram. The level at the input was adjusted to compensate for the loss of the interconnecting cable. The unit was tested operating at maximum power and on five test frequencies.

The Spurious limit was calculated as follows:

On any frequency removed from the assigned frequency by more than 250% of the authorised bandwidth

At least $43 + 10 \log P_{dB}$

$$(10 \log P_{\text{watts}}) - (43 + 10 \log (P_{\text{watts}} * 1000)) = \text{LIMIT} = -13 \text{ dBm}$$


RESULTS

FREQUENCY RANGE	FREQ. (MHz)	MEASURED LEVEL (dBm)	ATTENUATOR & CABLE LOSSES (dB)	EMISSION LEVEL (dBm)	LIMIT (dBm)
0 Hz - 2GHz	No Significant emissions within 20 dB's of the limit				-13


The test equipment used for the Transmitter Conducted Emissions:

TYPE OF EQUIPMENT	MAKER/SUPPLIER	MODEL No	SERIAL No	TRL No	ACTUAL EQUIPMENT USED
SPECTRUM ANALYSER	ANRITSU	MS2665C	MT26089	479	X
ATTENUATOR	BIRD	8304-300-N	N/A	220	X
CABLE	ROSENBERGER	MICRO COAX	N/A	280	X
ATTENUATOR	BIRD	8308-100	N/A	112	X
SIGNAL GENERATOR	MARCONI	2042	119388/080	176	X


Conducted emissions 153.785 MHz 0 – 1GHz




Conducted emissions 153.785 MHz 1 – 2GHz




Conducted emissions 155.280 MHz 0 – 1GHz




Conducted emissions 155.280 MHz 1 – 2GHz




Conducted emissions 158.865 MHz 0 – 1GHz




Conducted emissions 158.865 MHz 1 – 2GHz



Conducted emissions 161.520 MHz 0 – 1GHz



Conducted emissions 161.520 MHz 1 – 2GHz




TRANSMITTER TESTS

AMPLIFIER SPURIOUS EMISSIONS – RADIATED – Part 2.1053– UPLINK

Ambient temperature = 20°C
 Relative humidity = 80%
 Conditions = OATS
 Supply voltage = +110Vac
 Supply Frequency = N/A

Test Signal = F3E



The test was set up as per the diagram. The level at the input was adjusted to compensate for the loss of the interconnecting cable. The unit was tested operating maximum power on three test frequencies with a 50 ohm load on the output.

The Spurious limit was calculated as follows:

On any frequency removed from the assigned frequency by more that 250% of the authorised bandwidth

At least 43 + 10 log PdB

$$(10\log P_{\text{watts}}) - (43+10\log (P_{\text{watts}} * 1000)) = \text{LIMIT} = -13 \text{ dBm}$$


RESULTS

FREQUENCY RANGE	FREQ. (MHz)	MEAS. Rx. (dBµV)	CABLE LOSS (dB)	ANT FACTOR	FIELD STRENGTH (dBµV/m)	CALCULATED EIRP (dBm)	LIMIT (dBm)
0 Hz - 2GHz	No Significant emissions within 20 dB's of the limit						-13


The test equipment used for the Transmitter Spurious Emissions:

TYPE OF EQUIPMENT	MAKER/SUPPLIER	MODEL No	SERIAL No	TRL No	ACTUAL EQUIPMENT USED
SPECTRUM ANALYSER	ANRITSU	MS2665C	MT26089	479	X
HORN	EMCO	3115	9010-3581	139	X
ATTENUATOR	BIRD	8304-300-N	N/A	220	X
CABLE	ROSENBERGER	MICRO COAX	N/A	280	X
SIGNAL GENERATOR	MARCONI	2042	119388/080	176	X


Radiated emissions 153.785 MHz 0 – 1GHz




Radiated emissions 153.785 MHz 1 – 2GHz




Radiated emissions 158.865 MHz 0 – 1GHz




Radiated emissions 158.865 MHz 1 – 2GHz



Radiated emissions 161.520 MHz 0 – 1GHz




Radiated emissions 161.520 MHz 1 – 2GHz



AMPLIFIER GAIN – CONDUCTED – PART 2.1046 – DOWNLINK

Ambient temperature = 21°C
 Relative humidity = 50%
 Supply voltage = +110Vac
 Channel number = See test results

Radio Laboratory



Frequency MHz	Signal Generator input level dBm	Cable & Attenuator loss dB	Level at Spectrum Analyser dBm	Gain dB	Gain after 10dB input level increase dBm
153.785 MHz	-74	37.18	-24.59	86.59	77.47
154.325 MHz	-78	37.18	-22.40	92.78	85.10
155.280 MHz	-80	37.18	-21.77	95.41	86.77
159.090 MHz	-75	37.18	-20.59	91.59	83.07
160.830 MHz	-64	37.18	-4.94	96.24	86.48

Notes:


1. The signal generator input was increased by 10dBs and the level of the output signal remeasured.
2. Antenna Port input split into 3 channelised amplifiers

TYPE OF EQUIPMENT	MAKER/SUPPLIER	MODEL No	SERIAL No	TRL No	ACTUAL EQUIPMENT USED
SPECTRUM ANALYSER	ANRITSU	MS2665C	MT26089	479	X
ATTENUATOR	BIRD	8308-100	N/A	112	X
ATTENUATOR	BIRD	8304-300-N	N/A	220	X
CABLE	ROSENBERGER	MICRO COAX	N/A	280	X
SIGNAL GENERATOR	MARCONI	2042	119388/080	176	X

AMPLIFIER INTERMODULATION SPURIOUS EMISSIONS – CONDUCTED – PART 2.1053– DOWNLINK

Ambient temperature = 23°C
 Relative humidity = 46%
 Supply voltage = +110Vac

Radio Laboratory




The Intermodulation and spurious products were measured with the amplifier operating at maximum gain. A three tone test was conducted using the equipment as above. The input power level was adjusted so the level at point D was 10dB above the maximum input of -64dBm. The cable and attenuator loss between the EUT and the spectrum analyser was 36.71dB. The downlink input is split into three frequency ranges, 153.75 – 155.3MHz containing 5 channels, 158.85 – 159.3MHz containing 3 channels and 161.5-162MHz containing 1 channel. This test was performed with 3 carriers on the frequencies listed in table below. Sweep data is shown on the next pages for scan with the highest intermodulation product.

RF Input Frequency (MHz)			Highest Intermodulation Product Level (dBm)	Limit (dBm)
153.785	154.325	155.280	No intermodulation products within 20 dBs of the limit	-13
159.090	159.210	160.530	No intermodulation products within 20 dBs of the limit	-13
153.785	154.325	160.530	No intermodulation products within 20 dBs of the limit	-13

Test equipment used for intermodulation test


TYPE OF EQUIPMENT	MAKER/SUPPLIER	MODEL No	SERIAL No	TRL No	ACTUAL EQUIPMENT USED
SPECTRUM ANALYSER	ANRITSU	MS2665C	MT26089	479	X
SIGNAL GENERATOR	MARCONI	2042	119388/080	176	X
SIGNAL GENERATOR	MARCONI	2023	112224/040	UH105	X
SIGNAL GENERATOR	MARCONI	2022D	119224/035	UH89	X
COMBINER	ELCOM	RC-4-50	N/A	170	X

All Channels off No RF Inputs




Scan plot showing amplifiers channels

Intermodulation Inband



The above plot shows that all products (designated by ☆) are at least 20dB below the spurious limit.

Intermodulation Wideband




The above plot shows that there are no products outside the bands.

TRANSMITTER TESTS

AMPLIFIER MODULATED CHANNEL TEST – CONDUCTED – Part 2.1049– DOWNLINK

Ambient temperature = 23°C Radio Laboratory
 Relative humidity = 46%
 Supply voltage = +110Vac
 Channel number = See test results



This test was performed to show that the amplifier does not alter the input signal in any way. The input signal was set to the maximum input level (-64dBm) and modulated with a 2500Hz tone. The plots show the signal measured at the signal generator and the signal measured at the output of the EUT.


Note: The cables and attenuators had the following losses.

1. Cable and attenuators between EUT and spectrum analyser 26.89dB
2. Cable between signal generator and EUT 0.47dB


Cable and attenuator between EUT and spectrum analyser removed to show signal measured at the signal generator.

TYPE OF EQUIPMENT	MAKER/SUPPLIER	MODEL No	SERIAL No	TRL No	ACTUAL EQUIPMENT USED
SPECTRUM ANALYSER	ANRITSU	MS2665C	MT26089	479	X
ATTENUATOR	BIRD	8308-100	N/A	112	X
ATTENUATOR	BIRD	8304-300-N	N/A	220	X
CABLE	ROSENBERGER	MICRO COAX	N/A	280	X
SIGNAL GENERATOR	MARCONI	2042	119388/080	176	X

153.785 MHz Signal Generator deviation set to 2.5kHz




153.785 MHz Signal Generator and EUT deviation set to 2.5kHz




The above plots depicting the output waveshape show no measurable distortion visible when compared to the input signal.

154.325 MHz Signal Generator deviation set to 2.5kHz




154.325 MHz Signal Generator and EUT deviation set to 2.5kHz




The above plots depicting the output wavelshape show no measurable distortion visible when compared to the input signal.

155.280 MHz Signal Generator deviation set to 2.5kHz




155.280 MHz Signal Generator and EUT deviation set to 2.5kHz




The above plots depicting the output waveshape show no measurable distortion visible when compared to the input signal.

159.090 MHz Signal Generator deviation set to 2.5kHz




159.090 MHz Signal Generator and EUT deviation set to 2.5kHz




The above plots depicting the output waveshape show no measurable distortion visible when compared to the input signal.

160.830 MHz Signal Generator deviation set to 5kHz



160.830 MHz Signal Generator and EUT deviation set to 5kHz




The above plots depicting the output wveshape show no measurable distortion visible when compared to the input signal.

TRANSMITTER TESTS

AMPLIFIER SPURIOUS EMISSIONS – CONDUCTED – Part 2.10– DOWNLINK

Ambient temperature = 22°C
 Relative humidity = 48%
 Supply voltage = +110Vac

Radio Laboratory
 Test Signal = F3E



The test was set up as per the diagram. The level at the input was adjusted to compensate for the loss of the interconnecting cable. The unit was tested operating at maximum power and on three test frequencies.

The Spurious limit was calculated as follows:

On any frequency removed from the assigned frequency by more that 250% of the authorised bandwidth

At least 43 + 10 log PdB

$$(10\log P_{\text{watts}}) - (43+10\log (P_{\text{watts}} * 1000)) = \text{LIMIT} = -13 \text{ dBm}$$


RESULTS

FREQUENCY RANGE	FREQ. (MHz)	MEASURED LEVEL (dBm)	ATTENUATOR & CABLE LOSSES (dB)	EMISSION LEVEL (dBm)	LIMIT (dBm)
0 Hz - 2GHz	No Significant emissions within 20 dB's of the limit				-13


The test equipment used for the Transmitter Conducted Emissions:

TYPE OF EQUIPMENT	MAKER/SUPPLIER	MODEL No	SERIAL No	TRL No	ACTUAL EQUIPMENT USED
SPECTRUM ANALYSER	ANRITSU	MS2665C	MT26089	479	X
ATTENUATOR	BIRD	8308-100	N/A	112	X
ATTENUATOR	BIRD	8304-300-N	N/A	220	X
CABLE	ROSENBERGER	MICRO COAX	N/A	280	X
SIGNAL GENERATOR	MARCONI	2042	119388/080	176	X


Conducted emissions 153.785 MHz 0 – 1GHz




Conducted emissions 153.785 MHz 1 – 2GHz




Conducted emissions 155.280 MHz 0 – 1GHz




Conducted emissions 155.280 MHz 1 – 2GHz




Conducted emissions 159.090 MHz 0 – 1GHz




Conducted emissions 159.090 MHz 1 – 2GHz



Conducted emissions 160.830 MHz 0 – 1GHz




Conducted emissions 160.830 MHz 1 – 2GHz



TRANSMITTER TESTS

AMPLIFIER SPURIOUS EMISSIONS – RADIATED – Part 2.1053– DOWNLINK

Ambient temperature = 20°C
 Relative humidity = 80%
 Conditions = OATS
 Supply voltage = +110Vac
 Supply Frequency = N/A
 Test Signal = F3E



The test was set up as per the diagram. The level at the input was adjusted to compensate for the loss of the interconnecting cable. The unit was tested operating maximum power on three test frequencies with a 50 ohm load on the output.

The Spurious limit was calculated as follows:

On any frequency removed from the assigned frequency by more than 250% of the authorised bandwidth

At least $43 + 10 \log P_{dB}$

$$(10 \log P_{\text{watts}}) - (43 + 10 \log (P_{\text{watts}} * 1000)) = \text{LIMIT} = -13 \text{ dBm}$$


RESULTS

FREQUENCY RANGE	FREQ. (MHz)	MEAS. Rx. (dBµV)	CABLE LOSS (dB)	ANT FACTOR	FIELD STRENGTH (dBµV/m)	CALCULATED EIRP (dBm)	LIMIT (dBm)
0 Hz – 2 GHz	No Significant emissions within 20 dB's of the limit						-13


The test equipment used for the Transmitter Spurious Emissions:

TYPE OF EQUIPMENT	MAKER/SUPPLIER	MODEL No	SERIAL No	TRL No	ACTUAL EQUIPMENT USED
SPECTRUM ANALYSER	ANRITSU	MS2665C	MT26089	479	X
HORN	EMCO	3115	9010-3581	139	X
CABLE	ROSENBERGER	MICRO COAX	N/A	280	X
SIGNAL GENERATOR	MARCONI	2042	119388/080	176	X

Radiated emissions 153.785 MHz 0 – 1GHz




Radiated emissions 153.785 MHz 1 – 2GHz




The above test results show that there were no emissions within 20dBs of the -13dBm limit.

Radiated emissions 155.280 MHz 0 – 1GHz




Radiated emissions 155.280 MHz 1 – 2GHz




The above test results show that there were no emissions within 20dBs of the -13dBm limit.

Radiated emissions 160.830 MHz 0 – 1GHz



Radiated emissions 160.830 MHz 1 – 2GHz



The above test results show that there were no emissions within 20dBs of the -13dBm limit.

ANNEX A
PHOTOGRAPHS

PHOTOGRAPH No. 1

TEST SETUP



PHOTOGRAPH No. 2

TEST SETUP



ANNEX B
APPLICANT'S SUBMISSION OF DOCUMENTATION LIST

APPLICANT'S SUBMISSION OF DOCUMENTATION LIST

a.	TCB	-	APPLICATION	[X]
		-	FEE	[X]
b.	AGENT'S LETTER OF AUTHORISATION	-		[X]
c.	MODEL(s) vs IDENTITY	-		[]
d.	ALTERNATIVE TRADE NAME DECLARATION(s)	-		[]
e.	LABELLING	-	PHOTOGRAPHS	[]
		-	DECLARATION	[]
		-	DRAWINGS	[]
f.	TECHNICAL DESCRIPTION	-		[X]
g.	BLOCK DIAGRAMS	-	Tx	[X]
		-	Rx	[]
		-	PSU	[]
		-	AUX	[]
h.	CIRCUIT DIAGRAMS	-	Tx	[]
		-	Rx	[]
		-	PSU	[]
		-	AUX	[]
i.	COMPONENT LOCATION	-	Tx	[]
		-	Rx	[]
		-	PSU	[]
		-	AUX	[]
j.	PCB TRACK LAYOUT	-	Tx	[]
		-	Rx	[]
		-	PSU	[]
		-	AUX	[]
k.	BILL OF MATERIALS	-	Tx	[]
		-	Rx	[]
		-	PSU	[]
		-	AUX	[]
l.	USER INSTALLATION / OPERATING INSTRUCTIONS	-		[X]

ANNEX C
EQUIPMENT CALIBRATION

EQUIPMENT CALIBRATION

UH006	3m Range ERP CAL	TRL	01/03/05	12	01/03/06
UH028	Log Periodic Ant	Schwarbeck	28/04/05	24	28/04/07
UH029	Bicone Antenna	Schwarbeck	27/04/05	24	27/04/07
UH041	Multimeter	AVOmeter	14/12/04	12	14/12/05
UH120	Spectrum Analyser	Marconi	15/03/05	12	15/03/06
UH122	Oscilloscope	Tektronix	07/06/05	24	07/06/07
UH162	ERP Cable Cal	TRL	23/05/05	12	23/05/06
UH179	Power Sensor	Marconi	14/12/04	12	14/12/05
UH228	Power Sensor	Marconi	17/01/05	12	17/01/06
UH253	1m Cable N type	TRL	10/01/05	12	10/01/06
UH254	1m Cable N type	TRL	10/01/05	12	10/01/06
UH265	Notch filer	Telonic	24/06/05	12	24/06/06
L005	CMTA	R&S	22/10/04	12	22/10/05
L007	Loop Antenna	R&S	29/03/05	24	29/03/07
L138	1-18GHz Horn	EMCO	15/04/05	24	15/04/07
L139	1-18GHz Horn	EMCO	03/05/05	24	03/05/07
L176	Signal Generator	Marconi	31/01/05	12	31/01/06
L193	Bicone Antenna	Chase	12/10/03	24	12/10/05
L203	Log Periodic Ant	Chase	21/10/03	24	21/10/05
L254	Signal Generator	Marconi	13/12/04	12	13/12/05
L280	18GHz Cable	Rosenberger	10/01/05	12	10/01/06
L343	CCIR Noise Filter	TRL	07/06/05	12	07/06/06
L426	Temperature Indicator	Fluke	14/12/04	12	14/12/05
L479	Analyser	Anritsu	05/10/04	12	05/10/05
L552	Signal Generator	Agilent	25/04/05	12	25/04/06