		\mathbb{V}	
	•	76.20	
38.10		Xell Wireless BSR 3308-PS-3-10-18-NFPA FCC: NEOBSR3308PS IC: 8749A-BSR3308PS 100-240V~ 2.0A Max 50/60Hz	
WIT 2. PRI 3. USE 4. FOF 5. BAF 6. THE 7. PAF	H 3M 467MP BAG NTING 2.1 BACKGF 2.2 SYMBOL 2.3 FONTS: E RIBBON ACCOI R SERIAL NUMBE R CODE TYPE AC E LABELS MUST	SILVER COLOR METALIZED POLYESTER WITH ONE SIDE CK ADHESIVE + ADHESIVE 200MP ON ONE SIDE. ROUND "a": SILVER LS AND FONTS "b" : BLACK HELVETICA MEDIUM RDING TO LABEL MANUFACTURER RECOMENDATION. ER SEE LABEL INFORMATION. CCORDING TO CODE-128 BE SUPPLIED ON ROLL. LY TOHS REQUIREMENTS.	
 MA⁻ WIT PRI PRI PRI PRI PRI PAF THE PAF LAB YY MM 	TH 3M 467MP BAO NTING 2.1 BACKGF 2.2 SYMBOL 2.3 FONTS: E RIBBON ACCOI R SERIAL NUMBE R CODE TYPE AC E LABELS MUST RT MUST COMPL	CK ADHESIVE + ADHESIVE 200MP ON ONE SIDE. ROUND "a": SILVER _S AND FONTS "b" : BLACK HELVETICA MEDIUM RDING TO LABEL MANUFACTURER RECOMENDATION. ER SEE LABEL INFORMATION. CCORDING TO CODE-128 BE SUPPLIED ON ROLL. _Y ToHS REQUIREMENTS. DN:	
 MA⁻ WIT PRI PRI PRI PRI PRI PAF THE PAF LAB YY MMA 	H 3M 467MP BAG NTING 2.1 BACKGF 2.2 SYMBOL 2.3 FONTS: E RIBBON ACCOI R SERIAL NUMBE R CODE TYPE AC E LABELS MUST RT MUST COMPL BEL INFORMATIC Year (2 Digits) - Month (2 Digits)	CK ADHESIVE + ADHESIVE 200MP ON ONE SIDE. ROUND "a": SILVER S AND FONTS "b" : BLACK HELVETICA MEDIUM RDING TO LABEL MANUFACTURER RECOMENDATION. ER SEE LABEL INFORMATION. CCORDING TO CODE-128 BE SUPPLIED ON ROLL. Y ToHS REQUIREMENTS. DN:	
 MA⁻ WIT PRI PRI PRI PRI FOF BAF THE TAF LAB YY MM- ZZZ 	TH 3M 467MP BAG NTING 2.1 BACKGF 2.2 SYMBOL 2.3 FONTS: E RIBBON ACCOI R SERIAL NUMBE R CODE TYPE AC E LABELS MUST RT MUST COMPL BEL INFORMATIC Year (2 Digits) - Month (2 Digits) ZZZ- Serial No.	CK ADHESIVE + ADHESIVE 200MP ON ONE SIDE. ROUND "a": SILVER LS AND FONTS "b" : BLACK HELVETICA MEDIUM RDING TO LABEL MANUFACTURER RECOMENDATION. ER SEE LABEL INFORMATION. CORDING TO CODE-128 BE SUPPLIED ON ROLL. LY TOHS REQUIREMENTS. DN: No REVISION DA	ΓΕ ΒΥ
 MA⁻ WIT PRI PRI PRI PRI PAF THE LAB YY- MM- ZZZ 	TH 3M 467MP BAG NTING 2.1 BACKGF 2.2 SYMBOL 2.3 FONTS: E RIBBON ACCOI R SERIAL NUMBE CODE TYPE AC E LABELS MUST RT MUST COMPL BEL INFORMATIC Year (2 Digits) - Month (2 Digits) ZZZ- Serial No.	CK ADHESIVE + ADHESIVE 200MP ON ONE SIDE. ROUND "a": SILVER LS AND FONTS "b" : BLACK HELVETICA MEDIUM RDING TO LABEL MANUFACTURER RECOMENDATION. ER SEE LABEL INFORMATION. CORDING TO CODE-128 BE SUPPLIED ON ROLL. LY TOHS REQUIREMENTS. N: IGN OF AXELL WIRELESS LTD THIS DESIGN BY	5 4700
 MA⁻ WIT PRI PRI PRI PRI PAF THE LAB YY MM- ZZZ THIS IS A REPRODIO OTHERS AUTHORI GENERA ISO 2768 	TH 3M 467MP BAG NTING 2.1 BACKGF 2.2 SYMBOL 2.3 FONTS: E RIBBON ACCOI R SERIAL NUMBE CODE TYPE AC E LABELS MUST RT MUST COMPL BEL INFORMATIC Year (2 Digits) - Month (2 Digits) ZZZ- Serial No.	CK ADHESIVE + ADHESIVE 200MP ON ONE SIDE. ROUND "a": SILVER S AND FONTS "b" : BLACK HELVETICA MEDIUM RDING TO LABEL MANUFACTURER RECOMENDATION. ER SEE LABEL INFORMATION. CCORDING TO CODE-128 BE SUPPLIED ON ROLL. Y TOHS REQUIREMENTS. N: IGN OF AXELL WIRELESS LTD THIS DESIGN BY ILY IF EXPRESSLY AXELL WIRELESS LTD. ALL DIMENSIONS ARE IN mm UNLESS OTHERWISE STATED SE	5 4700