

Environmental evaluation and exposure limit according to FCC CFR 47part 1, §1.1307, §1.1310

The booster may be installed indoors or outdoors as stated in the User's manual page V, the calculation was done to confirm a safe distance.

Limit for power density for general population/uncontrolled exposure is $f/1500$ mW/cm² for 300 – 1500 MHz frequency range:

$$P = 758/1500 = 0.5 \text{ mW/cm}^2$$

The power density P (mW/cm²) = $P_T / 4\pi r^2$, where

P_T is the transmitted power, which is equal to the peak transmitter output power plus maximum antenna gain.

Indoor antenna installation

The maximum equivalent isotropically radiated power EIRP is

$$P_T = 35.73 \text{ dBm} + 0.2 \text{ dBi} = 35.93 \text{ dBm} = 3917 \text{ mW}, \text{ where}$$

35.73 dBm is the EUT maximum conducted output power in DL mode in 851-869 MHz with analog FM modulation;

0.2 dBi – antenna assembly gain.

The EUT maximum conducted output power in UL mode is 32.64 dBm (in 806-824 MHz with iDEN QAM modulation), that is less than in DL mode.

The minimum safe distance “r”, where RF exposure does not exceed FCC permissible limit, is

$$r = \sqrt{P_T / (P \times 4\pi)} = \sqrt{3917 / (0.5 \times 12.56)} = 25 \text{ cm}.$$

Outdoor antenna installation

The maximum equivalent isotropically radiated power EIRP is

$$P_T = 35.73 \text{ dBm} + 7 \text{ dBi} = 42.73 \text{ dBm} = 18750 \text{ mW}, \text{ where}$$

35.73 dBm is the EUT maximum conducted output power in DL mode in 851-861 MHz with analog FM modulation;

7 dBi – antenna assembly gain (please refer to page 8 of User_manual_27215A).

The minimum safe distance “r”, where RF exposure does not exceed FCC permissible limit, is

$$r = \sqrt{P_T / (P \times 4\pi)} = \sqrt{18750 / (0.5 \times 12.56)} = 54.6 \text{ cm} \approx 55 \text{ cm}.$$

A warning about a safe distance is contained in the user manual.