



Prüfbericht - Nr.: 14017607 001 <i>Test Report No.:</i>		Seite 1 von 11 <i>Page 1 of 11</i>	
Auftraggeber: <i>Client:</i>		Zaptoys International Ltd. Unit 1105, 11/F, Tower II South Seas Centre T.S.T. East, Kowloon Hong Kong	
Gegenstand der Prüfung: Low Power Transmitter (27.145MHz) <i>Test Item:</i>			
Bezeichnung: <i>Identification</i>		9304A, 9303A, 9474A, 9575A, 9525A, 9500A, 9535A and 9494A	
Serien-Nr.: <i>Serial No.</i>		Engineering sample	
Wareneingangs-Nr.: <i>Receipt No.</i>		071016011	
Eingangsdatum: <i>Date of receipt</i>		16.10.2007	
Prüfort: <i>Testing Location:</i>		TÜV Rheinland Hong Kong Ltd. 9th Floor, Oriental News Building, 7 Wang Tai Road, Kowloon Bay, Kowloon, Hong Kong Hong Kong Productivity Council HKPC Building, 78 Tat Chee Avenue, Kowloon, Hong Kong	
Prüfgrundlage: <i>Test Specification:</i>		FCC Part 15, Subpart C	
Prüfergebnis: <i>Test Result:</i>		Der Prüfgegenstand entspricht oben genannter Prüfgrundlage(n). <i>The test item passed the test specification(s).</i>	
Prüflaboratorium: <i>Testing Laboratory:</i>		TÜV Rheinland Hong Kong Ltd. 9th Floor, Oriental News Building, 7 Wang Tai Road, Kowloon Bay, Kowloon, Hong Kong	
geprüft / tested by:		kontrolliert / reviewed by:	
30.11.2007 Datum <i>Date</i>	Derek Leung Project Manager Name/Stellung <i>Name/Position</i>	30.11.2007 Datum <i>Date</i>	Thomas Berns Manager Name/Stellung <i>Name/Position</i>
 Unterschrift <i>Signature</i>		 Unterschrift <i>Signature</i>	
Sonstiges / Other Aspects: FCCID: NEX-9304A-27TX			
Abkürzungen:		Abbreviations:	
P(ass) = entspricht Prüfgrundlage F(ail) = entspricht nicht Prüfgrundlage N/A = nicht anwendbar N/T = nicht getestet		P(ass) = passed F(ail) = failed N/A = not applicable N/T = not tested	
Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens. <i>This test report relates to the a. m. test sample. Without permission of the test center this test report is not permitted to be duplicate in extracts. This test report does not entitle to carry any safety mark on this or similar products.</i>			

www.tuv.com

Test Summary

Radiated Emission of Carrier Frequency

Result: Pass

Spurious Radiated Emissions

Result: Pass

Bandwidth Measurement

Result: Pass

Content

List of Test and Measurement Instruments.....	4
General Product Information	5
Product Function and Intended Use.....	5
Independent Operation Modes.....	6
Submitted Documents	6
Related Submittal(s) Grants	6
Test Set-up and Operation Mode.....	7
Principle of Configuration Selection	7
Test Operation and Test Software	7
Special Accessories and Auxiliary Equipment	7
Countermeasures to achieve EMC Compliance.....	7
Test Methodology	8
Radiated Emission	8
Test Results	9
Radiated Emission of Carrier Frequency Subclause 15.227(a).....	9
Spurious Radiated Emissions Subclause 15.227(b).....	10
Bandwidth Measurement Subclause 15.227(b).....	11
Appendix 1: Test Result	
Appendix 2: Test Setup	
Appendix 3: EUT External Photo	
Appendix 4: EUT Internal Photo	
Appendix 5: FCCID Label, Block Diagram, Schematics	
Appendix 6: User Manual	

List of Test and Measurement Instruments

Kind of Equipment	Manufacturer	Type	S/N
Biconical Antenna	Rohde & Schwarz	HK116	841489/015
Log.-Periodic Antenna	Rohde & Schwarz	HL223	841516/017
Double Ridge Horn Antenna	EMCO	3115	9002-3347
Spectrum Analyzer	Rohde & Schwarz	FSP30	1093.4495K30
Test Receiver	Rohde & Schwarz	ESU26	100050

General Product Information

Product Function and Intended Use

The equipment under test (EUT) is a transmitter for a RC toy car operating at 27.145 MHz. The EUT has two control rods for commanding the forward, backward, left and right movement of the associated receiver.

FCCID: NEX-9304A - 27TX

Model	Product description
9304A	Radio Control Toy Transmitter

Client declared that 9304A, 9303A, 9474A, 9575A, 9525A, 9500A, 9535A and 9494A are identical and only difference is their outlook. 9304A has been chosen as the representative model for the testing in this report.

www.tuv.com

Independent Operation Modes

The basic operation modes are:

- Remote Control: On and Off

For further information refer to User Manual

Submitted Documents

The submitted documents are listed as follow:

- Circuit diagram
- Block diagram
- User manual
- Label artwork

Related Submittal(s) Grants

-

Test Set-up and Operation Mode

Principle of Configuration Selection

Emission: The equipment under test (EUT) was configured to measure its highest possible radiation level.

Test Operation and Test Software

Test operation should refer to test methodology.

- There was no special software to exercise the device.

Special Accessories and Auxiliary Equipment

The product has been tested together with the following additional accessories:

- none

Countermeasures to achieve EMC Compliance

- none

Test Methodology

Radiated Emission

The radiated emission measurements were performed according to the procedures in ANSI C63.4-2003.

The equipment under test (EUT) was placed at the middle of the 80 cm height turntable, and the turntable is 3 meters far from the measuring antenna. During the testing, the EUT was operated standalone and arranged for maximum emissions. The EUT was tested in three orthogonal planes.

The investigation is performed with the EUT rotated 360°, the antenna height scanned between 1m and 4m, and the antenna rotated to repeat the measurements for both the horizontal and vertical antenna polarizations. Repeat the measurement steps until the maximum emissions were obtained.

Test Results

Radiated Emission of Carrier Frequency

Subclause 15.227(a)

RESULT:
Pass

Test Specification : FCC Part 15 Subclause 15.227(a)
 Test Method : ANSI 63.4-2003
 Measurement Location : Semi Anechoic Chamber
 Measurement Distance : 3m
 Detector Function : Peak and Average
 Measurement BW : 100 kHz
 Supply Voltage : DC 9V

Polarization: Vertical

Detector Function	Frequency (MHz)	Electric Field Strength (dBuV/m)	Limit at 3m (dBuV/m)	Delta to Limit (dB)
Peak	27.1471	81.1	100.0	-18.9
Average	27.1471	75.2	80.0	-4.8

Polarization: Horizontal

Detector Function	Frequency (MHz)	Electric Field Strength (dBuV/m)	Limit at 3m (dBuV/m)	Delta to Limit (dB)
Peak	27.1471	66.2	100.0	-33.8
Average	27.1471	60.2	80.0	-19.8

Limit
Subclause 15.227(a)

Frequency within the band	Peak Emission		Average Emission	
	(microvolt/meter)	dBuV/m	(microvolt/meter)	dBuV/m
26.96-27.28 MHz	100,000	100.0	10,000	80.0

According to section 15.35(b), when average radiated emission measurements are specified in this part, including average emission measurements below 1000 MHz, there also is a limit on the peak level of the radio frequency emissions. Unless otherwise specified, the limit on peak radio frequency emissions is 20 dB above the maximum permitted average emission limit applicable to the equipment under test.

Spurious Radiated Emissions

Subclause 15.227(b)

RESULT:

Pass

Test Specification : FCC Part 15 Subclause 15.209
 Test Method : ANSI 63.4-2003
 Measurement Location : Semi Anechoic Chamber
 Measurement Distance : 3m
 Detector Function : Quasi Peak
 Measurement BW : 100 kHz
 Supply Voltage : DC 9V
 Measuring Frequency Range : 25-1000MHz

Operation mode:

Frequency (MHz)	Polarization	Electric Field Strength (dBuV/m)	Limit at 3m (dBuV/m)	Delta to Limit (dB)
54.294	V	25.1	40.00	-14.90
217.1765	V	18.6	46.02	-27.42
54.294	H	27.3	40.00	-12.70
81.441	H	16.4	40.00	-23.60

Remark: (1) None of the emissions fall into the restricted band as defined in Section 15.205(a). They comply with the radiated emission limits specified in Section 15.209.
 (2) There is no spurious emission found between lowest oscillating frequency in the EUT to 30 MHz.

Limit

Subclause 15.209

Radiated emissions, which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209.

Limit for Radiated Emission under Section 15.209:

Frequency (MHz)	Field strength (microvolt/meter)	Field strength (dBuV/m)	Measurement distance (meters)
30-88	100	$20 \cdot \log(100) = 40.00$	3
88-216	150	$20 \cdot \log(150) = 43.52$	3
216-960	200	$20 \cdot \log(200) = 46.02$	3
960-2500	500	$20 \cdot \log(500) = 53.98$	3

The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector and above 1000 MHz are based on the measurements employing an average detector.

Bandwidth Measurement**Subclause 15.227(b)****RESULT:****Pass**

Test Specification : FCC Part 15 section 227(b)
Port of Testing : Antenna port
Detector Function : Peak
Supply Voltage : DC 9V

The field strength of any emissions appearing at the lower edge 26.96 MHz and upper edge 27.28 MHz are 31.00dB and 31.56dB below the carrier respectively.

For test results refer to Appendix 1.

Limit**Subclause 15.227(b)**

The field strength of any emission which appears outside of this band shall not exceed the general radiated emission limits in Section 15.209.