

Produkte
Products

Prüfbericht - Nr.: 14023085 001 <i>Test Report No.:</i>			Seite 1 von 12 <i>Page 1 of 12</i>				
Auftraggeber: Zaptoys International Limited <i>Client:</i> Flat B, 2/F, Edwick Industrial Centre 4-30 Lei Muk Road Kwai Chung, N.T. Hong Kong							
Gegenstand der Prüfung: Low Power Transmitter (27.145MHz) <i>Test Item:</i>							
Bezeichnung: 9344D <i>Identification:</i>		Serien-Nr.: <i>Serial No.:</i>		Engineering sample			
Wareneingangs-Nr.: 00100309007-001 <i>Receipt No.:</i>		Eingangsdatum: 09.03.2010 <i>Date of Receipt:</i>					
Prüfort: TÜV Rheinland Hong Kong Ltd. <i>Testing Location:</i> 8/F, Niche Centre, 14 Wang Tai Road, Kowloon Bay, Kowloon, Hong Kong Hong Kong Productivity Council HKPC Building, 78 Tat Chee Avenue, Kowloon, Hong Kong							
Prüfgrundlage: FCC Part 15, Subpart C <i>Test Specification:</i>							
Prüfergebnis: Der Prüfgegenstand entspricht oben genannter Prüfgrundlage(n). <i>Test Result:</i> The test item passed the test specification(s).							
Prüflaboratorium: TÜV Rheinland Hong Kong Ltd. <i>Testing Laboratory:</i> 9th Floor, Emperor International Square, 7 Wang Tai Road, Kowloon Bay, Kowloon, Hong Kong							
geprüft / tested by:			kontrolliert / reviewed by:				
07.04.2010 Mika Chan Project Engineer			07.04.2010 Hugo Wan Project Manager				
Datum Date	Name/Stellung Name/Position	Unterschrift Signature	Datum Date	Name/Stellung Name/Position	Unterschrift Signature		
Sonstiges / Other Aspects: FCCID: NEX-9344D27TX							
<table style="width: 100%; border: none;"> <tr> <td style="width: 50%; vertical-align: top;"> Abkürzungen: P(ass) = entspricht Prüfgrundlage F(ail) = entspricht nicht Prüfgrundlage N/A = nicht anwendbar N/T = nicht getestet </td> <td style="width: 50%; vertical-align: top;"> Abbreviations: P(ass) = passed F(ail) = failed N/A = not applicable N/T = not tested </td> </tr> </table>						Abkürzungen: P(ass) = entspricht Prüfgrundlage F(ail) = entspricht nicht Prüfgrundlage N/A = nicht anwendbar N/T = nicht getestet	Abbreviations: P(ass) = passed F(ail) = failed N/A = not applicable N/T = not tested
Abkürzungen: P(ass) = entspricht Prüfgrundlage F(ail) = entspricht nicht Prüfgrundlage N/A = nicht anwendbar N/T = nicht getestet	Abbreviations: P(ass) = passed F(ail) = failed N/A = not applicable N/T = not tested						
<p>Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens. <i>This test report relates to the a. m. test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any safety mark on this or similar products.</i></p>							

Test Summary

Radiated Emission of Carrier Frequency

Result: Pass

Spurious Radiated Emissions

Result: Pass

Bandwidth Measurement

Result: Pass

Contents

List of Test and Measurement Instruments.....	4
General Product Information	5
Product Function and Intended Use.....	5
Ratings and System Details.....	5
Independent Operation Modes.....	6
Submitted Documents	6
Related Submittal(s) Grants	6
Test Set-up and Operation Mode.....	7
Principle of Configuration Selection	7
Test Operation and Test Software	7
Special Accessories and Auxiliary Equipment	7
Countermeasures to achieve EMC Compliance.....	7
Test Methodology	8
Radiated Emission.....	8
Field Strength Calculation	8
Test Results	9
Radiated Emission of Carrier Frequency Subclause 15.227(a)	9
Spurious Radiated Emissions Subclause 15.227(b).....	10
Bandwidth Measurement.....	12
Appendix 1 Test Protocol	
Appendix 2 Test Setup	
Appendix 3 EUT External Photo	
Appendix 4 EUT Internal Photo	
Appendix 5 FCCID Label, Block Diagram, Schematics and User manual	

List of Test and Measurement Instruments

TÜV Rheinland (Guangdong) Ltd. (Registration number: 833845)

Kind of Equipment	Manufacturer	Type	S/N	Cal Due Date
FSP30 Spectrum Analyzer	Rohde & Schwarz	FSP30	100286	16-Mar-11
EMI Test Receiver	Rohde & Schwarz	ESCI	100216	16-Mar-11
Trilog-Broadband Antenna	Schwarzbeck	VULB9168	209	21-Aug-11
Trilog-Broadband Antenna	Schwarzbeck	VULB9168	210	16-Mar-11
Double-Ridged Waveguide Horn Antenna	Rohde & Schwarz	HF 906	100385	24-Aug-11
Band Reject Filter	Micro-Tronics	BRM50702	023	16-Mar-11
Pre-Amplifier	MITEQ	AFS42-00101800-25-S-42	1101599	16-Mar-11
Double-Ridged Waveguide Horn Antenna	Rohde & Schwarz	HF 906	100407	16-Mar-11
Horn Antenna	EMCO	3160-09	21642	26-Jun-14
Pre-Amplifier	MITEQ	AFS33-18002650-30-8P-44	1108282	16-Mar-11
Horn Antenna	EMCO	3160-09	21645	24-Aug-14
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100111	16-Mar-11
Triple-Loop Antenna	Rohde & Schwarz	HM020	100021	16-Mar-11
SAC	Albatross Projects GmbH	N/A	9460000.9	#REF!

General Product Information

Product Function and Intended Use

The equipment under test (EUT) is a transmitter for a RC toy car operating at 27.145 MHz. The EUT has two control rods for commanding the forward, backward, left and right movement of the associated receiver.

FCCID: NEX-9344D27TX

Model	Product description
9344D	Radio Control Toy Transmitter

Ratings and System Details

	Transmitter
Frequency range	: 27.145MHz
Number of channels	: 1
Type of antenna	: Permanent wired antenna
Power supply	: Battery operated 9V
Ports	: none
Protection Class	: III

www.tuv.com

Independent Operation Modes

The basic operation modes are:

- Remote Control: On and Off

For further information refer to User Manual

Submitted Documents

The submitted documents are listed as follow:

- Circuit diagram
- Block diagram
- User manual
- Label artwork

Related Submittal(s) Grants

This is a single application for certification of the transmitter.

Test Set-up and Operation Mode

Principle of Configuration Selection

Emission: The equipment under test (EUT) was configured to measure its highest possible radiation level. The test modes were adapted accordingly in reference to the instructions for use.

Test Operation and Test Software

Test operation should refer to test methodology.

- There was no special software to exercise the device.

Special Accessories and Auxiliary Equipment

The product has been tested together with the following additional accessories:

- none

Countermeasures to achieve EMC Compliance

- none

Test Methodology

Radiated Emission

The radiated emission measurements were performed according to the procedures in ANSI C63.4-2003.

The equipment under test (EUT) was placed at the middle of the 80 cm height turntable, and the turntable is 3 meters far from the measuring antenna. During the testing, the EUT was operated standalone and arranged for maximum emissions. The EUT was tested in three orthogonal planes.

The investigation is performed with the EUT rotated 360°, the antenna height scanned between 1m and 4m, and the antenna rotated to repeat the measurements for both the horizontal and vertical antenna polarizations. Repeat the measurement steps until the maximum emissions were obtained.

All radiated tests were performed at an antenna to EUT with 3 meters distance, unless stated otherwise in particular parts of this test report.

Field Strength Calculation

The field strength at 3 m was established by adding the meter reading of the spectrum analyzer to the factors associated with antenna correction factor, cable loss, preamplifiers and filter attenuation.

The equation is expressed as follow:

$$FS = R + AF + CF + FA - PA$$

Where FS = Field Strength in dBuV/m at 3 meters.
R = Reading of Spectrum Analyzer in dBuV.
AF = Antenna Factor in dB.
CF = Cable Attenuation Factor in dB.
FA = Filter Attenuation Factor in dB.
PA = Preamplifier Factor in dB.

FA and PA are only be used for the measuring frequency above 1 GHz.

Test Results

Radiated Emission of Carrier Frequency

Subclause 15.227(a)

RESULT:
Pass

Test Specification : FCC Part 15 Subclause 15.227(a)
 Test Method : ANSI 63.4-2003
 Measurement Location : Semi Anechoic Chamber
 Measurement Distance : 3m
 Detector Function : Peak and Average
 Measurement BW : 120 kHz
 Supply Voltage : DC 9V

Polarization: Vertical

Detector function	Frequency (MHz)	Measured Field strength at 3m (dB μ V/m)	Delta to Limit (dB)
Peak	24.149	82.0	-18.0
Average	27.149	76.3	-3.7

Polarization: Horizontal

Detector function	Frequency (MHz)	Measured Field strength at 3m (dB μ V/m)	Delta to Limit (dB)
Peak	27.149	69.4	-30.6
Average	27.149	63.7	-16.3

Limit
Subclause 15.227(a)

Frequency within the band	Peak Emission		Average Emission	
	(μ V/m)	dB μ V/m	(μ V/m)	dB μ V/m
26.96-27.28 MHz	100,000	100.0	10,000	80.0

According to section 15.35(b), when average radiated emission measurements are specified in this part, including average emission measurements below 1000 MHz, there also is a limit on the peak level of the radio frequency emissions. Unless otherwise specified, the limit on peak radio frequency emissions is 20 dB above the maximum permitted average emission limit applicable to the equipment under test.

Spurious Radiated Emissions

Subclause 15.227(b)

RESULT:

Pass

Test Specification : FCC Part 15 Subclause 15.209
 Test Method : ANSI 63.4-2003
 Measurement Location : Semi Anechoic Chamber
 Measurement Distance : 3m
 Detector Function : Quasi Peak
 Measurement BW : 120 kHz
 Supply Voltage : DC 9V
 Measuring Frequency Range : 30-1000MHz

Polarization: Vertical

Frequency (MHz)	Field strength at 3m (dBuV/m)	Limit at 3m (dBuV/m)	Delta to Limit (dB)
40.800	11.1	40.0	-28.9
54.300	17.1	40.0	-22.9
81.450	14.1	40.0	-25.9
149.800	12.0	43.5	-31.5
*244.350	16.2	46.0	-29.8
754.450	21.6	46.0	-24.4

Polarization: Horizontal

Frequency (MHz)	Field strength at 3m (dBuV/m)	Limit at 3m (dBuV/m)	Delta to Limit (dB)
46.500	10.7	40.0	-29.3
141.500	11.4	40.0	-28.6
190.050	25.3	43.5	-18.2
*244.350	27.0	43.5	-16.5
*271.500	26.3	43.5	-17.2
736.500	21.3	43.5	-22.2

Remark: (1) '*' indicates the frequency of the emissions fall into the restricted band as defined in Section 15.205(a). They comply with the radiated emission limits specified in Section 15.209.
 (2) There is no spurious emission found between lowest oscillating frequency to 30 MHz.

www.tuv.com

Limit

Subclause 15.209

Radiated emissions, which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209.

Limit for Radiated Emission under Section 15.209:

Frequency (MHz)	Field strength ($\mu\text{V/m}$)	Field strength (dB $\mu\text{V/m}$)	Measurement distance (m)
30-88	100	$20 \cdot \log(100) = 40.0$	3
88-216	150	$20 \cdot \log(150) = 43.5$	3
216-960	200	$20 \cdot \log(200) = 46.0$	3
960-2500	500	$20 \cdot \log(500) = 54.0$	3

The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector and above 1000 MHz are based on the measurements employing an average detector.

www.tuv.com

Bandwidth Measurement

Port of Testing	:	Antenna port
Detector Function	:	Peak
Supply Voltage	:	DC 9V

The field strength of any emissions appearing at the lower edge 26.96 MHz and upper edge 27.28 MHz are 48.89 dB and 46.02 dB below the carrier respectively.

For test results refer to Appendix 1.