

<b>Prüfbericht - Nr.:</b> 14010299 001		<b>Seite 1 von 10</b>	
Test Report No.		Page 1 of 10	
<b>Auftraggeber:</b> Applicant		<b>Lucky Plastic Factory Ltd.</b> Suite 502, Chinachem Golden Plaza 77 Mody Road T.S.T. East, Kowloon Hong Kong	
<b>Gegenstand der Prüfung:</b> Test item		<b>Superregenerative Receiver</b>	
<b>Bezeichnung:</b> Identification	<b>9434, 9459, 9471</b>	<b>Serien-Nr.:</b> Serial No.	<b>Engineering sample</b>
<b>Wareneingangs-Nr.:</b> Receipt No.	<b>050624021</b> <b>060223057</b>	<b>Eingangsdatum:</b> Date of receipt	<b>24.06.2005</b> <b>23.02.2006</b>
<b>Prüfört:</b> Testing location		<b>TÜV Rheinland Hong Kong Ltd.</b> Unit 8, 25 <sup>th</sup> Floor, Skyline Tower, 39 Wang Kwong Road, Kowloon Bay Kowloon, Hong Kong  <b>Hong Kong Productivity Council</b> HKPC Building, 78 Tat Chee Avenue, Kowloon, Hong Kong	
<b>Prüfgrundlage:</b> Test specification		<b>FCC Part 15, Subpart B</b>	
<b>Prüfergebnis:</b> Test Result		<b>Das vorstehend beschriebene Gerät wurde geprüft und entspricht oben genannter Prüfgrundlage.</b> The above mentioned product was tested and <b>passed</b> .	
<b>geprüft / tested by:</b>		<b>kontrolliert / reviewed by:</b>	
01.03.2006	Hugo Wan Project Engineer	01.03.2006	Thomas Berns Senior Project Manager
<b>Datum</b> Date	<b>Name</b> Name	<b>Unterschrift</b> Signature	<b>Unterschrift</b> Signature
<b>Sonstiges:</b> FCCID: NEX-9434-49 Other Aspects			
<b>Abkürzungen:</b>		<b>Abbreviations:</b>	
OK, Pass, P	= entspricht Prüfgrundlage	OK, Pass, P	= passed
Fail, F	= entspricht nicht Prüfgrundlage	Fail, F	= failed
N/A	= nicht anwendbar	N/A	= not applicable
NT	= nicht getestet	NT	= not tested
<b>Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens.</b> This test report relates to the a. m. test sample. Without permission of the test center this test report is not permitted to be duplicate in extracts. This test report does not entitle to carry any safety mark on this or similar products.			

# Test Summary

## Conducted Emissions

*Result: Pass*

## Spurious Radiated Emissions

*Result: Pass*

## Contents

List of Test and Measurement Instruments.....	4
General Product Information .....	5
Product Function and Intended Use.....	5
Ratings and System Details .....	5
Independent Operation Modes.....	6
Submitted Documents .....	6
Related Submittal(s) Grants .....	6
Test Set-up and Operation Mode.....	7
Principle of Configuration Selection .....	7
Test Operation and Test Software.....	7
Special Accessories and Auxiliary Equipment .....	7
Countermeasures to achieve EMC Compliance.....	7
Test Methodology .....	8
Radiated Emission .....	8
Field Strength Calculation.....	8
Test Results .....	9
Conducted Emissions                      Section 15.107 .....	9
Spurious Radiated Emissions            Section 15.109 .....	10
Appendix 1: Test Setup	
Appendix 2: EUT External Photo	
Appendix 3: EUT Internal Photo	
Appendix 4: FCCID Label, Block Diagram, Schematics and User manual.	
Appendix 5: Test Results	

## List of Test and Measurement Instruments

Kind of Equipment	Manufacturer	Type	S/N
Test Receiver	Rohde & Schwarz	ESVS30	842807/009
Biconical Antenna	Rohde & Schwarz	HK116	841489/015
Log.-Periodic Antenna	Rohde & Schwarz	HL223	841516/017
Double Ridge Horn Antenna	EMCO	3115	9002-3347
Signal Generator	Rohde & Schwarz	SMY 01	844146/024
Test Receiver	Rohde & Schwarz	ESCS30	100201
LISN	Rohde & Schwarz	ESH3-Z5	100230

## General Product Information

### Product Function and Intended Use

The equipment under test (EUT) is a RC toy car operating at 49.86MHz. The EUT moves forward, backward, left and right according to the command of the associate transmitter.

The AC/DC adaptor is used to provide charging function for the rechargeable battery only. The battery is charged independently from the RC toy car.

#### FCCID: NEX-9434-49

Models	Product descriptions
9434	MCLAREN SLR
9459	ASTON MARTIN
9471	MUSTANG GT

### Ratings and System Details

	Receiver
Frequency range	: 49.86MHz
Number of channels	: 1
Type of antenna	: Fixed External Antenna
Power supply	: 9.6V rechargeable battery
Ports	: none
Protection Class	: III

	AC/DC adaptor
Model number	: DPX351358
Rating	: Input: 120VAC 50Hz 4.5W Output: 11.6VDC 165mA

## Independent Operation Modes

The basic operation modes are:

- Power: On and Off
- Motor movement: left and right, forward and backward.

For further information refer to User Manual

## Submitted Documents

The submitted documents are listed as follow:

- Circuit diagram
- Block diagram
- User manual
- Label artwork

## Related Submittal(s) Grants

This is a single application for certification of the Receiver.

## Test Set-up and Operation Mode

### Principle of Configuration Selection

**Emission:** The equipment under test (EUT) was configured to measure its highest possible radiation level. The test modes were adapted accordingly in reference to the instructions for use.

### Test Operation and Test Software

Test operation should refer to test methodology.

- There was no special software to exercise the device.

### Special Accessories and Auxiliary Equipment

The product has been tested together with the following additional accessories:

- none

### Countermeasures to achieve EMC Compliance

The test sample, which has been tested, contained the noise suppression parts as described in the Circuit Diagram or the Technical Construction File. No additional measures were employed to achieve compliance.

## Test Methodology

### Radiated Emission

The radiated emission measurements were performed according to the procedures in ANSI C63.4-2003.

The equipment under test (EUT) was placed at the middle of the 80 cm height turntable, and the turntable is 3 meters far from the measuring antenna. During the testing, the EUT was operated standalone and arranged for maximum emissions. The EUT was tested in three orthogonal planes.

The investigation is performed with the EUT rotated 360°, the antenna height scanned between 1m and 4m, and the antenna rotated to repeat the measurements for both the horizontal and vertical antenna polarizations. Repeat the measurement steps until the maximum emissions were obtained.

All radiated tests were performed at an antenna to EUT with 3 meters distance, unless stated otherwise in section 7.1.1 and 7.1.2 of this test report.

### Field Strength Calculation

The field strength at 3 m was established by adding the meter reading of the spectrum analyzer to the factors associated with antenna correction factor, cable loss, preamplifiers and filter attenuation.

The equation is expressed as follow:

$$FS = R + AF + CF + FA - PA$$

Where FS = Field Strength in dBuV/m at 3 meters.

R = Reading of Spectrum Analyzer in dBuV.

AF = Antenna Factor in dB.

CF = Cable Attenuation Factor in dB.

FA = Filter Attenuation Factor in dB.

PA = Preamplifier Factor in dB.

FA and PA are only be used for the measuring frequency above 1 GHz.



## Test Results

### Conducted Emissions

### Section 15.107

#### RESULT:

**Pass**

Test Specification : FCC Part 15 Section 15.107  
 Test Method : ANSI 63.4-2003  
 Measurement Location : Shield Room  
 Detector Function : Quasi Peak, Average  
 Measurement BW : 100 kHz  
 Supply Voltage : AC120V  
 Measuring Frequency Range: 0.15-30MHz

Measured Terminal	Frequency (MHz)	Quasi-peak		Average	
		Field Strength (dBμV)	Delta to limit (dBμV)	Field Strength (dBμV)	Delta to limit (dBμV)
L	0.150	35.7	-30.3	9.5	-46.5
	0.240	33.3	-28.8	7.1	-45.0
	0.360	29.7	-29.0	4.7	-44.0
N	0.378	34.1	-24.2	8.3	-40.0
	0.798	23.3	-28.8	0.8	-41.3

For test results refer to Appendix 1, page 1-2.

#### Limit

#### Section 15.107

Frequency of Emission (MHz)	Conducted Limit (dBμV)	
	Quasi-peak	Average
0.15-0.5	66 to 56 *	56 to 46*
0.5-5	56	46
5-30	60	50

\* Decreases with the logarithm of the frequency.

**Spurious Radiated Emissions****Section 15.109****RESULT:****Pass**

Test Specification : FCC Part 15 Section 15.109  
 Test Method : ANSI 63.4-2003  
 Measurement Location : Semi Anechoic Chamber  
 Measurement Distance : 3m  
 Detector Function : Quasi Peak  
 Measurement BW : 100 kHz  
 Supply Voltage : DC 9V  
 Measuring Frequency Range : 30-1000MHz

Polarization: Vertical

Frequency (MHz)	Field strength at 3m (dBμV/m)	Limit at 3m (dBμV/m)	Delta to Limit (dB)
49.70	31.80	40.00	-8.20
97.88	23.20	43.52	-20.32
144.98	34.60	43.52	-8.92
193.46	26.00	43.52	-17.52
201.68	17.50	43.52	-26.02
286.82	15.40	46.02	-30.62
878.90	25.40	46.02	-20.62

Polarization: Horizontal

Frequency (MHz)	Field strength at 3m (dBμV/m)	Limit at 3m (dBμV/m)	Delta to Limit (dB)
49.67	34.40	40.00	-5.60
97.52	28.70	43.52	-14.82
145.04	42.90	43.52	-0.62
193.04	35.50	43.52	-8.02
241.70	26.60	46.02	-19.42
337.46	20.10	46.02	-25.92
864.74	25.30	46.02	-20.72

The receiver was tested under receiving on mode. The spurious emissions are all complied with the limit.

**Limit****Section 15.109**

The field strength of radiated emissions from unintentional radiators at a distance of 3 meters:

Frequency (MHz)	Field strength (μV/m)	Field strength (dBμV/m)	Measurement distance (meters)
30-88	100	$20 \cdot \log(100) = 40.00$	3
88-216	150	$20 \cdot \log(150) = 43.52$	3
216-960	200	$20 \cdot \log(200) = 46.02$	3
Above 960	500	$20 \cdot \log(500) = 53.98$	3