

**FCC 15.247 & RSS-247
2.4 GHz Report**

for

POWERTECH INDUSTRIAL CO. LTD.

**10F, No. 407, Sec. 2, Chung-Shan Road,
Chung-Ho City, Taipei Hsien 235 Taiwan**

**Product Name : Zigbee Module
Model Name : EM3585
FCC ID : NHS-EM3585
IC : 3653A-EM3585**

TABLE OF CONTENTS

Description	Page
TEST REPORT CERTIFICATION	4
1. REPORT HISTORY.....	5
2. SUMMARY OF TEST RESULTS	6
3. GENERAL INFORMATION	7
3.1. Description of EUT	7
3.2. EUT Specifications Assessed in Current Report	8
3.3. Antenna Information	8
3.4. Test Configuration	9
3.5. Tested Supporting System List	10
3.6. Setup Configuration	10
3.7. Operating Condition of EUT	11
3.8. Description of Test Facility	11
3.9. Measurement Uncertainty	11
4. MEASUREMENT EQUIPMENT LIST	12
4.1. Conducted Emission Measurement.....	12
4.2. Radiated Emission Measurement.....	12
4.3. RF Conducted Measurement	12
5. CONDUCTED EMISSION MEASUREMET	13
5.1. Block Diagram of Test Setup	13
5.2. Power Line Conducted Emission Limit	13
5.3. Test Procedure	13
5.4. Conducted Emission Measurement Results	14
6. RADIATED EMISSION MEASUREMENT	16
6.1. Block Diagram of Test Setup	16
6.2. Radiated Emission Limits	17
6.3. Test Procedure	17
6.4. Measurement Result Explanation	18
6.5. Test Results	18
7. 6dB BANDWIDTH MEASUREMENT	27
7.1. Block Diagram of Test Setup	27
7.2. Specification Limits	27
7.3. Test Procedure	27
7.4. Test Results	27
8. MAXIMUM PEAK OUTPUT POWER MEASUREMENT	29
8.1. Block Diagram of Test Setup	29
8.2. Specification Limits	29
8.3. Test Procedure	29
8.4. Test Results	30
9. EMISSION LIMITATIONS MEASUREMENT	32
9.1. Block Diagram of Test Setup	32
9.2. Specification Limits	32

9.3. Test Procedure	32
9.4. Test Results.....	33
10. POWER SPECTRAL DENSITY	36
10.1. Block Diagram of Test Setup	36
10.2. Specification Limits	36
10.3. Test Procedure	36
10.4. Test Results.....	37
11. DEVIATION TO TEST SPECIFICATIONS.....	38

APPENDIX A TEST PHOTOGRAPHS

TEST REPORT CERTIFICATION

Applicant : POWERTECH INDUSTRIAL CO. LTD.
Manufacture : POWERTECH INDUSTRIAL CO. LTD.
Product Name : Zigbee Module
Model No. : EM3585
Serial No. : N/A
Power Supply : DC 3.3V

Applicable Standards:

FCC Rules and Regulations Part 15 Subpart C, Oct. 2014

RSS-Gen (Issue 4), November 2014

RSS-247 (Issue 1), May 2015

ANSI C63.10:2013

KDB 558074 D01 DTS Meas Guidance v03r03

AUDIX Technology Corp. tested the equipment mentioned in accordance with the requirements set forth in the above standards. Test results indicate that the equipment tested is capable of demonstrating compliance with the requirements as documented within this report. **AUDIX Technology Corp.** does not assume responsibility for any conclusions and generalizations drawn from the test results with regard to other specimens and samples.

Date of Test: 2015. 11. 10 ~ 17

Date of Report: 2015. 11. 23

Producer: 
(Annie Yu/Administrator)

Signatory: 
(Ben Cheng/Manager)

1. REPORT HISTORY

Revision	Date	Revision Summary	Report Number
0	2015. 11. 23	Original Report.	EM-F150710

2. SUMMARY OF TEST RESULTS

Rule		Description	Results
FCC	IC		
15.207	RSS-Gen §8.8	Conducted Emission	PASS
15.247(d)/ 15.205	RSS-Gen §8.9 RSS-247 §5.5	Radiated Band Edge and Radiated Spurious Emission	PASS
15.247(a)(2)	RSS-247 §5.2(1)	6dB Bandwidth	PASS
15.247(b)(3)	RSS-247 §5.4(4)	Maximum Peak Output	PASS
15.247(d)	RSS-247 §5.5	Conducted Band Edges and Conducted Spurious Emission	PASS
15.247 (e)	RSS-247 §5.2(2)	Power Spectral Density	PASS
15.203	---	Antenna Requirement	PASS

3. GENERAL INFORMATION

3.1. Description of EUT

Product	Zigbee Module
Model Number	EM3585
Serial Number	N/A
Applicant	POWERTECH INDUSTRIAL CO. LTD. 10F, No. 407, Sec. 2, Chung-Shan Road, Chung-Ho City, Taipei Hsien 235 Taiwan
Manufacture	POWERTECH INDUSTRIAL CO. LTD. 10F, No. 407, Sec. 2, Chung-Shan Road, Chung-Ho City, Taipei Hsien 235 Taiwan
RF Features	ZigBee (IEEE 802.15.4)
Transmit Type	1T1R
Device Category	<input type="checkbox"/> Outdoor Access Point <input type="checkbox"/> Fixed point-to-point Access Point <input type="checkbox"/> Indoor Access Point <input checked="" type="checkbox"/> Mobile and Portable client device
Date of Receipt of Sample	2015. 11. 05

3.2. EUT Specifications Assessed in Current Report

RF Features	Fundamental Range (MHz)	Channel Number	Modulation	Data Rate (Mbps)
ZigBee (IEEE 802.15.4)	2405-2480	16	DSSS (O-QPSK)	0.25

Channel List			
Channel Number	Frequency (MHz)	Channel Number	Frequency (MHz)
11	2405	19	2445
12	2410	20	2450
13	2415	21	2455
14	2420	22	2460
15	2425	23	2465
16	2430	24	2470
17	2435	25	2475
18	2440	26	2480

3.3. Antenna Information

Antenna Part Number	Manufacture	Antenna Type	Frequency	Max Gain (dBi)
---	Johanson Technology, Inc.	Chip Antenna	2400~2500MHz	0.5

3.4. Test Configuration

RF Features	Duty Cycle (x)	T (ms)	Duty Cycle Factor (dB)
Zigbee	1	N/A	N/A

Note: When duty cycle is less than 98% (0.98) that duty cycle factor $10\log(1/x)$ is needed to add in conducted test items measured in average detector.

	Item	Test Channel
Radiated Test Case	Radiated Band Edge ^{Note1}	11/26
	Radiated Spurious Emission (30MHz-1GHz) ^{Note1}	11/19/26
	Radiated Spurious Emission (Above 1GHz) ^{Note1}	11/19/26
Conducted Test Case	6dB Bandwidth	11/19/26
	Peak Power Spectral Density	11/19/26
	Peak Output Power	11/19/26
	Band Edge	11/19/26
	Spurious Emission	11/19/26

Note 1:

Mobile Device

Portable Device, and 3 axis were assessed. The worst scenario for Radiated Spurious Emission as follow:

- Lie
- Side
- Stand

3.5. Tested Supporting System List

3.5.1. Support Peripheral Unit


No.	Product	Brand	Model No.	Serial No.	FCC ID
1.	Notebook PC	DELL	P20G	N/A	N/A
2.	Test Jig	N/A	N/A	N/A	N/A
3.	Ember Debug Adapter	SILICON LABS	ISA3	N/A	N/A

3.5.2. Cable Lists


No.	Cable Description Of The Above Support Units
1.	Adapter: ACBEL, M/N AA90PM111, DC Cord: Shielded, Undetachable, 1.8m, Bonded a ferrite core AC Power Cord: Unshielded, Detachable, 1.8m
2.	LAN Cable: Shielded, Detachable, 1.0m USB Cable: Shielded, Detachable, 1.8m Cable: Unshielded, Detachable, 0.2m
3.	Cable: Unshielded, Detachable, 0.5m

3.6. Setup Configuration

3.6.1. EUT Configuration for Radiated Emission



3.6.2. EUT Configuration for Conducted Test Items



3.7. Operating Condition of EUT

Test program “ember.desktop” is used for enabling EUT RF function under continues transmitting and choosing channel. The EUT was transmit in a pulse transmission.

3.8. Description of Test Facility

Test Firm Name	:	AUDIX Technology Corporation EMC Department No. 53-11, Dingfu, Linkou Dist., New Taipei City 244, Taiwan
Test Location & Facility	:	Semi-Anechoic Chamber No. 53-11, Dingfu, Linkou Dist., New Taipei City 244, Taiwan May 06, 2015 File on Federal Communication Commission Registration Number: 90993
NVLAP Lab. Code	:	200077-0
TAF Accreditation No	:	1724

3.9. Measurement Uncertainty

Test Item	Frequency Range	Uncertainty
Conduction Test	150kHz~30MHz	±3.5dB
Radiation Test (Distance: 3m)	30MHz~300MHz	± 3.64dB
	300MHz~1000MHz	± 4.70dB
	Above 1GHz	± 2.94dB

Remark : Uncertainty = $ku_c(y)$

Test Item	Uncertainty
6dB Bandwidth	± 0.05kHz
Maximum peak output power	± 0.33dB
Power spectral density	± 0.13dB
Conducted Emission Limitations	± 0.13dB

4. MEASUREMENT EQUIPMENT LIST

4.1. Conducted Emission Measurement

Item	Type	Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Interval
1.	Test Receiver	R&S	ESCI	101276	2015. 04. 04	1 Year
2.	A.M.N.	R&S	ESH2-Z5	100366	2015. 03. 11	1 Year
3.	L.I.S.N.	Kyoritsu	KNW-407	8-881-13	2015. 01. 14	1 Year
4.	Pulse Limiter	R&S	ESH3-Z2	101495	2015. 01. 17	1 Year

4.2. Radiated Emission Measurement

4.2.1. Frequency Range 30MHz~1000MHz

Item	Type	Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Interval
1.	Spectrum Analyzer	Agilent	N9010A-526	MY53400071	2015. 09. 14	1 Year
2.	Test Receiver	R & S	ESCS30	100338	2015. 06. 24	1 Year
3.	Amplifier	HP	8447D	2944A06305	2015. 02. 12	1 Year
4.	Bilog Antenna	TESEQ	CBL6112D	33821	2015. 02. 27	1 Year

4.2.2. Frequency Range Above 1GHz

Item	Type	Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Interval
1.	Spectrum Analyzer	Agilent	E4446A	US44300366	2015. 08. 20	1 Year
2.	Test Receiver	R & S	ESCS30	100338	2015. 06. 24	1 Year
3.	Amplifier	Agilent	8449B	3008A02676	2015. 02. 11	1 Year
4.	2.4GHz Notch Filter	K&L	7NSL10-244 1.5E130.5-00	1	2015. 07. 22	1 Year
5.	3G High Pass Filter	Microware Circuits	H3G018G1	484796	NCR	NCR
6.	Double-Ridged Waveguide Horn	ETS-Lindgren	3117	00135902	2015. 03. 06	1 Year
7.	Horn Antenna	EMCO	3116	2653	2015. 10. 20	1 Year


4.3. RF Conducted Measurement

Item	Type	Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Interval
1.	Spectrum Analyzer	Agilent	N9030A-544	US51350140	2015. 06. 10	1 Year

5. CONDUCTED EMISSION MEASUREMET

5.1. Block Diagram of Test Setup

Shielded Room Setup Diagram



5.2. Power Line Conducted Emission Limit

Frequency	Conducted Limit	
	Quasi-Peak Level	Average Level
150kHz ~ 500kHz	66 ~ 56 dB μ V	56 ~ 46 dB μ V
500kHz ~ 5MHz	56 dB μ V	46 dB μ V
5MHz ~ 30MHz	60 dB μ V	50 dB μ V

Remark 1.: If the average limit is met when using a Quasi-Peak detector,

the measurement using the average detector is not required.

2.: The lower limit applies to the band edges.


5.3. Test Procedure

- 5.3.1. To set up the EUT as indicated in ANSI C 63.10. The EUT was placed on the table which has 80 cm height to the ground and 40 cm distance to the conducting wall.
- 5.3.2. Power supplier of the EUT was connected to the AC mains through an Artificial Mains Network (A.M.N.).
- 5.3.3. The AC power supplies to all peripheral devices must be provided through line impedance stabilization network (L.I.S.N.)
- 5.3.4. Checking frequency range from 150 kHz to 30 MHz and record the emission which does not have 20 dB below limit.

5.4. Conducted Emission Measurement Results

PASSED.


Test Date	2015/11/10	Temp./Hum.	24°C/64%
Test Voltage	DC 3.3V (Via test jig powered by Test JIG)		



Site no. : No.7 Shielded Room Data no. : 2
 Condition : ESH2-Z5 366 Phase : NEUTRAL
 Limit : FCC 15B-B
 Env. / Ins. : 24°C / 64% ESCI (1276) Engineer : Ken Yang
 EUT : EM3585
 Power Rating : DC 3.3V
 Test Mode : OPERATING

Freq. (MHz)	AMN Factor (dB)	Cable Loss (dB)	Pulse Att. (dB)	Emission					Remark
				Reading (dB μ V)	Level (dB μ V)	Limits (dB μ V)	Margin (dB)		
<hr/>									
1 0.194	0.12	0.03	9.85	20.51	30.51	53.84	23.33	Average	
2 0.194	0.12	0.03	9.85	40.62	50.62	63.84	13.22	QP	
3 0.263	0.12	0.03	9.86	17.79	27.80	51.34	23.54	Average	
4 0.263	0.12	0.03	9.86	32.31	42.32	61.34	19.02	QP	
5 0.592	0.14	0.04	9.85	17.74	27.77	46.00	18.23	Average	
6 0.592	0.14	0.04	9.85	32.01	42.04	56.00	13.96	QP	
7 3.123	0.23	0.08	9.86	19.31	29.48	46.00	16.52	Average	
8 3.123	0.23	0.08	9.86	28.71	38.88	56.00	17.12	QP	
9 9.451	0.40	0.14	9.89	18.85	29.28	50.00	20.72	Average	
10 9.451	0.40	0.14	9.89	22.93	33.36	60.00	26.64	QP	
11 23.140	0.68	0.23	9.96	20.72	31.59	50.00	18.41	Average	
12 23.140	0.68	0.23	9.96	25.07	35.94	60.00	24.06	QP	
<hr/>									

Remarks: 1. Emission Level= AMN Factor + Cable Loss + Pulse Att. + Reading.
 2. If the average limit is met when using a quasi-peak detector,
 the EUT shall be deemed to meet both limits and measurement
 with average detector is unnecessary.



Site no. : No.7 Shielded Room Data no. : 1
 Condition : ESH2-Z5 366 Phase : LINE
 Limit : FCC 15B-B
 Env. / Ins. : 24°C / 64% ESCI (1276) Engineer : Ken Yang
 EUT : EM3585
 Power Rating : DC 3.3V
 Test Mode : OPERATING

Freq. (MHz)	AMN Factor (dB)	Cable Loss (dB)	Pulse Att. (dB)	Emission				Remark
				Reading (dB μ V)	Level (dB μ V)	Limits (dB μ V)	Margin (dB)	
1 0.198	0.11	0.03	9.85	23.20	33.19	53.71	20.52	Average
2 0.198	0.11	0.03	9.85	40.65	50.64	63.71	13.07	QP
3 0.266	0.11	0.03	9.86	17.18	27.18	51.25	24.07	Average
4 0.266	0.11	0.03	9.86	30.93	40.93	61.25	20.32	QP
5 0.601	0.13	0.04	9.85	17.71	27.73	46.00	18.27	Average
6 0.601	0.13	0.04	9.85	31.50	41.52	56.00	14.48	QP
7 2.622	0.20	0.07	9.86	18.97	29.10	46.00	16.90	Average
8 2.622	0.20	0.07	9.86	29.33	39.46	56.00	16.54	QP
9 9.352	0.35	0.14	9.89	20.17	30.55	50.00	19.45	Average
10 9.352	0.35	0.14	9.89	24.69	35.07	60.00	24.93	QP
11 23.511	0.68	0.23	9.96	18.61	29.48	50.00	20.52	Average
12 23.511	0.68	0.23	9.96	23.34	34.21	60.00	25.79	QP

Remarks: 1. Emission Level= AMN Factor + Cable Loss + Pulse Att. + Reading.

2. If the average limit is met when using a quasi-peak detector,
 the EUT shall be deemed to meet both limits and measurement
 with average detector is unnecessary.


6. RADIATED EMISSION MEASUREMENT

6.1. Block Diagram of Test Setup

6.1.1. Block Diagram of EUT


Indicated as section 3.6

6.1.2. Setup Diagram for 30-1000 MHz



6.1.3. Semi-Anechoic Chamber (3m) Setup Diagram for above 1GHz

Antenna Tower



6.2. Radiated Emission Limits

In any 100kHz bandwidth outside the frequency band, the radio frequency power produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level. In addition, radiated emissions which fall in restricted bands, as defined in Section 15.205 and RSS-Gen Section 8.10 table 6, must also comply with the radiated emission limits specified as below.

Frequency (MHz)	Distance (m)	Field Strengths Limits	
		μV/m	dBμV/m
30 ~ 88	3	100	40.0
88 ~ 216	3	150	43.5
216 ~ 960	3	200	46.0
Above 960	3	500	54.0
Above 1000	3	74.0 dBμV/m (Peak) 54.0 dBμV/m (Average)	

Remark : (1) $\text{dB}\mu\text{V}/\text{m} = 20 \log (\mu\text{V}/\text{m})$

- (2) The tighter limit applies to the edge between two frequency bands.
- (3) Distance refers to the distance in meters between the measuring instrument antenna and the closed point of any part of the device or system.
- (4) Fundamental and emission fall within operation band are exempted from this section.
- (5) Pursuant to ANSI C63.10: 6.6.4.3, if the maximized peak measured value complies with the average limit, then it is unnecessary to perform an average measurement.

6.3. Test Procedure

The EUT setup on the turn table which has 1.5m height to the ground. The turn table rotated 360 degrees and antenna varied from 1 m to 4 m to find the maximum emission level. Both horizontal and vertical polarization are required. In order to find the maximum emission, all of the interface cables were manipulated according to ANSI C63.10-2013, RSS-Gen and RSS-247 regulation.

Frequency below 1 GHz:

Spectrum Analyzer is used for pre-testing with following setting:

- (1) RBW = 120KHz
- (2) VBW $\geq 3 \times$ RBW.
- (3) Detector = Peak.
- (4) Sweep time = auto.
- (5) Trace mode = max hold.
- (6) Allow sweeps to continue until the trace stabilizes.
- (7) When peak-detected value is lower than limit that the measurement using the Q.P. detector is not required. Otherwise using Q.P. for finally measurement.

Frequency above 1GHz to 10th harmonic:

Peak Detector:

- (1) RBW = 1MHz
- (2) VBW \geq 3 x RBW.
- (3) Detector = Peak.
- (4) Sweep time = auto.
- (5) Trace mode = max hold.
- (6) Allow sweeps to continue until the trace stabilizes.
- (7) When peak-detected value is lower than limit that the measurement using the average detector is not required. Otherwise using average detector for finally measurement.

Average Measurement:

Option 1:

- (1) RBW = 1 MHz
- (2) VBW = 1/T
- (3) Detector = Peak.
- (4) Sweep time = auto.
- (5) Trace mode = max hold.
- (6) Allow sweeps to continue until the trace stabilizes.

Option 2:

Average Emission Level= Peak Emission Level+ D.C.C.F.

6.4. Measurement Result Explanation

- Peak Emission Level=Antenna Factor + Cable Loss + Meter Reading
- Average Emission Level l=Antenna Factor + Cable Loss + Meter Reading
- Average Emission Level= Peak Emission Level+ DCCF
Duty Cycle Correction Factor (DCCF)= $20\log(\text{TX}_{\text{on}}/\text{TX}_{\text{on+off}})$ presented in section 3.4
- EPR= Peak Emission Level-95.2dB-2.14dBi

6.5. Test Results

PASSED.

Test Date	2015/11/17	Temp./Hum.	22°C/58%
Test Voltage	DC 3.3V (Via test jig powered by Test JIG)		

6.5.1. Emissions within Restricted Frequency Bands

6.5.1.1. Frequency Below 1 GHz

Mode	ZigBee	Frequency	TX 2405MHz
------	--------	-----------	------------

Antenna at Horizontal Polarization

Emission Frequency	Antenna Factor	Cable Loss	Meter Reading	Emission Level	Limits	Margin	Detector
(MHz)	(dB/m)	(dB)	(dB μ V)	(dB μ V/m)	(dB μ V/m)	(dB)	
299.66	13.12	4.65	25.04	42.81	46.00	3.19	Peak
500.45	16.98	6.44	19.83	43.25	46.00	2.75	Peak
749.74	19.41	6.95	10.11	36.47	46.00	9.53	Peak

Antenna at Vertical Polarization

Emission Frequency	Antenna Factor	Cable Loss	Meter Reading	Emission Level	Limits	Margin	Detector
(MHz)	(dB/m)	(dB)	(dB μ V)	(dB μ V/m)	(dB μ V/m)	(dB)	
299.66	13.12	4.65	20.99	38.76	46.00	7.24	Peak
500.45	16.98	6.44	19.40	42.82	46.00	3.18	Peak
749.74	19.41	6.95	6.86	33.22	46.00	12.78	Peak

Mode	ZigBee	Frequency	TX 2445MHz
------	--------	-----------	------------

Antenna at Horizontal Polarization

Emission Frequency	Antenna Factor	Cable Loss	Meter Reading	Emission Level	Limits	Margin	Detector
(MHz)	(dB/m)	(dB)	(dB μ V)	(dB μ V/m)	(dB μ V/m)	(dB)	
299.66	13.12	4.65	25.99	43.76	46.00	2.24	Peak
500.45	16.98	6.44	19.51	42.93	46.00	3.07	Peak
749.74	19.41	6.95	9.57	35.93	46.00	10.07	Peak

Antenna at Vertical Polarization

Emission Frequency	Antenna Factor	Cable Loss	Meter Reading	Emission Level	Limits	Margin	Detector
(MHz)	(dB/m)	(dB)	(dB μ V)	(dB μ V/m)	(dB μ V/m)	(dB)	
299.66	13.12	4.65	21.32	39.09	46.00	6.91	Peak
500.45	16.98	6.44	19.28	42.70	46.00	3.30	Peak
623.64	18.42	6.55	11.03	36.00	46.00	10.00	Peak

Mode	ZigBee	Frequency	TX 2480MHz
------	--------	-----------	------------

Antenna at Horizontal Polarization


Emission Frequency	Antenna Factor	Cable Loss	Meter Reading	Emission Level	Limits	Margin	Detector
(MHz)	(dB/m)	(dB)	(dB μ V)	(dB μ V/m)	(dB μ V/m)	(dB)	
299.66	13.12	4.65	24.95	42.72	46.00	3.28	Peak
500.45	16.98	6.44	19.56	42.98	46.00	3.02	Peak
749.74	19.41	6.95	11.64	38.00	46.00	8.00	Peak

Antenna at Vertical Polarization

Emission Frequency	Antenna Factor	Cable Loss	Meter Reading	Emission Level	Limits	Margin	Detector
(MHz)	(dB/m)	(dB)	(dB μ V)	(dB μ V/m)	(dB μ V/m)	(dB)	
299.66	13.12	4.65	20.58	38.35	46.00	7.65	Peak
500.45	16.98	6.44	20.06	43.48	46.00	2.52	Peak
749.74	19.41	6.95	6.89	33.25	46.00	12.75	Peak


6.5.1.2. Frequency Above 1 GHz to 10th harmonics

Band Edge:



Antenna at Horizontal Polarization


Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dB _u V)	Emission Level (dB _u V/m)	Limits (dB _u V/m)	Margin (dB)	Detector
2344.56	32.08	6.02	11.80	49.90	74.00	24.10	Peak
2390.04	32.16	6.08	10.90	49.14	74.00	24.86	Peak
2404.56	32.18	6.10	62.38	100.66	---	---	Peak



Antenna at Horizontal Polarization


Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dB _u V)	Emission Level (dB _u V/m)	Limits (dB _u V/m)	Margin (dB)	Detector
2389.92	32.16	6.08	-0.44	37.80	54.00	16.20	Average
2390.04	32.16	6.08	-0.41	37.83	54.00	16.17	Average
2405.04	32.18	6.10	58.61	96.89	---	---	Average

Mode	ZigBee	Frequency	TX 2405MHz
------	--------	-----------	------------



Antenna at Vertical Polarization


Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dB μ V)	Emission Level (dB μ V/m)	Limits (dB μ V/m)	Margin (dB)	Detector
2389.80	32.16	6.08	11.65	49.89	74.00	24.11	Peak
2390.04	32.16	6.08	10.58	48.82	74.00	25.18	Peak
2404.56	32.18	6.10	61.26	99.54	---	---	Peak



Antenna at Vertical Polarization


Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dB μ V)	Emission Level (dB μ V/m)	Limits (dB μ V/m)	Margin (dB)	Detector
2389.92	32.16	6.08	-0.77	37.47	54.00	16.53	Average
2390.04	32.16	6.08	-0.72	37.52	54.00	16.48	Average
2405.04	32.18	6.10	57.36	95.64	---	---	Average

Mode	ZigBee	Frequency	TX 2480MHz
------	--------	-----------	------------



Antenna at Horizontal Polarization


Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2479.44	32.28	6.18	55.90	94.36	---	---	Peak
2483.52	32.28	6.19	23.40	61.87	74.00	12.13	Peak
2483.60	32.28	6.19	23.22	61.69	74.00	12.31	Peak



Antenna at Horizontal Polarization


Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2480.00	32.28	6.18	52.15	90.61	---	---	Average
2483.52	32.28	6.19	13.28	51.75	54.00	2.25	Average
2483.60	32.28	6.19	12.64	51.11	54.00	2.89	Average

Mode	ZigBee	Frequency	TX 2480MHz
------	--------	-----------	------------



Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2479.44	32.28	6.18	55.60	94.06	---	---	Peak
2483.52	32.28	6.19	23.08	61.55	74.00	12.45	Peak
2483.60	32.28	6.19	23.14	61.61	74.00	12.39	Peak



Antenna at Vertical Polarization

Emission Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading (dBμV)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector
2480.00	32.28	6.18	51.55	90.01	---	---	Average
2483.52	32.28	6.19	12.78	51.25	54.00	2.75	Average
2483.60	32.28	6.19	12.13	50.60	54.00	3.40	Average

6.5.2. Emissions outside the frequency band:

The emissions (up to 25GHz) not reported for there is no emission be found.

Mode	ZigBee	Frequency	TX 2405MHz
------	--------	-----------	------------

Antenna at Horizontal Polarization

Emission Frequency	Antenna Factor	Cable Loss	Meter Reading	Emission Level	Limits	Margin
(MHz)	(dB/m)	(dB)	(dB μ V)	(dB μ V/m)	(dB μ V/m)	(dB)
4810.00	34.22	8.87	4.94	48.03	54.00	5.97 Peak

Antenna at Vertical Polarization

Emission Frequency	Antenna Factor	Cable Loss	Meter Reading	Emission Level	Limits	Margin
(MHz)	(dB/m)	(dB)	(dB μ V)	(dB μ V/m)	(dB μ V/m)	(dB)
4810.00	34.22	8.87	6.18	49.27	54.00	4.73 Peak

Mode	ZigBee	Frequency	TX 2445MHz
------	--------	-----------	------------

Antenna at Vertical Polarization

Emission Frequency	Antenna Factor	Cable Loss	Meter Reading	Emission Level	Limits	Margin
(MHz)	(dB/m)	(dB)	(dB μ V)	(dB μ V/m)	(dB μ V/m)	(dB)
4975.00	34.29	9.46	5.79	49.54	54.00	4.46 Peak

Mode	ZigBee	Frequency	TX 2480MHz
------	--------	-----------	------------

Antenna at Vertical Polarization


Emission Frequency	Antenna Factor	Cable Loss	Meter Reading	Emission Level	Limits	Margin
(MHz)	(dB/m)	(dB)	(dB μ V)	(dB μ V/m)	(dB μ V/m)	(dB)
4985.00	34.29	9.46	4.16	47.91	54.00	6.09 Peak

6.5.3. Emissions in Non-restricted Frequency Bands

Pursuant to KDB 558074 D01 v03r03 that emission levels below the 15.209 RSS-Gen Section 8.9 table 4 general radiated emissions limits is not required.

7. 6dB BANDWIDTH MEASUREMENT

7.1. Block Diagram of Test Setup



7.2. Specification Limits

The minimum 6dB bandwidth shall be at least 500kHz.

7.3. Test Procedure

Following measurement procedure is reference to KDB 558074 D01 DTS Meas Guidance v03r03:

■ Option 2

- (1) Set RBW = 100 kHz.
- (2) Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
- (3) Detector = Peak.
- (4) Trace mode = max hold.
- (5) Sweep = auto couple.
- (6) Allow the trace to stabilize.
- (7) Setting channel bandwidth function x dB to -6 dB to record the final bandwidth.


7.4. Test Results

Test Date	2015/11/18	Temp./Hum.	23°C/52%
Cable Loss	---	Test Voltage	DC 3.3V (Via test jig powered by Test JIG)

7.4.1. 6dB Bandwidth Result


Mode	Centre Frequency (MHz)	6 dB Bandwidth (MHz)
ZigBee	2405	1.597
	2445	1.599
	2480	1.603

7.4.2. Measurement Plots



8. MAXIMUM PEAK OUTPUT POWER MEASUREMENT

8.1. Block Diagram of Test Setup



8.2. Specification Limits

The Limits of maximum Peak Output Power for digital modulation in 2400-2483.5MHz is : 1Watt. (30dBm)

8.3. Test Procedure

Following measurement procedure is reference to KDB 558074 D01 DTS Meas Guidance v03r03:

PKPM1 Peak power meter method:

EUT is connected to power sensor and record the maximum output power.

Method AVGPM (Measurement using an RF average power meter):

EUT is connected to power sensor and record the maximum average output power and duty cycle factor is added when duty cycle presented in section 3.4 is < 98%.

RBW≥DTS bandwidth

- (1) Set span to at least 3 times the OBW
- (2) Set RBW \geq OBW
- (3) Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
- (4) Detector = Peak
- (5) Trace mode = max hold
- (6) Sweep = auto couple.
- (7) To find the peak amplitude level.

8.4. Test Results


Test Date	2015/11/18	Temp./Hum.	23°C/52%
Cable Loss	1.4dB	Test Voltage	DC 3.3V (Via test jig powered by Test JIG)

8.4.1. Peak Output Power

Mode	Centre Frequency (MHz)	Peak Output Power		Limit
		(dBm)	(W)	
ZigBee	2405	7.889	0.006150	< 30 dBm (1 W)
	2440	7.841	0.006083	
	2480	3.187	0.002083	


Note: The results have been included cable loss.

8.4.2. Peak Measurement Plots



9. EMISSION LIMITATIONS MEASUREMENT

9.1. Block Diagram of Test Setup



9.2. Specification Limits

In any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a)/RSS-Gen Section 8.9 table 4 is not required. In addition, radiated emissions which fall in restricted bands, as defined in Section 15.205(a)/RSS-Gen Section 8.10 table 6, must also comply with the radiated emission limits specified in Section 15.209(a)/RSS-Gen Section 8.9 table 4 (See Section 15.205(c)).

9.3. Test Procedure

Following measurement procedure is reference to KDB 558074 D01 DTS Meas Guidance v03r03:

■ Reference Level


- (1) Set analyzer center frequency to DTS channel center frequency.
- (2) Set the span to 1.5 times the DTS bandwidth.
- (3) Set the RBW to: 100 kHz.
- (4) Set the VBW $\geq 3 \times$ RBW.
- (5) Detector = peak.
- (6) Sweep time = auto couple.
- (7) Trace mode = max hold.
- (8) Allow trace to fully stabilize to find the max PSD as reference level.

■ Emission Level Measurement

- (1) Set analyzer center frequency to DTS channel center frequency.
- (2) Set the span to 1.5 times the DTS bandwidth.
- (3) Set the RBW to: 100 kHz.
- (4) Set the VBW $\geq 3 \times$ RBW.
- (5) Detector = peak.
- (6) Sweep time = auto couple.
- (7) Trace mode = max hold.
- (8) Allow trace to fully stabilize to find the max level.

9.4. Test Results

Test Date	2015/11/18	Temp./Hum.	23°C/52%
Mode	ZigBee	Frequency	TX 2405MHz
Cable Loss	1.4dB	Test Voltage	DC 3.3V (Via test jig powered by Test JIG)




File Number: CIM1511059


Report Number: EM-F150710

This test report may be reproduced in full only. The document may only be updated by AUDIX Technology Corp. personnel Any changes will be noted in the Document History section of the report.

Test Date	2015/11/18	Temp./Hum.	23°C/52%
Mode	ZigBee	Frequency	TX 2445MHz
Cable Loss	1.4dB	Test Voltage	DC 3.3V (Via test jig powered by Test JIG)




Test Date	2015/11/18	Temp./Hum.	23°C/52%
Mode	ZigBee	Frequency	TX 2480MHz
Cable Loss	1.4dB	Test Voltage	DC 3.3V (Via test jig powered by Test JIG)



10. POWER SPECTRAL DENSITY

10.1. Block Diagram of Test Setup



10.2. Specification Limits

The peak power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3kHz band.

10.3. Test Procedure

Following measurement procedure is reference to KDB 558074 D01 DTS Meas Guidance v03r03:

■Method PKPSD (peak PSD)


- (1) Set analyzer center frequency to DTS channel center frequency.
- (2) Set the span to 1.5 times the DTS bandwidth.
- (3) Set the RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
- (4) Set the VBW $\geq 3 \times \text{RBW}$.
- (5) Detector = peak.
- (6) Sweep time = auto couple.
- (7) Trace mode = max hold.
- (8) Allow trace to fully stabilize.
- (9) Use the peak marker function to determine the maximum amplitude level.
- (10) If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

□Method AVGPSD-2

- (1) Using peak PSD procedure step 1 to step 4.
- (2) Detector= RMS detector
- (3) Sweep time = auto couple
- (4) Trace mode = trace averaging over a minimum of 100 traces
- (5) Use the peak marker function to determine the maximum amplitude level.
- (6) Duty cycle factor is added when duty cycle presented in section 3.4 < 98%.
- (7) If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

10.4. Test Results

Test Date	2015/11/18	Temp./Hum.	23°C/52%
Cable Loss	1.4dB	Test Voltage	DC 3.3V (Via test jig powered by Test JIG)



11.DEVIATION TO TEST SPECIFICATIONS

【NONE】