The Measurement of Conducted Spurious Emissions

CONDUCTED SPURIOUS EMISSIONS MEASUREMENT

1. LIMITS OF CONDUCTED SPURIOUS EMISSIONS EASUREMENT

Below 20dB of the highest emission level of operating band (in 100KHz Resolution Bandwidth, see Section 15.247(c)). Emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the limits specified in Section 15.209(a) (see Section 15.205(c)).

2. TEST INSTRUMENTS

| Description & Manufacturer | Model No. | Serial No. | Calibrated Until |
|----------------------------|---------------------|------------|------------------|
| R&S SPECTRUM ANALYZER | FSP40 | 100036 | Nov. 27, 2005 |
| High pass filter | WHK3.1/18G- 10SS | SN4 | Jun. 8, 2005 |

NOTE:

1.The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.


3. TEST PROCEDURE

2.5GHz~13GHz:

The transmitter output was connected to the spectrum analyzer via a low lose cable and a high pass filter. Set both RBW and VBW of spectrum analyzer to 100 kHz with suitable frequency span including 100 kHz bandwidth from band edge. The band edges was measured and recorded.

13GHz~25GHz:

The transmitter output was connected to the spectrum analyzer via a low lose cable. Set both RBW and VBW of spectrum analyzer to 100 kHz with suitable frequency span including 100 kHz bandwidth from band edge. The band edges was measured and recorded.




5. EUT OPERATING CONDITIONS

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

TEST RESULTS - For 802.11b


The spectrum plots are attached on the following 2 pages. It shows compliance with the requirement in part 15.247(C),.15.205 and 15.209.

| EN | < E 1 | _ | TAT | N | | | 3 | 1 1 | |
|-----------------------|-------------------|----------------|-------------------------|-----------|-----|-----|------------|------|-----|
| 0 dBm 0 GHz | mab 0 | | 0 GHZ 3 dBm | 0 GHZ | | | 3 | | _ |
| [T1] -49.10 | -49.80 | T1 -49.28 | T1 -48,43 | 0000 | | - | 3- | + + | - |
| w. | 1 [T1] -49,80 | 171 Z | .236000 3 [T1 -48 | 648000000 | | | The second | | |
| Marker 4 12.0 | Marker | | | a | | | 3 | | _ |
| Mar | Mar | Mar | Marker | | | | MAN NO | | |
| kHz kHz | | | | | | | 3 | | |
| 100 | - | | | - | | | 3 | | _ |
| • RBW • VBW SWT | | | | | | | 3 | | |
| •• | | | - | - | | _ | 5 | | _ |
| 쀡 | | | | 11 | | | 4 Fault | | |
| 30 | | | | | | | - Ala | | |
| .Att | | | | dBm m | | | - Internet | | |
| | | dBm | | -12.09 0 | | | wheel | | |
| | 1 dB | 7.91 d | - | | | - | N 100 | | - |
| dBm | | -01 7. | | 05 | | | Tan | | |
| 20 dBm | Offset | Ĩ | 1 | 1 | | | - | | |
| Ref | 20 | | | 01 | -07 | -40 | 1 | -70- | -80 |
| 8 | | 1 PK | | | | | | | |
| v | | 11212 | 5 | | | | | | |
| | | | | | | | | | |
| | | | | | | | | | |
| | | | | | | | | | |
| | | | | | | | | | |




TEST RESULTS – For 802.11g

The spectrum plots are attached on the following 2 pages. It shows compliance with the requirement in part 15.247(C),.15.205 and 15.209.




Ch11




TEST RESULTS – For 802.11a, Normal mode


The spectrum plots are attached on the following 6 pages. It shows compliance with the requirement in part 15.247(C),.15.205 and 15.209.

Ch1





Ch4






Ch8






Ch13




TEST RESULTS – For 802.11a, Turbo

The spectrum plots are attached on the following 5 pages. It shows compliance with the requirement in part 15.247(C),.15.205 and 15.209.



Ch2



Ch3

