



EMC

TEST REPORT

REPORT NO. : F87070608
MODEL NO. : K3C800A, K2C800A
DATE OF TEST : July 10, 1998

PREPARED FOR : DEXIN CORP.

ADDRESS : 20F, 37, SEC. 2, SAN-MING RD.,
PAN-CHIAO CITY, TAIPEI HSIEN, TAIWAN

PREPARED BY: ADVANCE DATA TECHNOLOGY CORPORATION



Accredited Laboratory

12F, NO.1, SEC.4, NAN-KING EAST RD.,
TAIPEI, TAIWAN, R.O.C.

This test report consists of 13 pages in total. It may be duplicated completely for legal use with the allowance of the applicant. It shall not be reproduced except in full, without the written approval of our laboratory. It should not be used by the client to claim product endorsement by NVLAP or any agency of the U.S. government. The test result in the report only applies to the tested sample.



TABLE OF CONTENTS

1.	CERTIFICATION.....	3
2.	GENERAL INFORMATION.....	4
2.1	GENERAL DESCRIPTION OF EUT.....	4
2.2	DESCRIPTION OF SUPPORT UNITS.....	5
2.3	TEST METHODOLOGY AND CONFIGURATION.....	5
3.	TEST INSTRUMENTS.....	6
3.1	TEST INSTRUMENTS (EMISSION).....	6
3.2	LIMITS OF CONDUCTED AND RADIATED EMISSION.....	7
4.	TEST RESULTS (EMISSION).....	8
4.1	RADIO DISTURBANCE.....	8
4.1.1	EUT OPERATION CONDITION.....	8
4.2	TEST DATA OF CONDUCTED EMISSION.....	9
4.3	TEST DATA OF RADIATED EMISSION.....	10
5.	PHOTOGRAPHS OF THE TEST CONFIGURATION WITH MINIMUM MARGIN....	12



1.

CERTIFICATION

Issue Date: July 15, 1998

Product : MOUSE
Trade Name : DEXIN
Model No. : K3C800A, K2C800A
Applicant : DEXIN CORP.
Standard : FCC Part 15, Subpart B, Class B
ANSI C63.4-1992
CISPR 22:1993+A1+A2

We hereby certify that one sample of the designation has been tested in our facility on July 10, 1998. The test record, data evaluation and Equipment Under Test (EUT) configurations represent herein are true and accurate representation of the measurements of the sample's EMC characteristics under the conditions herein specified.

The test results show that the EUT as described in this report is in compliance with the Class B limits of conducted and radiated emission of applicable standards.

TESTED BY: Ken Liu, DATE: 7/15/98
(Ken Liu)

CHECKED BY: Sharon Hsiung, DATE: 7/15/98
(Sharon Hsiung)

APPROVED BY: Mike Su, DATE: 7/15/98
(Mike Su)

ADVANCE DATA TECHNOLOGY CORPORATION**NVLAP[®]**

Accredited Laboratory



2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

Product	:	MOUSE
Model No.	:	K3C800A, K2C800A
Power Supply Type	:	DC (from PC)
Data Cable	:	Shielded (1.5m)

Note: The EUT has two models, which are identical to each other in all aspects except for the following:

- MODEL: K3C800A (with three buttons)
- MODEL: K2C800A (with two buttons)

From the above models, model K3C800A was selected as the representative during the test and only its data is recorded in this report.

For more detailed features description, please refer to manufacturer's specification or User's Manual.



2.2 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories are used to form representative test configuration during the tests.

No.	Product	Brand	Model No.	FCC ID	I/O Cable
1	PERSONAL COMPUTER	HP	D2145A	B94C2145X	Nonshielded Power (1.8m)
2	MONITOR	ADI	PD-959	Doc approved	Shielded Signal (1.5m) Nonshielded Power (1.8m)
3	KEYBOARD	BTC	5140	E5XKBM10410	Shielded signal (1.4m)
4	PRINTER	HP	2225C+	DSI6XU2225	Shielded Signal (1.2m) Nonshielded Power (1.8m)
5	MODEM	ACEEX	1414	IFAXDM1414	Shielded signal (1.2m) Nonshielded Power (1.8m)

2.3 TEST METHODOLOGY AND CONFIGURATION

Both conducted and radiated testing were performed according to the procedures in ANSI C63.4:1992. Radiated testing was performed at an antenna to EUT distance of 3m and 10 m on an open area test site. Please refer to the photos of test configuration in Item 5.



3. TEST INSTRUMENTS

3.1 TEST INSTRUMENTS (EMISSION)

RADIATED EMISSION MEASUREMENT

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
HP Spectrum Analyzer	8590L	3544A01042	April 29, 1999
HP Preamplifier	8447D	2944A08313	Sept. 18, 1998
ROHDE & SCHWARZ TEST RECEIVER	ESVS 30	841977/008	Oct. 5, 1998
SCHWARZBECK Tunable Dipole Antenna	VHA 9103 UHA 9105	E101051 E101055	Nov. 28, 1998
CHASE BiLOG Antenna	CBL6111A	1647	Aug. 2, 1998
EMCO Turn Table	1016	1722	N/A
EMCO Tower	1051	1263	N/A
Open Field Test Site	Site 4	ADT-R04	Aug. 1, 1998

- Note: 1. The measurement uncertainty is less than +/- 3dB, which is calculated as per NAMA's document NIS81.
2. The calibration interval of the above test instruments is 12 months. And the calibrations are traceable to NML/ROC and NIST/USA.

CONDUCTED EMISSION MEASUREMENT

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
ROHDE & SCHWARZ Test Receiver	ESHS30	828765/002	July 31, 1998
ROHDE & SCHWARZ Artificial Mains Network	ESH2-Z5	828075/003	July 28, 1998
EMCO-L.I.S.N. Shielded Room	3825/2 Site 5	90031627 ADT-C05	July 28, 1998 N/A

- Note: 1. The measurement uncertainty is less than +/- 2.6dB, which is calculated as per NAMA's document NIS81.
2. The calibration interval of the above test instruments is 12 months. And the calibrations are traceable to NML/ROC and NIST/USA.



3.2 LIMITS OF CONDUCTED AND RADIATED EMISSION

LIMIT OF RADIATED EMISSION OF CISPR 22

FREQUENCY (MHz)	Class A (at 10m)	Class B (at 10m)
	dBuV/m	dBuV/m
30 - 230	40	30
230 - 1000	47	37

LIMIT OF RADIATED EMISSION OF FCC PART 15, SUBPART B FOR FREQUENCY ABOVE 1000 MHz

FREQUENCY (MHz)	Class A (at 10m)		Class B (at 3m)	
	uV/m	dBuV/m	uV/m	dBuV/m
Above 1000	300	49.5	500	54.0

- Note: (1) The lower limit shall apply at the transition frequencies.
 (2) Emission level (dBuV/m) = 20 log Emission level (uV/m).
 (3) All emanation from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

LIMIT OF CONDUCTED EMISSION OF CISPR 22

FREQUENCY (MHz)	Class A (dBuV)		Class B (dBuV)	
	Quasi-peak	Average	Quasi-peak	Average
0.15 - 0.5	79	66	66 - 56	56 - 46
0.50 - 5.0	73	60	56	46
5.0 - 30.0	73	60	60	50

- Note: (1) The lower limit shall apply at the transition frequencies.
 (2) The limit decreases linearly with the logarithm of the frequency in the range 0.15 to 0.50 MHz
 (3) All emanation from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.



4. TEST RESULTS (EMISSION)

4.1 RADIO DISTURBANCE

Frequency Range	:	0.15 - 30 MHz (Conducted Emission) 30 - 2000 MHz (Radiated Emission)
Input Voltage	:	120 Vac, 60 Hz
Temperature	:	29 °C
Humidity	:	60 %
Atmospheric Pressure	:	997 mbar

TEST RESULT	Remarks
PASS	Minimum passing margin of conducted emission: -17.1 dB at 4.191 MHz Minimum passing margin of radiated emission: -6.4 dB at 165.81 MHz

Note: The EUT can be connected to COM port via a PS/2 to RS232 adapter. During the pretest, the worst emission levels were found when the EUT was connected to the COM port and therefore the data of only this mode is recorded in this report.

4.1.1 EUT OPERATION CONDITION

1. Turn on the power of all equipments.
2. PC runs a test program to enable all functions.
3. PC reads and writes messages from FDD and HDD.
4. PC sends "H" messages to monitor and monitor displays "H" patterns on screen.
5. PC sends "H" messages to modem.
6. PC sends "H" messages to printer, and the printer prints them on paper.
7. Repeat steps 3-7.



4.2 TEST DATA OF CONDUCTED EMISSION

EUT: **MOUSE**MODEL: **K3C800A**

6 dB Bandwidth: 10 kHz

TEST PERSONNEL: *KEN*

Freq. [MHz]	L Level		N Level		Limit		Margin [dB (μV)]			
	[dB (μV)]		[dB (μV)]		[dB (μV)]		L		N	
	QP	AV	QP	AV	QP	AV	QP	AV	QP	AV
0.234	42.70	-	42.10	-	62.30	52.30	-19.6	-	-20.2	-
0.348	26.50	-	23.90	-	59.01	49.01	-32.5	-	-35.1	-
0.582	26.10	-	17.30	-	56.00	46.00	-29.9	-	-38.7	-
1.982	30.20	-	27.40	-	56.00	46.00	-25.8	-	-28.6	-
4.191	38.90	-	38.20	-	56.00	46.00	-17.1	-	-17.8	-
7.982	39.60	-	39.90	-	60.00	50.00	-20.4	-	-20.1	-

- Remarks:
1. "*": Undetectable
 2. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 3. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 4. The emission level of other frequencies were very low against the limit.
 5. Margin value = Emission level - Limit value.

ADT CO. SITE 5
CISPR 22 CLASS B

10. Jul 98 13:42


EUT: K3C800A
Test Spec: LISN : L

Report No. F87070608
Page 9-1
Tested by KEN

Fast Scan Settings (3 Ranges)

Frequencies			Receiver Settings					
Start	Stop	Step	IF BW	Detector	M-Time	Atten	Preamp	OpRge
150k	450k	3k	10k	PK	1ms	10dB	OFF	60dB
450k	5M	3k	10k	PK	1ms	10dB	OFF	60dB
5M	30M	3k	10k	PK	1ms	10dB	OFF	60dB

dBuV ◇ Mkr : 234.00 kHz 43.2 dBuV



ADT CO. SITE 5
 CISPR 22 CLASS B


10. JUL 98 14:01

EUT: K3C800A
 Test Spec: LISN : N

Report No. F87070608
 Page 9-2
 Tested by KEN

Fast Scan Settings (3 Ranges)

Frequencies			Receiver Settings					
Start	Stop	Step	IF BW	Detector	M-Time	Atten	Preamplifier	OpRge
150k	450k	3k	10k	PK	1ms	10dBLN	OFF	60dB
450k	5M	3k	10k	PK	1ms	10dBLN	OFF	60dB
5M	30M	3k	10k	PK	1ms	10dBLN	OFF	60dB





4.3 TEST DATA OF RADIATED EMISSION

EUT: **MOUSE**MODEL: **K3C800A**

ANTENNA: CHASE BILOG CBL 6111A

POLARITY: Horizontal

DETECTOR FUNCTION: Quasi-peak

6 dB BANDWIDTH: 120 kHz

FREQUENCY RANGE: 30-1000 MHz

MEASURED DISTANCE: 10 M

TEST PERSONNEL:

KEN

Frequency (MHz)	Correction Factor (dB/m)	Reading Data (dBuV)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)
57.27	8.6	12.0	20.6	30.0	-9.4
129.82	14.3	8.0	22.3	30.0	-7.7
165.78	11.9	10.4	22.3	30.0	-7.7
200.54	11.6	6.0	17.6	30.0	-12.4
232.12	13.7	11.0	24.7	37.0	-12.3
265.28	15.8	9.5	25.3	37.0	-11.7

- REMARKS :
1. Emission level (dBuV/m) = Correction Factor(dB/m) + Meter Reading (dBuV).
 2. Correction Factor(dB/m) = Ant. Factor(dB/m)+Cable loss(dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level - Limit value.



TEST DATA OF RADIATED EMISSION

EUT: **MOUSE**MODEL: **K3C800A**

ANTENNA: CHASE BILOG CBL 6111A

POLARITY: Vertical

DETECTOR FUNCTION: Quasi-peak

6 dB BANDWIDTH: 120 kHz

FREQUENCY RANGE: 30-1000 MHz

MEASURED DISTANCE: 10 M

TEST PERSONNEL: *KEN*

Frequency (MHz)	Correction Factor (dB/m)	Reading Data (dBuV)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)
57.00	8.1	13.1	21.2	30.0	-8.8
129.82	14.4	5.9	20.3	30.0	-9.7
165.81	12.4	11.2	23.6	30.0	-6.4
200.54	12.1	10.0	22.1	30.0	-7.9
232.12	13.4	9.3	22.7	37.0	-14.3
265.28	15.0	11.8	26.8	37.0	-10.2

- REMARKS :
1. Emission level (dBuV/m) = Correction Factor(dB/m) + Meter Reading (dBuV).
 2. Correction Factor(dB/m) = Ant. Factor(dB/m)+Cable loss(dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level - Limit value.