

# FCC TEST REPORT

**REPORT NO.:** RF940513L04

**MODEL NO.:** M071017

**RECEIVED:** May 12, 2005

**TESTED:** May 13 ~ May 24, 2005

**ISSUED:** May 25, 2005

**APPLICANT:** DEXIN Corporation

**ADDRESS:** 14F-8, No 258, Lian Cheng Rd., Chung Ho  
City, Taipei Hsien, Taiwan, R.O.C

**ISSUED BY:** Advance Data Technology Corporation

**LAB ADDRESS:** No. 47, 14<sup>th</sup> Ling, Chia Pau Tsuen, Lin Kou  
Hsiang 244, Taipei Hsien, Taiwan, R.O.C.

**TEST LOCATION:** No. 19, Hwa Ya 2<sup>nd</sup> Rd., Wen Hwa Tsuen,  
Kwei Shan Hsiang, Taoyuan Hsien 333,  
Taiwan, R.O.C.

This test report consists of 15 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product endorsement by CNLA, A2LA or any government agencies. The test results in the report only apply to the tested sample.



No. 2177-01



0528  
ILAC MRA



## Table of Contents

1	CERTIFICATION .....	3
2	SUMMARY OF TEST RESULTS .....	4
2.1	MEASUREMENT UNCERTAINTY .....	4
3	GENERAL INFORMATION .....	5
3.1	GENERAL DESCRIPTION OF EUT .....	5
3.2	DESCRIPTION OF TEST MODES .....	6
3.2.1	CONFIGURATION OF SYSTEM UNDER TEST .....	6
3.2.2	TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL .....	7
3.2	GENERAL DESCRIPTION OF APPLIED STANDARDS .....	7
3.3	DESCRIPTION OF SUPPORT UNITS .....	7
4	TEST PROCEDURE AND RESULT .....	8
4.1	CONDUCTED EMISSION MEASUREMENT .....	8
4.2	RADIATED EMISSION MEASUREMENT .....	8
4.2.1	LIMITS OF RADIATED EMISSION MEASUREMENT .....	8
4.2.2	TEST INSTRUMENT .....	9
4.2.3	TEST PROCEDURE .....	10
4.2.4	TEST SETUP .....	11
4.2.5	EUT OPERATING CONDITION .....	11
4.2.6	TEST RESULTS .....	12
4	PHOTOGRAPHS OF THE TEST CONFIGURATION .....	14
5	INFORMATION ON THE TESTING LABORATORIES .....	15



## 1 CERTIFICATION

**PRODUCT:** WIRELESS NUMERIC KEYPAD W/ BUILT IN OPTICAL MICE  
**BRAND NAME:** iConcepts  
**MODEL NO:** M071017  
**TEST SAMPLE:** ENGINEERING SAMPLE  
**TESTED:** May 13 ~ May 24, 2005  
**APPLICANT:** DEXIN Corporation  
**STANDARDS:** FCC Part 15, Subpart C (Section 15.209), ANSI C63.4-2003

The above equipment has been tested by **Advance Data Technology Corporation**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

**PREPARED BY** : Windy Chou , **DATE:** May 25, 2005  
(Windy Chou)

**TECHNICAL ACCEPTANCE** : Gary Chang , **DATE:** May 25, 2005  
Responsible for  
RF  
(Gary Chang)

**APPROVED BY** : Cody Chang , **DATE:** May 25, 2005  
(Cody Chang, Deputy Manager)



## 2 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

<b>APPLIED STANDARD: FCC Part 15, Subpart C</b>			
<b>STANDARD PARAGRAPH</b>	<b>TEST TYPE</b>	<b>RESULT</b>	<b>REMARK</b>
15.207	Conducted Emission Test	N/A	Power supply is 3Vdc from batteries
15.209	Radiated Emission Test	PASS	Minimum passing margin is -2.23dB at 434.33MHz

### 2.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4:

<b>MEASUREMENT</b>	<b>FREQUENCY</b>	<b>UNCERTAINTY</b>
Conducted emissions	9kHz~30MHz	2.44 dB
Radiated emissions	30MHz ~ 200MHz	3.63 dB
	200MHz ~1000MHz	3.65 dB
	1GHz ~ 18GHz	2.20 dB
	18GHz ~ 40GHz	1.88 dB

### 3 GENERAL INFORMATION

#### 3.1 GENERAL DESCRIPTION OF EUT

<b>PRODUCT</b>	WIRELESS NUMERIC KEYPAD W/ BUILT IN OPTICAL MICE
<b>MODEL NO.</b>	M071017
<b>POWER SUPPLY</b>	3Vdc from batteries
<b>MODULATION TYPE</b>	ASK
<b>CARRIER FREQUENCY OF EACH CHANNEL</b>	433.92MHz
<b>NUMBER OF CHANNEL</b>	1
<b>ANTENNA TYPE</b>	Internal copper trace antenna
<b>DATA CABLE</b>	NA
<b>I/O PORTS</b>	NA
<b>ASSOCIATED DEVICES</b>	NA

**NOTE:**

1. This EUT is a Wireless Mouse with Keyboard function.
2. The above EUT information was declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or User's Manual.


### 3.2 DESCRIPTION OF TEST MODES

One channel was provided to this EUT.

Channel	Frequency
1	433.92MHz

**Note:** There are two test modes. The test mode 1 is for the Keyboard function and test mode 2 is for the Mouse function.

#### 3.2.1 CONFIGURATION OF SYSTEM UNDER TEST





**3.2.2 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL**

EUT configure mode	Applicable to		Description
	PLC	RE<5G	
1	v	v	Keyboard function
2	v	v	Mouse function

Where PLC: Power Line Conducted Emission RE<5G RE: Radiated Emission below 5GHz

**Radiated Emission Test (Below 5 GHz):**

Following channel(s) was (were) selected for the final test as listed below.

EUT configure mode	Available Channel	Tested Channel	Modulation Type
1	1	1	ASK
2	1	1	ASK

**3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS**

The EUT is a WIRELESS NUMERIC KEYPAD W/ BUILT IN OPTICAL MICE. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

**FCC Part 15, Subpart C. (15.209)**  
**ANSI C63.4-2003**

All test items have been performed and recorded as per the above standards.

**3.4 DESCRIPTION OF SUPPORT UNITS**

NA

## 4 TEST PROCEDURE AND RESULT

### 4.1 CONDUCTED EMISSION MEASUREMENT

NA

### 4.2 RADIATED EMISSION MEASUREMENT

#### 4.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT

Field strength limits are at the distance of 3 meters, Emissions radiated outside of the specified bands, shall be according to the general radiated limits in 15.209 as following:

Frequencies (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.



## 4.2.2 TEST INSTRUMENT

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
Test Receiver ROHDE & SCHWARZ	ESI7	838496/016	Jan. 07, 2006
Spectrum Analyzer ROHDE & SCHWARZ	FSP40	100041	Nov. 29, 2005
BILOG Antenna SCHWARZBECK	VULB9168	9168-155	Jan. 22, 2006
HORN Antenna SCHWARZBECK	BBHA 9120D	9120D-404	Jan. 05, 2006
HORN Antenna SCHWARZBECK	BBHA 9170	BBHA 9170242	Jan. 23, 2006
Preamplifier Agilent	8447D	2944A10631	Nov. 17, 2005
Preamplifier Agilent	8449B	3008A01960	Nov. 14, 2005
RF signal cable HUBER+SUHNNER	SUCOFLEX 104	219272/4	Jan. 26, 2006
RF signal cable HUBER+SUHNNER	SUCOFLEX 104	219275/4	Jan. 26, 2006
Software ADT.	ADT_Radiated_V5.14	NA	NA
Antenna Tower inn-co GmbH	MA 4000	010303	NA
Antenna Tower Controller inn-co GmbH	CO2000	019303	NA
Turn Table ADT.	TT100.	TT93021704	NA
Turn Table Controller ADT.	SC100.	SC93021704	NA

- NOTE:**
1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
  2. The test was performed in HwaYa Chamber 3.
  3. The horn antenna and HP preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
  4. The IC Site Registration No. is IC4924-4.


### 4.2.3 TEST PROCEDURE

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10 dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10 dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

**NOTE:**

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Peak detection (PK) and Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 1MHz for Peak detection (PK) at frequency above 1GHz.

#### 4.2.4 TEST SETUP



For the actual test configuration, please refer to the related item in this test report - Photographs of the Test Configuration.

#### 4.2.5 EUT OPERATING CONDITION

Set the transmitter part of EUT under transmission condition continuously at specific channel frequency.



4.2.6 TEST RESULTS

**Below 1GHz Worst-Case Data**

<b>EUT</b>	WIRELESS NUMERIC KEYPAD W/ BUILT IN OPTICAL MICE	<b>MEASUREMENT DETAIL</b>	
<b>MODEL</b>	M071017	<b>FREQUENCY RANGE</b>	Below 5GHz
<b>INPUT POWER</b>	3Vdc	<b>DETECTOR FUNCTION</b>	Quasi-Peak
<b>ENVIRONMENTAL CONDITIONS</b>	25 deg. C, 64 % RH, 991 hPa	<b>TEST MODE</b>	1
<b>TESTED BY</b>	Brad Wu		

**ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M**

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	<b>*434.33</b>	<b>43.77 QP</b>	<b>46.00</b>	<b>-2.23</b>	<b>1.00 H</b>	<b>205</b>	<b>26.17</b>	<b>17.60</b>
2	739.52	23.07 QP	46.00	-22.93	1.00 H	238	0.09	22.98
3	819.22	23.42 QP	46.00	-22.58	1.50 H	223	-0.21	23.63
4	867.82	35.42 QP	46.00	-10.58	1.50 H	298	11.19	24.23
5	914.47	25.18 QP	46.00	-20.82	1.50 H	121	0.22	24.96
6	953.35	25.60 QP	46.00	-20.40	1.75 H	193	0.26	25.34

**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M**

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*434.33	35.05 QP	46.00	-10.95	1.00 V	112	17.45	17.60
2	735.63	23.14 QP	46.00	-22.86	1.75 V	10	0.26	22.89
3	819.22	22.75 QP	46.00	-23.25	1.75 V	298	-0.88	23.63
4	867.82	29.51 QP	46.00	-16.49	1.00 V	223	5.28	24.23
5	904.75	36.14 QP	46.00	-9.86	3.00 V	94	11.28	24.86
6	945.57	26.42 QP	46.00	-19.58	3.00 V	154	1.14	25.28

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
  2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
  3. The other emission levels were very low against the limit.
  4. Margin value = Emission level – Limit value.
  5. “\*” = Fundamental frequency



<b>EUT</b>	WIRELESS NUMERIC KEYPAD W/ BUILT IN OPTICAL MICE	<b>MEASUREMENT DETAIL</b>	
<b>MODEL</b>	M071017	<b>FREQUENCY RANGE</b>	Below 5GHz
<b>INPUT POWER</b>	3Vdc	<b>DETECTOR FUNCTION</b>	Quasi-Peak
<b>ENVIRONMENTAL CONDITIONS</b>	25 deg. C, 64 % RH, 991 hPa	<b>TEST MODE</b>	2
<b>TESTED BY</b>	Brad Wu		


<b>ANTENNA POLARITY &amp; TEST DISTANCE: HORIZONTAL AT 3 M</b>								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*434.33	42.91 QP	46.00	-3.09	2.00 H	166	25.31	17.60
2	741.46	23.19 QP	46.00	-22.81	1.00 H	130	0.16	23.03
3	809.50	23.48 QP	46.00	-22.52	2.00 H	16	-0.06	23.55
4	842.55	23.02 QP	46.00	-22.98	4.00 H	25	-0.82	23.84
5	867.82	38.60 QP	46.00	-7.40	1.00 H	130	14.37	24.23
6	945.57	26.36 QP	46.00	-19.64	1.00 H	139	1.07	25.28

<b>ANTENNA POLARITY &amp; TEST DISTANCE: VERTICAL AT 3 M</b>								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*434.33	36.45 QP	46.00	-9.55	2.00 V	55	18.85	17.60
2	720.08	22.45 QP	46.00	-23.55	2.00 V	175	-0.05	22.50
3	745.35	22.93 QP	46.00	-23.07	3.00 V	160	-0.20	23.13
4	817.27	23.39 QP	46.00	-22.61	4.00 V	160	-0.23	23.62
5	867.82	27.16 QP	46.00	-18.84	1.00 V	151	2.93	24.23
6	945.57	27.25 QP	46.00	-18.75	1.00 V	310	1.97	25.28

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
  2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
  3. The other emission levels were very low against the limit.
  4. Margin value = Emission level – Limit value.
  5. "\*" = Fundamental frequency

#### 4 PHOTOGRAPHS OF THE TEST CONFIGURATION

##### RADIATED EMISSION TEST





## 5 INFORMATION ON THE TESTING LABORATORIES

We, ADT Corp., were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved by the following approval agencies according to ISO/IEC 17025.

<b>USA</b>	FCC, NVLAP, UL , A2LA
<b>Germany</b>	TUV Rheinland
<b>Japan</b>	VCCI
<b>Norway</b>	NEMKO
<b>Canada</b>	INDUSTRY CANADA , CSA
<b>R.O.C.</b>	CNLA, BSMI, DGT
<b>Netherlands</b>	Telefication
<b>Singapore</b>	PSB , GOST-ASIA(MOU)
<b>Russia</b>	CERTIS(MOU)

Copies of accreditation certificates of our laboratories obtained from approval agencies can be downloaded from our web site: [www.adt.com.tw/index.5/phtml](http://www.adt.com.tw/index.5/phtml).

If you have any comments, please feel free to contact us at the following:

**Linko EMC/RF Lab:**

Tel: 886-2-26052180  
Fax: 886-2-26052943

**Hsin Chu EMC/RF Lab:**

Tel: 886-3-5935343  
Fax: 886-3-5935342

**Hwa Ya EMC/RF/Safety/Telecom Lab:**

Tel: 886-3-3183232  
Fax: 886-3-3185050

**Linko RF Lab.**

Tel: 886-3-3270910  
Fax: 886-3-3270892

**Web Site:** [www.adt.com.tw](http://www.adt.com.tw)

The address and road map of all our labs can be found in our web site also.