

FCC TEST REPORT

REPORT NO.: RF950513L01

MODEL NO.: WA-6266-15

RECEIVED: May 15, 2006

TESTED: May 16 ~ 17, 2006

ISSUED: May 22, 2006

APPLICANT: DEXIN Corporation

ADDRESS: 14F-8, No 258, Lian Cheng Rd., Chung Ho City,
Taipei Hsien, Taiwan, R.O.C.

ISSUED BY: Advance Data Technology Corporation

LAB ADDRESS: No. 47, 14th Ling, Chia Pau Tsuen, Lin Kou
Hsiang 244, Taipei Hsien, Taiwan, R.O.C.

TEST LOCATION: No. 19, Hwa Ya 2nd Rd., Wen Hwa Tsuen, Kwei
Shan Hsiang, Taoyuan Hsien 333, Taiwan,
R.O.C.

This test report consists of 17 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product endorsement by CNLA, A2LA or any government agencies. The test results in the report only apply to the tested sample.



Table of Contents

1	CERTIFICATION	3
2	SUMMARY OF TEST RESULTS	4
2.1	MEASUREMENT UNCERTAINTY	4
3	GENERAL INFORMATION	5
3.1	GENERAL DESCRIPTION OF EUT	5
3.1	DESCRIPTION OF TEST MODES	6
3.1.1	CONFIGURATION OF SYSTEM UNDER TEST	6
3.1.2	TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL	7
3.2	GENERAL DESCRIPTION OF APPLIED STANDARDS	7
3.3	DESCRIPTION OF SUPPORT UNITS	7
4	TEST PROCEDURE AND RESULT	8
4.1	CONDUCTED EMISSION MEASUREMENT	8
4.2	RADIATED EMISSION MEASUREMENT	8
4.2.1	LIMITS OF RADIATED EMISSION MEASUREMENT	8
4.2.2	TEST INSTRUMENT	9
4.2.3	TEST PROCEDURE	10
4.2.4	TEST SETUP	11
4.2.5	EUT OPERATING CONDITION	11
4.2.6	TEST RESULTS	12
4	PHOTOGRAPHS OF THE TEST CONFIGURATION	15
5	INFORMATION ON THE TESTING LABORATORIES	16
	APPENDIX-A	A-1



1 CERTIFICATION

PRODUCT: The DAYTONA 5 Button Wireless Optical Mini Mouse
MODEL: WA-6266-15
BRAND: Swiss Gear
APPLICANT: DEXIN Corporation
TESTED: May 16 ~ 17, 2006
TEST SAMPLE: ENGINEERING SAMPLE
STANDARDS: FCC Part 15, Subpart C (Section 15.227),
ANSI C63.4-2003

The above equipment has been tested by **Advance Data Technology Corporation**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

PREPARED BY : Rennie Wang , **DATE:** May 22, 2006
Rennie Wang

TECHNICAL ACCEPTANCE : Long Chen , **DATE:** May 22, 2006
Responsible for RF Long Chen

APPROVED BY : Gary Chang , **DATE:** May 22, 2006
Gary Chang / Supervisor

2 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC Part 15, Subpart C			
STANDARD PARAGRAPH	TEST TYPE	RESULT	REMARK
15.207	Conducted Emission Test	NA	Power supply is 3Vdc from batteries
15.227 15.209	Radiated Emission Test	PASS	Minimum passing margin is -1.67dB at 729.80MHz

2.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4:

MEASUREMENT	FREQUENCY	UNCERTAINTY
Radiated emissions	30MHz ~ 200MHz (Horizontal)	3.56 dB
	30MHz ~ 200MHz (Vertical)	3.71 dB
	200MHz ~1000MHz (Horizontal)	3.73 dB
	200MHz ~1000MHz (Vertical)	3.71 dB
	1GHz ~ 18GHz	2.26 dB
	18GHz ~ 40GHz	1.94 dB

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

3 GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

PRODUCT	The DAYTONA 5 Button Wireless Optical Mini Mouse
MODEL NO.	WA-6266-15
FCC ID	NIYMWP83-U
POWER SUPPLY	3Vdc from batteries for transmitter 5Vdc from host equipment for receiver
MODULATION TYPE	FSK
CARRIER FREQUENCY OF EACH CHANNEL	26.995 / 27.020 / 27.045 / 27.070 / 27.095 / 27.120 / 27.145 / 27.170 / 27.195 / 27.225 / 27.255 MHz
CHANNEL SPACING	25kHz
NUMBER OF CHANNEL	11
ANTENNA TYPE	Loop antenna
DATA CABLE	NA
I/O PORTS	USB
ASSOCIATED DEVICES	NA

NOTE:


1. The EUT is a set of The DAYTONA 5 Button Wireless Optical Mini Mouse with receiver.
2. The above EUT information was declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or User's Manual.

3.1 DESCRIPTION OF TEST MODES

Eleven channels were provided to this EUT.

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
1	26.995	7	27.145
2	27.020	8	27.170
3	27.045	9	27.195
4	27.070	10	27.225
5	27.095	11	27.255
6	27.120		

3.1.1 CONFIGURATION OF SYSTEM UNDER TEST



3.1.2 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL

EUT configure mode	Applicable to		Description
	PLC	RE<1G	
-	-	√	-

Where PLC: Power Line Conducted Emission

RE<1G RE: Radiated Emission below 1GHz

Radiated Emission Test (Below 1 GHz):

Following channel(s) was (were) selected for the final test as listed below.

EUT configure mode	EUT	Available Channel	Tested Channel	Modulation Type
-	Mouse	1-11	1	FSK

3.2 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart C. (15.227)
ANSI C63.4-2003

All test items have been performed and recorded as per the above standards.

3.3 DESCRIPTION OF SUPPORT UNITS

NA

4 TEST PROCEDURE AND RESULT

4.1 CONDUCTED EMISSION MEASUREMENT

NA

4.2 RADIATED EMISSION MEASUREMENT

4.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT

According to 15.227 the field strength of Emissions from intentional radiators operated under these frequencies bands shall not exceed the following:

Fundamental Frequency (MHz)	Field Strength of Fundamental (dBuV/m)	
	Peak	Average
26.96-27.28	100	80

Field strength limits are at the distance of 3 meters, Emissions radiated outside of the specified bands, shall be according to the general radiated limits in 15.209 as following:

Frequencies (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

4.2.2 TEST INSTRUMENT

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
Test Receiver ROHDE & SCHWARZ	ESI7	100033	May. 23, 2006
Spectrum Analyzer ROHDE & SCHWARZ	FSP40	100025	Dec. 05, 2006
BILOG Antenna SCHWARZBECK	VULB9168	9168-160	Jun. 01, 2006
HORN Antenna SCHWARZBECK	9120D	9120D-408	Jan. 08, 2007
HORN Antenna SCHWARZBECK	BBHA 9170	BBHA9170243	Jan. 19, 2007
Loop Antenna	HFH2-Z2	100070	Nov. 28, 2007
Preamplifier Agilent	8447D	2944A10633	Nov. 04, 2006
Preamplifier Agilent	8449B	3008A01964	Oct. 30, 2006
RF signal cable HUBER+SUHNNER	SUCOFLEX 104	214377/4	Dec. 13, 2006
RF signal cable HUBER+SUHNNER	SUCOFLEX 104	219272/4	Dec. 13, 2006
Software ADT.	ADT_Radiated_V5.14	NA	NA
Antenna Tower inn-co GmbH	MA 4000	013303	NA
Antenna Tower Controller inn-co GmbH	CO2000	017303	NA
Turn Table ADT.	TT100.	TT93021703	NA
Turn Table Controller ADT.	SC100.	SC93021703	NA

- NOTE:**
1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
 2. The test was performed in HwaYa Chamber 2.
 3. The horn antenna and HP preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
 4. The VCCI Site Registration No. is R-237.
 5. The IC Site Registration No. is IC4924-3.


4.2.3 TEST PROCEDURE

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10 dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10 dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

NOTE:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Peak detection (PK) and Quasi-peak detection (QP) at frequency below 1GHz.

4.2.4 TEST SETUP



For the actual test configuration, please refer to the related item in this test report - Photographs of the Test Configuration.

4.2.5 EUT OPERATING CONDITION

- a. Placed the EUT on the testing table.
- b. Set the EUT under transmitting condition.

4.2.6 TEST RESULTS

Radiated Worst-Case Data

INPUT POWER	3Vdc	FREQUENCY RANGE	Below 1000 MHz
ENVIRONMENTAL CONDITIONS	25 deg. C, 68 % RH, 991 hPa	DETECTOR FUNCTION	Peak / Average
TESTED BY	Morgan Chen		

TEST DISTANCE: 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*26.99	52.33 PK	100.00	-47.67	2.00	174	25.36	26.97
2	*26.99	42.28 AV	80.00	-37.72	2.00	174	15.31	26.97

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. "*" = Fundamental frequency.
 6. Loop Antenna was used for all frequency below 30MHz.

INPUT POWER	3Vdc	FREQUENCY RANGE	Below 1000 MHz
ENVIRONMENTAL CONDITIONS	25 deg. C, 68 % RH, 991 hPa	DETECTOR FUNCTION	Quasi-Peak
TESTED BY	Morgan Chen		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	241.88	41.40 QP	46.00	-4.60	1.25 H	235	28.97	12.43
2	269.10	35.28 QP	46.00	-10.72	2.50 H	346	21.09	14.19
3	323.53	38.41 QP	46.00	-7.59	2.00 H	331	22.15	16.26
4	377.96	40.14 QP	46.00	-5.86	1.50 H	277	22.55	17.59
5	457.66	32.53 QP	46.00	-13.47	2.00 H	346	13.16	19.38
6	469.32	36.02 QP	46.00	-9.98	2.00 H	73	16.34	19.68
7	502.36	32.34 QP	46.00	-13.66	2.00 H	73	11.83	20.51
8	648.16	39.58 QP	46.00	-6.42	2.50 H	169	16.04	23.54
9	675.37	38.53 QP	46.00	-7.47	1.50 H	277	14.60	23.93
10	702.59	35.26 QP	46.00	-10.74	1.00 H	25	10.86	24.40
11	729.80	44.33 QP	46.00	-1.67	2.50 H	346	18.84	25.49
12	784.23	42.14 QP	46.00	-3.86	1.50 H	271	15.59	26.55
13	836.71	38.27 QP	46.00	-7.73	1.00 H	238	11.27	27.01
14	863.93	32.81 QP	46.00	-13.19	1.50 H	277	5.55	27.26
15	891.14	36.65 QP	46.00	-9.35	1.25 H	235	9.15	27.50
16	918.36	31.74 QP	46.00	-14.26	2.00 H	73	3.88	27.86
17	945.57	35.31 QP	46.00	-10.69	2.50 H	1	7.04	28.27

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.



INPUT POWER	3Vdc	FREQUENCY RANGE	Below 1000 MHz
ENVIRONMENTAL CONDITIONS	25 deg. C, 68 % RH, 991 hPa	DETECTOR FUNCTION	Quasi-Peak
TESTED BY	Morgan Chen		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	187.45	19.11 QP	43.50	-24.39	1.00 V	142	7.33	11.78
2	214.67	20.03 QP	43.50	-23.47	1.00 V	325	8.42	11.61
3	241.88	31.49 QP	46.00	-14.51	1.25 V	295	19.07	12.43
4	269.10	30.57 QP	46.00	-15.43	1.00 V	13	16.38	14.19
5	323.53	32.63 QP	46.00	-13.37	1.25 V	43	16.37	16.26
6	377.96	29.18 QP	46.00	-16.82	1.25 V	178	11.59	17.59
7	648.16	33.14 QP	46.00	-12.86	1.00 V	253	9.61	23.54
8	675.37	32.76 QP	46.00	-13.24	1.25 V	178	8.83	23.93
9	702.59	31.39 QP	46.00	-14.61	1.00 V	28	6.98	24.40
10	729.80	36.78 QP	46.00	-9.22	1.00 V	13	11.30	25.49
11	784.23	36.75 QP	46.00	-9.25	1.00 V	4	10.20	26.55
12	809.50	30.63 QP	46.00	-15.37	1.25 V	136	3.88	26.76
13	836.71	33.31 QP	46.00	-12.69	1.25 V	256	6.30	27.01
14	891.14	31.32 QP	46.00	-14.68	1.25 V	295	3.82	27.50

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.

4 PHOTOGRAPHS OF THE TEST CONFIGURATION

RADIATED EMISSION TEST





5 INFORMATION ON THE TESTING LABORATORIES

We, ADT Corp., were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved by the following approval agencies according to ISO/IEC 17025.

USA	FCC, NVLAP, A2LA
Germany	TUV Rheinland
Japan	VCCI
Norway	NEMKO
Canada	INDUSTRY CANADA , CSA
R.O.C.	CNLA, BSMI, DGT
Netherlands	Telefication
Singapore	PSB , GOST-ASIA(MOU)
Russia	CERTIS(MOU)

Copies of accreditation certificates of our laboratories obtained from approval agencies can be downloaded from our web site: www.adt.com.tw/index.5/phtml.
If you have any comments, please feel free to contact us at the following:

Linko EMC/RF Lab:
Tel: 886-2-26052180
Fax: 886-2-26051924

Hsin Chu EMC/RF Lab:
Tel: 886-3-5935343
Fax: 886-3-5935342

Hwa Ya EMC/RF/Safety/Telecom Lab:
Tel: 886-3-3183232
Fax: 886-3-3185050

Linko RF Lab.
Tel: 886-3-3270910
Fax: 886-3-3270892

Web Site: www.adt.com.tw

The address and road map of all our labs can be found in our web site also.



APPENDIX-A

MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No any modifications are made to the EUT by the lab during the test.