

# SIEMENS

August 12, 2019

## FEDERAL COMMUNICATIONS COMMISSION

Authorization and Evaluation Division  
7435 Oakland Mills Road  
Columbia, MD 21046  
U.S.A.

**Subject: Reassessment Certification (Class II Permissive change)**

**Applicant: Siemens Canada Limited - Siemens Milltronics Process Instruments**  
**Model: 7ML5431**  
**FCC ID: NJA-LR250**

Dear Sir/Madam,

By signing this document we, Siemens Canada Limited - Siemens Milltronics Process Instruments would like to obtain a Reassessment Certification Class II Permissive change for the above Model and Certification number.

### Description of changes:

To the existing LR250 a new antenna type has been added to improve product marketability.

The new antenna (referred herein as Aluminum Horn Antenna) consist in a base 3in aluminum conical horn with a sealing PTFE insert at the horn base, ended at the aperture with an optional polypropylene lens and/or with various process connection options used to attach the horn to the measured process. The gain of the new antennas is comparable with the gain of the equivalent existing SITRANS LR250 standard horn antennas on which the current radio certification is based.

All the above changes are not modifying the RF characteristics of the SITRANS LR250 level radar family. A new version of the manual updated with this change is available.

### 1) Enclosure

No changes were made to the enclosure

### 2) Antenna and process connections

The Aluminum Horn Antenna is a new version of the existing 3in LR250 standard horn antenna. It consists in a 3in aluminum conical horn with a sealing PTFE insert at the horn base, ended at the aperture with an optional polypropylene lens and/or with various process connection options used to attach the horn to the process. The antenna can be used in the below two different groups of configurations

**Siemens Canada Limited**  
**Siemens Milltronics Process Instruments**

1954 Technology Drive  
Peterborough, Ontario  
K9J 6X7 / Canada

Tel.: (705) 745-2431  
Fax: (705) 741-0466  
[www.siemens.com/sensorsystems](http://www.siemens.com/sensorsystems)

# SIEMENS

Additional antenna list:	#1	#2
	Without process connection	Flanged horn
Manufacture:	SIEMENS	SIEMENS
Type:	3" Horn Antenna	3" Horn Antenna
Model (Configuration):	7ML5431-5QAX0-XSXX 7ML5431-5QBX0-XSXX	7ML5431-5QCX0-XSXX 7ML5431-5QDX0-XSXX 7ML5431-5QEX0-XSXX
Frequency range:	24.05-29.00 GHz	24.05-29.00 GHz
Impedance:	Waveguide input	Waveguide input
Gain (dBi):	22.9 dBi	24.6 dBi

- 1) Aluminum Horn Antenna - without process connection - Base horn without lens and process connection options as described in the #1 in the table above.
- 2) Aluminum Horn Antenna - flanged horn - Configuration obtained by attaching at the aperture of the base horn a polypropylene lens and a dielectric flange as described in the #2 in the table above.

The Aluminum Horn Antenna attaches permanently to the existing LR250 using screws after removing the existing lock nut. O-rings are placed at different locations to ensure sealing. The antenna connects to the circular waveguide present in the LR250 housing through a built-in waveguide with the same cross section as the housing waveguide. The microwave signal produced by the electronics inside the housing propagates through the waveguides, and it is transferred to the conical horn through the sealing PTFE insert. It propagates through the horn and then it is radiated into the free space either directly (antenna versions #1) or through the polypropylene lens (antenna version #2). To enhance the radiation pattern the lens is formed in a dual conical shape.

An assembly view with the associated part numbers is shown in the following drawing.

***LR250 - Approval drawing - A5E31444644A\_004.pdf***

The radiation patterns of the two versions of these antennas were measured and the results are presented in the attached report.

***Aluminum Horn Antenna directivity diagram.pdf***

### 3) Board stack

No changes were made to the boardstack

### 4) RF circuits

No changes were made to the RF circuits

### 5) Firmware

No changes affecting the RF circuitry control were made to the firmware

# SIEMENS

## 6) Manual


The new manuals are attached

## 7) Conclusion

To the existing LR250 a new antenna type has been added. No changes were done to the RF circuitry, boardstack or software. The gain of the new antennas is comparable with the gain of the highest gain antenna (standard 4in horn) on which the current radio approval is based.

Kindly confirm FCC acceptance of this Class II permissive change by return letter.

Sincere Regards



Thoai Bui  
Product Approval Specialist, R&D  
Siemens Canada Ltd. - SMP  
1954 Technology Drive  
Peterborough, Ontario, Canada, K9J 6X7  
Email: thoai.bui@siemens.com  
Tel.: 705-740-7005  
Fax: 705-741-0466

Sincere Regards



Dr. Gabriel Serban  
Sr. HF Designer, R&D  
Siemens Canada Ltd. - SMP  
1954 Technology Drive  
Peterborough, Ontario, Canada, K9J 6X7  
Email: gabriel.serban@siemens.com  
Tel.: 705-740-7659  
Fax: 705-741-0466