

## Test Report

**Report Number: 30674061**

**Project Number: 3067406**

**November 5, 2004**

**Testing performed on the**

**GSM Fixed Wireless Phone**

**Model: FX1900xg**

**FCC ID: NJIFW1900**

**to**

**FCC Parts 22H, 24E and Part 15 Subpart B**

**for**

**CSI Wireless Inc.**



A2LA Certificate Number: 1755-01

Test Performed by:

Intertek

1365 Adams Court

Menlo Park, CA 94025

Test Authorized by:

CSI Wireless

1909 Milmont Drive

Milpitas, CA 95035

**Prepared by:**

Handwritten signature of Bruce Gordon in blue ink.

Bruce Gordon, Test Engineer

**Date:** November 5, 2004

**Reviewed by:**

Handwritten signature of David Chernomordik in blue ink.

David Chernomordik, EMC Technical Manager

**Date:** November 5, 2004

*This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to copy or distribute this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program. This report must not be used to claim product endorsement by A2LA, NIST nor any other agency of the U.S. Government.*

## TABLE OF CONTENTS

<b>1.0</b>	<b>Introduction .....</b>	<b>4</b>
1.1	Test Summary .....	4
1.2	Product Description .....	5
1.3	Test Configuration .....	6
1.4	Related Submittal(s) Grants .....	6
<b>2.0</b>	<b>RF Power Output.....</b>	<b>7</b>
2.1	Test Procedure .....	7
2.2	Test Equipment .....	7
2.3	Test Results .....	7
<b>3.0</b>	<b>Radiated Power .....</b>	<b>8</b>
3.1	Test Procedure .....	8
3.2	Test Equipment .....	8
3.3	Test Results .....	9
<b>4.0</b>	<b>Occupied Bandwidth .....</b>	<b>10</b>
4.1	Test Procedure .....	10
4.2	Test Equipment .....	10
4.3	Test Results .....	10
<b>5.0</b>	<b>Out of Band Emissions at Antenna Terminals.....</b>	<b>15</b>
5.1	Test Procedure .....	15
5.2	Test Equipment .....	15
5.3	Test Results .....	15
<b>6.0</b>	<b>Field Strength of Spurious Radiation .....</b>	<b>31</b>
6.1	Test Procedure .....	31
6.2	Test Equipment .....	31
6.3	Test Results .....	32
<b>7.0</b>	<b>Frequency Stability vs Temperature.....</b>	<b>34</b>
7.1	Test Procedure .....	34
7.2	Test Result .....	34
<b>8.0</b>	<b>Frequency Stability vs Voltage .....</b>	<b>35</b>
8.1	Test Procedure .....	35
8.2	Test Result .....	35
<b>9.0</b>	<b>RF Exposure Evaluation .....</b>	<b>36</b>
<b>10.0</b>	<b>Radiated Emissions from digital part and receiver .....</b>	<b>37</b>
10.1	Radiated Emission Limits .....	37
10.2	Field Strength Calculation .....	38
10.3	Test Results .....	38

**11.0 Line Conducted Emissions,.....41**

11.1 Test Procedure ..... 41

11.2 Test Equipment..... 41

11.3 Test Results..... 41

**12.0 List of Test Equipment .....44**

**13.0 Document History .....45**

## 1.0 Introduction

### 1.1 Test Summary

FCC RULE	DESCRIPTION OF TEST	RESULT	PAGE
2.1046	RF Power Output	Complies	7
22.913, 24.232	ERP, EIRP	Complies	8
2.1047	Modulation Requirements	Not applicable	-
2.1049	Occupied Bandwidth, Emission Designator	Complies	10
2.1051, 22.901(d), 24.238(a)	Out of Band Emissions at Antenna Terminals	Complies	15
2.1053	Field Strength of Spurious Radiation	Complies	31
2.1055	Frequency Stability vs. Temperature	Complies	34
2.1055	Frequency Stability vs. Voltage	Complies	35
2.1091	RF Exposure evaluation	Complies	36

## 1.2 Product Description

The FX1900xg is a dual band GSM desktop phone which operates in the 824-849 MHz and 1850-1910 bands.

For more information, please refer to the attached product description.

<b>Use of Product</b>	Desktop Phone
<b>Whether quantity (&gt;1) production is planned</b>	Yes
<b>Cellular Phone standards</b>	GSM
<b>RF Output Power</b>	32 dBm (Cell band) 29 dBm (PCS band)
<b>Frequency Range</b>	824-849 MHz; 1850-1910 MHz
<b>Antenna (e) &amp; Gain</b>	0 dBi
<b>Detachable antenna?</b>	Yes
<b>External input</b>	Audio

**EUT receive date:** October 25, 2004


**EUT receive condition:** The prototype version of the EUT was received in good condition with no apparent damage. As declared by the Applicant it is identical to the production units.

**Test start date:** October 25, 2004


**Test completion date:** November 4, 2004

### 1.3 Test Configuration


Antenna conducted measurements



ERP/EIRP measurements



Spurious Radiated emission measurements



### 1.4 Related Submittal(s) Grants

None

## 2.0 RF Power Output

### FCC 2.1046

#### 2.1 Test Procedure

The transmitter output was connected to a Base Station Simulator (BSS). The transmitter conducted output power was recorded from the BSS display.

Tests were performed at three frequencies (low, middle, and high channels) in Cellular in PCS bands.

#### 2.2 Test Equipment

R & S model CMU 200 Universal Radio Communication Tester (Base Station Simulator).

#### 2.3 Test Results

Channel	Frequency MHz	Measured Output Power dBm
<b>Cellular Band</b>		
128	825.2	32.2
189	836.4	32.2
251	848.8	32.3
<b>PCS band</b>		
512	1850.2	29.0
661	1880.0	28.9
810	1909.8	28.9

### 3.0 Radiated Power

#### FCC 22.913

The Effective Radiated Power (ERP) of mobile transmitters and auxiliary test transmitters must not exceed 7 Watts.

#### FCC 24.232

The Equivalent Isotropic Radiated Power (EIRP) must not exceed 2 Watts.

### 3.1 Test Procedure

The EUT was positioned on a non-conductive turntable, 0.8m above the ground plane on an open test site. The radiated emission at the fundamental frequency was measured at 3m distance with a test antenna and spectrum analyzer. During the measurement, the resolution bandwidths of the spectrum analyzer was set to 300 kHz.

The highest emission level was recorded with the rotation of the turntable and the raising and lowering of the test antenna. The spectrum analyzer reading was recorded.

ERP in frequency band 824-849 MHz, and EIRP in frequency band 1851.25-1910 MHz were measured using a substitution method. The EUT was replaced by half-wave dipole (824-849 MHz) or horn antenna (1850-19010 MHz) connected to a signal generator. The spectrum analyzer reading was recorded and ERP/EIRP was calculated as follows:

$$\text{ERP} = U_1 - U_2 + V_g; \text{ EIRP} = U_1 - U_2 + V_g + G$$

Where  $U_1$  &  $U_2$  are spectrum analyzer readings in dBuV when measured field strength from EUT & generator accordingly;  $V_g$  is the generator output in dBm;  $G$  is the transmitting antenna gain.

### 3.2 Test Equipment

EMCO 3148 Log Periodic Antenna  
EMCO 3115 Horn Antenna  
CDI Robert's Antenna  
Hewlett Packard 83732A signal generator  
Rohde & Schwarz FSP 40 Spectrum Analyzer



### 3.3 Test Results

<b>Complies</b>	Refer to the data below
-----------------	-------------------------

Frequency MHz	SA Reading (EUT) dB(uV)	SA Reading (Signal Gen & Tuned Dipole) dB(uV)	Signal Generator Power dBm	ERP (EUT) dBm
<b>Cellular Band</b>				
824.2	108.4	86.0	9.6	32.0
836.4	108.4	85.5	9.6	32.5
848.8	109.0	86.2	9.6	32.4
<b>PCS Band</b>				
Frequency MHz	SA Reading (EUT) dB(uV)	SA Reading (Signal Gen & Horn Antenna) dB(uV)	Signal Gen. Power + Horn Antenna Gain dBm	EIRP (EUT) dBm
1850.2	100.9	86.7	9.4	30.6
1880.0	100.1	86.7	9.4	29.8
1909.8	100.1	86.7	9.4	29.8

#### **4.0 Occupied Bandwidth**

FCC 2.1049

##### **4.1 Test Procedure**

A calibrated directional coupler was used to connect a BSS and a spectrum analyzer to the transmitter output. The Occupied Bandwidth (defined as the 99% Power Bandwidth) was measured with the FSP 40 Spectrum Analyzer.


##### **4.2 Test Equipment**

Rohde & Schwarz model CMU 200 Universal Radio Communication Tester (Base Station Simulator).  
Rohde & Schwarz FSP 40 Spectrum Analyzer.  
Directional Coupler

##### **4.3 Test Results**


Refer to attached plots 4.1 - 4.4. The Emission Designator was determined as 250KGXW.

Plot 4.1




Comment: Reference level, GSM 850, Ch 189  
 Date: 26.OCT.2004 12:30:06

Plot 4.2




Comment: Occupied bandwidth, GSM 850, Ch 189  
 Date: 26.OCT.2004 12:33:52

Plot 4.3



Comment: Reference level, GSM 1900, Ch 661  
Date: 26.OCT.2004 15:50:48

Plot 4.4



Comment: Occupied bandwidth, GSM 1900, Ch 661  
Date: 26.OCT.2004 16:15:39

## 5.0 Out of Band Emissions at Antenna Terminals

FCC 22.901(d), 22.901(d), 22.917(f), 24.238(a)

### Out of Band Emissions:

The mean power of emissions must be attenuated below the mean power of the unmodulated carrier (P) on any frequency outside the frequency band by at least  $(43 + 10 \log P)$  dB.

### 5.1 Test Procedure

A calibrated directional coupler was used to connect a BSS and a spectrum analyzer to the transmitter output. The antenna conducted emissions were measured with the FSP 40 Spectrum Analyzer. Sufficient scans were taken to show the out-of-band emissions up to 10th harmonic.

For frequencies within 1 MHz above and below the band-edge frequencies, the spectrum analyzer resolution bandwidth (RBW) of 3 kHz was used. If for frequencies more than 1 MHz above and below the band-edge frequencies the RBW less than 1 MHz was used, The Bandwidth Correction Factor of  $10\log(1 \text{ MHz}/\text{RBW})$  was applied.


### 5.2 Test Equipment

Rohde & Schwarz model CMU 200 Universal Radio Communication Tester (Base Station Simulator).  
Rohde & Schwarz FSP 40 Spectrum Analyzer.  
Directional Coupler

### 5.3 Test Results

<b>Complies</b>	Refer to the following plots 5.1 – 5.15
-----------------	---


Plot 5.1



Comment: Lower band-edge, GSM 850, Ch 128  
 Date: 26.OCT.2004 13:13:16




Plot 5.2




Comment: Out-of-band, GSM 850, Ch 128  
 Date: 26.OCT.2004 13:27:37

Plot 5.3




Comment: Out-of-band, GSM 850, Ch 128  
Date: 26.OCT.2004 13:29:20

Plot 5.4



Comment: Upper band-edge, GSM 850, Ch 251  
 Date: 26.OCT.2004 14:48:51

Plot 5.5




Comment: Out-of-band, GSM 850, Ch 251  
 Date: 26.OCT.2004 14:52:49

Plot 5.6



\*RBW 100 kHz Marker 1 [T1 ]  
 \*VBW 100 kHz -33.56 dBm  
 Ref 30 dBm Att 20 dB SWT 15 ms 914.200000000 MHz

1 RM\*  
 VIEW




Comment: Out-of-band, GSM 850, Ch 251  
 Date: 26.OCT.2004 14:54:35

Plot 5.7




\*RBW 100 kHz Marker 1 [T1 ]  
 \*VBW 100 kHz -42.19 dBm  
 Ref 30 dBm Att 20 dB SWT 900 ms 1.000000000 GHz

1 RM\*  
 VIEW




Comment: Out-of-band, GSM 850, Ch 251  
 Date: 26.OCT.2004 14:56:03

Plot 5.8



Comment: Lower band-edge, GSM 1900, Ch 512  
 Date: 26.OCT.2004 16:20:06


Plot 5.9



Comment: Out-of-band, GSM 1900, Ch 512  
Date: 26.OCT.2004 16:21:52




Plot 5.10




Comment: Out-of-band, GSM 1900, Ch 512, add BCF=10 dB  
 Date: 26.OCT.2004 16:34:04

Plot 5.11




Comment: Out-of-band, GSM 1900, Ch 512  
 Date: 26.OCT.2004 16:36:40

Plot 5.12




Comment: Out-of-band, GSM 1900, Ch 512  
Date: 26.OCT.2004 16:37:56

Plot 5.13




Comment: Upper band-edge, GSM 1900, Ch 810  
Date: 26.OCT.2004 16:56:17

Plot 5.14



Comment: Out-of-band, GSM 1900, Ch 810  
 Date: 26.OCT.2004 16:58:15



## **6.0 Field Strength of Spurious Radiation**

FCC 2.1053, 22.901(d), 24.238(a)

### **6.1 Test Procedure**

The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The EUT was powered from fully charged battery.

The frequency range up to tenth harmonic of each of the three fundamental frequency (low, middle, and high channels) for each band (cellular and PCS) was investigated. The tests were performed with the EUT placed on three orthogonal axes. The worst case of emissions was reported.

For spurious emissions attenuation, the substitution method was used. On each frequency where the Field Strength was found above 63.4 dBuV/m (which corresponds to ERP = -33 dBm), the EUT was substituted by a reference antenna (half-wave dipole - below 1 GHz, or Horn antenna - above 1GHz), connected to a signal generator. The signal generator output was adjusted to obtain the same reading as from EUT. The ERP/EIRP at the spurious emissions frequency was calculated as in section 3. The spurious emissions attenuation was calculated as the difference between ERP/EIRP at the fundamental frequency (see section 3) and at the spurious emissions frequency.

### **6.2 Test Equipment**

EMCO 3115 Horn Antennas  
Hewlett Packard 83732A signal generator  
Rohde & Schwarz FSP 40 Spectrum Analyzer

### 6.3 Test Results

#### Spurious Emissions (Measured by Substitution Method)

Frequency	Antenna Polariz.	SA Reading (EUT)	Mode	Signal Generator Output required to have the same SA Reading as from EUT	ERP*	ERP Limit	ERP Margin
MHz		dB(μV)		V <sub>g</sub> dBm	dBm	dBm	dBm
Channel 824.2 MHz							
1648.4	V	41.7	GSM	-39.2	-32.8	-13.0	-19.8
2472.6	V	42.5	GSM	-34.8	-27.3	-13.0	-14.3
3296.8	V	44.5	GSM	-30.8	-23.1	-13.0	-10.1
4121.0	V	46.9	GSM	-27.3	-19.1	-13.0	-6.1
4945.2	V	43.5	GSM	-28.9	-20.2	-13.0	-7.2
5769.4	V	20.0	GSM	-51.8	-42.5	-13.0	-29.5
6593.6	V	20.0	GSM	-49.9	-40.1	-13.0	-27.1
7417.8	V	20.0	GSM	-47.1	-37.9	-13.0	-24.9
8242.0	V	20.0	GSM	-45.0	-35.5	-13.0	-22.5
Channel 836.4 MHz							
1672.8	V	40.8	GSM	-40.1	-33.7	-13.0	-20.7
2509.2	V	40.8	GSM	-36.5	-29.0	-13.0	-16.0
3345.6	V	42.3	GSM	-33.0	-25.3	-13.0	-12.3
4182.0	V	45.3	GSM	-28.9	-20.7	-13.0	-7.7
5018.4	V	43.6	GSM	-28.8	-20.1	-13.0	-7.1
5854.8	V	20.0	GSM	-51.8	-42.5	-13.0	-29.5
6691.2	V	20.0	GSM	-49.9	-40.1	-13.0	-27.1
7527.6	V	20.0	GSM	-47.1	-37.9	-13.0	-24.9
8364.0	V	20.0	GSM	-45.0	-35.5	-13.0	-22.5
Channel 848.8 MHz							
1697.6	V	43.0	GSM	-37.9	-31.5	-13.0	-18.5
2546.4	V	40.5	GSM	-36.8	-29.3	-13.0	-16.3
3395.2	V	42.2	GSM	-33.1	-25.4	-13.0	-12.4
4244.0	V	46.1	GSM	-28.1	-19.9	-13.0	-6.9
5092.8	V	45.7	GSM	-26.7	-18.0	-13.0	-5.0
5941.6	V	20.0	GSM	-51.8	-42.5	-13.0	-29.5
6790.4	V	20.0	GSM	-49.9	-40.1	-13.0	-27.1
7639.2	V	20.0	GSM	-47.1	-37.9	-13.0	-24.9
8488.0	V	24.5	GSM	-40.5	-31.0	-13.0	-18

\* ERP is calculated as:  $ERP_{(dBm)} = V_{g(dBm)} + G_{(dBd)}$



Frequency	Antenna Polariz.	SA Reading (EUT)	Mode	Signal Generator Output required to have the same SA Reading as from EUT	EIRP*	EIRP Limit	EIRP Margin
MHz		dB(μV)		V <sub>g</sub> dBm	dBm	dBm	dBm
Channel 1850.2 MHz							
3700.4	V	40.8	GSM	-34.1	-24.3	-13.0	-11.3
5550.6	V	48.2	GSM	-24.2	-13.2	-13.0	-0.2
7400.8	V	30.0	GSM	-39.5	-28.1	-13.0	-15.1
9251.0	V	30.0	GSM	-37.0	-25.2	-13.0	-12.2
11101.2	V	30.0	GSM	-34.5	-22.0	-13.0	-9.0
12951.4	V	30.0	GSM	-34.3	-21.5	-13.0	-8.5
14801.6	V	30.0	GSM	-34.0	-21.1	-13.0	-8.1
16651.8	V	30.0	GSM	-30.0	-15.2	-13.0	-2.2
18502.0	V	26.0	GSM	-28.0	-17.9	-13.0	-4.9
Channel 1880 MHz							
3760.0	V	41.3	GSM	-33.6	-23.8	-13.0	-10.8
5640.0	V	45.9	GSM	-26.3	-15.2	-13.0	-2.2
7520.0	V	29.0	GSM	-40.0	-28.6	-13.0	-15.6
9400.0	V	22.0	GSM	-44.8	-33.0	-13.0	-20.0
11280.0	V	19.0	GSM	-45.4	-33.0	-13.0	-20.0
13160.0	V	19.0	GSM	-45.2	-32.5	-13.0	-19.5
15040.0	V	30.0	GSM	-33.9	-20.0	-13.0	-7.0
16920.0	V	30.0	GSM	-29.8	-16.4	-13.0	-3.4
18800.0	V	26.0	GSM	-28.0	-17.9	-13.0	-4.9
Channel 1909.8 MHz							
3819.6	V	44.5	GSM	-30.4	-20.6	-13.0	-7.6
5729.4	V	41.3	GSM	-30.9	-19.7	-13.0	-6.7
7639.2	V	31.2	GSM	-37.8	-26.4	-13.0	-13.4
9549.0	V	21.7	GSM	-45.1	-33.3	-13.0	-20.3
11458.8	V	19.5	GSM	-44.9	-32.5	-13.0	-19.5
13368.6	V	19.5	GSM	-44.7	-32.4	-13.0	-19.4
15278.4	V	30.0	GSM	-33.9	-18.6	-13.0	-5.6
17188.2	V	30.0	GSM	-29.8	-17.3	-13.0	-4.3
19098.0	V	26.0	GSM	-28.0	-17.9	-13.0	-4.9

\* EIRP is calculated as:  $EIRP_{(dBm)} = V_{g(dBm)} + G_{(dBi)}$

Test Result:	Complies
--------------	----------

## 7.0 Frequency Stability vs Temperature FCC 2.1055

### 7.1 Test Procedure

The EUT was powered from AC/DC adapter and placed inside the temperature chamber. After the temperature stabilized for approximately 20 minutes, the transmitting frequency was recorded. The difference between assigned channel frequency and real frequency was measured by a BSS.

### 7.2 Test Result

Temperature (°C)	GSM850 Channel 189, 836.4 MHz	GSM1900 Channel 661, 1880 MHz
	Difference Hz	Difference Hz
-30	-57	-83
-20	-54	-81
-10	-53	-73
0	-49	-72
10	-45	-63
20	-47	-73
30	-49	-75
40	-53	-78
50	-58	-87

## 8.0 Frequency Stability vs Voltage

### FCC 2.1055

#### 8.1 Test Procedure

Since the EUT may be used with a power adaptor and with a internal battery, frequency stability was measured when the EUT was powered from AC and DC at the nominal voltages and at 85% and 115% of the nominal voltages. The difference between assigned channel frequency and real frequency was measured by a BSS.

#### 8.2 Test Result

Voltage	GSM850 Channel 189, 836.4 MHz	GSM1900 Channel 661, 1880 MHz
	Difference Hz	Difference Hz
138 VAC	-51	-77
120 VAC	-47	-73
102 VAC	-52	-74
5.52 VDC	-53	-67
4.8 VDC	-47	-73
4.3 VDC *	-44	-65

\* The end point of the battery voltage according to the specification of the battery

## 9.0 RF Exposure Evaluation

### FCC 2.1091

The EUT is a device used in mobile applications. The maximum EIRP is 1.78 W without taken into account the Duty Cycle, which is 1/8 for GSM devices. To show compliance with RF Exposure Requirement, the Power Density was calculated using the formula:

$$S = \text{EIRP} / 4\pi D^2$$

where: S is Power Density in W/m<sup>2</sup>

D is the distance from the antenna.

The distance, where S = MPE,

$$D_{\min} = \sqrt{(\text{EIRP}) / 4\pi(\text{MPE})}$$

For general population/uncontrolled exposure MPE = 10 W/m<sup>2</sup>

Therefore,  $D_{\min} = 0.12 \text{ m}$

In conclusion, the EUT meets the FCC Part 2.1091 MPE requirements at 0.2 m.

## 10.0 Radiated Emissions from digital parts and receiver FCC 15.109

### 10.1 Radiated Emission Limits

The following radiated emission limits apply to Class B unintentional radiators:

**Radiated Emissions Limits, Section 15.109**

<i>Frequency (MHz)</i>	<i>Class B at 3 m (<math>\mu</math>V/m)</i>	<i>Class B at 10m (dB<math>\mu</math>V/m)</i>
30-88	100	40.0
88-216	150	43.5
216-960	200	46.0
Above 960	500	54.0

*Note: Three sets of units are commonly used for EMI measurement, decibels below one milliwatt (-dBm), decibels above a microvolt (dB $\mu$ V), and microvolts ( $\mu$ V). To convert between them, use the following formulas:  $20 \text{ LOG}_{10}(\mu V) = \text{dB}\mu V$ ,  $\text{dBm} = \text{dB}\mu V - 107$ .*

## 10.2 Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain (if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CF - AG$$

Where FS = Field Strength in dB(μV/m)

RA = Receiver Amplitude (including preamplifier) in dB(μV)

CF = Cable Attenuation Factor in dB

AF = Antenna Factor in dB

AG = Amplifier Gain in dB

Assume a receiver reading of 52.0 dB(μV) is obtained. The antennas factor of 7.4 dB(1/m) and cable factor of 1.6 dB is added. The amplifier gain of 29 dB is subtracted, giving field strength of 32 dB(μV/m). This value in dB(μV/m) was converted to its corresponding level in μV/m.

$$RA = 52.0 \text{ dB}(\mu\text{V})$$

$$AF = 7.4 \text{ dB}(1/\text{m})$$

$$CF = 1.6 \text{ dB}$$

$$AG = 29.0 \text{ dB}$$

$$FS = 52.0 + 7.4 + 1.6 - 29.0 = 32 \text{ dB}(\mu\text{V}/\text{m})$$



$$\text{Level in } \mu\text{V}/\text{m} = \text{Common Antilogarithm } [(32 \text{ dB}\mu\text{V}/\text{m})/20] = 39.8 \mu\text{V}/\text{m}$$

## 10.3 Test Results

Test Result:	Complies by 14.6 dB
--------------	---------------------

Frequency range investigated is from 30 MHz to 10000 MHz.

## 10.3 Test Results (Continued)



### Radiated Emissions 30 MHz – 10000 MHz

#### FCC Class B (Horizontal)

EUT Model Number: GSM Desktop Phone



ITS Job Number: 3067406

Operator: AK & BG

Test Date: October 29, 2004

Frequency	Pk FS	Limit@3m	Margin	RA	AG	CF	AF
MHz	dB(uV/m)	dB(uV/m)	dB	dB(uV)	dB	dB	dB(1/m)
210.26	20.4	43.5	-23.1	36.7	32.2	5.1	10.8
216.00	20.3	43.5	-23.2	29.1	32.2	5.1	11.2
262.80	19.6	46.0	-26.4	34.0	32.2	5.4	12.5
458.42	24.6	46.0	-21.4	33.7	32.3	6.2	17.1
574.82	25.7	46.0	-20.3	32.3	32.5	6.7	19.2
802.77	25.9	46.0	-20.1	29.5	32.4	7.3	21.6

## 10.3 Test Results (Continued)



### Radiated Emissions 30 MHz – 5000 MHz

#### FCC Class B (Vertical)

EUT Model Number: GSM Desktop Phone

ITS Job Number: 3067406

Company: CSI Wireless

Test Date: October 29, 2004

Operator: AK & BG

Frequency	Pk FS	Limit@3m	Margin	RA	AG	CF	AF
MHz	dB(uV/m)	dB(uV/m)	dB	dB(uV)	dB	dB	dB(1/m)
37.27	25.4	40.0	-14.6	46.0	32.4	3.8	8.0
49.40	16.7	40.0	-23.3	38.9	32.4	3.9	6.2
86.58	11.8	40.0	-28.2	33.0	32.3	4.3	6.8
210.26	15.2	43.5	-28.3	31.6	32.2	5.1	10.7
459.23	28.2	46.0	-17.8	38.0	32.3	6.2	16.4
988.68	24.0	54.0	-30.0	24.9	31.2	8.3	21.9



## 11.0 Line Conducted Emissions, FCC 15.107

### 11.1 Test Procedure

Test procedure described in the ANSI C63.4 Standard was employed.

The EUT was connected to the charger, that was connected to the AC line through the LISNs.

Both HOT and NEUTRAL leads were tested.

### 11.2 Test Equipment

HP8568B Spectrum Analyzer


FCC LISN

### 11.3 Test Results


Test Result:	Complies by 4.2 dB
--------------	--------------------

See the attached plots.

## 11.3 Test Results (Continued)



## 11.3 Test Results (Continued)



## 12.0 List of Test Equipment

Measurement equipment used for compliance testing utilized the equipment on the following list:

Equipment	Manufacturer	Model/Type	Serial #	Cal Int	Cal Due
Base Station Simulator	Rohde & Schwarz	CMU-200	652478	12	11/6/04
EMI Receiver	Rhode-Schwarz	FSP-40	100030	12	9/15/05
Spectrum Analyzer Display w/85650 QP Adapter <sub>LC Room</sub>	Hewlett Packard	8568A	2134A02584 2521AB1021	12	11/18/04
Signal Generator	Hewlett Packard	83732A	322A00119	12	3/04/05
Double-ridged Horn Antenna	EMCO	3115	9170-3712	12	6/18/05
Double-ridged Horn Antenna	EMCO	3115	8812-3049	12	4/14/05
Dipole Antenna	CDI	Roberts	331	12	2/09/05
BI-Log Antenna	EMCO	3143	9509-1164	12	4/06/05
Pre-Amplifier	Sonoma Inst.	310	185634	12	3/25/05
Pre-Amplifier	Miteq	AMF-4D-001180-24-10P	799159	12	3/25/05
RF Filter Section	Hewlett Packard	85460A	3448A00267	12	9/10/05
EMI Receiver	Hewlett Packard	8546A	3710A00373	12	9/10/05
LISN	FCC	FCC-LISN-50-50-M-H	2011	12	2/10/05

**13.0 Document History**

<b>Revision/ Job Number</b>	<b>Writer Initials</b>	<b>Date</b>	<b>Change</b>
1.0 / 3067406	BG	November 5, 2004	Original document