

FCC Test Report

FCC ID : NKR-DHUB81

Equipment : 11abgn WLAN/Bluetooth Combo adapter

Model No. : DHUB-81, 700-0022-001

Brand Name : WNC

Applicant : Wistron Neweb Corporation

Address : 20 Park Avenue II, Hsinchu Science Park,

Hsinchu 308, Taiwan, R.O.C.

Standard : 47 CFR FCC Part 15.247

Received Date : Feb. 18, 2014

Tested Date : Feb. 20 ~ Feb. 28, 2014

We, International Certification Corp., would like to declare that the tested sample has been evaluated and in compliance with the requirement of the above standards. The test results contained in this report refer exclusively to the product. It may be duplicated completely for legal use with the approval of the applicant. It shall not be reproduced except in full without the written approval of our laboratory.

Approved & Reviewed by:

Gary Chang / Manager

lac-MRA

Testing Laboratory

Report No.: FR421807AD Report Version: Rev. 01 Page: 1 of 46



Table of Contents

| 1 | GENERAL DESCRIPTION | 5 |
|-----|--------------------------------------------------------|----|
| 1.1 | Information | 5 |
| 1.2 | Local Support Equipment List | 7 |
| 1.3 | Test Setup Chart | 7 |
| 1.4 | The Equipment List | 8 |
| 1.5 | Test Standards | 9 |
| 1.6 | Measurement Uncertainty | g |
| 2 | TEST CONFIGURATION | 10 |
| 2.1 | Testing Condition | 10 |
| 2.2 | The Worst Test Modes and Channel Details | 10 |
| 3 | TRANSMITTER TEST RESULTS | 11 |
| 3.1 | Conducted Emissions | 11 |
| 3.2 | Unwanted Emissions into Restricted Frequency Bands | 14 |
| 3.3 | Unwanted Emissions into Non-Restricted Frequency Bands | 30 |
| 3.4 | Conducted Output Power | 35 |
| 3.5 | Number of Hopping Frequency | 37 |
| 3.6 | 20dB and Occupied Bandwidth | 39 |
| 3.7 | Channel Separation | 41 |
| 3.8 | Number of Dwell Time | 43 |
| 4 | TEST LABORATORY INFORMATION | 46 |



Release Record

| Report No. | Version | Description | Issued Date |
|------------|---------|---------------|---------------|
| FR421807AD | Rev. 01 | Initial issue | Apr. 21, 2014 |

Report No.: FR421807AD Page : 3 of 46



Summary of Test Results

| FCC Rules | Test Items | Measured | Result |
|---------------------|----------------------------|---------------------------------------------------------------------------|--------|
| 15.207 | Conducted Emissions | [dBuV]: 0.156MHz 47.77 (Margin -7.92dB) - AV | Pass |
| 15.247(d) 15.209 | Radiated Emissions | Radiated Emissions [dBuV/m at 3m]: 898.22MHz 39.85 (Margin - 6.15dB) - PK | |
| 15.247(d) | Band Edge | Meet the requirement of limit | Pass |
| 15.247(b)(1) | Conducted Output Power | Power [dBm]: BR: 3.95 EDR: 5.61 | Pass |
| 15.247(a)(1)(iii) | Number of Hopping Channels | Meet the requirement of limit | Pass |
| 15.247(a)(1) | Hopping Channel Separation | Meet the requirement of limit | Pass |
| 15.247(a)(1)(iii) | Dwell Time | Meet the requirement of limit | Pass |
| 15.203 | Antenna Requirement | Meet the requirement of limit | Pass |

Report No.: FR421807AD Page: 4 of 46



1 General Description

1.1 Information

1.1.1 Product Details

The following models are provided to this EUT.

| Brand Name | Model Name | Product Name | Description | |
|------------|--------------|-----------------------|-------------------|--|
| WNC | DHUB-81 | 11abgn WLAN/Bluetooth | markating purpose | |
| VVINC | 700-0022-001 | Combo adapter | marketing purpose | |

[★] All models are electrically identical, different model names are for marketing purpose.

1.1.2 Specification of the Equipment under Test (EUT)

| RF General Information | | | | | | | | |
|------------------------------------------------------------------------|----------|-----------|-----------|--------|--|--|--|--|
| Frequency Range (MHz) Bluetooth Ch. Frequency Channel Number Data Rate | | | | | | | | |
| 2400-2483.5 | BR V4.0 | 2402-2480 | 0-78 [79] | 1 Mbps | | | | |
| 2400-2483.5 | EDR V4.0 | 2402-2480 | 0-78 [79] | 2 Mbps | | | | |
| 2400-2483.5 | EDR V4.0 | 2402-2480 | 0-78 [79] | 3 Mbps | | | | |

Note 1: RF output power specifies that Maximum Peak Conducted Output Power.

1.1.3 Antenna Details

| Ant. No. | Туре | Type Gain (dBi) Connector | | Remark |
|----------|---------|---------------------------|--|--------|
| 1 | Printed | -2.48 | | |

1.1.4 Power Supply Type of Equipment under Test (EUT)

| Power Supply Type | 5Vdc from host |
|-------------------|----------------|
|-------------------|----------------|

1.1.5 Accessories

N/A

Report No.: FR421807AD Page: 5 of 46

The above models, model **DHUB-81** was selected as a representative one for the final test and only its data was recorded in this report.

Note 2: Bluetooth BR uses a GFSK.

Note 3: Bluetooth EDR uses a combination of $\pi/4$ -DQPSK and 8DPSK.



1.1.6 Channel List

| Frequency band (MHz) | | | | 2400~2483.5 | | | |
|----------------------|--------------------|---------|--------------------|-------------|--------------------|---------|--------------------|
| Channel | Frequency (MHz) | Channel | Frequency (MHz) | Channel | Frequency (MHz) | Channel | Frequency (MHz) |
| 0 | 2402 | 20 | 2422 | 40 | 2442 | 60 | 2462 |
| 1 | 2403 | 21 | 2423 | 41 | 2443 | 61 | 2463 |
| 2 | 2404 | 22 | 2424 | 42 | 2444 | 62 | 2464 |
| 3 | 2405 | 23 | 2425 | 43 | 2445 | 63 | 2465 |
| 4 | 2406 | 24 | 2426 | 44 | 2446 | 64 | 2466 |
| 5 | 2407 | 25 | 2427 | 45 | 2447 | 65 | 2467 |
| 6 | 2408 | 26 | 2428 | 46 | 2448 | 66 | 2468 |
| 7 | 2409 | 27 | 2429 | 47 | 2449 | 67 | 2469 |
| 8 | 2410 | 28 | 2430 | 48 | 2450 | 68 | 2470 |
| 9 | 2411 | 29 | 2431 | 49 | 2451 | 69 | 2471 |
| 10 | 2412 | 30 | 2432 | 50 | 2452 | 70 | 2472 |
| 11 | 2413 | 31 | 2433 | 51 | 2453 | 71 | 2473 |
| 12 | 2414 | 32 | 2434 | 52 | 2454 | 72 | 2474 |
| 13 | 2415 | 33 | 2435 | 53 | 2455 | 73 | 2475 |
| 14 | 2416 | 34 | 2436 | 54 | 2456 | 74 | 2476 |
| 15 | 2417 | 35 | 2437 | 55 | 2457 | 75 | 2477 |
| 16 | 2418 | 36 | 2438 | 56 | 2458 | 76 | 2478 |
| 17 | 2419 | 37 | 2439 | 57 | 2459 | 77 | 2479 |
| 18 | 2420 | 38 | 2440 | 58 | 2460 | 78 | 2480 |
| 19 | 2421 | 39 | 2441 | 59 | 2461 | | |

1.1.7 Test Tool and Duty Cycle

| Test Tool | Blue Tool, V1.6.2.0 |
|-----------|---------------------|

1.1.8 Power Setting

| Madulation Mada | Test Frequency (MHz) | | | |
|-----------------|----------------------|------|------|--|
| Modulation Mode | 2402 | 2441 | 2480 | |
| GFSK/1Mbps | 0 | 0 | 0 | |
| 8DPSK/3Mbps | 0 | 0 | 0 | |


Report No.: FR421807AD Page: 6 of 46



1.2 Local Support Equipment List

| | Support Equipment List | | | | | | | |
|-----|------------------------|-------|-------|-----|--------|------------------------------------------|--|--|
| No. | Equipment | Brand | Model | S/N | FCC ID | Signal cable / Length (m) | | |
| 1 | Notebook | DELL | E6430 | | DoC | USB 0.5m non-shielded cable with 1 core. | | |

1.3 Test Setup Chart



Report No.: FR421807AD Page: 7 of 46



1.4 The Equipment List

| Conducted Emission Conduction room 1 / (CO01-WS) | | | | | | | | |
|---------------------------------------------------|---------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|--|--|-----------------------------------------------------------------------------|
| | | | | | | | | Instrument Manufacturer Model No. Serial No. Calibration Date Calibration U |
| R&S | ESCS 30 | 100169 | Oct. 15, 2013 | Oct. 14, 2014 | | | | |
| SCHWARZBECK | Schwarzbeck 8127 | 8127-667 | Nov. 23, 2013 | Nov. 22, 2014 | | | | |
| SCHWARZBECK | Schwarzbeck 8127 | 8127-666 | Dec. 04, 2013 | Dec. 03, 2014 | | | | |
| Woken | CFD200-NL | CFD200-NL-001 | Apr. 24, 2013 | Apr. 23, 2014 | | | | |
| NA | 50 | 04 | Apr. 22, 2013 | Apr. 21, 2014 | | | | |
| | Conduction room 1 / (Manufacturer R&S SCHWARZBECK SCHWARZBECK Woken | Conduction room 1 / (CO01-WS) Manufacturer Model No. R&S ESCS 30 SCHWARZBECK Schwarzbeck 8127 SCHWARZBECK Schwarzbeck 8127 Woken CFD200-NL | Manufacturer Model No. Serial No. R&S ESCS 30 100169 SCHWARZBECK Schwarzbeck 8127 8127-667 SCHWARZBECK Schwarzbeck 8127 8127-666 Woken CFD200-NL CFD200-NL-001 | Manufacturer Model No. Serial No. Calibration Date R&S ESCS 30 100169 Oct. 15, 2013 SCHWARZBECK Schwarzbeck 8127 8127-667 Nov. 23, 2013 SCHWARZBECK Schwarzbeck 8127 8127-666 Dec. 04, 2013 Woken CFD200-NL CFD200-NL-001 Apr. 24, 2013 | | | | |

| Test Item | Radiated Emission | | | | |
|-------------------------|----------------------------------------------------|-----------------------|------------------|---------------|-------------------|
| Test Site | 966 chamber 2 / (03C | CH02-WS) | | | |
| Instrument | Manufacturer Model No. Serial No. Calibration Date | | | | Calibration Until |
| Spectrum Analyzer | R&S | FSV40 | 101499 | Feb. 08, 2014 | Feb. 07, 2015 |
| Receiver | R&S | ESR3 | 101657 | Jan. 18, 2014 | Jan. 17, 2015 |
| Bilog Antenna | SCHWARZBECK | VULB9168 | VULB9168-524 | Jan. 08, 2014 | Jan. 07, 2015 |
| Horn Antenna 1G-18G | SCHWARZBECK | BBHA 9120 D | BBHA 9120 D 1095 | Jan. 07, 2014 | Jan. 06, 2015 |
| Horn Antenna 18G-40G | SCHWARZBECK | BBHA 9170 | BBHA 9170517 | Dec. 27, 2013 | Dec. 26, 2014 |
| Preamplifier | Burgeon | BPA-530 | 100218 | Dec. 09, 2013 | Dec. 08, 2014 |
| Preamplifier | Agilent | 83017A | MY39501309 | Dec. 09, 2013 | Dec. 08, 2014 |
| Preamplifier | EM | EM18G40G | 060572 | Jun. 20, 2013 | Jun. 19, 2014 |
| RF Cable | HUBER+SUHNER | SUCOFLEX104 | MY16140/4 | Dec. 17, 2013 | Dec. 16, 2014 |
| RF Cable | HUBER+SUHNER | SUCOFLEX104 | MY16018/4 | Dec. 17, 2013 | Dec. 16, 2014 |
| RF Cable | HUBER+SUHNER | SUCOFLEX104 | MY16015/4 | Dec. 17, 2013 | Dec. 16, 2014 |
| LF cable 3M | Woken | CFD400NL-LW | CFD400NL-003 | Dec. 17, 2013 | Dec. 16, 2014 |
| LF cable 10M | Woken | CFD400NL-LW | CFD400NL-004 | Dec. 17, 2013 | Dec. 16, 2014 |
| Note: Calibration Inter | rval of instruments liste | ed above is one year. | • | | • |

| Test Item | Radiated Emission ab | Radiated Emission above 1GHz | | | | | | | |
|---------------------------------------------------------------------|----------------------|----------------------------------------------------------------------|--|--|--|--|--|--|--|
| Test Site | 966 chamber 2 / (03C | 966 chamber 2 / (03CH02-WS) | | | | | | | |
| Instrument | Manufacturer | Manufacturer Model No. Serial No. Calibration Date Calibration Until | | | | | | | |
| Loop Antenna | R&S | R&S HFH2-Z2 100330 Nov. 15, 2012 Nov. 14, 2014 | | | | | | | |
| Note: Calibration Interval of instruments listed above is two year. | | | | | | | | | |

Report No.: FR421807AD Page: 8 of 46



| Test Item | RF Conducted | | | | | | | |
|---------------------------------------------------------------------|------------------------------------------------------------------|-----------|------------|------------------|-------------------|--|--|--|
| Test Site | (TH01-WS) | | | | | | | |
| Instrument | Manufacturer | Model No. | Serial No. | Calibration Date | Calibration Until | | | |
| Spectrum Analyzer | R&S | FSV40 | 101063 | Feb. 17, 2014 | Feb. 16, 2015 | | | |
| Power Meter | Anritsu | ML2495A | 1241002 | Oct. 24, 2013 | Oct. 23, 2014 | | | |
| Power Sensor | Power Sensor Anritsu MA2411B 1207366 Oct. 24, 2013 Oct. 23, 2014 | | | | | | | |
| Note: Calibration Interval of instruments listed above is one year. | | | | | | | | |

1.5 Test Standards

According to the specification of EUT, the EUT must comply with following standards and KDB documents.

47 CFR FCC Part 15.247 FCC Public notice DA 00-705 ANSI C63.10-2009

Note: The EUT has been tested and complied with FCC part 15B requirement. FCC Part 15B test results are issued to another report.

1.6 Measurement Uncertainty

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2)

| Measurement Uncertainty | | | | | |
|-------------------------|-------------|--|--|--|--|
| Parameters | Uncertainty | | | | |
| Bandwidth | ±35.286 Hz | | | | |
| Conducted power | ±0.536 dB | | | | |
| Frequency error | ±35.286 Hz | | | | |
| Temperature | ±0.3 °C | | | | |
| Conducted emission | ±2.946 dB | | | | |
| AC conducted emission | ±2.43 dB | | | | |
| Radiated emission | ±2.49 dB | | | | |

Report No.: FR421807AD Page: 9 of 46



2 Test Configuration

2.1 Testing Condition

| Test Item | Test Site | Ambient Condition | Tested By |
|--------------------|-----------|-------------------|-----------------------------|
| AC Conduction | CO01-WS | 19°C / 65% | Skys Huang |
| Radiated Emissions | 03CH02-WS | 18°C / 63% | Anderson Hong Aska Huang |
| RF Conducted | TH01-WS | 22°C / 62% | Mark Liao |

FCC site registration No.: 657002IC site registration No.: 10807A-2

2.2 The Worst Test Modes and Channel Details

| Test item | Mode | Test Frequency (MHz) | Data Rate (Mbps) | Test Configuration |
|----------------------------|---------------|--------------------------------------|---------------------|-----------------------|
| Conducted Emissions | 8DPSK | 2441 | 3Mbps | - |
| Radiated Emissions < 1GHz | 8DPSK | 2441 | 3Mbps | - |
| Radiated Emissions > 1GHz | GFSK 8DPSK | 2402, 2441, 2480 2402, 2441, 2480 | 1Mbps 3Mbps | - |
| Conducted Output Power | GFSK 8DPSK | 2402, 2441, 2480 2402, 2441, 2480 | 1Mbps 3Mbps | - |
| Number of Hopping Channels | GFSK 8DPSK | 2402~2480 2402~2480 | 1Mbps 3Mbps | - |
| Hopping Channel Separation | GFSK 8DPSK | 2402, 2441, 2480 2402, 2441, 2480 | 1Mbps 3Mbps | - |
| Dwell Time | GFSK 8DPSK | 2402 2402 | 1Mbps 3Mbps | - |

NOTE:

Report No.: FR421807AD Page: 10 of 46

The EUT was pretested with 3 orientations placed on the table for the radiated emission measurement -X, Y, and Z-plane. The **Z-plane** results were found as the worst case and were shown in this report.



3 Transmitter Test Results

3.1 Conducted Emissions


3.1.1 Limit of Conducted Emissions

| Conducted Emissions Limit | | | | | | | |
|----------------------------------------------------------|----|----|--|--|--|--|--|
| Frequency Emission (MHz) Quasi-Peak Average | | | | | | | |
| 0.15-0.5 66 - 56 * 56 - | | | | | | | |
| 0.5-5 | 56 | 46 | | | | | |
| 5-30 60 50 | | | | | | | |
| Note 1: * Decreases with the logarithm of the frequency. | | | | | | | |

3.1.2 Test Procedures

- 1. The device is placed on a test table, raised 80 cm above the reference ground plane. The vertical conducting plane is located 40 cm to the rear of the device.
- 2. The device is connected to line impedance stabilization network (LISN) and other accessories are connected to other LISN. Measured levels of AC power line conducted emission are across the 50 Ω LISN port.
- 3. AC conducted emission measurements is made over frequency range from 150 kHz to 30 MHz.
- 4. This measurement was performed with AC 120V / 60Hz.

3.1.3 Test Setup




Note: 1. Support units were connected to second LISN.

Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes

Report No.: FR421807AD Page: 11 of 46




3.1.4 Test Result of Conducted Emissions



Report No.: FR421807AD Page: 12 of 46





Report No.: FR421807AD Page: 13 of 46



3.2 Unwanted Emissions into Restricted Frequency Bands

3.2.1 Limit of Unwanted Emissions into Restricted Frequency Bands

| Restricted Band Emissions Limit | | | | | | | |
|---------------------------------|-----------------------|-------------------------|----------------------|--|--|--|--|
| Frequency Range (MHz) | Field Strength (uV/m) | Field Strength (dBuV/m) | Measure Distance (m) | | | | |
| 0.009~0.490 | 2400/F(kHz) | 48.5 - 13.8 | 300 | | | | |
| 0.490~1.705 | 24000/F(kHz) | 33.8 - 23 | 30 | | | | |
| 1.705~30.0 | 30 | 29 | 30 | | | | |
| 30~88 | 100 | 40 | 3 | | | | |
| 88~216 | 150 | 43.5 | 3 | | | | |
| 216~960 | 200 | 46 | 3 | | | | |
| Above 960 | 500 | 54 | 3 | | | | |

Note 1:

Qusai-Peak value is measured for frequency below 1GHz except for 9–90 kHz, 110–490 kHz frequency band. Peak and average value are measured for frequency above 1GHz. The limit on average radio frequency emission is as above table. The limit on peak radio frequency emissions is 20 dB above the maximum permitted average emission limit

Note 2:

Measurements may be performed at a distance other than what is specified provided. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor as below, Frequency at or above 30 MHz: 20 dB/decade Frequency below 30 MHz: 40 dB/decade.

3.2.2 Test Procedures

- Measurement is made at a semi-anechoic chamber that incorporates a turntable allowing a EUT rotation of 360°. A continuously-rotating, remotely-controlled turntable is installed at the test site to support the EUT and facilitate determination of the direction of maximum radiation for each EUT emission frequency. The EUT is placed at a height of 0.8 m test table above the ground plane.
- 2. Measurement is made with the antenna positioned in both the horizontal and vertical planes of polarization. The measurement antenna is varied in height (1m ~ 4m) above the reference ground plane to obtain the maximum signal strength. Distance between EUT and antenna is 3 m.
- 3. This investigation is performed with the EUT rotated 360°, the antenna height scanned between 1 m and 4 m, and the antenna rotated to repeat the measurements for both the horizontal and vertical antenna polarizations.

Note:

3

- 1. 120kHz measurement bandwidth of test receiver and Quasi-peak detector is for radiated emission below 1GHz.
- 2. Radiated emission above 1GHz / Peak value RBW=1MHz, VBW=3MHz and Peak detector

Radiated emission above 1GHz / Average value for harmonics
The average value is: Average = Peak value + 20log(Duty cycle) Where the duty factor is calculated from following formula for DH5 packet type which has worst duty factor:


20log (Duty cycle) = 20log
$$\frac{1s / 1600 * 5}{100 \text{ ms}}$$
 = -30.1dB

4. Radiated emission above 1GHz / Average value for other emissions RBW=1MHz, VBW=1/T and Peak detector

Report No.: FR421807AD Page: 14 of 46




3.2.3 Test Setup



Report No.: FR421807AD Page : 15 of 46



3.2.4 Transmitter Radiated Unwanted Emissions (Below 1GHz)



Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

Report No.: FR421807AD Page: 16 of 46



| Modulation | | 8 | 8DPSK T | | Test Fre | est Freq. (MHz) | | 2441 | | | | | |
|--------------|----|-------|---------|----------|----------|-----------------|------------------|--------------------|---------|--------|-----|-------|-------|
| Polarization | | | ١ | Vertical | | | | | | | | | |
| | 90 | Level | (dBuV/r | n) | | | | | | | | | |
| | 80 | | | | | | | | | | | | |
| | 70 | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | 60 | | | | | | | | | | FCC | CLAS | S-B |
| | 50 | | | | | | | | | | | | |
| | 40 | | | | | | | 4 | | | | i | |
| | 30 | 1 | 2 | | 3 | | | - | | | | | |
| | 20 | | | | | | | | | | | | |
| | 10 | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| | 0 | 30 | 100. | 20 | 0. 30 | 0. 40 | 00. 50 Freque | 0. 60 ncy (MHz) | 0. 700. | 800. | 9 | 00. | 1000 |
| | | | Fre | q. E | Emission | Limit | Margin | SA | Factor | Remark | : 4 | ANT | Turn |
| | | | | | level | | | reading | _ | | | ligh | Table |
| | | | MH | Z | dBuV/m | dBuV/n | n dB | dBuV | dB | | (| m | deg |
| : | 1 | | 50 | .48 | 28.80 | 40.00 | -11.20 | 45.51 | -16.71 | Peak | | | |
| | 2 | | | .93 | | | -17.32 | | -22.06 | Peak | | | |
| | 3 | | | .73 | | | -15.32 | | -18.21 | Peak | | | |
| • | 4 | | 527 | .81 | 32.77 | 46.00 | -13.23 | 44.02 | -11.25 | Peak | | | |

44.35 -6.79

-5.45

45.30

Peak

Peak

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

798.53

39.85

Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.


37.56 46.00 -8.44

46.00 -6.15

Report No.: FR421807AD Page: 17 of 46



3.2.5 Transmitter Radiated Unwanted Emissions (Above 1GHz) for GFSK




Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR421807AD Page: 18 of 46






Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR421807AD Page: 19 of 46






Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR421807AD Page: 20 of 46






Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR421807AD Page: 21 of 46






Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR421807AD Page: 22 of 46





Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)


*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR421807AD Page: 23 of 46



3.2.6 Transmitter Radiated Unwanted Emissions (Above 1GHz) for 8DPSK




Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR421807AD Page: 24 of 46






Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR421807AD Page: 25 of 46






Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR421807AD Page: 26 of 46






Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR421807AD Page: 27 of 46






Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR421807AD Page: 28 of 46





Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR421807AD Page: 29 of 46



3.3 Unwanted Emissions into Non-Restricted Frequency Bands

3.3.1 Limit of Unwanted Emissions into Non-Restricted Frequency Bands

The peak output power measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz.

3.3.2 Test Procedures


Reference Level Measurement

- Set the RBW = 100 kHz, VBW = 300 kHz, Detector = peak.
- 2. Set Sweep time = auto couple, Trace mode = max hold.
- 3. Allow trace to fully stabilize.
- 4. Use the peak marker function to determine the maximum amplitude level.

Unwanted Emissions Level Measurement

- 1. Set RBW = 100 kHz, VBW = 300 kHz, Detector = peak.
- 2. Trace Mode = max hold, Sweep = auto couple.
- 3. Allow the trace to stabilize.
- Use peak marker function to determine maximum amplitude of all unwanted emissions within any 100 kHz bandwidth.

3.3.3 Test Setup




Report No.: FR421807AD Page: 30 of 46




3.3.4 Unwanted Emissions into Non-Restricted Frequency Bands

GFSK



Report No.: FR421807AD Page: 31 of 46






Report No.: FR421807AD Page: 32 of 46




8DPSK



Report No.: FR421807AD Page: 33 of 46





Report No.: FR421807AD Page: 34 of 46



3.4 Conducted Output Power

3.4.1 Limit of Unwanted Emissions into Non-Restricted Frequency Bands

| 1 Watt For frequency hopping systems operating in the 2400–2483.5 MHz band employing at least 75 non overlapping hopping channels, and all frequency hopping systems in the 5725–5850 MHz band. |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 0.125 Watt For all other frequency hopping systems in the 2400–2483.5 MHz band. |
| 0.125 Watt For Frequency hopping systems operating in the 2400–2483.5 MHz band have hopping channel carrier frequencies that are separated by two-thirds of the 20 dB bandwidth of the hopping channel. |

3.4.2 Test Procedures

- A wideband power meter is used for power measurement. Bandwidth of power senor and meter is 50MHz
- 2 If duty cycle of test signal is not 100 %, trigger and gating function of power meter will be enabled to capture transmission burst for measuring output power

3.4.3 Test Setup



Report No.: FR421807AD Page: 35 of 46



3.4.4 Test Result of Conducted Output Power

| Modulation Mode | Freq. (MHz) | Output Power (mW) | Output Power (dBm) | Limit (mW) |
|-----------------|-------------|-------------------|-----------------------|------------|
| GFSK | 2402 | 2.44 | 3.88 | 125 |
| GFSK | 2441 | 2.48 | 3.95 | 125 |
| GFSK | 2480 | 2.18 | 3.38 | 125 |
| 8DPSK | 2402 | 3.57 | 5.53 | 125 |
| 8DPSK | 2441 | 3.64 | 5.61 | 125 |
| 8DPSK | 2480 | 3.33 | 5.23 | 125 |

| Modulation Mode | Freq. (MHz) | AV Output Power (mW) | AV Output Power (dBm) |
|-----------------|-------------|----------------------|-----------------------|
| GFSK | 2402 | 2.32 | 3.65 |
| GFSK | 2441 | 2.29 | 3.60 |
| GFSK | 2480 | 2.07 | 3.15 |
| 8DPSK | 2402 | 1.80 | 2.55 |
| 8DPSK | 2441 | 1.83 | 2.63 |
| 8DPSK | 2480 | 1.67 | 2.22 |

Note: Average power is for reference only

Report No.: FR421807AD Page: 36 of 46



3.5 Number of Hopping Frequency


3.5.1 Limit of Number of Hopping Frequency

Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels.

3.5.2 Test Procedures

- 1. Set RBW = 100kHz, VBW = 300kHz, Sweep time = Auto, Detector = Peak Trace max hold.
- 2 Allow trace to stabilize.


3.5.3 Test Setup



Report No.: FR421807AD Page: 37 of 46



3.5.4 Test Result of Number of Hopping Frequency



Report No.: FR421807AD Page: 38 of 46




3.6 20dB and Occupied Bandwidth

3.6.1 Test Procedures

- 1. Set RBW=30kHz, VBW=100kHz, Sweep time = Auto, Detector=Peak Trace max hold
- 2 Allow trace to stabilize
- 3 Use N dB function of spectrum analyzer to measuring 20 dB bandwidth
- 4. Use Occupied bandwidth function of spectrum analyzer to measuring 99% occupied bandwidth

3.6.2 Test Setup




Report No.: FR421807AD Page: 39 of 46



3.6.3 Test result of 20dB and Occupied Bandwidth

| Modulation Mode | Freq. (MHz) | 20dB Bandwidth (MHz) | Occupied Bandwidth (MHz) |
|-----------------|-------------|----------------------|--------------------------|
| GFSK | 2402 | 0.9435 | 0.8813 |
| GFSK | 2441 | 0.9435 | 0.8813 |
| GFSK | 2480 | 0.9435 | 0.8770 |
| 8DPSK | 2402 | 1.3000 | 1.1896 |
| 8DPSK | 2441 | 1.3044 | 1.1939 |
| 8DPSK | 2480 | 1.3044 | 1.1939 |



Report No.: FR421807AD Page: 40 of 46



3.7 Channel Separation


3.7.1 Limit of Channel Separation

- Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.
- Frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater.

3.7.2 Test Procedures

- 1. Set RBW=100kHz, VBW=300kHz, Sweep time = Auto, Detector=Peak Trace max hold
- 2 Allow trace to stabilize
- 3 Use the marker-delta function to determine the separation between the peaks of the adjacent channels. The EUT shall show compliance with the appropriate regulatory limit

3.7.3 Test Setup




Report No.: FR421807AD Page: 41 of 46



3.7.4 Test result of Channel Separation

| Modulation Mode | Freq. (MHz) | Channel Separation (MHz) | 20dB Bandwidth (MHz) | Minimum Limit (MHz) |
|-----------------|-------------|-----------------------------|-------------------------|------------------------|
| GFSK | 2402 | 1.000 | 0.9435 | 0.629 |
| GFSK | 2441 | 1.000 | 0.9435 | 0.629 |
| GFSK | 2480 | 1.000 | 0.9435 | 0.629 |
| 8DPSK | 2402 | 1.000 | 1.3000 | 0.867 |
| 8DPSK | 2441 | 1.000 | 1.3044 | 0.870 |
| 8DPSK | 2480 | 1.000 | 1.3044 | 0.870 |



Report No.: FR421807AD Page: 42 of 46



3.8 Number of Dwell Time


3.8.1 Limit of Dwell time

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

3.8.2 Test Procedures

- Set RBW=100kHz,VBW=300kHz,Sweep time = 500us(DH1),2ms(DH3),4ms(DH5), Detector=Peak, Span=0Hz,Trace max hold
- 2 Enable gating and trigger function of spectrum analyzer to measure burst on time.
- 3. The DH1 packet can cover a single time slot. A maximum length packet has duration of 1 time slots. The hopping rate is 1600 hops/second so the maximum dwell time is 1/1600 seconds, or 0.625ms. DH1 Packet permit maximum 1600 / 79 /2 = 10.12 hops per second in each channel (1 time slot RX, 1 time slot TX). So, the dwell time is the time duration of the pulse times 10.12 x 31.6 = 320 within 31.6 seconds.
- 4. The DH3 packet can cover up to 3 time slots. A maximum length packet has duration of 3 time slots. The hopping rate is 1600 hops/second so the maximum dwell time is 3/1600 seconds, or 1.875ms. DH3 Packet permit maximum 1600 / 79 / 4 = 5.06 hops per second in each channel (3 time slots RX, 1 time slot TX). So, the dwell time is the time duration of the pulse times 5.06 x 31.6 = 160 within 31.6 seconds.
- The DH5 packet can cover up to 5 time slots. Operate DH5 at maximum dwell time and maximum duty cycle. A maximum length packet has duration of 5 time slots. The hopping rate is 1600 hops/second so the maximum dwell time is 5/1600 seconds, or 3.125ms. DH5 Packet permit maximum 1600/ 79 / 6 = 3.37 hops per second in each channel (5 time slots RX, 1 time slot TX). So, the dwell time is the time duration of the pulse times 3.37 x 31.6 = 106.6 within 31.6 seconds

3.8.3 Test Setup




Report No.: FR421807AD Page: 43 of 46




3.8.4 Test Result of Dwell Time

| Modulation Mode | Freq. (MHz) | No. of Pulse in a 31.6 (79Hopping*0.4) | Length of Pulse Time (msec) | Result (sec) | Limit (msec) |
|--------------------|----------------|-------------------------------------------|-----------------------------------|-----------------|-----------------|
| GFSK | 2402 | 320 | 0.43768 | 0.140 | 400 |
| GFSK | 2441 | 160 | 1.70145 | 0.272 | 400 |
| GFSK | 2480 | 106.6 | 2.94928 | 0.314 | 400 |
| 8DPSK | 2402 | 320 | 0.44520 | 0.142 | 400 |
| 8DPSK | 2441 | 160 | 1.71187 | 0.274 | 400 |
| 8DPSK | 2480 | 106.6 | 2.95607 | 0.315 | 400 |



Report No.: FR421807AD Page: 44 of 46





Report No.: FR421807AD Page: 45 of 46



4 Test laboratory information

Established in 2012, ICC provides foremost EMC & RF Testing and advisory consultation services by our skilled engineers and technicians. Our services employ a wide variety of advanced edge test equipment and one of the widest certification extents in the business.

International Certification Corp, it is our definitive objective is to institute long term, trust-based associations with our clients. The expectation we set up with our clients is based on outstanding service, practical expertise and devotion to a certified value structure. Our passion is to grant our clients with best EMC / RF services by oriented knowledgeable and accommodating staff.

Our Test sites are located at Linkou District and Kwei Shan Hsiang. Location map can be found on our website http://www.icertifi.com.tw.

Linkou Kwei Shan

Tel: 886-2-2601-1640 Tel: 886-3-271-8666

No. 30-2, Ding Fwu Tsuen, Lin Kou District, New Taipei
City, Taiwan, R.O.C.

No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan
Hsiang, Tao Yuan Hsien 333, Taiwan, R.O.C.

If you have any suggestion, please feel free to contact us as below information

Tel: 886-3-271-8666 Fax: 886-3-318-0155

Email: ICC_Service@icertifi.com.tw

==END==

Report No.: FR421807AD Page: 46 of 46