

# FCC Test Report

**FCC ID** : NKR-SP69  
**Equipment** : 11abgn/ac WLAN/Bluetooth Combo Module  
**Model No.** : DHUB-SP69  
**Brand Name** : SHARP Corporation  
**Applicant** : Wistron NeWeb Corp.  
**Address** : 20 Park Avenue II, Hsinchu Science Park,  
Hsinchu 308, Taiwan, R.O.C.  
**Standard** : 47 CFR FCC Part 15.247  
**Received Date** : Oct. 03, 2014  
**Tested Date** : Oct. 06 ~ Nov. 12, 2014

We, International Certification Corp., would like to declare that the tested sample has been evaluated and in compliance with the requirement of the above standards. The test results contained in this report refer exclusively to the product. It may be duplicated completely for legal use with the approval of the applicant. It shall not be reproduced except in full without the written approval of our laboratory.

Approved & Reviewed by:

  
\_\_\_\_\_  
Gary Chang / Manager



---

## Table of Contents

<b>1</b>	<b>GENERAL DESCRIPTION .....</b>	<b>5</b>
1.1	Information.....	5
1.2	Local Support Equipment List .....	8
1.3	Test Setup Chart .....	8
1.4	The Equipment List .....	9
1.5	Test Standards .....	10
1.6	Measurement Uncertainty .....	10
<b>2</b>	<b>TEST CONFIGURATION .....</b>	<b>11</b>
2.1	Testing Condition .....	11
2.2	The Worst Test Modes and Channel Details .....	11
<b>3</b>	<b>TRANSMITTER TEST RESULTS.....</b>	<b>12</b>
3.1	Conducted Emissions.....	12
3.2	6dB and Occupied Bandwidth .....	15
3.3	RF Output Power .....	18
3.4	Power Spectral Density .....	20
3.5	Unwanted Emissions into Restricted Frequency Bands .....	22
3.6	Emissions in Non-Restricted Frequency Bands .....	50
<b>4</b>	<b>TEST LABORATORY INFORMATION .....</b>	<b>63</b>

---

## Release Record

Report No.	Version	Description	Issued Date
FR4O1301AC	Rev. 01	Initial issue	Dec. 04, 2014

## Summary of Test Results

FCC Rules	Test Items	Measured	Result
15.207	Conducted Emissions	[dBuV]: 0.502MHz 33.45 (Margin -12.55dB) - AV	Pass
15.247(d) 15.209	Radiated Emissions	[dBuV/m at 3m]: 2390.00MHz 52.98 (Margin -1.02dB) - AV	Pass
15.247(b)(3)	Maximum Output Power	Max Power [dBm]: 27.44	Pass
15.247(a)(2)	6dB Bandwidth	Meet the requirement of limit	Pass
15.247(e)	Power Spectral Density	Meet the requirement of limit	Pass
15.203	Antenna Requirement	Meet the requirement of limit	Pass

# 1 General Description

## 1.1 Information

### 1.1.1 Specification of the Equipment under Test (EUT)

RF General Information					
Frequency Range (MHz)	IEEE Std. 802.11	Ch. Freq. (MHz)	Channel Number	Transmit Chains (N <sub>TX</sub> )	Data Rate / MCS
2400-2483.5	b	2412-2462	1-11 [11]	1 <sup>NOTE 4</sup>	1-11 Mbps
2400-2483.5	g	2412-2462	1-11 [11]	2	6-54 Mbps
2400-2483.5	n (HT20)	2412-2462	1-11 [11]	2	MCS 0-15
2400-2483.5	n (HT40)	2422-2452	3-9 [7]	2	MCS 0-15

Note 1: RF output power specifies that Maximum Peak Conducted Output Power.  
 Note 2: 802.11b uses a combination of DSSS-DBPSK, DQPSK, CCK modulation.  
 Note 3: 802.11g/n uses a combination of OFDM-BPSK, QPSK, 16QAM, 64QAM modulation.  
 Note 4: 802.11b supports diversity function.  
 Note 5: 802.11n supports MIMO CDD and beamforming function.

### 1.1.2 Antenna Details

Ant. No.	Model	Type	Connector	Operating Frequencies (MHz) / Antenna Gain (dBi)				
				2400~2483.5	5150~5250	5250~5350	5470~5725	5725~5850
1	Left antenna	Printed	NA	4.29	3.02	3.51	4.25	4.32
2	Right antenna	Printed	NA	4.47	4.35	4.43	4.43	4.19

### 1.1.3 Power Supply Type of Equipment under Test (EUT)

<b>Power Supply Type</b>	5Vdc from host
--------------------------	----------------

### 1.1.4 Accessories

N/A

### 1.1.5 Channel List

Frequency band (MHz)		2400~2483.5	
802.11 b / g / n HT20		802.11n HT40	
Channel	Frequency(MHz)	Channel	Frequency(MHz)
1	2412	3	2422
2	2417	4	2427
3	2422	5	2432
4	2427	6	2437
5	2432	7	2442
6	2437	8	2447
7	2442	9	2452
8	2447	---	---
9	2452	---	---
10	2457	---	---
11	2462	---	---

### 1.1.6 Test Tool and Duty Cycle

Test Tool	MTool, Version: 2.0.1.1		
Duty Cycle and Duty Factor	Mode	Duty cycle (%)	Duty factor (dB)
	11b	100.00%	0.00
	11g	99.52%	0.02
	HT20	91.03%	0.41
	HT40	77.93%	1.08

### 1.1.7 Power Setting

Modulation Mode	Test Frequency (MHz)	Power Set
11b	2412	64
11b	2437	78
11b	2462	62
11g	2412	60
11g	2437	72
11g	2462	64
HT20	2412	56
HT20	2437	72
HT20	2462	60
HT40	2422	40
HT40	2437	50
HT40	2452	44


## 1.2 Local Support Equipment List

Support Equipment List					
No.	Equipment	Brand	Model	FCC ID	Signal cable / Length (m)
1	Notebook	DELL	Latitude E6430	DoC	Fixture cable, 0.12m non-shielded w/o core.
2	AP	LINSYS	EA6900	DoC	---

Note:

- 1) No.2 was provided by applicant.
- 2) No.2 was for 11n / 11ac mode use only.

## 1.3 Test Setup Chart



Note: The support AP was for beamforming test use only.



## 1.4 The Equipment List

Test Item	Conducted Emission				
Test Site	Conduction room 1 / (CO01-WS)				
Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Until
EMC Receiver	R&S	ESCS 30	100174	Apr. 14. 2014	Apr. 13. 2015
LISN	SCHWARZBECK	Schwarzbeck 8127	8127-667	Nov. 23, 2013	Nov. 22, 2014
LISN (Support Unit)	SCHWARZBECK	Schwarzbeck 8127	8127-666	Dec. 04, 2013	Dec. 03, 2014
RF Cable-CON	Woken	CFD200-NL	CFD200-NL-001	Apr. 23, 2014	Apr. 22, 2015
50 ohm terminal (Support Unit)	NA	50	04	Apr. 18, 2014	Apr. 17, 2015
Measurement Software	AUDIX	e3	6.120210k	NA	NA

Note: Calibration Interval of instruments listed above is one year.

Test Item	Radiated Emission				
Test Site	966 chamber 3 / (03CH03-WS)				
Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Until
Spectrum Analyzer	Agilent	N9010A	MY53400091	Sep. 16, 2014	Sep. 15, 2015
Receiver	R&S	ESR3	101657	Jan. 18, 2014	Jan. 17, 2015
Bilog Antenna	SCHWARZBECK	VULB9168	VULB9168-562	Feb. 07, 2014	Feb. 06, 2015
Horn Antenna 1G-18G	SCHWARZBECK	BBHA 9120 D	BBHA 9120 D 1206	Feb. 20, 2014	Feb. 19, 2015
Horn Antenna 18G-40G	SCHWARZBECK	BBHA 9170	BBHA9170154	Jan. 10, 2014	Jan. 09, 2015
Preamplifier	EMC	EMC02325	980187	Nov. 22, 2013	Nov. 21, 2014
Preamplifier	Agilent	83017A	MY53270014	Sep. 17, 2014	Sep. 16, 2015
Preamplifier	EMC	EMC184045B	980192	Aug. 26, 2014	Aug. 25, 2015
RF cable-3M	HUBER+SUHNER	SUCOFLEX104	MY22620/4	Feb. 19, 2014	Feb. 18, 2015
RF cable-8M	HUBER+SUHNER	SUCOFLEX104	MY22601/4	Feb. 19, 2014	Feb. 18, 2015
RF cable-1M	HUBER+SUHNER	SUCOFLEX104	MY22624/4	Feb. 19, 2014	Feb. 18, 2015
LF cable-0.8M	EMC	EMC8D-NM-NM-800	EMC8D-NM-NM-800-001	Feb. 17, 2014	Feb. 16, 2015
LF cable-3M	EMC	EMC8D-NM-NM-3000	131103	Feb. 17, 2014	Feb. 16, 2015
LF cable-13M	EMC	EMC8D-NM-NM-13000	131104	Feb. 17, 2014	Feb. 16, 2015
Measurement Software	AUDIX	e3	6.120210g	NA	NA

Note: Calibration Interval of instruments listed above is one year.

Loop Antenna	R&S	HFH2-Z2	100330	Nov. 15, 2012	Nov. 14, 2014
--------------	-----	---------	--------	---------------	---------------

Note: Calibration Interval of instruments listed above is two year.

<b>Test Item</b>	RF Conducted				
<b>Test Site</b>	(TH01-WS)				
<b>Instrument</b>	<b>Manufacturer</b>	<b>Model No.</b>	<b>Serial No.</b>	<b>Calibration Date</b>	<b>Calibration Until</b>
Spectrum Analyzer	R&S	FSV40	101063	Feb. 17, 2014	Feb. 16, 2015
Power Meter	Anritsu	ML2495A	1241002	Sep. 29, 2014	Sep. 28, 2015
Power Sensor	Anritsu	MA2411B	1207366	Sep. 29, 2014	Sep. 28, 2015
Measurement Software	Sporton	Sporton_1	1.3.30	NA	NA
Note: Calibration Interval of instruments listed above is one year.					

## 1.5 Test Standards

According to the specification of EUT, the EUT must comply with following standards and KDB documents.

47 CFR FCC Part 15.247

ANSI C63.10-2009

FCC KDB 558074 D01 DTS Meas Guidance v03r02

FCC KDB 662911 D01 Multiple Transmitter Output v02r01

## 1.6 Measurement Uncertainty

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2))

Measurement Uncertainty	
Parameters	Uncertainty
Bandwidth	±34.134 Hz
Conducted power	±0.808 dB
Frequency error	±34.134 Hz
Temperature	±0.6 °C
Conducted emission	±2.670 dB
AC conducted emission	±2.92 dB
Radiated emission ≤ 1GHz	±3.26 dB
Radiated emission > 1GHz	±4.94 dB

## 2 Test Configuration

### 2.1 Testing Condition

Test Item	Test Site	Ambient Condition	Tested By
AC Conduction	CO01-WS	22°C / 69%	Peter Lin
Radiated Emissions	03CH03-WS	21-22°C / 61-63%	Anderson Hung Aska Huang
RF Conducted	TH01-WS	22°C / 63%	Brad Wu

➤ FCC site registration No.: 390588

➤ IC site registration No.: 10807C-1

### 2.2 The Worst Test Modes and Channel Details

Test item	Modulation Mode	Test Frequency (MHz)	Data Rate (Mbps) / MCS	Test Configuration
Conducted Emissions	HT20	2437	MCS 8	2Tx
Radiated Emissions ≤1GHz	HT20	2437	MCS 8	2Tx
Radiated Emissions >1GHz Maximum Output Power 6dB bandwidth Power spectral density	11b	2412 / 2437 / 2462	1 Mbps	1Tx / chain 1
	11g	2412 / 2437 / 2462	6 Mbps	2Tx
	HT20	2412 / 2437 / 2462	MCS 0 MCS 8	2Tx
	HT40	2422 / 2437 / 2452	MCS 0 MCS 8	2Tx

**NOTE:**

- The device supports diversity function that listed as below:
  - 802.11b, 1Tx, chain 0 or chain 1.  
After pre-testing, **chain 1** has the worst emission value, therefore the following test results came out from this.
- The device supports non-beamforming and beamforming function in 802.11n. After pre-testing, **beamforming mode** has the worst emission value, therefore the following test results came out from this.
- The EUT was pretested with 3 orientations placed on the table for the radiated emission measurement – X, Y, and Z-plane. The **Y-plane** results were found as the worst case and were shown in this report.

## 3 Transmitter Test Results

### 3.1 Conducted Emissions

#### 3.1.1 Limit of Conducted Emissions

Conducted Emissions Limit		
Frequency Emission (MHz)	Quasi-Peak	Average
0.15-0.5	66 - 56 *	56 - 46 *
0.5-5	56	46
5-30	60	50

Note 1: \* Decreases with the logarithm of the frequency.

#### 3.1.2 Test Procedures


1. The device is placed on a test table, raised 80 cm above the reference ground plane. The vertical conducting plane is located 40 cm to the rear of the device.
2. The device is connected to line impedance stabilization network (LISN) and other accessories are connected to other LISN. Measured levels of AC power line conducted emission are across the 50  $\Omega$  LISN port.
3. AC conducted emission measurements is made over frequency range from 150 kHz to 30 MHz.
4. This measurement was performed with AC 120V / 60Hz.

#### 3.1.3 Test Setup




- Note: 1. Support units were connected to second LISN.  
 2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes

### 3.1.4 Test Result of Conducted Emissions



<b>Modulation</b>	HT20	<b>Test Freq. (MHz)</b>	2437
<b>Power Phase</b>	Neutral		



	Freq MHz	Level dBuV	Limit Line dBuV	Over Limit dB	Read Level dBuV	LISN factor dB	cable loss dB	Remark
1	0.155	37.87	55.74	-17.87	37.37	0.48	0.02	Average
2	0.155	46.88	65.74	-18.86	46.38	0.48	0.02	QP
3	0.252	24.34	51.69	-27.35	23.85	0.48	0.01	Average
4	0.252	36.79	61.69	-24.90	36.30	0.48	0.01	QP
5*	0.502	33.45	46.00	-12.55	32.96	0.47	0.02	Average
6	0.502	38.82	56.00	-17.18	38.33	0.47	0.02	QP
7	1.810	24.10	46.00	-21.90	23.58	0.50	0.02	Average
8	1.810	28.93	56.00	-27.07	28.41	0.50	0.02	QP
9	4.070	15.57	46.00	-30.43	14.90	0.52	0.15	Average
10	4.070	22.01	56.00	-33.99	21.34	0.52	0.15	QP
11	9.328	17.45	50.00	-32.55	16.65	0.56	0.24	Average
12	9.328	26.62	60.00	-33.38	25.82	0.56	0.24	QP

Note 1: Level (dBuV) = Read Level (dBuV) + LISN Factor (dB) + Cable Loss (dB).  
 Note 2: Over Limit (dB) = Level (dBuV) – Limit Line (dBuV).

## 3.2 6dB and Occupied Bandwidth


### 3.2.1 Limit of 6dB Bandwidth

The minimum 6dB bandwidth shall be at least 500 kHz.

### 3.2.2 Test Procedures


1. Set resolution bandwidth (RBW) = 100 kHz, Video bandwidth = 300 kHz.
2. Detector = Peak, Trace mode = max hold.
3. Sweep = auto couple, Allow the trace to stabilize.
4. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower) that are attenuated by 6dB relative to the maximum level measured in the fundamental emission.

### 3.2.3 Test Setup




### 3.2.4 Test Result of 6dB and Occupied Bandwidth

Modulation Mode	N <sub>TX</sub>	Freq. (MHz)	6dB Bandwidth (MHz)				Limit (kHz)
			Chain 0	Chain 1	Chain 2	Chain 3	
11b	1	2412	---	9.04	---	---	500
11b	1	2437	---	9.10	---	---	500
11b	1	2462	---	8.58	---	---	500
11g	2	2412	16.35	16.35	---	---	500
11g	2	2437	16.41	16.35	---	---	500
11g	2	2462	16.35	16.35	---	---	500
HT20	2	2412	17.62	17.57	---	---	500
HT20	2	2437	17.57	17.62	---	---	500
HT20	2	2462	17.62	17.57	---	---	500
HT40	2	2422	36.41	36.41	---	---	500
HT40	2	2437	36.41	36.41	---	---	500
HT40	2	2452	36.41	36.41	---	---	500





Modulation Mode	N <sub>TX</sub>	Freq. (MHz)	99% Occupied Bandwidth (MHz)			
			Chain 0	Chain 1	Chain 2	Chain 3
11b	1	2412	---	11.79	---	---
11b	1	2437	---	12.01	---	---
11b	1	2462	---	11.27	---	---
11g	2	2412	18.28	17.07	---	---
11g	2	2437	17.15	17.63	---	---
11g	2	2462	17.18	17.06	---	---
HT20	2	2412	18.17	18.00	---	---
HT20	2	2437	18.35	18.03	---	---
HT20	2	2462	18.16	17.99	---	---
HT40	2	2422	36.82	36.62	---	---
HT40	2	2437	36.66	36.56	---	---
HT40	2	2452	36.66	36.62	---	---



## 3.3 RF Output Power

### 3.3.1 Limit of RF Output Power

Conducted power shall not exceed 1Watt.


- Antenna gain  $\leq$  6dBi, no any corresponding reduction is in output power limit.
- Antenna gain  $>$  6dBi
  - Non Fixed, point to point operations.  
The conducted output power from the intentional radiator shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dB
  - Fixed, point to point operations  
Systems operating in the 2400–2483.5 MHz band that are used exclusively for fixed, point-to-point Operations, maximum peak output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.

Systems operating in the 5725–5850 MHz band that are used exclusively for fixed, point-to-point operations ,no any corresponding reduction is in transmitter peak output power

### 3.3.2 Test Procedures

- Maximum Peak Conducted Output Power
  - Spectrum analyzer**
    1. Set RBW = 1MHz, VBW = 3MHz, Detector = Peak.
    2. Sweep time = auto, Trace mode = max hold, Allow trace to fully stabilize.
    3. Use the spectrum analyzer channel power measurement function with the band limits set equal to the DTS bandwidth edges.
  - Power meter**
    1. A broadband Peak RF power meter is used for output power measurement. The video bandwidth of power meter is greater than DTS bandwidth of EUT. If duty cycle of test signal is not 100 %, trigger and gating function of power meter will be enabled to capture transmission burst for measuring output power.
- Maximum Conducted Output Power ( For reference only )
  - Power meter**
    1. A broadband Average RF power meter is used for output power measurement. The video bandwidth of power meter is greater than DTS bandwidth of EUT. If duty cycle of test signal is not 100 %, trigger and gating function of power meter will be enabled to capture transmission burst for measuring output power.

### 3.3.3 Test Setup



### 3.3.4 Test Result of Maximum Output Power

Modulation Mode	N <sub>TX</sub>	Freq. (MHz)	Peak conducted output power (dBm)				Total Power (mW)	Total Power (dBm)	Limit (dBm)
			Chain 0	Chain 1	Chain 2	Chain 3			
11b	1	2412	---	20.82	---	---	120.781	20.82	30.00
11b	1	2437	---	24.67	---	---	293.089	24.67	30.00
11b	1	2462	---	19.60	---	---	91.201	19.60	30.00
11g	2	2412	22.53	21.61	---	---	323.938	25.10	30.00
11g	2	2437	24.01	24.27	---	---	519.068	27.15	30.00
11g	2	2462	22.23	22.67	---	---	352.036	25.47	30.00
HT20	2	2412	22.27	22.22	---	---	335.380	25.26	28.61
HT20	2	2437	24.27	24.58	---	---	554.379	27.44	28.61
HT20	2	2462	21.88	22.56	---	---	334.472	25.24	28.61
HT40	2	2422	18.62	20.05	---	---	173.936	22.40	28.61
HT40	2	2437	21.55	22.21	---	---	309.231	24.90	28.61
HT40	2	2452	19.13	20.86	---	---	203.745	23.09	28.61

Note: 11n mode supports Beamforming.

Directional Antenna gain for 11n mode is  $10 * \log((10^{4.29/20} + 10^{4.47/20})^2 / 2) = 7.39 \text{ dBi} > 6 \text{ dBi}$ , conducted power limit of HT20 and HT40 is reduced to  $30 \text{ dBm} - (7.39 \text{ dBi} - 6 \text{ dBi}) = 28.61 \text{ dBm}$

Modulation Mode	N <sub>TX</sub>	Freq. (MHz)	Conducted (average) output power (dBm)				Total Power (mW)	Total Power (dBm)	Limit (dBm)
			Chain 0	Chain 1	Chain 2	Chain 3			
11b	1	2412	---	16.72	---	---	46.989	16.72	30.00
11b	1	2437	---	21.55	---	---	142.889	21.55	30.00
11b	1	2462	---	16.19	---	---	41.591	16.19	30.00
11g	2	2412	15.27	15.20	---	---	66.764	18.25	30.00
11g	2	2437	18.44	18.25	---	---	136.658	21.36	30.00
11g	2	2462	15.67	16.33	---	---	79.851	19.02	30.00
HT20	2	2412	14.51	14.48	---	---	56.303	17.51	28.61
HT20	2	2437	18.56	18.45	---	---	141.764	21.52	28.61
HT20	2	2462	14.91	15.38	---	---	65.489	18.16	28.61
HT40	2	2422	10.59	11.42	---	---	25.323	14.04	28.61
HT40	2	2437	13.25	13.80	---	---	45.123	16.54	28.61
HT40	2	2452	11.83	12.63	---	---	33.564	15.26	28.61

Note: Conducted average output power is for reference only.

## 3.4 Power Spectral Density


### 3.4.1 Limit of Power Spectral Density

Power spectral density shall not be greater than 8 dBm in any 3 kHz band.

### 3.4.2 Test Procedures

- Maximum peak conducted output power was used to demonstrate compliance to the fundamental output power limit.
  1. Set the RBW = 3kHz, VBW = 10kHz.
  2. Detector = Peak, Sweep time = auto couple.
  3. Trace mode = max hold, allow trace to fully stabilize.
  4. Use the peak marker function to determine the maximum amplitude level.
- Maximum (average) conducted output power was used to demonstrate compliance to the fundamental output power limit.
  1. Set the RBW = 100kHz, VBW = 300 kHz.
  2. Detector = RMS, Sweep time = auto couple.
  3. Set the sweep time to:  $\geq 10 \times (\text{number of measurement points in sweep}) \times (\text{maximum data rate per stream})$ .
  4. Perform the measurement over a single sweep.
  5. Use the peak marker function to determine the maximum amplitude level.

### 3.4.3 Test Setup




### 3.4.4 Test Result of Power Spectral Density

Modulation Mode	N <sub>TX</sub>	Freq. (MHz)	Total Power Spectral Density (dBm/3kHz)	Limit (dBm/3kHz)
11b	1	2412	-6.07	8.00
11b	1	2437	-2.25	8.00
11b	1	2462	-6.35	8.00
11g	2	2412	-7.31	6.61
11g	2	2437	-4.12	6.61
11g	2	2462	-6.47	6.61
HT20	2	2412	-8.58	6.61
HT20	2	2437	-4.85	6.61
HT20	2	2462	-7.91	6.61
HT40	2	2422	-15.79	6.61
HT40	2	2437	-13.20	6.61
HT40	2	2452	-15.56	6.61

Note:

1. D.F is duty factor.
2. Test result for 2 Tx mode is bin-by-bin summing measured value of each TX port.
3. Directional gain for 2 Tx mode =  $10 * \log((10^{4.29/20} + 10^{4.47/20})^2 / 2) = 7.39 \text{ dBi} > 6 \text{ dBi}$ .  
Limit shall be reduced to  $8 \text{ dBm} - (7.39 \text{ dBi} - 6 \text{ dBi}) = 6.61 \text{ dBm}$



## 3.5 Unwanted Emissions into Restricted Frequency Bands

### 3.5.1 Limit of Unwanted Emissions into Restricted Frequency Bands

Restricted Band Emissions Limit			
Frequency Range (MHz)	Field Strength (uV/m)	Field Strength (dBuV/m)	Measure Distance (m)
0.009~0.490	2400/F(kHz)	48.5 - 13.8	300
0.490~1.705	24000/F(kHz)	33.8 - 23	30
1.705~30.0	30	29	30
30~88	100	40	3
88~216	150	43.5	3
216~960	200	46	3
Above 960	500	54	3

**Note 1:**  
 Qusai-Peak value is measured for frequency below 1GHz except for 9–90 kHz, 110–490 kHz frequency band. Peak and average value are measured for frequency above 1GHz. The limit on average radio frequency emission is as above table. The limit on peak radio frequency emissions is 20 dB above the maximum permitted average emission limit

**Note 2:**  
 Measurements may be performed at a distance other than what is specified provided. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor as below, Frequency at or above 30 MHz: 20 dB/decade Frequency below 30 MHz: 40 dB/decade.

### 3.5.2 Test Procedures


1. Measurement is made at a semi-anechoic chamber that incorporates a turntable allowing a EUT rotation of 360°. A continuously-rotating, remotely-controlled turntable is installed at the test site to support the EUT and facilitate determination of the direction of maximum radiation for each EUT emission frequency. The EUT is placed at a height of 0.8 m test table above the ground plane.
2. Measurement is made with the antenna positioned in both the horizontal and vertical planes of polarization. The measurement antenna is varied in height (1m ~ 4m) above the reference ground plane to obtain the maximum signal strength. Distance between EUT and antenna is 3 m.
3. This investigation is performed with the EUT rotated 360°, the antenna height scanned between 1 m and 4 m, and the antenna rotated to repeat the measurements for both the horizontal and vertical antenna polarizations.

Note:


1. 120kHz measurement bandwidth of test receiver and Quasi-peak detector is for radiated emission below 1GHz.
2. RBW=1MHz, VBW=3MHz and Peak detector is for peak measured value of radiated emission above 1GHz.
3. RBW=1MHz, VBW=1/T and Peak detector is for average measured value of radiated emission above 1GHz.

### 3.5.3 Test Setup

#### Radiated Emissions below 1 GHz




#### Radiated Emissions above 1 GHz



### 3.5.4 Transmitter Radiated Unwanted Emissions (Below 1GHz)

Modulation	HT20	Test Freq. (MHz)	2437
Polarization	Horizontal	Transmit Chains (N <sub>TX</sub> )	2Tx



The graph plots Level (dBuV/m) on the y-axis (0 to 90) against Frequency (MHz) on the x-axis (30 to 1000). A red stepped line represents the FCC CLASS-B limit, which is 40 dBuV/m from 30 to 100 MHz, 43.5 dBuV/m from 100 to 200 MHz, 46 dBuV/m from 200 to 1000 MHz, and 55 dBuV/m above 1000 MHz. Six blue vertical lines represent emission peaks labeled 1 through 6, with their levels and margins indicated in the table below.


	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	69.77	36.18	40.00	-3.82	51.51	-15.33	Peak	---	---
2	165.80	26.05	43.50	-17.45	39.76	-13.71	Peak	---	---
3	233.70	40.73	46.00	-5.27	55.83	-15.10	Peak	---	---
4	354.95	38.13	46.00	-7.87	49.36	-11.23	Peak	---	---
5	482.02	33.27	46.00	-12.73	41.49	-8.22	Peak	---	---
6	724.52	33.97	46.00	-12.03	37.62	-3.65	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)  
 \*Factor includes antenna factor, cable loss and amplifier gain  
 Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).  
 Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.



<b>Modulation</b>	HT20	<b>Test Freq. (MHz)</b>	2437
<b>Polarization</b>	Vertical	<b>Transmit Chains (N<sub>TX</sub>)</b>	2Tx



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	119.24	28.83	43.50	-14.67	44.57	-15.74	Peak	---	---
2	279.29	32.22	46.00	-13.78	45.35	-13.13	Peak	---	---
3	279.29	32.22	46.00	-13.78	45.35	-13.13	Peak	---	---
4	366.59	31.44	46.00	-14.56	42.40	-10.96	Peak	---	---
5	480.08	30.68	46.00	-15.32	38.92	-8.24	Peak	---	---
6	731.31	33.30	46.00	-12.70	36.82	-3.52	Peak	---	---


Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor , cable loss and amplifier gain


Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

### 3.5.5 Transmitter Radiated Unwanted Emissions (Above 1GHz) for 11b

Modulation	11b	Test Freq. (MHz)	2412																																																																													
Polarization	Horizontal	Transmit Chains (N <sub>TX</sub> )	1Tx																																																																													
																																																																																
	<table border="1"> <thead> <tr> <th>Freq.</th> <th>Emission level</th> <th>Limit</th> <th>Margin</th> <th>SA reading</th> <th>Factor</th> <th>Remark</th> <th>ANT High cm</th> <th>Turn Table deg</th> </tr> <tr> <th>MHz</th> <th>dBuV/m</th> <th>dBuV/m</th> <th>dB</th> <th>dBuV</th> <th>dB</th> <th></th> <th></th> <th></th> </tr> </thead> <tbody> <tr> <td>1</td> <td>2387.00</td> <td>52.89</td> <td>54.00</td> <td>-1.11</td> <td>54.58</td> <td>-1.69</td> <td>Average</td> <td>---</td> </tr> <tr> <td>2</td> <td>2387.00</td> <td>59.58</td> <td>74.00</td> <td>-14.42</td> <td>61.27</td> <td>-1.69</td> <td>Peak</td> <td>---</td> </tr> <tr> <td>3</td> <td>3618.00</td> <td>42.15</td> <td>54.00</td> <td>-11.85</td> <td>40.35</td> <td>1.80</td> <td>Average</td> <td>---</td> </tr> <tr> <td>4</td> <td>3618.00</td> <td>46.44</td> <td>74.00</td> <td>-27.56</td> <td>44.64</td> <td>1.80</td> <td>Peak</td> <td>---</td> </tr> <tr> <td>5</td> <td>4824.00</td> <td>45.03</td> <td>54.00</td> <td>-8.97</td> <td>39.63</td> <td>5.40</td> <td>Average</td> <td>---</td> </tr> <tr> <td>6</td> <td>4824.00</td> <td>48.60</td> <td>74.00</td> <td>-25.40</td> <td>43.20</td> <td>5.40</td> <td>Peak</td> <td>---</td> </tr> </tbody> </table>	Freq.	Emission level	Limit	Margin	SA reading	Factor	Remark	ANT High cm	Turn Table deg	MHz	dBuV/m	dBuV/m	dB	dBuV	dB				1	2387.00	52.89	54.00	-1.11	54.58	-1.69	Average	---	2	2387.00	59.58	74.00	-14.42	61.27	-1.69	Peak	---	3	3618.00	42.15	54.00	-11.85	40.35	1.80	Average	---	4	3618.00	46.44	74.00	-27.56	44.64	1.80	Peak	---	5	4824.00	45.03	54.00	-8.97	39.63	5.40	Average	---	6	4824.00	48.60	74.00	-25.40	43.20	5.40	Peak	---							
Freq.	Emission level	Limit	Margin	SA reading	Factor	Remark	ANT High cm	Turn Table deg																																																																								
MHz	dBuV/m	dBuV/m	dB	dBuV	dB																																																																											
1	2387.00	52.89	54.00	-1.11	54.58	-1.69	Average	---																																																																								
2	2387.00	59.58	74.00	-14.42	61.27	-1.69	Peak	---																																																																								
3	3618.00	42.15	54.00	-11.85	40.35	1.80	Average	---																																																																								
4	3618.00	46.44	74.00	-27.56	44.64	1.80	Peak	---																																																																								
5	4824.00	45.03	54.00	-8.97	39.63	5.40	Average	---																																																																								
6	4824.00	48.60	74.00	-25.40	43.20	5.40	Peak	---																																																																								
<p>Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)            *Factor includes antenna factor , cable loss and amplifier gain            Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).</p>																																																																																

<b>Modulation</b>	11b	<b>Test Freq. (MHz)</b>	2412
<b>Polarization</b>	Vertical	<b>Transmit Chains (N<sub>TX</sub>)</b>	1Tx




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2387.00	44.27	54.00	-9.73	45.96	-1.69	Average	---	---
2	2387.00	53.45	74.00	-20.55	55.14	-1.69	Peak	---	---
3	3618.00	46.23	54.00	-7.77	44.43	1.80	Average	---	---
4	3618.00	50.11	74.00	-23.89	48.31	1.80	Peak	---	---
5	4824.00	51.02	54.00	-2.98	45.62	5.40	Average	---	---
6	4824.00	53.55	74.00	-20.45	48.15	5.40	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

<b>Modulation</b>	11b	<b>Test Freq. (MHz)</b>	2437
<b>Polarization</b>	Horizontal	<b>Transmit Chains (N<sub>TX</sub>)</b>	1Tx




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	52.93	54.00	-1.07	54.61	-1.68	Average	---	---
2	2390.00	62.80	74.00	-11.20	64.48	-1.68	Peak	---	---
3	2483.50	49.15	54.00	-4.85	50.49	-1.34	Average	---	---
4	2483.50	60.04	74.00	-13.96	61.38	-1.34	Peak	---	---
5	3655.50	42.29	54.00	-11.71	40.36	1.93	Average	---	---
6	3655.50	46.19	74.00	-27.81	44.26	1.93	Peak	---	---
7	4874.00	45.96	54.00	-8.04	40.43	5.53	Average	---	---
8	4874.00	49.52	74.00	-24.48	43.99	5.53	Peak	---	---
9	7311.00	49.98	54.00	-4.02	38.69	11.29	Average	---	---
10	7311.00	55.60	74.00	-18.40	44.31	11.29	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

<b>Modulation</b>	11b	<b>Test Freq. (MHz)</b>	2437
<b>Polarization</b>	Vertical	<b>Transmit Chains (N<sub>TX</sub>)</b>	1Tx




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	46.07	54.00	-7.93	47.75	-1.68	Average	---	---
2	2390.00	55.83	74.00	-18.17	57.51	-1.68	Peak	---	---
3	2483.50	44.49	54.00	-9.51	45.83	-1.34	Average	---	---
4	2483.50	56.78	74.00	-17.22	58.12	-1.34	Peak	---	---
5	3655.50	47.40	54.00	-6.60	45.47	1.93	Average	---	---
6	3655.50	50.13	74.00	-23.87	48.20	1.93	Peak	---	---
7	4874.00	50.63	54.00	-3.37	45.10	5.53	Average	---	---
8	4874.00	52.91	74.00	-21.09	47.38	5.53	Peak	---	---
9	7311.00	46.21	54.00	-7.79	34.92	11.29	Average	---	---
10	7311.00	53.86	74.00	-20.14	42.57	11.29	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

<b>Modulation</b>	11b	<b>Test Freq. (MHz)</b>	2462
<b>Polarization</b>	Horizontal	<b>Transmit Chains (N<sub>TX</sub>)</b>	1Tx




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2483.50	52.82	54.00	-1.18	54.16	-1.34	Average	---	---
2	2483.50	60.84	74.00	-13.16	62.18	-1.34	Peak	---	---
3	4924.00	49.05	54.00	-4.95	43.40	5.65	Average	---	---
4	4924.00	51.86	74.00	-22.14	46.21	5.65	Peak	---	---
5	7386.00	49.43	54.00	-4.57	38.11	11.32	Average	---	---
6	7386.00	55.13	74.00	-18.87	43.81	11.32	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

<b>Modulation</b>	11b	<b>Test Freq. (MHz)</b>	2462
<b>Polarization</b>	Vertical	<b>Transmit Chains (N<sub>TX</sub>)</b>	1Tx




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2483.50	49.28	54.00	-4.72	50.62	-1.34	Average	---	---
2	2483.50	56.63	74.00	-17.37	57.97	-1.34	Peak	---	---
3	4924.00	50.41	54.00	-3.59	44.76	5.65	Average	---	---
4	4924.00	52.64	74.00	-21.36	46.99	5.65	Peak	---	---
5	7386.00	46.30	54.00	-7.70	34.98	11.32	Average	---	---
6	7386.00	53.88	74.00	-20.12	42.56	11.32	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor , cable loss and amplifier gain


Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

### 3.5.6 Transmitter Radiated Unwanted Emissions (Above 1GHz) for 11g

Modulation	11g	Test Freq. (MHz)	2412																																																																														
Polarization	Horizontal	Transmit Chains (N <sub>TX</sub> )	2Tx																																																																														
																																																																																	
	<table border="1"> <thead> <tr> <th></th> <th>Freq.</th> <th>Emission level</th> <th>Limit</th> <th>Margin</th> <th>SA reading</th> <th>Factor</th> <th>Remark</th> <th>ANT High cm</th> <th>Turn Table deg</th> </tr> <tr> <th></th> <th>MHz</th> <th>dBuV/m</th> <th>dBuV/m</th> <th>dB</th> <th>dBuV</th> <th>dB</th> <th></th> <th></th> <th></th> </tr> </thead> <tbody> <tr> <td>1</td> <td>2390.00</td> <td>52.60</td> <td>54.00</td> <td>-1.40</td> <td>54.28</td> <td>-1.68</td> <td>Average</td> <td>---</td> <td>---</td> </tr> <tr> <td>2</td> <td>2390.00</td> <td>69.02</td> <td>74.00</td> <td>-4.98</td> <td>70.70</td> <td>-1.68</td> <td>Peak</td> <td>---</td> <td>---</td> </tr> <tr> <td>3</td> <td>3618.00</td> <td>43.53</td> <td>54.00</td> <td>-10.47</td> <td>41.73</td> <td>1.80</td> <td>Average</td> <td>---</td> <td>---</td> </tr> <tr> <td>4</td> <td>3618.00</td> <td>47.34</td> <td>74.00</td> <td>-26.66</td> <td>45.54</td> <td>1.80</td> <td>Peak</td> <td>---</td> <td>---</td> </tr> <tr> <td>5</td> <td>4824.00</td> <td>33.06</td> <td>54.00</td> <td>-20.94</td> <td>27.66</td> <td>5.40</td> <td>Average</td> <td>---</td> <td>---</td> </tr> <tr> <td>6</td> <td>4824.00</td> <td>44.53</td> <td>74.00</td> <td>-29.47</td> <td>39.13</td> <td>5.40</td> <td>Peak</td> <td>---</td> <td>---</td> </tr> </tbody> </table>		Freq.	Emission level	Limit	Margin	SA reading	Factor	Remark	ANT High cm	Turn Table deg		MHz	dBuV/m	dBuV/m	dB	dBuV	dB				1	2390.00	52.60	54.00	-1.40	54.28	-1.68	Average	---	---	2	2390.00	69.02	74.00	-4.98	70.70	-1.68	Peak	---	---	3	3618.00	43.53	54.00	-10.47	41.73	1.80	Average	---	---	4	3618.00	47.34	74.00	-26.66	45.54	1.80	Peak	---	---	5	4824.00	33.06	54.00	-20.94	27.66	5.40	Average	---	---	6	4824.00	44.53	74.00	-29.47	39.13	5.40	Peak	---	---
	Freq.	Emission level	Limit	Margin	SA reading	Factor	Remark	ANT High cm	Turn Table deg																																																																								
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB																																																																											
1	2390.00	52.60	54.00	-1.40	54.28	-1.68	Average	---	---																																																																								
2	2390.00	69.02	74.00	-4.98	70.70	-1.68	Peak	---	---																																																																								
3	3618.00	43.53	54.00	-10.47	41.73	1.80	Average	---	---																																																																								
4	3618.00	47.34	74.00	-26.66	45.54	1.80	Peak	---	---																																																																								
5	4824.00	33.06	54.00	-20.94	27.66	5.40	Average	---	---																																																																								
6	4824.00	44.53	74.00	-29.47	39.13	5.40	Peak	---	---																																																																								
<p>Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)            *Factor includes antenna factor , cable loss and amplifier gain            Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).</p>																																																																																	



<b>Modulation</b>	11g	<b>Test Freq. (MHz)</b>	2412
<b>Polarization</b>	Vertical	<b>Transmit Chains (N<sub>TX</sub>)</b>	2Tx




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	50.14	54.00	-3.86	51.82	-1.68	Average	---	---
2	2390.00	64.82	74.00	-9.18	66.50	-1.68	Peak	---	---
3	3618.00	48.12	54.00	-5.88	46.32	1.80	Average	---	---
4	3618.00	50.47	74.00	-23.53	48.67	1.80	Peak	---	---
5	4824.00	33.84	54.00	-20.16	28.44	5.40	Average	---	---
6	4824.00	45.09	74.00	-28.91	39.69	5.40	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

<b>Modulation</b>	11g	<b>Test Freq. (MHz)</b>	2437
<b>Polarization</b>	Horizontal	<b>Transmit Chains (N<sub>TX</sub>)</b>	2Tx




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	52.53	54.00	-1.47	54.21	-1.68	Average	---	---
2	2390.00	70.70	74.00	-3.30	72.38	-1.68	Peak	---	---
3	2483.50	51.88	54.00	-2.12	53.22	-1.34	Average	---	---
4	2483.50	67.39	74.00	-6.61	68.73	-1.34	Peak	---	---
5	3655.50	42.37	54.00	-11.63	40.44	1.93	Average	---	---
6	3655.50	47.65	74.00	-26.35	45.72	1.93	Peak	---	---
7	4874.00	38.42	54.00	-15.58	32.89	5.53	Average	---	---
8	4874.00	50.65	74.00	-23.35	45.12	5.53	Peak	---	---
9	7311.00	39.96	54.00	-14.04	28.67	11.29	Average	---	---
10	7311.00	51.63	74.00	-22.37	40.34	11.29	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

<b>Modulation</b>	11g	<b>Test Freq. (MHz)</b>	2437
<b>Polarization</b>	Vertical	<b>Transmit Chains (N<sub>TX</sub>)</b>	2Tx




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	48.22	54.00	-5.78	49.90	-1.68	Average	---	---
2	2390.00	62.98	74.00	-11.02	64.66	-1.68	Peak	---	---
3	2483.50	47.51	54.00	-6.49	48.85	-1.34	Average	---	---
4	2483.50	62.17	74.00	-11.83	63.51	-1.34	Peak	---	---
5	3655.50	48.03	54.00	-5.97	46.10	1.93	Average	---	---
6	3655.50	50.90	74.00	-23.10	48.97	1.93	Peak	---	---
7	4874.00	41.97	54.00	-12.03	36.44	5.53	Average	---	---
8	4874.00	52.81	74.00	-21.19	47.28	5.53	Peak	---	---
9	7311.00	40.25	54.00	-13.75	28.96	11.29	Average	---	---
10	7311.00	52.64	74.00	-21.36	41.35	11.29	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

<b>Modulation</b>	11g	<b>Test Freq. (MHz)</b>	2462
<b>Polarization</b>	Horizontal	<b>Transmit Chains (N<sub>TX</sub>)</b>	2Tx




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2483.50	52.88	54.00	-1.12	54.22	-1.34	Average	---	---
2	2483.50	69.12	74.00	-4.88	70.46	-1.34	Peak	---	---
3	3693.00	42.48	54.00	-11.52	40.42	2.06	Average	---	---
4	3693.00	46.62	74.00	-27.38	44.56	2.06	Peak	---	---
5	4924.00	37.70	54.00	-16.30	32.05	5.65	Average	---	---
6	4924.00	49.66	74.00	-24.34	44.01	5.65	Peak	---	---
7	7386.00	38.85	54.00	-15.15	27.53	11.32	Average	---	---
8	7386.00	51.83	74.00	-22.17	40.51	11.32	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

<b>Modulation</b>	11g	<b>Test Freq. (MHz)</b>	2462
<b>Polarization</b>	Vertical	<b>Transmit Chains (N<sub>TX</sub>)</b>	2Tx




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2483.50	48.48	54.00	-5.52	49.82	-1.34	Average	---	---
2	2483.50	60.89	74.00	-13.11	62.23	-1.34	Peak	---	---
3	3693.00	46.52	54.00	-7.48	44.46	2.06	Average	---	---
4	3693.00	50.18	74.00	-23.82	48.12	2.06	Peak	---	---
5	4924.00	41.24	54.00	-12.76	35.59	5.65	Average	---	---
6	4924.00	52.96	74.00	-21.04	47.31	5.65	Peak	---	---
7	7386.00	38.36	54.00	-15.64	27.04	11.32	Average	---	---
8	7386.00	51.63	74.00	-22.37	40.31	11.32	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)


\*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

### 3.5.7 Transmitter Radiated Unwanted Emissions (Above 1GHz) for HT20

Modulation	HT20	Test Freq. (MHz)	2412						
Polarization	Horizontal	Transmit Chains (N <sub>TX</sub> )	2Tx						
									
	Freq.	Emission level	Limit	Margin	SA reading	Factor	Remark	ANT High	Turn Table
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB		cm	deg
1	2390.00	52.96	54.00	-1.04	54.64	-1.68	Average	---	---
2	2390.00	66.14	74.00	-7.86	67.82	-1.68	Peak	---	---
3	3618.00	43.22	54.00	-10.78	41.42	1.80	Average	---	---
4	3618.00	47.33	74.00	-26.67	45.53	1.80	Peak	---	---
5	4824.00	32.93	54.00	-21.07	27.53	5.40	Average	---	---
6	4824.00	45.64	74.00	-28.36	40.24	5.40	Peak	---	---
<p>Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)            *Factor includes antenna factor , cable loss and amplifier gain            Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).</p>									

<b>Modulation</b>	HT20	<b>Test Freq. (MHz)</b>	2412
<b>Polarization</b>	Vertical	<b>Transmit Chains (N<sub>TX</sub>)</b>	2Tx




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	52.05	54.00	-1.95	53.73	-1.68	Average	---	---
2	2390.00	66.68	74.00	-7.32	68.36	-1.68	Peak	---	---
3	3618.00	47.91	54.00	-6.09	46.11	1.80	Average	---	---
4	3618.00	50.63	74.00	-23.37	48.83	1.80	Peak	---	---
5	4824.00	33.62	54.00	-20.38	28.22	5.40	Average	---	---
6	4824.00	45.77	74.00	-28.23	40.37	5.40	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

<b>Modulation</b>	HT20	<b>Test Freq. (MHz)</b>	2437
<b>Polarization</b>	Horizontal	<b>Transmit Chains (N<sub>TX</sub>)</b>	2Tx



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	52.98	54.00	-1.02	54.66	-1.68	Average	---	---
2	2390.00	67.28	74.00	-6.72	68.96	-1.68	Peak	---	---
3	2483.50	52.15	54.00	-1.85	53.49	-1.34	Average	---	---
4	2483.50	66.88	74.00	-7.12	68.22	-1.34	Peak	---	---
5	3655.50	42.14	54.00	-11.86	40.21	1.93	Average	---	---
6	3655.50	47.20	74.00	-26.80	45.27	1.93	Peak	---	---
7	4874.00	39.28	54.00	-14.72	33.75	5.53	Average	---	---
8	4874.00	51.44	74.00	-22.56	45.91	5.53	Peak	---	---
9	7311.00	39.44	54.00	-14.56	28.15	11.29	Average	---	---
10	7311.00	51.53	74.00	-22.47	40.24	11.29	Peak	---	---


Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).



<b>Modulation</b>	HT20	<b>Test Freq. (MHz)</b>	2437
<b>Polarization</b>	Vertical	<b>Transmit Chains (N<sub>TX</sub>)</b>	2Tx




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	49.35	54.00	-4.65	51.03	-1.68	Average	---	---
2	2390.00	62.98	74.00	-11.02	64.66	-1.68	Peak	---	---
3	2483.50	45.70	54.00	-8.30	47.04	-1.34	Average	---	---
4	2483.50	59.42	74.00	-14.58	60.76	-1.34	Peak	---	---
5	3655.50	48.30	54.00	-5.70	46.37	1.93	Average	---	---
6	3655.50	50.88	74.00	-23.12	48.95	1.93	Peak	---	---
7	4874.00	42.06	54.00	-11.94	36.53	5.53	Average	---	---
8	4874.00	53.84	74.00	-20.16	48.31	5.53	Peak	---	---
9	7311.00	39.37	54.00	-14.63	28.08	11.29	Average	---	---
10	7311.00	51.66	74.00	-22.34	40.37	11.29	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

<b>Modulation</b>	HT20	<b>Test Freq. (MHz)</b>	2462
<b>Polarization</b>	Horizontal	<b>Transmit Chains (N<sub>TX</sub>)</b>	2Tx




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2483.50	52.90	54.00	-1.10	54.24	-1.34	Average	---	---
2	2483.50	68.05	74.00	-5.95	69.39	-1.34	Peak	---	---
3	3693.00	42.42	54.00	-11.58	40.36	2.06	Average	---	---
4	3693.00	46.80	74.00	-27.20	44.74	2.06	Peak	---	---
5	4924.00	38.07	54.00	-15.93	32.42	5.65	Average	---	---
6	4924.00	53.18	74.00	-20.82	47.53	5.65	Peak	---	---
7	7386.00	39.03	54.00	-14.97	27.71	11.32	Average	---	---
8	7386.00	51.85	74.00	-22.15	40.53	11.32	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

<b>Modulation</b>	HT20	<b>Test Freq. (MHz)</b>	2462
<b>Polarization</b>	Vertical	<b>Transmit Chains (N<sub>TX</sub>)</b>	2Tx



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2483.50	48.54	54.00	-5.46	49.88	-1.34	Average	---	---
2	2483.50	62.63	74.00	-11.37	63.97	-1.34	Peak	---	---
3	3693.00	46.42	54.00	-7.58	44.36	2.06	Average	---	---
4	3693.00	50.30	74.00	-23.70	48.24	2.06	Peak	---	---
5	4924.00	40.03	54.00	-13.97	34.38	5.65	Average	---	---
6	4924.00	52.06	74.00	-21.94	46.41	5.65	Peak	---	---
7	7386.00	38.93	54.00	-15.07	27.61	11.32	Average	---	---
8	7386.00	51.57	74.00	-22.43	40.25	11.32	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)


\*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

### 3.5.8 Transmitter Radiated Unwanted Emissions (Above 1GHz) for HT40

Modulation	HT40	Test Freq. (MHz)	2422																																																																						
Polarization	Horizontal	Transmit Chains (N <sub>TX</sub> )	2Tx																																																																						
	<table border="1"> <thead> <tr> <th>Freq.</th> <th>Emission level</th> <th>Limit</th> <th>Margin</th> <th>SA reading</th> <th>Factor</th> <th>Remark</th> <th>ANT High cm</th> <th>Turn Table deg</th> </tr> <tr> <th>MHz</th> <th>dBuV/m</th> <th>dBuV/m</th> <th>dB</th> <th>dBuV</th> <th>dB</th> <th></th> <th></th> <th></th> </tr> </thead> <tbody> <tr> <td>1</td> <td>2390.00</td> <td>52.95</td> <td>54.00</td> <td>-1.05</td> <td>54.63</td> <td>-1.68</td> <td>Average</td> <td>---</td> </tr> <tr> <td>2</td> <td>2390.00</td> <td>64.84</td> <td>74.00</td> <td>-9.16</td> <td>66.52</td> <td>-1.68</td> <td>Peak</td> <td>---</td> </tr> <tr> <td>3</td> <td>3633.00</td> <td>42.20</td> <td>54.00</td> <td>-11.80</td> <td>40.35</td> <td>1.85</td> <td>Average</td> <td>---</td> </tr> <tr> <td>4</td> <td>3633.00</td> <td>46.12</td> <td>74.00</td> <td>-27.88</td> <td>44.27</td> <td>1.85</td> <td>Peak</td> <td>---</td> </tr> <tr> <td>5</td> <td>4844.00</td> <td>33.69</td> <td>54.00</td> <td>-20.31</td> <td>28.24</td> <td>5.45</td> <td>Average</td> <td>---</td> </tr> <tr> <td>6</td> <td>4844.00</td> <td>44.98</td> <td>74.00</td> <td>-29.02</td> <td>39.53</td> <td>5.45</td> <td>Peak</td> <td>---</td> </tr> </tbody> </table>	Freq.	Emission level	Limit	Margin	SA reading	Factor	Remark	ANT High cm	Turn Table deg	MHz	dBuV/m	dBuV/m	dB	dBuV	dB				1	2390.00	52.95	54.00	-1.05	54.63	-1.68	Average	---	2	2390.00	64.84	74.00	-9.16	66.52	-1.68	Peak	---	3	3633.00	42.20	54.00	-11.80	40.35	1.85	Average	---	4	3633.00	46.12	74.00	-27.88	44.27	1.85	Peak	---	5	4844.00	33.69	54.00	-20.31	28.24	5.45	Average	---	6	4844.00	44.98	74.00	-29.02	39.53	5.45	Peak	---
Freq.	Emission level	Limit	Margin	SA reading	Factor	Remark	ANT High cm	Turn Table deg																																																																	
MHz	dBuV/m	dBuV/m	dB	dBuV	dB																																																																				
1	2390.00	52.95	54.00	-1.05	54.63	-1.68	Average	---																																																																	
2	2390.00	64.84	74.00	-9.16	66.52	-1.68	Peak	---																																																																	
3	3633.00	42.20	54.00	-11.80	40.35	1.85	Average	---																																																																	
4	3633.00	46.12	74.00	-27.88	44.27	1.85	Peak	---																																																																	
5	4844.00	33.69	54.00	-20.31	28.24	5.45	Average	---																																																																	
6	4844.00	44.98	74.00	-29.02	39.53	5.45	Peak	---																																																																	
<p>Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)            *Factor includes antenna factor , cable loss and amplifier gain            Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).</p>																																																																									

<b>Modulation</b>	HT40	<b>Test Freq. (MHz)</b>	2422
<b>Polarization</b>	Vertical	<b>Transmit Chains (N<sub>TX</sub>)</b>	2Tx




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	51.95	54.00	-2.05	53.63	-1.68	Average	---	---
2	2390.00	64.10	74.00	-9.90	65.78	-1.68	Peak	---	---
3	3633.00	46.16	54.00	-7.84	44.31	1.85	Average	---	---
4	3633.00	50.27	74.00	-23.73	48.42	1.85	Peak	---	---
5	4844.00	34.76	54.00	-19.24	29.31	5.45	Average	---	---
6	4844.00	46.80	74.00	-27.20	41.35	5.45	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

<b>Modulation</b>	HT40	<b>Test Freq. (MHz)</b>	2437
<b>Polarization</b>	Horizontal	<b>Transmit Chains (N<sub>TX</sub>)</b>	2Tx




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	52.74	54.00	-1.26	54.42	-1.68	Average	---	---
2	2390.00	68.18	74.00	-5.82	69.86	-1.68	Peak	---	---
3	2483.50	48.33	54.00	-5.67	49.67	-1.34	Average	---	---
4	2483.50	61.85	74.00	-12.15	63.19	-1.34	Peak	---	---
5	3655.50	42.30	54.00	-11.70	40.37	1.93	Average	---	---
6	3655.50	46.45	74.00	-27.55	44.52	1.93	Peak	---	---
7	4874.00	34.17	54.00	-19.83	28.64	5.53	Average	---	---
8	4874.00	45.78	74.00	-28.22	40.25	5.53	Peak	---	---
9	7311.00	38.60	54.00	-15.40	27.31	11.29	Average	---	---
10	7311.00	51.57	74.00	-22.43	40.28	11.29	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

<b>Modulation</b>	HT40	<b>Test Freq. (MHz)</b>	2437
<b>Polarization</b>	Vertical	<b>Transmit Chains (N<sub>TX</sub>)</b>	2Tx




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	51.76	54.00	-2.24	53.44	-1.68	Average	---	---
2	2390.00	66.07	74.00	-7.93	67.75	-1.68	Peak	---	---
3	2483.50	46.54	54.00	-7.46	47.88	-1.34	Average	---	---
4	2483.50	61.14	74.00	-12.86	62.48	-1.34	Peak	---	---
5	3655.50	46.31	54.00	-7.69	44.38	1.93	Average	---	---
6	3655.50	50.31	74.00	-23.69	48.38	1.93	Peak	---	---
7	4874.00	35.83	54.00	-18.17	30.30	5.53	Average	---	---
8	4874.00	45.81	74.00	-28.19	40.28	5.53	Peak	---	---
9	7311.00	38.57	54.00	-15.43	27.28	11.29	Average	---	---
10	7311.00	50.93	74.00	-23.07	39.64	11.29	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

<b>Modulation</b>	HT40	<b>Test Freq. (MHz)</b>	2452
<b>Polarization</b>	Horizontal	<b>Transmit Chains (N<sub>TX</sub>)</b>	2Tx



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2483.50	52.93	54.00	-1.07	54.27	-1.34	Average	---	---
2	2483.50	66.15	74.00	-7.85	67.49	-1.34	Peak	---	---
3	3678.00	42.59	54.00	-11.41	40.59	2.00	Average	---	---
4	3678.00	46.41	74.00	-27.59	44.41	2.00	Peak	---	---
5	4904.00	33.81	54.00	-20.19	28.21	5.60	Average	---	---
6	4904.00	45.04	74.00	-28.96	39.44	5.60	Peak	---	---
7	7356.00	38.93	54.00	-15.07	27.62	11.31	Average	---	---
8	7356.00	51.72	74.00	-22.28	40.41	11.31	Peak	---	---


Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).



<b>Modulation</b>	HT40	<b>Test Freq. (MHz)</b>	2452
<b>Polarization</b>	Vertical	<b>Transmit Chains (N<sub>TX</sub>)</b>	2Tx



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2483.50	44.24	54.00	-9.76	45.58	-1.34	Average	---	---
2	2483.50	55.45	74.00	-18.55	56.79	-1.34	Peak	---	---
3	3678.00	46.20	54.00	-7.80	44.20	2.00	Average	---	---
4	3678.00	50.21	74.00	-23.79	48.21	2.00	Peak	---	---
5	4904.00	34.21	54.00	-19.79	28.61	5.60	Average	---	---
6	4904.00	45.99	74.00	-28.01	40.39	5.60	Peak	---	---
7	7356.00	38.89	54.00	-15.11	27.58	11.31	Average	---	---
8	7356.00	50.85	74.00	-23.15	39.54	11.31	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

## 3.6 Emissions in Non-Restricted Frequency Bands

### 3.6.1 Emissions in Non-Restricted Frequency Bands Limit

Peak power in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz

### 3.6.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

### 3.6.3 Test Procedures


#### Reference level measurement

1. Set RBW=100kHz, VBW = 300kHz , Detector = Peak, Sweep time = Auto
2. Trace = max hold , Allow Trace to fully stabilize
3. Use the peak marker function to determine the maximum PSD level

#### Emission level measurement

1. Set RBW=100kHz, VBW = 300kHz , Detector = Peak, Sweep time = Auto
2. Trace = max hold , Allow Trace to fully stabilize
3. Scan Frequency range is up to 25GHz
4. Use the peak marker function to determine the maximum amplitude level

### 3.6.4 Test Setup





### 3.6.5 Test Result of Emissions in non-restricted frequency bands


This test item is performed on each TX output individually without summing or adding  $10 \log(N_{ANT})$  since measurements are made relative to the in-band emissions on the individual outputs. Only worst test result of each operating mode is presented.

### 3.6.6 Unwanted Emissions into Non-Restricted Frequency Bands


802.11b









802.11g













802.11n HT20









802.11n HT40







## 4 Test laboratory information

Established in 2012, ICC provides foremost EMC & RF Testing and advisory consultation services by our skilled engineers and technicians. Our services employ a wide variety of advanced edge test equipment and one of the widest certification extents in the business.

International Certification Corp, it is our definitive objective is to institute long term, trust-based associations with our clients. The expectation we set up with our clients is based on outstanding service, practical expertise and devotion to a certified value structure. Our passion is to grant our clients with best EMC / RF services by oriented knowledgeable and accommodating staff.

Our Test sites are located at Linkou District and Kwei Shan Hsiang. Location map can be found on our website <http://www.icertifi.com.tw>.

### **Linkou**

Tel: 886-2-2601-1640

No. 30-2, Ding Fwu Tsuen, Lin  
Kou District, New Taipei City,  
Taiwan, R.O.C.

### **Kwei Shan**

Tel: 886-3-271-8666

No. 3-1, Lane 6, Wen San 3rd St.,  
Kwei Shan Hsiang, Tao Yuan  
Hsien 333, Taiwan, R.O.C.

### **Kwei Shan Site II**

Tel: 886-3-271-8640

No. 14-1, Lane 19, Wen San 3rd  
St., Kwei Shan Hsiang, Tao Yuan  
Hsien 333, Taiwan, R.O.C.

If you have any suggestion, please feel free to contact us as below information

Tel: 886-3-271-8666

Fax: 886-3-318-0155

Email: ICC\_Service@icertifi.com.tw

==END==