

FCC RF Exposure Report

FCC ID : NKR-SP69
Equipment : 11abgn/ac WLAN/Bluetooth Combo Module
Model No. : DHUB-SP69
Brand Name : SHARP Corporation
Applicant : Wistron NeWeb Corp.
Address : 20 Park Avenue II, Hsinchu Science Park,
Hsinchu 308, Taiwan, R.O.C.
Standard : 47 CFR FCC Part 2.1091
Received Date : Oct. 03, 2014
Tested Date : Oct. 03 ~ Nov. 12, 2014

We, International Certification Corp., would like to declare that the tested sample has been evaluated and in compliance with the requirement of the above standards. The test results contained in this report refer exclusively to the product. It may be duplicated completely for legal use with the approval of the applicant. It shall not be reproduced except in full without the written approval of our laboratory.

Approved & Reviewed by:



Gary Chang / Manager



Testing Laboratory
2732

Table of Contents

| | | |
|----------|--|----------|
| 1 | MPE EVALUATION OF MOBILE DEVICES | 4 |
| 1.1 | LIMITS FOR GENERAL POPULATION/UNCONTROLLED EXPOSURE..... | 4 |
| 1.2 | MPE EVALUATION FORMULA | 4 |
| 1.3 | MPE EVALUATION RESULTS | 5 |
| 2 | TEST LABORATORY INFORMATION | 7 |

Release Record

| Report No. | Version | Description | Issued Date |
|------------|---------|---------------|---------------|
| FA4O1301 | Rev. 01 | Initial issue | Dec. 04, 2014 |

1 MPE EVALUATION OF MOBILE DEVICES

Human exposure to RF emissions from mobile devices (47 CFR §2.1091) may be evaluated based on the MPE limits adopted by the FCC for electric and magnetic field strength and/or power density, as appropriate, since exposures are assumed to occur at distances of 20 cm or more from persons.

1.1 LIMITS FOR GENERAL POPULATION/UNCONTROLLED EXPOSURE

| Frequency Range (MHz) | Power Density (mW /cm ²) | Averaging Time (minutes) |
|-----------------------|--------------------------------------|--------------------------|
| 300~1500 | F/1500 | 30 |
| 1500~100000 | 1.0 | 30 |

1.2 MPE EVALUATION FORMULA

$$Pd = \frac{Pt}{4 * Pi * R^2}$$

Where

Pd= Power density in mW/cm²

Pt= EIRP in Mw

Pi= 3.1416

R= Measurement distance

1.3 MPE EVALUATION RESULTS

MPE Evaluation of Single Transmission

| Wireless Function | Mode | Maximum Conducted Power (dBm) | Antenna Gain (dBi) | Distance (cm) | Power Density (mW/cm ²) | Limit (mW/cm ²) |
|-------------------|-------|-------------------------------|--------------------|---------------|-------------------------------------|-----------------------------|
| 2412~2462 | 11b | 21.55 | 4.47 | 20 | 0.080 | 1 |
| | 11g | 21.36 | 4.47 | 20 | 0.076 | 1 |
| | HT20 | 21.52 | 7.39 | 20 | 0.155 | 1 |
| | HT40 | 16.54 | 7.39 | 20 | 0.049 | 1 |
| 5180~5240 | 11a | 19.69 | 4.35 | 20 | 0.050 | 1 |
| | HT20 | 19.00 | 6.72 | 20 | 0.074 | 1 |
| | HT40 | 21.4 | 6.72 | 20 | 0.129 | 1 |
| | VHT20 | 19.14 | 6.72 | 20 | 0.077 | 1 |
| | VHT40 | 21.49 | 6.72 | 20 | 0.132 | 1 |
| | VHT80 | 18.11 | 6.72 | 20 | 0.060 | 1 |
| 5260~5320 | 11a | 20.91 | 4.43 | 20 | 0.068 | 1 |
| | HT20 | 19.63 | 6.99 | 20 | 0.091 | 1 |
| | HT40 | 20.70 | 6.99 | 20 | 0.117 | 1 |
| | VHT20 | 19.76 | 6.99 | 20 | 0.094 | 1 |
| | VHT40 | 20.78 | 6.99 | 20 | 0.119 | 1 |
| | VHT80 | 17.64 | 6.99 | 20 | 0.058 | 1 |
| 5500~5720 | 11a | 22.41 | 4.43 | 20 | 0.096 | 1 |
| | HT20 | 21.71 | 7.35 | 20 | 0.160 | 1 |
| | HT40 | 22.20 | 7.35 | 20 | 0.179 | 1 |
| | VHT20 | 21.80 | 7.35 | 20 | 0.164 | 1 |
| | VHT40 | 22.30 | 7.35 | 20 | 0.184 | 1 |
| | VHT80 | 21.13 | 7.35 | 20 | 0.140 | 1 |
| 5745~5825 | 11a | 21.21 | 4.32 | 20 | 0.071 | 1 |
| | HT20 | 20.77 | 7.27 | 20 | 0.127 | 1 |
| | HT40 | 20.28 | 7.27 | 20 | 0.113 | 1 |
| | VHT20 | 20.89 | 7.27 | 20 | 0.130 | 1 |
| | VHT40 | 20.35 | 7.27 | 20 | 0.115 | 1 |
| | VHT80 | 15.67 | 7.27 | 20 | 0.039 | 1 |

Note: 11n / 11ac mode supports beamforming, thus antenna gain is calculated for directional gain not gain of single antenna.

| Wireless Function | Frequency Range (MHz) | Maximum Conducted Power (dBm) | Antenna Gain (dBi) | Distance (cm) | Power Density (mW/cm ²) | Limit (mW/cm ²) |
|-------------------|-----------------------|-------------------------------|--------------------|---------------|-------------------------------------|-----------------------------|
| BT EDR | 2402~2480 | 11.69 | 4.2 | 20 | 0.008 | 1 |
| BT LE | 2402~2480 | 8.41 | 4.2 | 20 | 0.004 | 1 |

MPE Evaluation of Simultaneous Transmission

WLAN 2.4G and BT can transmit at the same time, and WLAN 5G and BT can transmit at the same time , MPE evaluation is as below formula

$PD1 / \text{Limit}1 + PD2 / \text{Limit} 2 + \dots < 1$, PD = Power density

MPE Evaluation = Maximum MPE of BT + Maximum MPE of 2.4GHz = $0.008 / 1 + 0.155 / 1 = 0.163 < 1$

MPE Evaluation = Maximum MPE of BT + Maximum MPE of 5GHz = $0.008 / 1 + 0.184 / 1 = 0.192 < 1$

Conclusion

MPE evaluations of single and simultaneous transmission meet the requirement of standard.

2 Test laboratory information

Established in 2012, ICC provides foremost EMC & RF Testing and advisory consultation services by our skilled engineers and technicians. Our services employ a wide variety of advanced edge test equipment and one of the widest certification extents in the business.

International Certification Corp, it is our definitive objective is to institute long term, trust-based associations with our clients. The expectation we set up with our clients is based on outstanding service, practical expertise and devotion to a certified value structure. Our passion is to grant our clients with best EMC / RF services by oriented knowledgeable and accommodating staff.

Our Test sites are located at Linkou District and Kwei Shan Hsiang. Location map can be found on our website <http://www.icertifi.com.tw>.

Linkou

Tel: 886-2-2601-1640

No. 30-2, Ding Fwu Tsuen, Lin
Kou District, New Taipei City,
Taiwan, R.O.C.

Kwei Shan

Tel: 886-3-271-8666

No. 3-1, Lane 6, Wen San 3rd St.,
Kwei Shan Hsiang, Tao Yuan
Hsien 333, Taiwan, R.O.C.

Kwei Shan Site II

Tel: 886-3-271-8640

No. 14-1, Lane 19, Wen San 3rd
St., Kwei Shan Hsiang, Tao Yuan
Hsien 333, Taiwan, R.O.C.

If you have any suggestion, please feel free to contact us as below information

Tel: 886-3-271-8666

Fax: 886-3-318-0155

Email: ICC_Service@icertifi.com.tw

==END==