

FCC RF Exposure Report

Report No.: MFBCKS-WTW-P23070373

FCC ID: NKR-VMC-9628NV1

Model No.: VMC-9628NV1

Received Date: 2023/7/17

Issued Date: 2023/9/28

Applicant: Wistron NeWeb Corporation

Address: 20 Park Ave. II, Hsinchu Science Park, Hsinchu 308, Taiwan

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
Lin Kou Laboratories

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan

Test Location: No. 19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City
33383, Taiwan

**FCC Registration /
Designation Number:** 788550 / TW0003



This report is governed by, and incorporates by reference, the Conditions of Testing as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. Statements of conformity are based on simple acceptance criteria without taking measurement uncertainty into account, unless otherwise requested in writing. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.

Table of Contents

Release Control Record	3
1 Certificate of Conformity	4
2 General Information	5
2.1 General Description of EUT	5
3 RF Exposure	6
3.1 Limits for Maximum Permissible Exposure (MPE)	6
3.2 MPE Calculation Formula	6
3.3 Classification	6
4 Calculation Result of Maximum Conducted Power	7

Release Control Record

Issue No.	Description	Date Issued
MFCKS-WTW-P23070373	Original release	2023/9/28

1 Certificate of Conformity

Product: 2G/3G/4G Module

Brand: WNC

Test Model: VMC-9628NV1

Sample Status: Engineering sample

Applicant: Wistron NeWeb Corporation

FCC Rule Part: FCC Part 2 (Section 2.1091)

Standards: KDB 447498 D01 General RF Exposure Guidance v06

We, **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, declare that the equipment above has been found compliance with the requirement limits of applicable standards. The test record, data evaluation and Equipment Under Test (EUT) configurations represented herein are true and accurate under the standards herein specified.

Prepared by : _____

Vera Huang

Date: _____

2023/9/28

Vera Huang / Specialist

Approved by : _____

Jeremy Lin

Date: _____

2023/9/28

Jeremy Lin / Project Engineer

2 General Information

2.1 General Description of EUT

Product	2G/3G/4G Module	
Brand	WNC	
Test Model	VMC-9628NV1	
Status of EUT	Engineering sample	
Power Supply Rating	3.8Vdc from power supply	
Modulation Type	GSM/GPRS	GMSK
	EDGE	GMSK, 8PSK
	WCDMA	QPSK
	LTE	QPSK, 16QAM
Operating Frequency	GSM850	824.2 ~ 848.8 MHz
	GSM1900	1850.2 ~ 1909.8 MHz
	WCDMA Band 2	1852.4 ~ 1907.6 MHz
	WCDMA Band 4	1712.4 ~ 1752.6 MHz
	WCDMA Band 5	826.4 ~ 846.6 MHz
	LTE Band 2	1850.7 ~ 1909.3 MHz
	LTE Band 4	1710.7 ~ 1754.3MHz
	LTE Band 5	824.7 ~ 848.3 MHz
	LTE Band 7	2502.5 ~ 2567.5 MHz
	LTE Band 12	699.7 ~ 715.3 MHz
	LTE Band 13	779.5 ~ 784.5 MHz
LTE Band 17	706.5 ~ 713.5 MHz	
Antenna Type	Dipole Antenna with 2 dBi gain	
Antenna Connector	SMA	
Accessory Device	N/A	
Cable Supplied	N/A	

Note: Detail antenna specification please refer to antenna datasheet an antenna gain measurement report.

3 RF Exposure

3.1 Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)
Limits For General Population / Uncontrolled Exposure				
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f ²)*	30
30-300	27.5	0.073	0.2	30
300-1500	f/1500	30
1500-100,000	1.0	30

f = Frequency in MHz; *Plane-wave equivalent power density

3.2 MPE Calculation Formula

$$Pd = (Pout * G) / (4 * pi * r^2)$$

where

Pd = power density in mW/cm²

Pout = output power to antenna in mW

G = gain of antenna in linear scale

pi = 3.1416

r = distance between observation point and center of the radiator in cm

3.3 Classification

The antenna of this product, under normal use condition, is at least 27cm away from the body of the user. So, this device is classified as **Mobile Device**.

4 Calculation Result of Maximum Conducted Power

Mode	Tune-Up Power (dBm)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
GSM850	35	2	27	0.547	0.550
GSM1900	32	2	27	0.274	1.000
WCDMA Band 2	25.7	2	27	0.064	1.000
WCDMA Band 4	25.7	2	27	0.064	1.000
WCDMA Band 5	25.7	2	27	0.064	0.550
LTE Band 2	25.7	2	27	0.064	1.000
LTE Band 4	25.7	2	27	0.064	1.000
LTE Band 5	25.7	2	27	0.064	0.550
LTE Band 7	25.7	2	27	0.064	1.000
LTE Band 12	25.7	2	27	0.064	0.466
LTE Band 13	25.7	2	27	0.064	0.520
LTE Band 17	25.7	2	27	0.064	0.469

Note: Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

---END---