



# FCC TEST REPORT

**REPORT NO.:** RF900810R01

**MODEL NO.:** WarpLink2414 (for Wistron)  
CWA700 (for Alexon)

**RECEIVED:** August 10, 2001

**TESTED:** August 23~ August 27, 2001

**APPLICANT:** Acer NeWeb Corporation

**ADDRESS:** 5F, NO.16 SEC 2, CHING KUO ROAD, HSINCHU  
300, TAIWAN, R.O.C.

**ISSUED BY:** Advance Data Technology Corporation

**LAB LOCATION:** 47 14th Lin, Chiapau Tsun, Linko, Taipei,  
Taiwan, R.O.C.

This test report consists of 49 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product endorsement by CNLA, NVLAP or any government agencies. The test results in the report only apply to the tested sample.



0528



Lab Code: 200102-0



## Table of Contents

1	CERTIFICATION .....	4
2	SUMMARY OF TEST RESULTS .....	5
3	GENERAL INFORMATION.....	6
3.1	GENERAL DESCRIPTION OF EUT .....	6
3.2	DESCRIPTION OF TEST MODES.....	7
3.3	GENERAL DESCRIPTION OF APPLIED STANDARDS .....	7
3.4	DESCRIPTION OF SUPPORT UNITS .....	8
4	TEST TYPES AND RESULTS.....	9
4.1	CONDUCTED EMISSION MEASUREMENT .....	9
4.1.1	LIMITS OF CONDUCTED EMISSION MEASUREMENT .....	9
4.1.2	TEST INSTRUMENTS.....	9
4.1.3	TEST PROCEDURES .....	10
4.1.4	TEST SETUP .....	10
4.1.5	EUT OPERATING CONDITIONS .....	11
4.1.6	TEST RESULTS .....	12
4.2	RADIATED EMISSION MEASUREMENT .....	18
4.2.1	LIMITS OF RADIATED EMISSION MEASUREMENT .....	18
4.2.2	TEST INSTRUMENTS.....	19
4.2.3	TEST PROCEDURES .....	20
4.2.4	TEST SETUP .....	21
4.2.5	EUT OPERATING CONDITIONS .....	21
4.2.6	TEST RESULTS .....	22
4.3	6DB BANDWIDTH MEASUREMENT .....	27
4.3.1	LIMITS OF 6dB BANDWIDTH MEASUREMENT .....	27
4.3.2	TEST INSTRUMENTS.....	27
4.3.3	TEST PROCEDURE.....	28
4.3.4	TEST SETUP .....	28
4.3.5	EUT OPERATING CONDITIONS .....	28
4.3.6	TEST RESULTS .....	29
4.4	MAXIMUM PEAK OUTPUT POWER .....	33
4.4.1	LIMITS OF MAXIMUM PEAK OUTPUT POWER MEASUREMENT .....	33
4.4.2	TEST INSTRUMENTS.....	33
4.4.3	TEST PROCEDURES .....	34
4.4.4	TEST SETUP .....	34
4.4.5	EUT OPERATING CONDITIONS .....	34



4.4.6	TEST RESULTS .....	35
4.5	POWER SPECTRAL DENSITY MEASUREMENT .....	36
4.5.1	LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT .....	36
4.5.2	TEST INSTRUMENTS.....	36
4.5.3	TEST PROCEDURE.....	37
4.5.4	TEST SETUP .....	37
4.5.5	EUT OPERATING CONDITIONS .....	37
4.5.6	TEST RESULTS .....	38
4.6	BAND EDGES MEASUREMENT .....	42
4.6.1	LIMITS OF BAND EDGES MEASUREMENT .....	42
4.6.2	TEST INSTRUMENTS.....	42
4.6.3	TEST PROCEDURE.....	42
4.6.4	EUT OPERATING CONDITION .....	43
4.6.5	TEST RESULTS .....	43
4.7	ANTENNA REQUIREMENT .....	46
4.7.1	STANDARD APPLICABLE .....	46
4.7.2	ANTENNA CONNECTED CONSTRUCTION .....	46
5	PHOTOGRAPHS OF THE TEST CONFIGURATION.....	47
6	INFORMATION ON THE TESTING LABORATORIES .....	49



# 1 CERTIFICATION

**PRODUCT :** IEEE 802.11b 11Mbps Wireless LAN Card  
**BRAND NAME :** Wistron  
**MODEL NO. :** WarpLink2414  
**OEM BRAND NAME :** Alexon  
**OEM MODEL NO. :** CWA700  
**APPLICANT :** Acer NeWeb Corp.  
**STANDARDS :** 47 CFR Part 15, Subpart C (Section 15.247),  
ANSI C63.4-1992

We, **Advance Data Technology Corporation**, hereby certify that one sample of the designation has been tested in our facility from August 23, 2001 to August 27, 2001, The test record, data evaluation and Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions herein specified.

TESTED BY : Gary Chang · DATE: Aug 29, 2001  
Gary Chang

CHECKED BY : Emily Lu · DATE: Aug 29, 2001  
Emily Lu

APPROVED BY : Alan Lane · DATE: Aug 29, 2001  
Dr. Alan Lane, Manager



## 2 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

<b>APPLIED STANDARD: 47 CFR Part 15, Subpart C</b>			
<b>Standard Section</b>	<b>Test Type and Limit</b>	<b>Result</b>	<b>REMARK</b>
15.107	AC Power Conducted Emission Limit: 48dBuV	PASS	Meet the requirement of limit Minimum passing margin is -7.62dBuV at 2.699MHz
15.247(a)(2)	Spectrum Bandwidth of a Direct Sequence Spread Spectrum System Limit: min. 500kHz	PASS	Meet the requirement of limit
15.247(b)	Maximum Peak Output Power Limit: max. 30dBm	PASS	Meet the requirement of limit
15.247(c)	Transmitter Radiated Emissions Limit: Table 15.209	PASS	Meet the requirement of limit Minimum passing margin is -7.90dBuV at 8251.00 MHz
15.247(d)	Power Spectral Density Limit: max. 8dBm	PASS	Meet the requirement of limit
15.247(c)	Band Edge Measurement Limit: 20 dB less than the peak value of fundamental frequency	PASS	Meet the requirement of limit



### 3 GENERAL INFORMATION

#### 3.1 GENERAL DESCRIPTION OF EUT

<b>PRODUCT</b>	IEEE 802.11b 11Mbps Wireless LAN Card
<b>MODEL NO.</b>	WarpLink2414
<b>POWER SUPPLY</b>	3.3VDC from notebook
<b>MODULATION TYPE</b>	CCK, BPSK, QPSK
<b>RADIO TECHNOLOGY</b>	DSSS
<b>TRANSFER RATE</b>	1/2/5.5/11Mbps
<b>FREQUENCY RANGE</b>	2412MHz ~ 2462MHz
<b>NUMBER OF CHANNEL</b>	11
<b>OUTPUT POWER</b>	17dBm
<b>ANTENNA TYPE</b>	Meander PIFA
<b>DATA CABLE</b>	NA
<b>I/O PORTS</b>	NA
<b>ASSOCIATED DEVICES</b>	NA

**NOTE:**

1. The EUT can offer you great flexibility and freedom to build your own ideal wireless LAN. You can connect your PC/notebook to an access point wirelessly to share a "connected" environment, such as your local area network.
2. Model: WarpLink2414 and CWA700 are identical, except brand name and model number.
3. For a more detailed features description, please refer to the manufacturer's specifications or User's Manual.



### 3.2 DESCRIPTION OF TEST MODES

Eleven channels are provided in this EUT.

Channel	Frequency	Channel	Frequency
1	2412 MHz	7	2442 MHz
2	2417 MHz	8	2447 MHz
3	2422 MHz	9	2452 MHz
4	2427 MHz	10	2457 MHz
5	2432 MHz	11	2462 MHz
6	2437 MHz		

**NOTE:**

1. Below 1 GHz, the channel 1, 6, and 11 were pre-tested in chamber. The channel 11, worst case one, was chosen for final test.
2. Above 1 GHz, the channel 1, 6, and 11 were tested individually.

### 3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a IEEE 802.11b 11Mbps Wireless LAN Card. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

**FCC CFR 47 Part 15, Subpart C. (15.247)**  
**ANSI C63.4 : 1992**

All tests have been performed and recorded as per the above standards.

**NOTE:** The EUT is also considered as a kind of computer peripheral, because the connection to computer is necessary for typical use. It has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (DoC). The test report has been issued separately.



### 3.4 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	NOTEBOOK	IBM	ThinkPad 380XD	97-84L54	FCC DoC Approved
2	PRINTER	HP	2225C+	3123S97230	DSI6XU2225
3	MODEM	ACEEX	1414	980020510	IFAXDM1414

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	NA
2	1.2m braid shielded wire, terminated with DB25 and Centronics connector via metallic frame, w/o core.
3	1.2 m braid shielded wire, terminated with DB25 and DB9 connector via metallic frame, w/o core.

**NOTE:** All power cords of the above support units are non shielded (1.8m).





## 4 TEST TYPES AND RESULTS

### 4.1 CONDUCTED EMISSION MEASUREMENT

#### 4.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY (MHz)	Class B (dBuV)	
	Quasi-peak	Average
0.45 – 30	48	-

**NOTE:**

1. The lower limit shall apply at the transition frequencies.
2. All emanations from a class B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

#### 4.1.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
ROHDE & SCHWARZ Test Receiver	ESCS30	834115/016	Feb. 21, 2002
ROHDE & SCHWARZ Artificial Mains Network (For EUT)	ESH2-Z5	892107/003	July 10, 2002
ROHDE & SCHWARZ 4-wire ISN	ENY41	838119/028	Dec. 12, 2001
ROHDE & SCHWARZ 2-wire ISN	ENY22	837497/018	Dec. 3, 2001
EMCO L.I.S.N. (For peripherals)	3825/2	9504-2359	July 10, 2002
Software	Cond-V2J	NA	NA
RF cable (JYEBAO)	RG-58A/U	Cable-C03.01	July 11, 2002
Terminator (For EMCO LISN)	NA	E1-01-300	Feb. 20, 2002
Terminator (For EMCO LISN)	NA	E1-01-301	Feb. 20, 2002
Shielded Room	Site 3	ADT-C03	NA
VCCI Site Registration No.	Site 3	C-274	NA


**NOTE:**

1. The measurement uncertainty is less than +/- 2.6dB, which is calculated as per the NAMAS document NIS81.
2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
3. "\*" = These equipments are used for the final measurement.

#### 4.1.3 TEST PROCEDURES

- The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- The frequency range from 450 kHz to 30 MHz was searched. Emission levels over 10dB under the prescribed limits could not be reported

#### 4.1.4 TEST SETUP



- Note:**
- Support units were connected to second LISN.
  - Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.



#### 4.1.5 EUT OPERATING CONDITIONS

- a. Connected the EUT to a computer system placed on a testing table.
- b. The computer system ran a test program to enable EUT under transmission/receiving condition continuously at specific channel frequency.
- c. The computer system sent "H" messages to its screen.
- d. The computer system sent "H" messages to modem.
- e. The computer system sent "H" messages to printer, and the printer prints them on paper.




4.1.6 TEST RESULTS

<b>EUT</b>	IEEE 802.11b 11Mbps Wireless LAN Card	<b>MODEL</b>	WARPLINK2414
<b>MODE</b>	Channel 1	<b>6dB BANDWIDTH</b>	10 kHz
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>PHASE</b>	Line (L)
<b>ENVIRONMENTAL CONDITIONS</b>	30 deg. C, 70%RH, 1005 hPa	<b>TESTED BY:</b> Gary Chang	

No	Freq.	Corr. Factor	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
	[MHz]		Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	2.480	0.22	29.45	-	29.67	-	48.00	-	-18.33	-
2	2.800	0.24	38.97	-	39.21	-	48.00	-	-8.79	-
3	5.156	0.32	31.61	-	31.93	-	48.00	-	-16.07	-
4	8.461	0.37	33.71	-	34.08	-	48.00	-	-13.92	-
5	12.480	0.45	33.83	-	34.28	-	48.00	-	-13.72	-
6	22.570	0.55	37.05	-	37.60	-	48.00	-	-10.40	-

**NOTE:**

1. QP. and AV. are abbreviations of quasi-peak and average individually.
2. "-": NA
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Emission Level = Reading Value + Correction Factor.






<b>EUT</b>	IEEE 802.11b 11Mbps Wireless LAN Card	<b>MODEL</b>	WARPLINK2414
<b>MODE</b>	Channel 1	<b>6dB BANDWIDTH</b>	10 kHz
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>PHASE</b>	Neutral (N)
<b>ENVIRONMENTAL CONDITIONS</b>	30 deg. C, 70%RH, 1005 hPa	<b>TESTED BY:</b> Gary Chang	

No	Freq.	Corr. Factor	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
	[MHz]		(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.
1	2.485	0.22	35.95	-	36.17	-	48.00	-	-11.83	-
2	2.645	0.23	35.49	-	35.72	-	48.00	-	-12.28	-
3	8.879	0.38	33.94	-	34.32	-	48.00	-	-13.68	-
4	10.082	0.40	35.08	-	35.48	-	48.00	-	-12.52	-
5	12.965	0.52	33.70	-	34.22	-	48.00	-	-13.78	-
6	22.570	0.95	37.54	-	38.49	-	48.00	-	-9.51	-

**NOTE:**

1. QP. and AV. are abbreviations of quasi-peak and average individually.
2. "-": NA
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Emission Level = Reading Value + Correction Factor.






<b>EUT</b>	IEEE 802.11b 11Mbps Wireless LAN Card	<b>MODEL</b>	WARPLINK2414
<b>MODE</b>	Channel 6	<b>6dB BANDWIDTH</b>	10 kHz
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>PHASE</b>	Line (L)
<b>ENVIRONMENTAL CONDITIONS</b>	30 deg. C, 70%RH, 1005 hPa	<b>TESTED BY:</b> Gary Chang	

No	Freq.	Corr. Factor	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
	[MHz]		(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.
1	2.697	0.23	39.11	-	39.34	-	48.00	-	-8.66	-
2	2.806	0.24	39.11	-	39.35	-	48.00	-	-8.65	-
3	8.379	0.37	33.38	-	33.75	-	48.00	-	-14.25	-
4	10.242	0.40	33.08	-	33.48	-	48.00	-	-14.52	-
5	17.969	0.56	32.02	-	32.58	-	48.00	-	-15.42	-
6	22.570	0.55	37.05	-	37.60	-	48.00	-	-10.40	-

**NOTE:**

1. QP. and AV. are abbreviations of quasi-peak and average individually.
2. "-": NA
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Emission Level = Reading Value + Correction Factor.






<b>EUT</b>	IEEE 802.11b 11Mbps Wireless LAN Card	<b>MODEL</b>	WARPLINK2414
<b>MODE</b>	Channel 6	<b>6dB BANDWIDTH</b>	10 kHz
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>PHASE</b>	Neutral (N)
<b>ENVIRONMENTAL CONDITIONS</b>	30 deg. C, 70%RH, 1005 hPa	<b>TESTED BY:</b> Gary Chang	

No	Freq.	Corr. Factor	Reading Value [dB (Uv)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	2.340	0.22	32.76	-	32.98	-	48.00	-	-15.02	-
2	2.648	0.23	36.89	-	37.12	-	48.00	-	-10.88	-
3	2.754	0.24	37.05	-	37.29	-	48.00	-	-10.71	-
4	4.852	0.31	31.30	-	31.61	-	48.00	-	-16.39	-
5	10.188	0.41	34.53	-	34.94	-	48.00	-	-13.06	-
6	22.570	0.95	37.60	-	38.55	-	48.00	-	-9.45	-

**NOTE:**

1. QP. and AV. are abbreviations of quasi-peak and average individually.
2. "-": NA
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Emission Level = Reading Value + Correction Factor.






<b>EUT</b>	IEEE 802.11b 11Mbps Wireless LAN Card	<b>MODEL</b>	WARPLINK2414
<b>MODE</b>	Channel 11	<b>6dB BANDWIDTH</b>	10 kHz
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>PHASE</b>	Line (L)
<b>ENVIRONMENTAL CONDITIONS</b>	30 deg. C, 70%RH, 1005 hPa	<b>TESTED BY:</b> Gary Chang	

No	Freq.	Corr. Factor	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
	[MHz]		(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.
1	2.438	0.22	35.06	-	35.28	-	48.00	-	-12.72	-
2	2.699	0.23	40.15	-	40.38	-	48.00	-	-7.62	-
3	2.802	0.24	39.05	-	39.29	-	48.00	-	-8.71	-
4	9.875	0.40	33.91	-	34.31	-	48.00	-	-13.69	-
5	12.180	0.44	34.01	-	34.45	-	48.00	-	-13.55	-
6	21.949	0.56	33.39	-	33.95	-	48.00	-	-14.05	-

**NOTE:**

1. QP. and AV. are abbreviations of quasi-peak and average individually.
2. "-": NA
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Emission Level = Reading Value + Correction Factor.








<b>EUT</b>	IEEE 802.11b 11Mbps Wireless LAN Card	<b>MODEL</b>	WARPLINK2414
<b>MODE</b>	Channel 11	<b>6dB BANDWIDTH</b>	10 kHz
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>PHASE</b>	Netural (N)
<b>ENVIRONMENTAL CONDITIONS</b>	30 deg. C, 70%RH, 1005 hPa	<b>TESTED BY:</b> Gary Chang	

No	Freq.	Corr. Factor	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
	[MHz]		(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.
1	2.496	0.22	32.51	-	32.73	-	48.00	-	-15.27	-
2	2.750	0.24	38.03	-	38.27	-	48.00	-	-9.73	-
3	8.492	0.37	33.10	-	33.47	-	48.00	-	-14.53	-
4	10.297	0.41	34.54	-	34.95	-	48.00	-	-13.05	-
5	12.320	0.49	34.15	-	34.64	-	48.00	-	-13.36	-
6	22.570	0.95	37.50	-	38.45	-	48.00	-	-9.55	-

**NOTE:**

1. QP. and AV. are abbreviations of quasi-peak and average individually.
2. "-": NA
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Emission Level = Reading Value + Correction Factor.





## 4.2 RADIATED EMISSION MEASUREMENT

### 4.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT

Field strength limits are at the distance of 3 meters, emissions radiated outside of the specified bands, shall be according to the general radiated limits in 15.209 as following:

Frequencies (MHz)	Field Strength of Fundamental	
	uV/m	dBuV/m
30-88	100	40.0
88-216	150	43.5
216-960	200	46.0
Above 960	500	54.0

**NOTE:**

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.



#### 4.2.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
* HP Spectrum Analyzer	8590L	3544A01176	May 7, 2002
* HP Preamplifier	8447D	2944A08485	Nov. 3, 2001
* HP Preamplifier	8449B	3008A01201	Dec. 13, 2001
* ROHDE & SCHWARZ TEST RECEIVER	ESMI	839013/007 839379/002	Jan. 25, 2002
SCHWARZBECK Tunable Dipole Antenna	VHA 9103 UHA 9105	E101051 E101055	Nov. 23, 2001
* CHASE BILOG Antenna	CBL6112A	2221	Aug. 2, 2002
* SCHWARZBECK Horn Antenna	BBHA9120-D1	D130	July 6, 2002
* EMCO Horn Antenna	3115	9312-4192	April 15, 2002
* EMCO Turn Table	1060	1115	NA
* SHOSHIN Tower	AP-4701	A6Y005	NA
* Software	AS61D4	NA	NA
* ANRITSU RF Switches	MP59B	M35046	Aug. 2, 2002
* TIMES RF cable	LMR-600	CABLE-ST5-01	Aug. 2, 2002
* Antenna (Horn)	BBHA9120-D	D130	July 10, 2002
Open Field Test Site	Site 5	ADT-R05	July 28, 2002
VCCI Site Registration No.	Site 5	R-1039	NA
Site Registration No.	FCC: 90422 Canada IC: IC 3789 VCCI : R-1039		

**NOTE:**

1. The measurement uncertainty is less than +/- 3.0dB, which is calculated as per the NAMAS document NIS81.
2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
3. "\*" = These equipments are used for the final measurement.




#### 4.2.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 10 meter open area test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10 dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10 dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

**NOTE:**

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Peak detection (PK) and Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1 MHz for Peak detection at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 300 Hz for Average detection (AV) at frequency above 1GHz.

#### 4.2.4 TEST SETUP



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

#### 4.2.5 EUT OPERATING CONDITIONS

Same as 4.1.5.



## 4.2.6 TEST RESULTS

<b>EUT</b>	IEEE 802.11b 11Mbps Wireless LAN Card	<b>MODEL</b>	WARPLINK2414
<b>MODE</b>	Channel 11	<b>FREQUENCY RANGE</b>	30-1000 MHz
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>DETECTOR FUNCTION</b>	Quasi-Peak
<b>ENVIRONMENTAL CONDITIONS</b>	30 deg. C, 70% RH, 1050 hPa	<b>TESTED BY:</b> Gary Chang	

**ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M**

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB)	Cable Factor (dB)	Pre-Amp. Factor (dB)	Correction Factor (dB)
1	220.47	30.0 QP	46.00	-16.00	1.23H	101	18.20	10.26	1.52	0.00	-11.79
2	308.40	31.0 QP	46.00	-15.00	1.12H	296	15.70	13.38	1.91	0.00	-15.29
3	440.14	35.1 QP	46.00	-10.90	1.00H	316	16.40	16.32	2.38	0.00	-18.69
4	528.03	35.0 QP	46.00	-11.00	2.29H	305	14.80	17.62	2.60	0.00	-20.22
5	616.20	34.5 QP	46.00	-11.50	1.94H	32	12.80	18.82	2.89	0.00	-21.71
6	748.20	34.8 QP	46.00	-11.20	1.71H	84	11.40	20.14	3.26	0.00	-23.40

**NOTE:**

1. Emission level = Raw value - Correction Factor
2. Correction Factor = Pre-Amp. Factor - Ant. Factor - Cable loss  
(Pre-Amp. Factor = 0, when a Pre-Amplifier is not used for the test.)
3. Margin value = Emission level - Limit value
4. The other emission levels were very low against the limit.



<b>EUT</b>	IEEE 802.11b 11Mbps Wireless LAN Card	<b>MODEL</b>	WARPLINK2414
<b>MODE</b>	Channel 11	<b>FREQUENCY RANGE</b>	30-1000 MHz
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>DETECTOR FUNCTION</b>	Quasi-Peak
<b>ENVIRONMENTAL CONDITIONS</b>	30 deg. C, 70% RH, 1050 hPa	<b>TESTED BY:</b> Gary Chang	

**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M**

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB)	Cable Factor (dB)	Pre-Amp. Factor (dB)	Correction Factor (dB)
1	264.08	32.9 QP	46.00	-13.10	2.35V	74	18.50	12.75	1.70	0.00	-14.45
2	527.07	34.4 QP	46.00	-11.60	2.21V	103	14.20	17.62	2.60	0.00	-20.22
3	660.03	35.1 QP	46.00	-10.90	1.68V	71	12.80	19.25	3.05	0.00	-22.29
4	748.50	33.9 QP	46.00	-12.10	2.27V	171	10.50	20.14	3.26	0.00	-23.40
5	792.02	35.4 QP	46.00	-10.60	1.17V	330	11.50	20.60	3.31	0.00	-23.91
6	880.17	32.6 QP	46.00	-13.40	1.24V	68	8.40	20.68	3.55	0.00	-24.24

**NOTE:**

1. Emission level = Raw value - Correction Factor
2. Correction Factor = Pre-Amp. Factor - Ant. Factor - Cable loss  
(Pre-Amp. Factor = 0, when a Pre-Amplifier is not used for the test.)
3. Margin value = Emission level - Limit value
4. The other emission levels were very low against the limit.



<b>EUT</b>	IEEE 802.11b 11Mbps Wireless LAN Card	<b>MODEL</b>	WARPLINK2414
<b>MODE</b>	Channel 1	<b>FREQUENCY RANGE</b>	Above 1000 MHz
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>DETECTOR FUNCTION</b>	Peak(PK) Average (AV)
<b>ENVIRONMENTAL CONDITIONS</b>	30 deg. C, 70% RH, 1050 hPa	<b>TESTED BY:</b> Gary Chang	

#### ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB)	Cable Factor (dB)	Pre-Amp. Factor (dB)	Correction Factor (dB)
1	2037.80	47.7 Pk	74.00	-26.30	1.22H	191	19.12	25.27	3.29	0.00	-28.57
2	*2413.50	101.7 Pk	-	-	1.45H	310	70.85	27.19	3.62	0.00	-30.82
3	*2413.50	91.0 Av	-	-	1.45H	310	60.20	27.19	3.62	0.00	-30.82
4	4075.80	50.7 Pk	74.00	-23.30	1.84H	96	15.80	30.18	4.77	0.00	-34.96
5	4824.40	50.9 Pk	74.00	-23.10	1.26H	293	14.30	31.43	5.21	0.00	-36.64
6	6113.20	48.3 Pk	74.00	-25.70	1.25H	301	9.50	32.83	5.98	0.00	-38.81

#### ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB)	Cable Factor (dB)	Pre-Amp. Factor (dB)	Correction Factor (dB)
1	2037.70	47.2 Pk	74.00	-26.80	1.00V	139	18.60	25.27	3.29	0.00	-28.57
2	*2413.60	103.9 Pk	-	-	1.05V	57	73.06	27.19	3.62	0.00	-30.81.
3	*2413.60	92.3 Av	-	-	1.05V	57	61.50	27.19	3.62	0.00	-30.81.
4	4075.50	50.0 Pk	74.00	-24.00	1.85V	48	15.10	30.18	4.77	0.00	-34.96
5	4824.50	49.8 Pk	74.00	-24.20	1.05V	13	13.20	31.43	5.21	0.00	-36.65
6	6113.20	48.2 Pk	74.00	-25.80	1.85V	124	9.40	32.83	5.98	0.00	-38.82

#### NOTE:

1. Emission level = Raw value - Correction Factor
2. Correction Factor = Pre-Amp. Factor - Ant. Factor - Cable loss  
(Pre-Amp. Factor = 0, when a Pre-Amplifier is not used for the test.)
3. Margin value = Emission level - Limit value
4. " \* " : Fundamental frequency
5. The other emission levels were very low against the limit.





<b>EUT</b>	IEEE 802.11b 11Mbps Wireless LAN Card	<b>MODEL</b>	WARPLINK2414
<b>MODE</b>	Channel 6	<b>FREQUENCY RANGE</b>	Above 1000 MHz
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>DETECTOR FUNCTION</b>	Peak(PK) Average (AV)
<b>ENVIRONMENTAL CONDITIONS</b>	30 deg. C, 70% RH, 1050 hPa	<b>TESTED BY:</b> Gary Chang	

<b>ANTENNA POLARITY &amp; TEST DISTANCE: HORIZONTAL AT 3 M</b>											
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB)	Cable Factor (dB)	Pre-Amp. Factor (dB)	Correction Factor (dB)
1	2062.90	47.1 Pk	74.00	-26.90	1.00H	268	18.40	25.39	3.31	0.00	-28.70
2	*2438.50	103.5 Pk	-	-	1.48H	60	72.53	27.30	3.64	0.00	-30.94.
3	*2438.50	92.4 Av	-	-	1.48H	60	61.50	27.30	3.64	0.00	-30.94.
4	4125.50	49.3 Pk	74.00	-24.70	1.25H	203	14.20	30.28	4.79	0.00	-35.07
5	4874.50	51.4 Pk	74.00	-22.60	1.18H	122	14.70	31.47	5.25	0.00	-36.72
6	6188.30	48.3 Pk	74.00	-25.70	1.37H	171	9.10	33.19	6.01	0.00	-39.20
7	8251.00	56.1 Pk	74.00	-17.90	1.25H	230	12.40	36.70	7.01	0.00	-43.71
8	8251.00	46.1 Av	54.00	-7.90	1.25H	230	2.40	36.70	7.01	0.00	-43.71

<b>ANTENNA POLARITY &amp; TEST DISTANCE: VERTICAL AT 3 M</b>											
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB)	Cable Factor (dB)	Pre-Amp. Factor (dB)	Correction Factor (dB)
1	2063.50	47.1 Pk	74.00	-26.90	1.02V	230	18.40	25.39	3.31	0.00	-28.70
2	*2438.50	105.0 Pk	-	-	1.02V	36	74.07	27.30	3.64	0.00	-30.94.
3	*2438.50	95.1 Av	-	-	1.02V	36	64.20	27.30	3.64	0.00	-30.94.
4	4125.90	50.9 Pk	74.00	-23.10	1.11V	113	15.80	30.28	4.79	0.00	-35.07
5	4874.30	50.3 Pk	74.00	-23.70	1.39V	187	13.60	31.47	5.25	0.00	-36.72
6	6188.20	49.4 Pk	74.00	-24.60	1.50V	205	10.20	33.19	6.01	0.00	-39.20

**NOTE:**

1. Emission level = Raw value - Correction Factor
2. Correction Factor = Pre-Amp. Factor - Ant. Factor - Cable loss  
(Pre-Amp. Factor = 0, when a Pre-Amplifier is not used for the test.)
3. Margin value = Emission level - Limit value
4. “ \* “ : Fundamental frequency
5. The other emission levels were very low against the limit.



<b>EUT</b>	IEEE 802.11b 11Mbps Wireless LAN Card	<b>MODEL</b>	WARPLINK2414
<b>MODE</b>	Channel 11	<b>FREQUENCY RANGE</b>	Above 1000 MHz
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>DETECTOR FUNCTION</b>	Peak(PK) Average (AV)
<b>ENVIRONMENTAL CONDITIONS</b>	30 deg. C, 70% RH, 1050 hPa	<b>TESTED BY:</b> Gary Chang	

#### ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB)	Cable Factor (dB)	Pre-Amp. Factor (dB)	Correction Factor (dB)
1	2087.70	47.8 Pk	74.00	-26.20	1.20H	281	19.00	25.50	3.33	0.00	-28.83
2	*2463.50	104.6 Pk	-	-	1.10H	5	73.50	27.41	3.66	0.00	-31.08
3	*2463.50	97.2 Av	-	-	1.10H	5	66.10	27.41	3.66	0.00	-31.08
4	2483.50	54.4 Pk	74.00	-19.60	1.23H	223	23.20	27.52	3.68	0.00	-31.20.
5	2483.50	41.6 Av	54.00	-12.40	1.23H	223	10.40	27.52	3.68	0.00	-31.20
6	4175.10	51.4 Pk	74.00	-22.60	2.02H	306	16.20	30.38	4.81	0.00	-35.19
7	4924.40	51.0 Pk	74.00	-23.00	1.31H	204	14.20	31.51	5.28	0.00	-36.80
8	6263.20	50.4 Pk	74.00	-23.60	1.89H	304	10.87	33.46	6.03	0.00	-39.49

#### ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB)	Cable Factor (dB)	Pre-Amp. Factor (dB)	Correction Factor (dB)
1	2087.90	46.9 Pk	74.00	-27.10	1.21V	179	18.12	25.50	3.33	0.00	-28.83
2	*2463.70	104.1 Pk	-	-	1.03V	347	73.06	27.41	3.66	0.00	-31.08
3	*2463.70	96.2 Av	-	-	1.03V	347	65.10	27.41	3.66	0.00	-31.08
4	2483.50	49.1 Pk	74.00	-24.90	1.51V	6	17.90	27.52	3.68	0.00	-31.21
5	4175.40	50.9 Pk	74.00	-23.10	1.68V	351	15.70	30.38	4.81	0.00	-35.19
6	4924.60	51.0 Pk	74.00	-23.00	1.36V	93	14.20	31.51	5.28	0.00	-36.81
7	6263.20	47.9 Pk	74.00	-26.10	1.25V	124	8.40	33.46	6.03	0.00	-39.50

#### NOTE:

1. Emission level = Raw value - Correction Factor
2. Correction Factor = Pre-Amp. Factor - Ant. Factor - Cable loss  
(Pre-Amp. Factor = 0, when a Pre-Amplifier is not used for the test.)
3. Margin value = Emission level - Limit value
4. " \* " : Fundamental frequency
5. The other emission levels were very low against the limit.



### 4.3 6DB BANDWIDTH MEASUREMENT

#### 4.3.1 LIMITS OF 6dB BANDWIDTH MEASUREMENT

The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

#### 4.3.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
ROHDE & SCHWARZ TEST RECEIVER	ESMI	839379/002	Dec. 28, 2001
HP ATTENUATOR	8496B	3247A18505	Cal. on use
HP PLOTTER	7475A	2641V27755	N/A


**NOTE:**

- 1.The measurement uncertainty is less than +/- 2.6dB, which is calculated as per the NAMAS document NIS81.
- 2.The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

### 4.3.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with 100 kHz RBW and 100 kHz VBW. The 6 dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 6 dB.

### 4.3.4 TEST SETUP



For the actual test configuration, please refer to the related Item – Photographs of the Test Configuration.

### 4.3.5 EUT OPERATING CONDITIONS

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.




## 4.3.6 TEST RESULTS

<b>EUT</b>	IEEE 802.11b 11Mbps Wireless LAN Card	<b>MODEL</b>	WARPLINK2414
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>ENVIRONMENTAL CONDITIONS</b>	28 deg. C, 75%RH, 1005 hPa
<b>TESTED BY:</b> James Lee			

<b>CHANNEL</b>	<b>CHANNEL FREQUENCY (MHz)</b>	<b>6 dB BANDWIDTH (MHz)</b>	<b>MINIMUM LIMIT (MHz)</b>	<b>PASS/FAIL</b>
1	2412	9.58	0.5	PASS
6	2437	10.44	0.5	PASS
11	2462	9.22	0.5	PASS




CH1






CH6





CH11







#### 4.4 MAXIMUM PEAK OUTPUT POWER

##### 4.4.1 LIMITS OF MAXIMUM PEAK OUTPUT POWER MEASUREMENT

The Maximum Peak Output Power Measurement is 30dBm.

##### 4.4.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
ROHDE & SCHWARZ TEST RECEIVER	ESMI	839379/002	Dec. 28, 2001
HP ATTENUATOR	8496B	3247A18505	Cal. on use
HP PLOTTER	7475A	2641V27755	N/A

**NOTE:**


1. The measurement uncertainty is less than +/- 2.6dB, which is calculated as per the NAMAS document NIS81.
2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

#### 4.4.3 TEST PROCEDURES

- a. The transmitter output was connected to the spectrum analyzer through an attenuator.
- b. The center frequency of the spectrum analyzer was set to the fundamental frequency and using 3 MHz RBW and 3 MHz VBW.
- c. The span of the spectrum analyzer should be larger than 6dB BandWidth plus 10MHz.
- d. Used Peak Search to read the peak power after Maximum Hold function was activated.
- e. Shifted the marker to +/- 3MHz and +/-6MHz, and recorded the reading.
- f. The Maximum Peak Output Power was the linear summation of the 5 readings in (4) and (5).

**NOTE:** This measurement is the total power of 15MHz bandwidth which is far more wider than 6dB bandwidth.

#### 4.4.4 TEST SETUP



#### 4.4.5 EUT OPERATING CONDITIONS

Same as Item 4.3.5



4.4.6 TEST RESULTS

<b>EUT</b>	IEEE 802.11b 11Mbps Wireless LAN Card	<b>MODEL</b>	WARPLINK2414
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>ENVIRONMENTAL CONDITIONS</b>	27 deg. C, 75%RH, 1005 hPa
<b>TESTED BY:</b> James Lee			

<b>CHANNEL</b>	<b>CHANNEL FREQUENCY (MHz)</b>	<b>PEAK POWER OUTPUT (dBm)</b>	<b>PEAK POWER LIMIT (dBm)</b>	<b>PASS/FAIL</b>
1	2412	18.15	30	PASS
6	2437	18.10	30	PASS
11	2462	18.10	30	PASS



## 4.5 POWER SPECTRAL DENSITY MEASUREMENT

### 4.5.1 LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT

The Maximum of Power Spectral Density Measurement is 8dBm.

### 4.5.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
ROHDE & SCHWARZ TEST RECEIVER	ESMI	839379/002	Dec. 28, 2001
HP ATTENUATOR	8496B	3247A18505	Cal. on use
HP PLOTTER	7475A	2641V27755	N/A


**NOTE:**

1. The measurement uncertainty is less than +/- 2.6dB, which is calculated as per the NAMAS document NIS81.
2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

### 4.5.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer through an attenuator, the bandwidth of the fundamental frequency was measured with the spectrum analyzer using 3 kHz RBW and 30 kHz VBW, set sweep time=span/3kHz. The power spectral density was measured and recorded. The sweep time is allowed to be longer than span/3KHz for a full response of the mixer in the spectrum analyzer.

### 4.5.4 TEST SETUP



### 4.5.5 EUT OPERATING CONDITIONS

Same as 4.3.5




## 4.5.6 TEST RESULTS

<b>EUT</b>	IEEE 802.11b 11Mbps Wireless LAN Card	<b>MODEL</b>	WARPLINK2414
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>ENVIRONMENTAL CONDITIONS</b>	28 deg. C, 75%RH, 1005 hPa
<b>TESTED BY:</b> James Lee			

<b>CHANNEL NUMBER</b>	<b>CHANNEL FREQUENCY (MHz )</b>	<b>RF POWER LEVEL IN 3 KHz BW (dBm)</b>	<b>MAXIMUM LIMIT (dBm)</b>	<b>PASS/FAIL</b>
1	2412	-11.35	8	PASS
6	2437	-11.37	8	PASS
11	2462	-11.40	8	PASS




CH1






CH6







CH11





## 4.6 BAND EDGES MEASUREMENT

### 4.6.1 LIMITS OF BAND EDGES MEASUREMENT

Below  $-20\text{dB}$  of the highest emission level of operating band (in 100KHz Resolution Bandwidth).

### 4.6.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
ROHDE & SCHWARZ TEST RECEIVER	ESMI	848926/005 846839/018	Dec 28, 2001
HP ATTENUATOR	8496B	3247A18505	Cal. on use
HP PLOTTER	7475A	2641V27755	N/A

**NOTE:**

1. The measurement uncertainty is less than  $\pm 2.6\text{dB}$ , which is calculated as per the NAMAS document NIS81.
2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

### 4.6.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer via a low lose cable. Set both RBW and VBW of spectrum analyzer to 100 kHz with suitable frequency span including 100 kHz bandwidth from band edge. The band edges was measured and recorded.




#### 4.6.4 EUT OPERATING CONDITION


Same as Item 4.3.5

#### 4.6.5 TEST RESULTS

The spectrum plots are attached on the following 2 pages. D2 line indicates the highest level, D1 line indicates the 20dB offset below D2. It shows compliance with the requirement in part 15.247(C).

**NOTE:** The band edge emission plot on the following 2 pages shows 20.0dB delta between carrier maximum power and local maximum emission in restrict band (2.4941GHz). The emission of carrier strength list in the test result of channel 11 at the item 4.2.6 (Page 26) is 97.2dBuV/m, so the maximum field strength in restrict band is  $97.2 - 49.31 = 47.89$  dBuV/m which is under 54 dBuV/m limit.







## **4.7 ANTENNA REQUIREMENT**

### **4.7.1 STANDARD APPLICABLE**

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

### **4.7.2 ANTENNA CONNECTED CONSTRUCTION**


The antenna used in this product is Meander PIFA. The antenna connector is Soldered. And the maximum Gain of this antenna is only -1dBi.

## 5 PHOTOGRAPHS OF THE TEST CONFIGURATION

### CONDUCTED EMISSION TEST



### RADIATED EMISSION TEST







## 6 INFORMATION ON THE TESTING LABORATORIES

We, ADT Corp., were founded in 1988 to provide our best service in EMC and Safety consultation. Our laboratories are accredited and approved by the following approval agencies according to ISO/IEC 17025, Guide 25 or EN 45001:

<b>USA</b>	FCC, NVLAP
<b>Germany</b>	TUV Rheinland
<b>Japan</b>	VCCI
<b>New Zealand</b>	MoC
<b>Norway</b>	NEMKO
<b>R.O.C.</b>	BSMI, DGT, CNLA

Copies of accreditation certificates of our laboratories obtained from approval agencies can be downloaded from our web site:

[www.adt.com.tw/index.5/phtml](http://www.adt.com.tw/index.5/phtml).

If you have any comments, please feel free to contact us at the following:

**Lin Kou EMC Lab:**

Tel: 886-2-26052180

Fax: 886-2-26052943

**Hsin Chu EMC Lab:**

Tel: 886-35-935343

Fax: 886-35-935342

**Lin Kou Safety Lab:**

Tel: 886-2-26093195

Fax: 886-2-26093184

**Lin Kou RF&Telecom Lab**

Tel: 886-3-3270910

Fax: 886-3-3270892

**Email:** [service@mail.adt.com.tw](mailto:service@mail.adt.com.tw)

**Web Site:** [www.adt.com.tw](http://www.adt.com.tw)

The address and road map of all our labs can be found in our web site also.