

# FCC TEST REPORT

**REPORT NO.:** RF911008R04

**MODEL NO.:** BT-510

**RECEIVED:** Oct. 8, 2002

**TESTED:** Oct. 14 ~ 15, 2002

**APPLICANT:** Wistron NeWeb Corp.

**ADDRESS:** No. 10-1, Li-hsin Road I, Science-based  
Industrial Park, Hsinchu 300, Taiwan, R.O.C.

**ISSUED BY:** Advance Data Technology Corporation

**LAB LOCATION:** 47 14th Lin, Chiapau Tsun, Linko, Taipei,  
Taiwan, R.O.C.

This test report consists of 61 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product endorsement by CNLA, NVLAP or any government agencies. The test results in the report only apply to the tested sample.



0528  
ILAC MRA



Lab Code: 200102-0



# TABLE OF CONTENTS

1	CERTIFICATION .....	4
2	SUMMARY OF TEST RESULTS.....	5
3	GENERAL INFORMATION .....	6
3.1	GENERAL DESCRIPTION OF EUT.....	6
3.2	DESCRIPTION OF TEST MODES.....	7
3.3	GENERAL DESCRIPTION OF APPLIED STANDARDS.....	7
3.4	DESCRIPTION OF SUPPORT UNITS.....	8
4	TEST PROCEDURES AND RESULTS .....	9
4.1	CONDUCTED EMISSION MEASUREMENT.....	9
4.1.1	LIMITS OF CONDUCTED EMISSION MEASUREMENT .....	9
4.1.2	TEST INSTRUMENTS .....	9
4.1.3	TEST PROCEDURES .....	10
4.1.4	DEVIATION FROM TEST STANDARD .....	10
4.1.5	TEST SETUP .....	11
4.1.6	TEST RESULTS .....	12
4.2	NUMBER OF HOPPING FREQUENCY USED.....	18
4.2.1	LIMIT OF HOPPING FREQUENCY USED .....	18
4.2.2	TEST INSTRUMENTS .....	18
4.2.3	TEST PROCEDURES .....	19
4.2.4	DEVIATION FROM TEST STANDARD .....	19
4.2.5	TEST SETUP .....	19
4.2.6	TEST RESULTS .....	19
4.3	DWELL TIME ON EACH CHANNEL.....	22
4.3.1	LIMIT OF DWELL TIME USED.....	22
4.3.2	TEST INSTRUMENTS .....	22
4.3.3	TEST PROCEDURES .....	23
4.3.4	DEVIATION FROM TEST STANDARD .....	23
4.3.5	TEST SETUP .....	23
4.3.6	TEST RESULTS .....	24
4.4	CHANNEL BANDWIDTH.....	28
4.4.1	LIMITS OF CHANNEL BANDWIDTH.....	28
4.4.2	TEST INSTRUMENTS .....	28
4.4.3	TEST PROCEDURE .....	29
4.4.4	DEVIATION FROM TEST STANDARD .....	29
4.4.5	TEST SETUP .....	29
4.4.6	EUT OPERATING CONDITION .....	29
4.4.7	TEST RESULTS .....	30
4.5	HOPPING CHANNEL SEPARATION .....	34
4.5.1	LIMIT OF HOPPING CHANNEL SEPARATION.....	34
4.5.2	TEST INSTRUMENTS .....	34
4.5.3	TEST PROCEDURES .....	35




4.5.4	DEVIATION FROM TEST STANDARD .....	35
4.5.5	TEST SETUP .....	35
4.5.6	TEST RESULTS .....	36
4.6	MAXIMUM PEAK OUTPUT POWER .....	40
4.6.1	LIMITS OF MAXIMUM PEAK OUTPUT POWER MEASUREMENT .....	40
4.6.2	INSTRUMENTS.....	40
4.6.3	TEST PROCEDURES .....	41
4.6.4	DEVIATION FROM TEST STANDARD .....	41
4.6.5	TEST SETUP .....	41
4.6.6	EUT OPERATING CONDITION .....	41
4.6.7	TEST RESULTS .....	42
4.7	RADIATED EMISSION MEASUREMENT.....	46
4.7.1	LIMITS OF RADIATED EMISSION MEASUREMENT .....	46
4.7.2	TEST INSTRUMENTS .....	47
4.7.3	TEST PROCEDURES .....	48
4.7.4	DEVIATION FROM TEST STANDARD .....	48
4.7.5	TEST SETUP .....	49
4.7.6	TEST RESULTS .....	50
4.7.7	TEST RESULTS .....	51
4.8	BAND EDGES MEASUREMENT.....	54
4.8.1	LIMITS OF BAND EDGES MEASUREMENT .....	54
4.8.2	TEST INSTRUMENTS .....	54
4.8.3	TEST PROCEDURE .....	54
4.8.4	EUT OPERATING CONDITION .....	55
4.7.8	DEVIATION FROM TEST STANDARD .....	55
4.8.5	TEST RESULTS .....	55
4.9	ANTENNA REQUIREMENT .....	58
4.9.1	STANDARD APPLICABLE .....	58
4.9.2	ANTENNA CONNECTED CONSTRUCTION.....	58
5	PHOTOGRAPHS OF THE TEST CONFIGURATION .....	59
6	INFORMATION ON THE TESTING LABORATORIES.....	61



# 1 CERTIFICATION

**PRODUCT :** Bluetooth Dongle  
**BRAND NAME :** Wistron NeWeb  
**MODEL NO. :** BT-510  
**APPLICANT :** Wistron NeWeb Corp.  
**STANDARDS :** 47 CFR Part 15, Subpart C (Section 15.247),  
ANSI C63.4-1992

We, **Advance Data Technology Corporation**, hereby certify that one sample of the designation has been tested in our facility from Oct. 14, 2002 to Oct. 15, 2002, The test record, data evaluation and Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions herein specified.

CHECKED BY :  , DATE : Oct. 22, 2002  
Emily Lu

APPROVED BY :  , DATE : Oct. 22, 2002  
Dr. Alan Lane, Manager

## 2 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

<b>APPLIED STANDARD: 47 CFR Part 15, Subpart C</b>			
<b>Standard Section</b>	<b>Test Type and Limit</b>	<b>Result</b>	<b>REMARK</b>
15.207	AC Power Conducted Emission	PASS	Meet the requirement of limit Minimum passing margin is -16.40dBuV at 0.170MHz
15.247(a)(1)(I)-(ii)	Number of Hopping Frequency Used Spec.: At least 75 channels	PASS	Meet the requirement of limit
15.247(a)(1)(ii)	Dwell Time on Each Channel Spec. : Max. 0.4 second within 30 second	PASS	Meet the requirement of limit
15.247(a)(1)(I)-(ii)	Hopping Channel Separation Spec. : Min. 25kHz or 20dB bandwidth	PASS	Meet the requirement of limit
15.247(a)(2)	Spectrum Bandwidth of a Frequency Hopping Sequence Spread Spectrum System Spec.: Max. 1MHz	PASS	Meet the requirement of limit
15.247(b)	Maximum Peak Output Power Spec.: max. 30dBm	PASS	Meet the requirement of limit
15.247(c)	Transmitter Radiated Emissions Spec.: Table 15.209	PASS	Meet the requirement of limit Minimum passing margin is -10.1dBuV at 7440.0MHz
15.247(c)	Band Edge Measurement	PASS	Meet the requirement of limit

### 3 GENERAL INFORMATION

#### 3.1 GENERAL DESCRIPTION OF EUT

<b>PRODUCT</b>	Bluetooth Dongle
<b>MODEL NO.</b>	BT-510
<b>POWER SUPPLY</b>	5.0VDC from host equipment
<b>MODULATION TYPE</b>	GFSK (FHSS)
<b>FREQUENCY RANGE</b>	2402MHz ~ 2480MHz
<b>NUMBER OF CHANNEL</b>	79
<b>OUTPUT POWER</b>	0.17dBm
<b>ANTENNA TYPE</b>	Meander IFA Antenna
<b>DATA CABLE</b>	NA
<b>I/O PORTS</b>	USB port
<b>ASSOCIATED DEVICES</b>	NA

**NOTE:**

1. With the features of small, lightweight and easy plug-and play, Bluetooth USB Adapter enables the integration of Bluetooth technology into your personal computers.
2. Three outer appearances are provided to this EUT.
3. For more detailed feature description of the EUT, please refer to user's manual.



### **3.2 DESCRIPTION OF TEST MODES**

The software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel frequencies individually.

### **3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS**

The EUT is a Bluetooth Dongle. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

**FCC CFR 47 Part 15, Subpart C. (15.247)**  
**ANSI C63.4 : 1992**

All tests have been performed and recorded as per the above standards.

**NOTE:** The EUT is also considered as a kind of computer peripheral, because the connection to computer is necessary for typical use. It has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (DoC). The test report has been issued separately.



### 3.4 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	NOTEBOOK	DELL	PP01L	TW-09C748-12800-19O-B220	FCC DoC APPROVED
2	PRINTER	EPSON	LQ-300+	DCGY017096	FCC DoC APPROVED
3	MODEM	ACEEX	1414	980020504	IFAXDM1414

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	NA
2	1.2m braid shielded wire, terminated with DB25 and Centronics connector via metallic frame, w/o core
3	1.2 m braid shielded wire, terminated with DB25 and DB9 connector via metallic frame, w/o core.

**NOTE:** All power cords of the above support units are non shielded (1.8m).





## 4 TEST PROCEDURES AND RESULTS

### 4.1 CONDUCTED EMISSION MEASUREMENT

#### 4.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dB $\mu$ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56	56 to 46
0.5-5	56	46
5-30	60	50

- NOTE:**
1. The lower limit shall apply at the transition frequencies.
  2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.
  3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

#### 4.1.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
ROHDE & SCHWARZ Test Receiver	ESCS30	834115/016	Mar. 3, 2003
ROHDE & SCHWARZ Artificial Mains Network (For EUT)	ESH3-Z5	847265/023	Jan. 10, 2003
* ROHDE & SCHWARZ 4-wire ISN	ENY41	838119/028	Dec. 10, 2002
* ROHDE & SCHWARZ 2-wire ISN	ENY22	837497/018	Dec. 10, 2002
EMCO L.I.S.N. (For peripherals)	3825/2	9504-2359	July 10, 2003
Software	Cond-V2L	NA	NA
RF cable (JYEBAO)	5D-FB	Cable-C03.01	July 11, 2003
Terminator (For EMCO LISN)	NA	E1-01-300	Feb. 20, 2003
Terminator (For EMCO LISN)	NA	E1-01-301	Feb. 20, 2003
Shielded Room	Site 3	ADT-C03	NA
VCCI Site Registration No.	Site 3	C-274	NA

- NOTE:**
1. The measurement uncertainty is less than +/- 2.6dB, which is calculated as per the NAMAS document NIS81.
  2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
  3. “\*”: These equipment are used for conducted telecom port test only (if tested).
  4. The test was performed in ADT Open Site No. 3.




#### 4.1.3 TEST PROCEDURES

- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150kHz to 30MHz was searched. Emission levels over 10dB under the prescribed limits could not be reported

#### 4.1.4 DEVIATION FROM TEST STANDARD

No deviation

## 4.1.5 TEST SETUP



- Note:**
1. Support units were connected to second LISN.
  2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.




### 4.1.6 TEST RESULTS

<b>EUT</b>	Bluetooth Dongle	<b>MODEL</b>	BT-510
<b>MODE</b>	Channel 0	<b>6dB BANDWIDTH</b>	9 kHz
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>PHASE</b>	Line (L)
<b>ENVIRONMENTAL CONDITIONS</b>	24 deg. C, 48%RH, 1005 hPa	<b>TESTED BY:</b> Cody Chang	

No	Freq.	Corr. Factor	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
	[MHz]		Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.170	0.10	48.48	-	48.58	-	64.98	54.98	-16.40	-
2	0.224	0.10	39.10	-	39.20	-	62.66	52.66	-23.46	-
3	0.283	0.10	36.64	-	36.74	-	60.73	50.73	-23.99	-
4	0.399	0.10	33.19	-	33.29	-	57.88	47.88	-24.59	-
5	3.574	0.46	23.27	-	23.73	-	56.00	46.00	-32.27	-
6	3.973	0.50	23.95	-	24.45	-	56.00	46.00	-31.55	-

**NOTE:**

1. QP. and AV. are abbreviations of quasi-peak and average individually.
2. "-": NA
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Emission Level = Reading Value + Correction Factor.






<b>EUT</b>	Bluetooth Dongle	<b>MODEL</b>	BT-510
<b>MODE</b>	Channel 0	<b>6dB BANDWIDTH</b>	9 kHz
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>PHASE</b>	Neutral (N)
<b>ENVIRONMENTAL CONDITIONS</b>	24 deg. C, 48%RH, 1005 hPa	<b>TESTED BY:</b> Cody Chang	

No	Freq.	Corr. Factor	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
	[MHz]		Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.170	0.10	47.87	-	47.97	-	64.98	54.98	-17.01	-
2	0.224	0.10	37.24	-	37.34	-	62.66	52.66	-25.32	-
3	0.283	0.10	33.90	-	34.00	-	60.73	50.73	-26.73	-
4	0.511	0.12	26.40	-	26.52	-	56.00	46.00	-29.48	-
5	3.461	0.37	28.95	-	29.32	-	56.00	46.00	-26.68	-
6	4.027	0.40	27.51	-	27.91	-	56.00	46.00	-28.09	-

**NOTE:**

1. QP. and AV. are abbreviations of quasi-peak and average individually.
2. "-": NA
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Emission Level = Reading Value + Correction Factor.






<b>EUT</b>	Bluetooth Dongle	<b>MODEL</b>	BT-510
<b>MODE</b>	Channel 39	<b>6dB BANDWIDTH</b>	9 kHz
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>PHASE</b>	Line (L)
<b>ENVIRONMENTAL CONDITIONS</b>	24 deg. C, 48%RH, 1005 hPa	<b>TESTED BY:</b> Cody Chang	

No	Freq.	Corr. Factor	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
	[MHz]		Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.170	0.10	48.28	-	48.38	-	64.98	54.98	-16.60	-
2	0.228	0.10	40.72	-	40.82	-	62.52	52.52	-21.70	-
3	0.283	0.10	36.42	-	36.52	-	60.73	50.73	-24.21	-
4	0.400	0.10	31.21	-	31.31	-	57.85	47.85	-26.54	-
5	0.510	0.12	29.07	-	29.19	-	56.00	46.00	-26.81	-
6	3.914	0.49	27.23	-	27.72	-	56.00	46.00	-28.28	-

**NOTE:**

1. QP. and AV. are abbreviations of quasi-peak and average individually.
2. "-": NA
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Emission Level = Reading Value + Correction Factor.






<b>EUT</b>	Bluetooth Dongle	<b>MODEL</b>	BT-510
<b>MODE</b>	Channel 39	<b>6dB BANDWIDTH</b>	9 kHz
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>PHASE</b>	Neutral (N)
<b>ENVIRONMENTAL CONDITIONS</b>	24 deg. C, 48%RH, 1005 hPa	<b>TESTED BY:</b> Cody Chang	

No	Freq.	Corr. Factor	Reading Value [dB (Uv)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
	[MHz]		(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.
1	0.170	0.10	47.85	-	47.95	-	64.98	54.98	-17.03	-
2	0.228	0.10	38.82	-	38.92	-	62.52	52.52	-23.60	-
3	0.283	0.10	33.70	-	33.80	-	60.74	50.74	-26.94	-
4	0.340	0.10	30.89	-	30.99	-	59.20	49.20	-28.21	-
5	3.402	0.37	26.51	-	26.88	-	56.00	46.00	-29.12	-
6	3.633	0.38	29.57	-	29.95	-	56.00	46.00	-26.05	-

**NOTE:**

1. QP. and AV. are abbreviations of quasi-peak and average individually.
2. "-": NA
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Emission Level = Reading Value + Correction Factor.






<b>EUT</b>	Bluetooth Dongle	<b>MODEL</b>	BT-510
<b>MODE</b>	Channel 78	<b>6dB BANDWIDTH</b>	9 kHz
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>PHASE</b>	Line (L)
<b>ENVIRONMENTAL CONDITIONS</b>	24 deg. C, 48%RH, 1005 hPa	<b>TESTED BY:</b> Cody Chang	

No	Freq.	Corr. Factor	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
	[MHz]		Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.170	0.10	48.30	-	48.40	-	64.98	54.98	-16.58	-
2	0.224	0.10	38.76	-	38.86	-	62.66	52.66	-23.80	-
3	0.283	0.10	36.34	-	36.44	-	60.73	50.73	-24.29	-
4	0.397	0.10	33.71	-	33.81	-	57.91	47.91	-24.10	-
5	0.455	0.11	30.45	-	30.56	-	56.79	46.79	-26.23	-
6	3.633	0.46	27.14	-	27.60	-	56.00	46.00	-28.40	-

**NOTE:**

1. QP. and AV. are abbreviations of quasi-peak and average individually.
2. "-": NA
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Emission Level = Reading Value + Correction Factor.








<b>EUT</b>	Bluetooth Dongle	<b>MODEL</b>	BT-510
<b>MODE</b>	Channel 78	<b>6dB BANDWIDTH</b>	9 kHz
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>PHASE</b>	Neutral (N)
<b>ENVIRONMENTAL CONDITIONS</b>	24 deg. C, 48%RH, 1005 hPa	<b>TESTED BY:</b> Cody Chang	

No	Freq.	Corr. Factor	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
	[MHz]		Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.171	0.10	47.97	-	48.07	-	64.92	54.92	-16.85	-
2	0.228	0.10	38.88	-	38.98	-	62.52	52.52	-23.54	-
3	0.283	0.10	33.88	-	33.98	-	60.73	50.73	-26.75	-
4	0.338	0.10	28.94	-	29.04	-	59.26	49.26	-30.22	-
5	3.463	0.37	28.73	-	29.10	-	56.00	46.00	-26.90	-
6	3.859	0.39	31.27	-	31.66	-	56.00	46.00	-24.34	-

**NOTE:**

1. QP. and AV. are abbreviations of quasi-peak and average individually.
2. "-": NA
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Emission Level = Reading Value + Correction Factor.





## 4.2 NUMBER OF HOPPING FREQUENCY USED

### 4.2.1 LIMIT OF HOPPING FREQUENCY USED

At least 75 hopping frequencies, and should be equally spaced.

### 4.2.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
SPECTRUM ANALYZER	FSEK30	100049	July 24, 2003

**NOTE:**

- 1.The measurement uncertainty is less than +/- 2.6dB, which is calculated as per the NAMAS document NIS81.
- 2.The calibration interval of the above test instruments is 12 months. And the calibrations are traceable to NML/ROC and NIST/USA.


#### 4.2.3 TEST PROCEDURES

1. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
2. Turn on the EUT and connect its antenna terminal to measurement via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.
3. Set the SA on MaxHold Mode, and then keep the EUT in hopping mode. Record all the signals from each channel until each one has been recorded.
4. Set the SA on View mode and then plot the result on SA screen.
5. Repeat above procedures until all frequencies measured were complete.

#### 4.2.4 DEVIATION FROM TEST STANDARD


No deviation


#### 4.2.5 TEST SETUP



#### 4.2.6 TEST RESULTS

There are 79 hopping frequencies in the hopping mode. Please refer to next two pages for the test result. On the plots, it shows that the hopping frequencies are equally spaced.





### 4.3 DWELL TIME ON EACH CHANNEL

#### 4.3.1 LIMIT OF DWELL TIME USED

For FHSS, the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 30 second period. For hybrid systems, the average time of occupancy on any frequency should not exceed 0.4 seconds within a time period in seconds equal to the number of hopping frequencies employed multiplied by 0.4.

#### 4.3.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
SPECTRUM ANALYZER	FSEK30	100049	July 24, 2003

#### NOTES:

- 1.The measurement uncertainty is less than +/- 2.6dB, which is calculated as per the NAMAS document NIS81.
- 2.The calibration interval of the above test instruments is 12 months. And the calibrations are traceable to NML/ROC and NIST/USA.


#### 4.3.3 TEST PROCEDURES

1. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
2. Turn on the EUT and connect its antenna terminal to measurement via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.
3. Adjust the center frequency of SA on any frequency be measured and set SA to zero span mode. And then, set RBW and VBW of spectrum analyzer to proper value.
4. Measure the time duration of one transmission on the measured frequency. And then plot the result with time difference of this time duration.
5. Repeat above procedures until all frequencies measured were complete.

#### 4.3.4 DEVIATION FROM TEST STANDARD

No deviation

#### 4.3.5 TEST SETUP





#### 4.3.6 TEST RESULTS

CHANNEL	DWELL TIME
0	81.418ms
39	77.772ms
78	78.380ms

**NOTE:** This product is averagely hopped on 79 frequencies. The maximum hopping rate is 500 hops/sec. The longest pulse duration is 134.00 $\mu$ sec.


So, the longest Dwell Time =  $134.00 \mu \text{ sec} \times 1600 \div 79 \times 30 = 81.418 \text{ msec}$ . which is smaller than 0.4sec.

Test plots of the transmitting time slot are shown on next three pages.






Channel 0






Channel 39



Channel 78





#### 4.4 CHANNEL BANDWIDTH

##### 4.4.1 LIMITS OF CHANNEL BANDWIDTH

For frequency hopping system operating in the 2400-2483.5 MHz, the maximum 20 dB bandwidth of the hopping channel is 1 MHz.

##### 4.4.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
SPECTRUM ANALYZER	FSEK30	100049	July 24, 2003

##### NOTES:

- 1.The measurement uncertainty is less than +/- 2.6dB, which is calculated as per the NAMAS document NIS81.
- 2.The calibration interval of the above test instruments is 12 months. And the calibrations are traceable to NML/ROC and NIST/USA.


#### 4.4.3 TEST PROCEDURE

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 20dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.

#### 4.4.4 DEVIATION FROM TEST STANDARD

No deviation

#### 4.4.5 TEST SETUP



#### 4.4.6 EUT OPERATING CONDITION

The software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel frequencies individually.




## 4.4.7 TEST RESULTS

<b>CHANNEL</b>	<b>CHANNEL FREQUENCY (MHz)</b>	<b>20dB BANDWIDTH (kHz)</b>	<b>MAXIMUM LIMIT (MHz)</b>	<b>PASS/FAIL</b>
0	2402	708.00	1	PASS
39	2441	708.00	1	PASS
78	2480	744.00	1	PASS




Channel 0






Channel 39





Channel 78



## 4.5 HOPPING CHANNEL SEPARATION

### 4.5.1 LIMIT OF HOPPING CHANNEL SEPARATION

At least 25KHz or 20dB bandwidth (whichever is greater).

### 4.5.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
SPECTRUM ANALYZER	FSEK30	100049	July 24, 2003

#### NOTES:

- 1.The measurement uncertainty is less than +/- 2.6dB, which is calculated as per the NAMAS document NIS81.
- 2.The calibration interval of the above test instruments is 12 months. And the calibrations are traceable to NML/ROC and NIST/USA.

#### 4.5.3 TEST PROCEDURES

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range.
3. By using the MaxHold function record the separation of two adjacent channels.
4. Measure the frequency difference of these two adjacent channels by SA MARK function. And then plot the result on SA screen.
5. Repeat above procedures until all frequencies measured were complete.

#### 4.5.4 DEVIATION FROM TEST STANDARD

No deviation

#### 4.5.5 TEST SETUP






#### 4.5.6 TEST RESULTS


Channel	Frequency (MHz)	Adjacent Channel Separation	Minimum Limit (kHz)	Pass / Fail
0	2402	1MHz	708.00	PASS
39	2441	1MHz	708.00	PASS
78	2480	1MHz	744.00	PASS

The minimum limit is 20dB bandwidth. Test results please refer to next three pages.


Channel 0



Channel 39



Channel 78





## 4.6 MAXIMUM PEAK OUTPUT POWER

### 4.6.1 LIMITS OF MAXIMUM PEAK OUTPUT POWER MEASUREMENT

The Limit of Maximum Peak Output Power Measurement is 30dBm.

### 4.6.2 INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
SPECTRUM ANALYZER	FSEK30	100049	July 24, 2003

#### NOTES:

- 1.The measurement uncertainty is less than +/- 2.6dB, which is calculated as per the NAMAS document NIS81.
- 2.The calibration interval of the above test instruments is 12 months. And the calibrations are traceable to NML/ROC and NIST/USA.



#### 4.6.3 TEST PROCEDURES

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. The center frequency of the spectrum analyzer is set to the fundamental frequency and using 3 MHz RBW and 3 MHz VBW.
4. Measure the frequency difference of two frequencies that were attenuated 20dB from the reference level. Record the frequency difference as the emission bandwidth.
5. Repeat above procedures until all frequencies measured were complete.

#### 4.6.4 DEVIATION FROM TEST STANDARD

No deviation

#### 4.6.5 TEST SETUP



For the actual test configuration, please refer to the related Item – Photographs of the Test Configuration.

#### 4.6.6 EUT OPERATING CONDITION

The software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel frequencies individually.




## 4.6.7 TEST RESULTS


Output Power Into Antenna:

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER OUTPUT (dBm)	PEAK POWER LIMIT (dBm)	PASS/FAIL
0	2402	0.17	30	PASS
39	2441	-1.04	30	PASS
78	2480	-2.16	30	PASS

Channel 0




Channel 39





Channel 78





## 4.7 RADIATED EMISSION MEASUREMENT

### 4.7.1 LIMITS OF RADIATED EMISSION MEASUREMENT

Field strength limits are at the distance of 3 meters, emissions radiated outside of the specified bands, shall be according to the general radiated limits in 15.209 as following:

Frequencies (MHz)	Field Strength of Fundamental	
	uV/m	dBuV/m
30-88	100	40.0
88-216	150	43.5
216-960	200	46.0
Above 960	500	54.0

**NOTE:**

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.



## 4.7.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
* HP Spectrum Analyzer	8590L	3544A01176	May 13, 2003
* HP Preamplifier	8447D	2944A08485	Oct. 30, 2002
* HP Preamplifier	8449B	3008A01201	Dec. 06, 2002
* HP Preamplifier	8449B	3008A01292	Aug. 07, 2003
* ROHDE & SCHWARZ TEST RECEIVER	ESMI	839013/007 839379/002	Jan. 27, 2003
SCHWARZBECK Tunable Dipole Antenna	VHA 9103 UHA 9105	E101051 E101055	Nov. 23, 2002
ANTENNA (Large Biconical)	VHBA9123	449	Dec. 10, 2002
* CHASE BILOG Antenna	CBL6112A	2221	Aug. 02, 2003
* SCHWARZBECK Horn Antenna	BBHA9120-D1	D130	Jul. 03, 2003
* EMCO Horn Antenna	3115	9312-4192	Apr. 09, 2003
* EMCO Turn Table	1060	1115	NA
* SHOSHIN Tower	AP-4701	A6Y005	NA
* Software	AS61D4	NA	NA
* ANRITSU RF Switches	MP59B	M35046	Jan. 25, 2003
* TIMES RF cable	LMR-600	CABLE-ST5-01	Jul. 12, 2003
Open Field Test Site	Site 5	ADT-R05	Jul. 19, 2003
VCCI Site Registration No.	Site 5	R-1039	NA

- NOTE:**
1. The measurement uncertainty is less than +/- 3.0dB, which is calculated as per the NAMAS document NIS81.
  2. The calibration interval of the above test instruments is 12 months. And the calibrations are traceable to NML/ROC and NIST/USA.
  3. "\*" = These equipment are used for the final measurement.
  4. The horn antenna and HP preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
  5. The test was performed in ADT Open Site No. 5.



#### 4.7.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 10 meter open area test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10 dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10 dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

**NOTE:**


1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Peak detection (PK) and Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1 MHz for Peak detection at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 300 Hz for Average detection (AV) at frequency above 1GHz.

#### 4.7.4 DEVIATION FROM TEST STANDARD

No deviation



## 4.7.5 TEST SETUP



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

## 4.7.6 TEST RESULTS

**Digital Portion:**

<b>EUT</b>	Bluetooth Dongle	<b>MODEL</b>	BT-510
<b>MODE</b>	Channel 78	<b>FREQUENCY RANGE</b>	30-1000 MHz
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>DETECTOR FUNCTION</b>	Quasi-Peak
<b>ENVIRONMENTAL CONDITIONS</b>	25 deg. C, 60%RH, 1050 hPa	<b>TESTED BY:</b> Gary Chang	

**ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M**

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB)	Cable Factor (dB)	Pre-Amp. Factor (dB)	Correction Factor (dB)
1	144.00	24.0 QP	43.50	-19.50	1.46H	4	9.94	10.58	3.48	0.00	-14.06
2	240.00	25.0 QP	46.00	-21.00	1.22H	8	9.04	11.41	4.55	0.00	-15.96
3	288.00	26.2 QP	46.00	-19.80	1.05H	56	8.30	12.88	5.01	0.00	-17.91
4	336.00	24.0 QP	46.00	-22.00	1.02H	24	4.55	13.92	5.53	0.00	-19.46
5	432.00	28.0 QP	46.00	-18.00	1.02H	148	5.29	16.28	6.43	0.00	-22.71
6	512.00	26.2 QP	46.00	-19.80	1.12H	189	2.06	17.42	6.72	0.00	-24.14

**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M**

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB)	Cable Factor (dB)	Pre-Amp. Factor (dB)	Correction Factor (dB)
1	144.00	28.0 QP	43.50	-15.50	1.27V	263	13.94	10.58	3.48	0.00	-14.06
2	240.00	25.4 QP	46.00	-20.60	1.01V	318	9.44	11.41	4.55	0.00	-15.97
3	252.00	27.0 QP	46.00	-19.00	1.15V	77	9.98	12.29	4.73	0.00	-17.03
4	336.00	26.0 QP	46.00	-20.00	1.08V	241	6.55	13.92	5.53	0.00	-19.46
5	400.00	25.1 QP	46.00	-20.90	1.12V	171	2.82	16.11	6.18	0.00	-22.29
6	432.00	27.0 QP	46.00	-19.00	1.15V	186	4.29	16.28	6.43	0.00	-22.72

**NOTE:**

1. Emission level = Raw value - Correction Factor
2. Correction Factor = Pre-Amp. Factor - Ant. Factor - Cable loss  
(Pre-Amp. Factor = 0, when a Pre-Amplifier is not used for the test.)
3. Margin value = Emission level - Limit value
4. The other emission levels were very low against the limit.

## 4.7.7 TEST RESULTS

## RF Portion :

<b>EUT</b>	Bluetooth Dongle	<b>MODEL</b>	BT-510
<b>MODE</b>	Channel 0	<b>FREQUENCY RANGE</b>	Above 1000 MHz
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>DETECTOR FUNCTION</b>	Peak(PK) Average (AV)
<b>ENVIRONMENTAL CONDITIONS</b>	25 deg. C, 60%RH, 1050 hPa	<b>TESTED BY:</b> Gary Chang	

**ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M**

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB)	Cable Factor (dB)	Pre-Amp. Factor (dB)	Correction Factor (dB)
1	*2402.00	96.5 PK			1.09H	141	103.00	27.67	2.53	36.72	6.52
2	*2402.00	58.6 AV			1.09H	141	72.80	27.67	2.53	36.72	6.52
3	4804.00	45.8 PK	74.00	-28.20	1.00H	311	47.00	31.52	4.01	36.70	1.18
4	7206.00	18.8 AV	54.00	-35.20	1.77H	4	37.00	36.13	5.51	36.98	-4.66
5	7206.00	56.7 PK	74.00	-17.30	1.77H	3	14.14	36.13	5.51	36.98	-4.66

**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M**

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB)	Cable Factor (dB)	Pre-Amp. Factor (dB)	Correction Factor (dB)
1	*2402.00	55.3 AV			1.03V	44	72.00	27.67	2.53	36.72	6.52
2	*2402.00	93.2 PK			1.03V	44	99.70	27.67	2.53	36.72	6.52
3	4804.00	48.8 PK	74.00	-25.20	1.19V	31	50.00	31.52	4.01	36.70	1.18
4	7206.00	16.8 AV	54.00	-37.20	1.30V	323	12.14	36.13	5.51	36.98	-4.66
5	7206.00	54.7 PK	74.00	-19.30	1.30V	323	50.00	36.13	5.51	36.98	-4.66

**NOTE:**

- Emission level = Raw value - Correction Factor
- Correction Factor = Pre-Amp. Factor - Ant. Factor - Cable loss  
(Pre-Amp. Factor = 0, when a Pre-Amplifier is not used for the test.)
- Margin value = Emission level - Limit value
- " \* " : Fundamental frequency
- The other emission levels were very low against the limit.
- The DH1 packet was only used for a transmit dwell time on a channel and it was the worse case duty cycle, based upon bluetooth theory the transmitter is on 0.625us per 49ms per channel.  
Therefore, the duty cycle equal to the following:  $20\log(0.625/49)=37.9\text{dB}$
- Average value = peak reading – 20 log(duty cycle)

<b>EUT</b>	Bluetooth Dongle	<b>MODEL</b>	BT-510
<b>MODE</b>	Channel 39	<b>FREQUENCY RANGE</b>	Above 1000 MHz
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>DETECTOR FUNCTION</b>	Peak(PK) Average (AV)
<b>ENVIRONMENTAL CONDITIONS</b>	25 deg. C, 60%RH, 1050 hPa	<b>TESTED BY:</b> Gary Chang	

#### ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB)	Cable Factor (dB)	Pre-Amp. Factor (dB)	Correction Factor (dB)
1	*2441.00	59.1 AV			1.58H	356	71.76	27.81	2.66	36.71	6.24
2	*2441.00	97.0 PK			1.58H	356	103.20	27.81	2.66	36.71	6.24
3	4882.00	46.1 PK	74.00	-27.90	1.42H	85	47.20	31.59	4.03	36.70	1.08
4	7322.00	18.5 AV	54.00	-35.50	1.09H	317	13.48	36.33	5.72	37.03	-5.02
5	7322.00	56.4 PK	74.00	-17.60	1.09H	317	51.40	36.33	5.72	37.03	-5.03

#### ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB)	Cable Factor (dB)	Pre-Amp. Factor (dB)	Correction Factor (dB)
1	*2441.00	94.8 PK			1.14V	259	101.00	27.81	2.66	36.71	6.24
2	*2441.00	56.9 AV			1.14V	259	70.80	27.81	2.66	36.71	6.24
3	4882.00	45.0 PK	74.00	-29.00	1.23V	328	46.10	31.59	4.03	36.70	1.09
4	7322.00	57.0 PK	74.00	-17.00	1.57V	46	52.00	36.33	5.72	37.03	-5.02
5	7322.00	19.1 AV	54.00	-34.90	1.57V	46	14.08	36.33	5.72	37.03	-5.02

#### NOTE:

- Emission level = Raw value - Correction Factor
- Correction Factor = Pre-Amp. Factor - Ant. Factor - Cable loss  
(Pre-Amp. Factor = 0, when a Pre-Amplifier is not used for the test.)
- Margin value = Emission level - Limit value
- " \* " : Fundamental frequency
- The other emission levels were very low against the limit.
- The DH1 packet was only used for a transmit dwell time on a channel and it was the worse case duty cycle, based upon bluetooth theory the transmitter is on 0.625us per 49ms per channel.  
Therefore, the duty cycle equal to the following:  $20\log(0.625/49)=37.9\text{dB}$
- Average value = peak reading – 20 log(duty cycle)



<b>EUT</b>	Bluetooth Dongle	<b>MODEL</b>	BT-510
<b>MODE</b>	Channel 78	<b>FREQUENCY RANGE</b>	Above 1000 MHz
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>DETECTOR FUNCTION</b>	Peak(PK) Average (AV)
<b>ENVIRONMENTAL CONDITIONS</b>	25 deg. C, 60%RH, 1050 hPa	<b>TESTED BY:</b> Gary Chang	

**ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M**

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB)	Cable Factor (dB)	Pre-Amp. Factor (dB)	Correction Factor (dB)
1	*2480.00	97.5 PK			1.27H	129	103.50	27.96	2.78	36.70	5.96
2	*2480.00	59.6 AV			1.27H	129	69.00	27.96	2.78	36.70	5.97
3	4960.00	47.3 PK	74.00	-26.70	1.19H	154	48.20	31.72	4.08	36.70	0.89
4	7440.00	18.9 AV	54.00	-35.10	1.36H	217	13.51	36.54	5.93	37.08	-5.39
5	7440.00	56.8 PK	74.00	-17.20	1.36H	215	51.40	36.54	5.93	37.08	-5.39

**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M**

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (DbuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Antenna Factor (dB)	Cable Factor (dB)	Pre-Amp. Factor (dB)	Correction Factor (dB)
1	*2480.00	58.3 AV			1.29V	320	68.00	27.96	2.78	36.70	5.96
2	*2480.00	96.2 PK			1.29V	320	102.20	27.96	2.78	36.70	5.96
3	7440.00	56.8 PK	74.00	-17.20	1.72V	351	51.40	36.54	5.93	37.08	-5.40
4	7440.00	18.9AV	54.00	-35.10	1.72V	351	13.51	36.54	5.93	37.08	-5.39

**NOTE:**

- Emission level = Raw value - Correction Factor
- Correction Factor = Pre-Amp. Factor - Ant. Factor - Cable loss  
(Pre-Amp. Factor = 0, when a Pre-Amplifier is not used for the test.)
- Margin value = Emission level - Limit value
- " \* " : Fundamental frequency
- The other emission levels were very low against the limit.
- The DH1 packet was only used for a transmit dwell time on a channel and it was the worse case duty cycle, based upon bluetooth theory the transmitter is on 0.625us per 49ms per channel. Therefore, the duty cycle equal to the following:  $20\log(0.625/49)=37.9\text{dB}$
- Average value = peak reading –  $20\log(\text{duty cycle})$

#### 8. 4.8 BAND EDGES MEASUREMENT

##### 4.8.1 LIMITS OF BAND EDGES MEASUREMENT

Below  $-20\text{dB}$  of the highest emission level of operating band (in 100KHz RB).

##### 4.8.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
SPECTRUM ANALYZER	FSEK30	100049	July 24, 2003

##### Notes:

- 1.The measurement uncertainty is less than  $\pm 2.6\text{dB}$ , which is calculated as per the NAMAS document NIS81.
- 2.The calibration interval of the above test instruments is 12 months. And the calibrations are traceable to NML/ROC and NIST/USA.

##### 4.8.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer via a low lose cable. Set both RBW and VBW of spectrum analyzer to 100 kHz with suitable frequency span including 100 kHz bandwidth from band edge. The band edges was measured and recorded.



#### 4.8.4 EUT OPERATING CONDITION

The software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel frequencies individually.


#### 4.7.8 DEVIATION FROM TEST STANDARD

No deviation


#### 4.8.5 TEST RESULTS

The spectrum plots are attached on the following 2 pages. D2 line indicates the highest level, D1 line indicates the 20dB offset below D2. It shows compliance with the requirement in part 15.247(C).

**NOTE:** The band edge emission plot on the following 2 pages shows 41.25dB / 49.08dB delta between carrier maximum power and local maximum emission in restrict band (2.4836GHz / 2.3884GHz). The emission of carrier strength list in the test result of channel 78 at the item 4.7.7(Page 53) is 59.6 dBuV/m, so the maximum field strength in restrict band is  $59.6 - 41.25 = 18.35$ dBuV/m which is under 54dBuV/m limit.









## **4.9 ANTENNA REQUIREMENT**

### **4.9.1 STANDARD APPLICABLE**

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6 dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.


### **4.9.2 ANTENNA CONNECTED CONSTRUCTION**

The antenna used in this product is Meander IFA Antenna. There is no antenna connector. The maximum Gain of this antenna is only -1dBi.

## 5 PHOTOGRAPHS OF THE TEST CONFIGURATION CONDUCTED EMISSION TEST



### RADIATED EMISSION TEST





## 6 INFORMATION ON THE TESTING LABORATORIES

We, ADT Corp., were founded in 1988 to provide our best service in EMC and Safety consultation. Our laboratories are accredited and approved by the following approval agencies according to ISO/IEC 17025, Guide 25 or EN 45001:

<b>USA</b>	FCC, NVLAP
<b>Germany</b>	TUV Rheinland
<b>Japan</b>	VCCI
<b>New Zealand</b>	MoC
<b>Norway</b>	NEMKO
<b>R.O.C.</b>	BSMI, DGT, CNLA

Copies of accreditation certificates of our laboratories obtained from approval agencies can be downloaded from our web site: [www.adt.com.tw/index.5/phtml](http://www.adt.com.tw/index.5/phtml).

If you have any comments, please feel free to contact us at the following:

**Lin Kou EMC Lab:**

Tel: 886-2-26052180

Fax: 886-2-26052943

**Hsin Chu EMC Lab:**

Tel: 886-35-935343

Fax: 886-35-935342

**Lin Kou Safety Lab:**

Tel: 886-2-26093195

Fax: 886-2-26093184

**Lin Kou RF&Telecom Lab**

Tel: 886-3-3270910

Fax: 886-3-3270892

**Email:** [service@mail.adt.com.tw](mailto:service@mail.adt.com.tw)

**Web Site:** [www.adt.com.tw](http://www.adt.com.tw)

The address and road map of all our labs can be found in our web site also.