


6.5 Band Edge Measurement

6.5.1 Test Procedure (Conducted)

1. The transmitter output of EUT was connected to the spectrum analyzer.
 Equipment mode: Spectrum analyzer
 Detector function: Peak mode
 SPAN: 100MHz
 RBW: 100KHz
 VBW: 100KHz
 Center frequency: 2.4GHz, 2.4835GHz.
2. Using Peak Search to read the peak power of Carrier frequencies after Maximum Hold function is completed
3. Find the next peak frequency outside the operation frequency band

6.5.2 Test Setup (Conducted)



6.5.3 Test Data:

Table: Band Edge measurement (Conducted)

Temp. (deg. C): 25

Test Engr: Mailes Hsieh

Humidity (%): 50

Channel	Frequency (MHz)	Spectrum Reading (dBuV)	Carrier - Outsideband Limit: >20dB (dB)	Pass/Fail
1	2413.2	108.07	---	---
Outside band	2399.7	80.21	27.86	Pass
11	2455.7	108.84	---	---
Outside band	2474.2	78.61	30.23	Pass

Note: Two RF output(MAIN & AUX) have been test,the worse data shown above.

Band Edge Conducted measurement



Band Edge Conducted Measurement



6.5.4 Test Procedure (Radiated)

1. Antenna and Turntable test procedure same as Radiated Emission Measurement.
Equipment mode: Spectrum analyzer
Detector function: Peak mode
SPAN: 100MHz
RBW: 1MHz
VBW: 1MHz
Center frequency: 2.395GHz, 2.48GHz.
2. Using Peak Search to read the peak power of Carrier frequencies after Maximum Hold function is completed.
3. Find the next peak frequency outside the operation frequency band
4. For peak frequency emission level measurement in Restricted Band ,
Change RBW: 1MHz
VBW: 10Hz
Span: 100MHz.
5. Get the spectrum reading after Maximum Hold function is completed.

6.5.5 Test Setup (Radiated)

Same as *Radiated Emission Measurement*

6.5.6 Test Data

Table Band Edge measurement (Radiated)

Temp. (deg. C): 25

Test Engr: Mailes Hsieh

Humidity (%): 50

Channel	Frequency (MHz)	Spectrum Reading (dBuV)	Correction Factor (dB/m)	Emission Level (dBuV/m)	dBc (Limit: > 20dBc)	Limit (dBuV/m)	Equip. Setup VBW	Pass or Fail
1(peak mode)	2414.8	73.19	31.1	104.29	---	---	1MHz	---
Outside band	2400	52.71	31.1	83.81	20.48	---	1MHz	Pass
1(average mode)	2405.6	62.16	31.1	93.26	---	---	10Hz	---
Restricted band	2389.9	15.77	31.1	46.87	---	54	10Hz	Pass
11(peak mode)	2464.7	76.8	31.1	107.9	---	---	1MHz	---
Outside band	2478.5	46.02	31.1	77.12	30.78	---	1MHz	Pass
11(average mode)	2467.2	65.74	31.1	96.84	---	---	10Hz	---
Restricted band	2483.6	21.05	31.1	52.15	---	54	10Hz	Pass

Note:

The Spectrum plot of emission level measurement in Restricted band is attached.

Emission Level=Spectrum Reading+Correction Factor

Correction Factor=Antenna Factor+cable loss–amplifier gain

Both Horizontal and Vertical polarizaion have been tested and the worst data is listed above.

Band Edge measurement for radiated emission in Restricted Band(Radiated)
Peak Mode (Channel 1)



Band Edge measurement for radiated emission in Restricted Band(Radiated)
Average Mode (Channel 1)



Band Edge measurement for radiated emission in Restricted Band(Radiated)
Peak Mode (Channel 11)



Band Edge measurement for radiated emission in Restricted Band(Radiated)
Average Mode (Channel 11)



6.6 RF Exposure Measurement [Section 15.247(b)(4) & 1.1307(b)]


See MPE report

6.7 DSSS Peak Power Spectral Density [Section 15.247(d)]

6.7.1 Test Procedure

1. The Transmitter output of EUT was connected to the spectrum analyzer.
 Equipment mode: Spectrum analyzer
 Detector function: Peak mode
 SPAN:1.5MHz
 RBW: 3KHz
 VBW: 30KHz
 Center frequency: fundamental frequency tested.
 Sweep time= 500 sec.
2. Using Peak Search to read the peak power after Maximum Hold function is completed.

6.7.2 Test Setup



6.7.3 Test Data

Maximum Peak Output Power Density

Temp. (deg. C): 25

Test Engr:


Mailes
Hsieh

Humidity (%): 50

Chennel	Frequency (MHz)	Spectrum Reading (dBm/3KHz)	Cable Loss (dB)	Peak Power Output (dBm/3KHz)	Limit (dBm/3KHz)	Pass/Fail
1	2412	-11.34	1.1	-10.24	8	Pass
6	2437	-11.07	1.1	-9.97	8	Pass
11	2462	-9.8	1.1	-8.7	8	Pass

Note: Two RF output(MAIN & AUX) have been test,the worse data shown above.


Channel 1



Channel 6



Channel 11



7. Appendix

7.1 Appendix A: Measurement Procedure for Power line Conducted Emissions

The measurements are performed in a 3.5m x 3.4m x 2.5m shielded room, which referred as Conduction 01 test site, or a 3m x 3m x 2.3m test site, which referred as Conduction 02 test site. The EUT was placed on non-conduction 1.0m x 1.5m table, which is 0.8 meters above an earth-grounded.

Power to the EUT was provided through the LISN which has the Impedance (50ohm/50uH) vs. Frequency Characteristic in accordance with the required standard. Power to the LISNs were filtered to eliminate ambient signal interference and these filters were bonded to the ground plane. Peripheral equipment required to provide a functional system (support equipment) for EUT testing was powered from the second LISN through a ganged, metal power outlet box which is bonded to the ground plane at the LISN.

If the EUT is supplied with a flexible power cord, the power cord length in excess of the distance separating the EUT from the LISN shall be folded back and forth at the center of the lead so as to form a bundle not exceeding 40cm in length. If the EUT is provided with a permanently coiled power cord, bundling of the cord is not required. If the EUT is supplied without a power cord, the EUT shall be connected to the LISN by a power cord of the type specified by the manufacturer which shall not be longer than 1 meter. The excess power cord shall be bundled as described above. If a non-flexible power cord is provided with the EUT, it shall be cut to the length necessary to attach the EUT to the LISN and shall not be bundled.

The interconnecting cables were arranged and moved to get the maximum emission. Both the line of power cord, hot and neutral, were measured.

The highest emissions were analyzed in details by operating the spectrum analyzer in fixed tuned mode to determine the nature of the emissions and to provide information which could be useful in reducing their amplitude.

7.2 Appendix B: Test Procedure for Radiated Emissions

Preliminary Measurements in the Anechoic Chamber

The radiated emissions are initially measured in the anechoic chamber at a measurement distance of 3 meters. Desktop EUT are placed on a wooden stand 0.8 meter in height. The measurement antenna is 3 meters from the EUT. The test setup in anechoic chamber is the same as open site. The turntable rotated 360°. The antenna height is varied from 1-2.5m. The primary objective of the radiated measurements in the anechoic chamber is to identify the frequency spectrum in the absence of the electromagnetic environment existing on the open test site. The frequencies can then be pre-selected on the open test site to obtain the corresponding amplitude. The initial scan is made with the spectrum analyzer in automatic sweep mode. The spectrum peaks are then measured manually to determine the exact frequencies.

Measurements on the Open Site or 10m EMC Chamber

The radiated emissions test will then be repeated on the open site or 10m EMC chamber to measure the amplitudes accurately and without the multiple reflections existing in the shielded room. The EUT and support equipment are set up on the turntable of one of the 3 or 10 meter open field sites. Desktop EUT are set up on a wooden stand 0.8 meter above the ground.

For the initial measurements, the receiving antenna is varied from 1-4 meter height and is changed in the vertical plane from vertical to horizontal polarization at each frequency. Both readings are recorded with the quasi-peak detector with 120KHz bandwidth. For frequency between 30 MHz and 1000MHz, the reading is recorded with peak detector or quasi-peak detector. For frequency above 1 GHz, the reading is recorded with peak detector or average detector with 1 MHz bandwidth.

At the highest amplitudes observed, the EUT is rotated in the horizontal plane while changing the antenna polarization in the vertical plane to maximize the reading. The interconnecting cables were arranged and moved to get the maximum emission. Once the maximum reading is obtained, the antenna elevation and polarization will be varied between specified limits to maximize the readings.

7.3 Appendix C: Test Equipment

7.3.1 Test Equipment List

Location	Equipment Name	Brand	Model	S/N	Last Cal. Date	Next Cal. Date
Conduction	Coaxial Cable 1F-C2	Harbourindustries	RG400	1F-C2	06/02/2003	06/02/2004
Conduction	Digital Hygro-Thermometer Conduct	MicroLife	HT-2126G	ISL-Conductio n02	12/04/2002	12/04/2004
Conduction	EMI Receiver 03	HP	85460A	3448A00209	01/08/2004	01/08/2005
Conduction	LISN 01	R&S	ESH2-Z5	890485/013	04/30/2003	04/30/2004
Conduction	LISN 04	EMCO	3810/2	9604-1429	12/18/2003	12/18/2004
Radiation	BILOG Antenna 08	Schaffner	CBL6112B	2756	06/03/2003	06/03/2004
Radiation	Coaxial Cable Chmb 02-10M	Belden	RG-8/U	Chmb 02-10M	09/09/2003	09/09/2004
Radiation	Microwave Cable Chmb 02 3M	HUBER+SUHNER AG.	Sucoflex 103	42731/3 & 42729/3	03/17/2004	03/17/2005
Radiation	Digital Hygro-Thermometer Chmb 02	MicroLife	HT-2126G	Chmb 02	12/04/2002	12/04/2004
Radiation	EMI Receiver 02	HP	85460A	3448A00183	10/02/2003	10/02/2004
Radiation	EMI Receiver 04	AFJ	ER 55CR	55390143233	05/20/2003	05/20/2004
Radiation	Spectrum Analyzer 13	Advantest	R3132	121200411	02/12/2004	02/12/2005
Rad. Above 1Ghz	Horn Antenna 02	Com-Power	AH-118	10088	02/17/2004	02/17/2005
Rad. Above 1Ghz	Horn Antenna 04	Com-Power	AH-826	081-001	01/07/2004	01/07/2005
Rad. Above 1Ghz	Horn Antenna 05	Com-Power	AH-640	100A	09/18/2003	09/18/2005
Rad. Above 1Ghz	Microwave Cable RF SK-01	HUBER+SUHNER AG.	Sucoflex 102	22139 /2	02/17/2004	02/17/2005
Rad. Above 1Ghz	Peak Power Analyzer	HP	8990A	3621A01269	01/02/2004	01/02/2005
Rad. Above 1Ghz	Power Sensor Radar	HP	84815A	3318A01828	01/02/2004	01/02/2006
Rad. Spurious Emission	Power Meter 01	HP	438A	3513U06187	01/07/2004	01/07/2005
Rad. Spurious Emission	Power Sensor RF 01	HP	8481H	MY41091048	06/17/2003	06/17/2004
Rad. Above 1Ghz	Preamplifier 02	MITEQ	AFS44-0010265 0-40-10P-44	728229	05/13/2003	05/13/2004
Rad. Above 1Ghz	Preamplifier 09	MITEQ	AFS44-0010265 0-40-10P-44	858687	05/13/2003	05/13/2004
Rad. Above 1Ghz	Preamplifier 10	MITEQ	JS-26004000-27 -5A	818471	N/A	N/A
Rad. Above 1Ghz	Spectrum Analyzer 07	Advantest	R3182	110600649	04/08/2004	04/08/2005


Note: Calibration is traceable to NIST or national or international standards.

7.3.2 Software for Controlling Spectrum/Receiver and Calculating Test Data



Radiation/Conduction	Filename	Version	Issued Date
Conduction	Tile.exe	1.12E	7/7/2000
Radiation	Tile.exe	1.12C	6/16/2000

7.4 Appendix D: Layout of EUT and Support Equipment

7.4.1 General Conducted Test Configuration



7.4.2 General Radiation Test Configuration



7.5 Appendix E: Description of Support Equipment

7.5.1 Description of Support Equipment

Support Unit 1.

Description:	Notebook Personal Computer
Model No.:	Aspire1510,ZP2,ZP2A
Brand:	acer
AC Power Adapter Manufacturer:	LSE(Model:ADP-90FB REV:F) LSE(Model:0202C1990) LSE(Model:0317A19135) Delta(Model:ADP-90FB REV:F) LiteOn(Model:ADP-135DBB)
HDD:	HGST (Model: IC25N030ATMR04-0)
Modem Card:	Ambit (Model: T60M283.10)
FDD:	Panasonic (Model:UJ-266A343FC)
SDRAM:	Infineon (Model:HYS64D32020GDL-6-B)
1394 C0nnecto:r:	one 4 Pins
USB Connector:	four 4 Pins
RJ11 Connector:	one 2 Pins
RJ45 Connector:	one 8 Pins
VGA Connector:	one 15 Pins
PCMCIA Slot	one
Line out Port:	one
Line-in Port:	one
Parallel Port	one 25pins
DC IN Port:	one
Battery:	Li-ION DC14.8V 4400mAh
LCD:	QSI (Model:QD150XL06-01)
CPU	AMD Athlon 64 2800+, 3000+, 4000+

Support Unit 2.

Description:	USB 2.0 Card Reader/Writer
Model Number:	UID12W
Serial Number:	N/A
Power Supply Type:	From USB Port
USB 2.0 Port:	one 4-pin
SD/MMC Card Slot:	one
SecureDigital Card (Option):	SD (Model: SD-M16B1) 16MB
USB Cable:	Shielded, Detachable (With Cord)
FCC ID:	(Comply with FCC DOC)

Support Unit 3.

Description:	USB 2.0 Card Reader/Writer
Model Number:	UID12W
Serial Number:	N/A
Power Supply Type:	From USB Port
USB 2.0 Port:	one 4-pin
SD/MMC Card Slot:	one
SecureDigital Card (Option):	SD (Model: SD-M16B1) 16MB
USB Cable:	Shielded, Detachable (With Cord)
FCC ID:	(Comply with FCC DOC)

Support Unit 4.

Description:	Digital Video Camera
Model:	DCR-PC100
Serial Number:	173009
Power Supply Type:	AC Power Adaptor (SONY, Model: AC-L10A)
Power Cord:	Nonshielded, Detachable
FCC ID:	(Comply with FCC DOC)

Support Unit 5.

Description:	DELL USB Mouse
Model Number:	M-UR69
Serial Number:	LNA24412741
Power Supply Type:	N/A
Power Cord:	N/A
FCC ID:	N/A (Comply with FCC DOC)

Support Unit 6.

Description:	DELL USB Keyboard
Model Number:	RT7D10
Serial Number:	TH-05695W-37171-2B7-1021
Power Supply Type:	N/A
Power Cord:	N/A
FCC ID:	AQ6-7D10

Support Unit 7.

Description:	KOKA Headphone
Model Number:	ST-304
Serial Number:	N/A
Power Supply Type:	N/A
Power Cord:	N/A
FCC ID:	N/A

Support Unit 8.

Description:	KOKA Microphone
Model Number:	DM-510
Serial Number:	N/A
Power Supply Type:	N/A
Power Cord:	N/A
FCC ID:	N/A

Support Unit 9.

Description:	HP Printer (for parallel interface port)
Model Number:	C2642A
Serial Number:	TH84T1N3J3
Power Supply Type:	AC Adaptor (HP Model: C2175A)
Power Cord:	Non-shielded, Detachable
Data Cable:	Shielded, Detachable, With Metal Hood
FCC ID:	B94C2642X

Support Unit 10.

Description:	DELL 19" LCD Monitor
Model:	2000FP
AC Adapter:	DELL(ADP-70EB)
Serial Number:	N/A
DSUB In:	One 15 Pins
DVI In:	One Pins
S-Video In:	One7 Pins
Power Cord:	Non-shielded, Detachable
FCC ID:	(Comply with FCC DOC)

7.5.2 Software for Controlling Support Unit

A test program which generates a complete line of continuously repeating "H" pattern is used as the software test program. The program was executed as follows:

- A. Read and write to the disk drives.
- B. R/W memory card form EUT USB Port through Card Reader/Writer
- C. R/W memory card form EUT USB Port through Card Reader/Writer
- D. Capture the image from digital video camera then transfer to display.(CCD).
- E. Send audio signal to the headphone.
- F. Receive audio signal from the microphone.
- G. Send H pattern to the parallel port device (Printer).
- H. Send H pattern to the video port device (LCD Monitor).
- I. The RF software makes the transmitter contiunely sending RF signals
- J. Repeat the above steps.

	Filename	Issued Date
Monitor	HH.bat	8/20/1991
Printer1	Wordpad.exe	11/11/1999
Digital Video Camera	Divpcam.exe	12/10/1998
Winthrax	Winthrax.exe	5/21/1996
Winthrax	Winthrax.exe	5/21/1996
Atheros_1.6.2002	ART.exe	2003/12/17

7.5.3 I/O Cable Condition of EUT and Support Units

Description	Path	Cable Length	Cable Type	Connector Type
AC Power Cord	110V (~240V) to AC Power Cord Inlet (3-pin)	1.8M	Nonshielded, Detachable	Plastic Head
Printer Data Cable	Printer to PC Parallel port	1.5M	Shielded, Detachable	Metal Head
Microphone Data Cable	Microphone to PC Line In Port	1.5M	Nonshielded, Undetachable	Plastic Head
Headphone Data Cable	Headphone to PC Line Out Port	1.2M	Nonshielded, Undetachable	Plastic Head
Keyboard Data Cable	Keyboard to PC Keyboard port	1.8M	Shielded, Undetachable	Metal Head
Mouse Data Cable	Mouse to PC Mouse port	1.8M	Shielded, Un-detachable	Metal Head
Digital Video Camera 1394 Data Cable	Digital Video Camera to 1394 port of PC	1.0M	Shielded, Detachable	Metal Head
USB Data Cable	EUT USB Port to Card Reader/Writer	1.0 M	Shielded, detachable (with cord)	Metal Head
USB Data Cable	EUT USB Port to Card Reader/Writer	1.0 M	Shielded, detachable (with cord)	Metal Head
LCD Monitor D-SUB Data Cable	LCD Monitor to EUT D-SUB Port	1.6M	Shielded, Detachable	Metal Head
LCD Monitor S Data Cable	LCD Monitor to EUT S Port	1.6M	Shielded, Detachable	Metal Head

7.6 Appendix F: Accuracy of Measurement

Test Site: Conduction 02

Item	Source of Uncertainty	Probability Distribution	Total Uncertainties (dB)		Standard Uncertainty (dB)	
1	Systematic Effects: (Assessment from 20 repeat observation; 1 reading on EUT)	Normal	k=2	0.104	k=1	0.052
2	Random Effects: (Assessment from 20 random observations; 1 reading on EUT)	Normal	k=2	0.330	k=1	0.165
3	Receiver Calibration	Rectangular	k=1.73	1.000	k=1	0.577
4	LISN Factor Calibration	Normal	k=2	1.200	k=1	0.600
5	Cable Loss Calibration	Normal	k=2	1.000	k=1	0.500
6	Combined Standard Uncertainty Uc(y)	Normal			k=1	0.850
7	Total Uncertainty @95% mim. Confidence Level	Normal	k=2	1.701		

Measurement Uncertainty Calculations:

$$Uc(y) = \text{square root} (u_1(y)^2 + u_2(y)^2 + \dots + u_n(y)^2)$$

$$U = 2 * Uc(y)$$

Note: The measurement Uncertainties mentioned above also refer to NIS 81-1994 of NAMAS : The treatment of Uncertainty in EMC Measurement.

Test Site: Chamber 02-3M

Item	Source of Uncertainty	Probability Distribution	Total Uncertainties (dB)		Standard Uncertainty (dB)	
			k	Value	k	Value
1	Systematic Effects: (Assessment from 20 repeat observation; 1 reading on EUT)	Normal	k=2	0.067	k=1	0.034
2	Random Effects: (Assessment from 20 random observations; 1 reading on EUT)	Normal	k=2	0.103	k=1	0.052
3	Receiver Calibration	Rectangular	k=1.73	1.000	k=1	0.577
4	Antenna Factor Calibration	Normal	k=2	1.700	k=1	0.850
5	Cable Loss Calibration	Normal	k=2	1.000	k=1	0.500
6	Combined Standard Uncertainty Uc(y)	Normal			k=1	1.029
7	Total Uncertainty @95% mim. Confidence Level	Normal	k=2	2.059		

Measurement Uncertainty Calculations:


$$U_c(y) = \text{square root} (u_1(y)^2 + u_2(y)^2 + \dots + u_n(y)^2)$$

$$U = 2 * U_c(y)$$


Note: The measurement Uncertainties mentioned above also refer to NIS 81-1994 of NAMAS : The treatment of Uncertainty in EMC Measurement.

7.7 Appendix G: Photographs of EUT Configuration Test Set Up


The Front View of Highest Conducted Set-up For EUT



The Back View of Highest Conducted Set-up For EUT



The Front View of Highest Radiated Set-up For EUT



The Back View of Highest Radiated Set-up For EUT



7.8 Appendix H: Antenna Spec.

Please refer to the attached file.