

RF Exposure Evaluation Declaration

Product Name : LGA module
Trade Name : WNC
Model No. : IMQ6
FCC ID : NKRIMQ6

Applicant : Wistron Neweb Corporation
Address : 20 Park Avenue II, Hsinchu Science Park, Hsinchu
308, Taiwan, R.O.C

Date of Receipt : Sep. 24, 2020
Date of Declaration : Nov. 30, 2020
Report No. : 2090881R-E3082100013
Report Version : V1.0



The declaration results relate only to the samples calculated.
The declaration shall not be reproduced except in full without the written approval of DEKRA Testing and Certification Co., Ltd..

RF Exposure Evaluation Declaration

Issued Date : Nov. 30, 2020

Report No. : 2090881R-E3082100013



Product Name : LGA module
Applicant : Wistron Neweb Corporation
Address : 20 Park Avenue II, Hsinchu Science Park, Hsinchu 308, Taiwan, R.O.C
Manufacturer : Wistron Neweb Corporation
Address : 20 Park Avenue II, Hsinchu Science Park, Hsinchu 308, Taiwan, R.O.C
Trade Name : WNC
Model No. : IMQ6
FCC ID : NKRIMQ6
EUT Voltage : DC 3.8V
Testing Voltage : DC 3.8V
Applicable Standard : FCC 47 CFR Part 2.1091 Radiofrequency radiation exposure evaluation: mobile devices.
Test Lab : Hsin Chu Laboratory
Address : No.372-2, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County 310, Taiwan, R.O.C.
TEL: +886-3-582-8001 / FAX: +886-3-582-8958
Test Result : Complied

Tested By :

Max Chang

(Max Chang / Engineer)

Approved By :

Louis Hsu

(Louis Hsu / Deputy Manager)

Revision History

Version	Description	Issued Date
V1.0	Initial issue of report	Nov. 30, 2020

1.1. Test Facility

Ambient conditions in the laboratory:

Items	Test Item	Required	Test Site
Temperature (°C)	Peak Output Power	15 - 35	1
Humidity (%RH)		25 - 75	

Note: Test site information refers to Laboratory Information.

Laboratory Information

USA : FCC Registration Number: TW3024
Canada : IC Registration Number: 22397-1 / 22397-2 / 22397-3

The address and introduction of DEKRA Testing and Certification Co., Ltd. laboratories can be founded in our Web site: <http://www.dekra.com.tw>

If you have any comments, please don't hesitate to contact us. Our test sites as below:

Test Laboratory	DEKRA Testing and Certification Co., Ltd.
Address	1. No.372, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County 31061, Taiwan, R.O.C. 2. No.372-2, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County 31061, Taiwan, R.O.C.
Phone number	1. +886-3-582-8001 2. +886-3-582-8001
Fax number	1. +886-3-582-8958 2. +886-3-582-8958
Email address	info.tw@dekra.com
Website	http://www.dekra.com.tw

1.2. List of Test Equipment

Peak Output Power / SR12-H

Instrument	Manufacturer	Model No.	Serial No.	Cal. Date	Next Cal. Date
Signal & Spectrum Analyzer	R&S	FSV40	101049	2020/03/30	2021/03/29
EXA Signal Analyzer	Keysight	N9010A	MY51440132	2020/02/21	2021/02/20
Spectrum Analyzer	Keysight	N9030B	MY57140404	2020/06/03	2021/06/02
Spectrum Analyzer	Keysight	N9010B	MY57110159	2020/04/15	2021/04/14
Wireless Conn. Tseter	R&S	CMW500	157118	2020/07/23	2021/07/22
Wideband Radio Communication Tester	R&S	CMW500	106071	2020/02/03	2021/02/02

Note: All equipment upon which need to calibrated are with calibration period of 1 year.

1.3. Uncertainty

Test item	Uncertainty
Peak Output Power	± 2.26 dB

Note: Determining compliance shall be based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

2. RF Exposure Evaluation

2.1. Limits

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (Minutes)
(A) Limits for Occupational/ Control Exposures				
300-1500	--	--	F/300	6
1500-100,000	--	--	5	6
(B) Limits for General Population/ Uncontrolled Exposures				
300-1500	--	--	F/1500	6
1500-100,000	--	--	1	30

F= Frequency in MHz

RF Field Strength Limits for Controlled Use Devices (Controlled Environment)

Frequency Range (MHz)	Electric Field (V/m rms)	Magnetic Field (A/m rms)	Power Density (W/m ²)	Reference Period (minutes)
0.003-1023	170	180	-	Instantaneous*
0.1-10	-	1.6/ <i>f</i>	-	6**
1.29-10	193/ <i>f</i> 0.5	-	-	6**
10-20	61.4	0.163	10	6
20-48	129.8/ <i>f</i> 0.25	0.3444/ <i>f</i> 0.25	44.72/ <i>f</i> 0.5	6
48-100	49.33	0.1309	6.455	6
100-6000	15.60 <i>f</i> 0.25	0.04138 <i>f</i> 0.25	0.6455 <i>f</i> 0.5	6
6000-15000	137	0.364	50	6
15000-150000	137	0.364	50	616000/ <i>f</i> 1.2
150000-300000	0.354 <i>f</i> 0.5	9.40 x 10 ⁻⁴ <i>f</i> 0.5	3.33 x 10 ⁻⁴ <i>f</i>	616000/ <i>f</i> 1.2

Note: *f* is frequency in MHz. *Based on nerve stimulation (NS). ** Based on specific absorption rate (SAR).

Friis Formula

Friis transmission formula: $P_d = (P_{out} * G) / (4 * \pi * r^2)$

Where

P_d = power density in mW/cm^2

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

P_d is the limit of MPE, $1 mW/cm^2$. If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

2.2. Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

2.3. Test Result of RF Exposure Evaluation

Product	LGA module		
Test Mode	Transmit		
Test Condition	RF Exposure Evaluation		
Date of Test	2020/09/26	Test Site	SR12-H
Temperature(°C)	25	Humidity (%RH)	64

Band	Frequency (MHz) (Lowest Frequency)	Maximum conducted output power (per tune-up) (dBm)	Maximum conducted output power (per tune-up) (mW)	Power Density (mW/cm ²)	Antenna Gain (dBi)	Antenna Gain (linear)	Duty cycle (%)	FCC MPE limit (mW/cm ²)	FCC EIRP /ERP limit (W)	Evaluation distance for compliance with MPE limits (cm)	Antenna gain to meet FCC /IC MPE limit (dBi)	Antenna gain to meet FCC EIRP/ERP limit (dBi)	Maximum antenna gain to meet all the limits (dBi)
GSM 850	836.6	32.470	1766.038	0.070	2.000	1.585	12.5	0.558	3.00	20	6.00	4.45	4.45
DCS 1900	1880	28.700	741.310	0.029	2.000	1.585	12.5	1.000	3.00	20	6.00	8.22	6.00

The conducted power using GPRS class 8 (1 up and 1 down), duty cycle is 12.5%.

Product	LGA module		
Test Mode	Transmit		
Test Condition	RF Exposure Evaluation		
Date of Test	2020/09/27	Test Site	SR12-H
Temperature(°C)	24	Humidity (%RH)	67

Band	Frequency (MHz) (Lowest Frequency)	Maximum conducted output power (per tune-up) (dBm)	Maximum conducted output power (per tune-up) (mW)	Power Density (mW/cm ²)	Antenna Gain (dBi)	Antenna Gain (linear)	Duty cycle (%)	FCC MPE limit (mW/cm ²)	FCC EIRP /ERP limit (W)	Evaluation distance for compliance with MPE limits (cm)	Antenna gain to meet FCC /IC MPE limit (dBi)	Antenna gain to meet FCC EIRP/ERP limit (dBi)	Maximum antenna gain to meet all the limits (dBi)
LTE Band 12	699.7	22.160	164.437	0.048	1.660	1.466	100	0.466	3.00	20	6.00	14.76	6.00
LTE Band 13	779.5	22.220	166.725	0.047	1.490	1.409	100	0.520	3.00	20	6.00	14.70	6.00
LTE Band 5	824.7	22.190	165.577	0.069	3.200	2.089	100	0.550	7.00	20	6.00	18.41	6.00
LTE Band 4	1710.7	21.210	132.130	0.038	1.620	1.452	100	1.000	1.00	20	8.70	8.79	8.70
LTE Band 2	1850.7	20.910	123.310	0.035	1.560	1.432	100	1.000	2.00	20	9.00	12.10	9.00