

# RF Exposure Evaluation Declaration

Product Name : LGA module  
Trade Name : WNC  
Model No. : IMQ7  
FCC ID : NKRIMQ7

Applicant : Wistron Neweb Corporation  
Address : 20 Park Avenue II, Hsinchu Science Park,  
Hsinchu 308, Taiwan, R.O.C

Date of Receipt : Nov. 27, 2020  
Date of Declaration : Dec. 17, 2020  
Report No. : 20B0952R-E3082100013  
Report Version : V1.0



The declaration results relate only to the samples calculated.  
The declaration shall not be reproduced except in full without the written approval of DEKRA Testing and Certification Co., Ltd.

# RF Exposure Evaluation Declaration

Issued Date : Dec. 17, 2020

Report No. : 20B0952R-E3082100013



Product Name : LGA module  
Applicant : Wistron Neweb Corporation  
Address : 20 Park Avenue II, Hsinchu Science Park, Hsinchu 308,  
Taiwan, R.O.C  
Manufacturer : Wistron Neweb Corporation  
Address : 20 Park Avenue II, Hsinchu Science Park, Hsinchu 308,  
Taiwan, R.O.C  
Trade Name : WNC  
Model No. : IMQ7  
FCC ID : NKRIMQ7  
EUT Voltage : DC 3.8V  
Testing Voltage : DC 3.8V  
Applicable Standard : FCC 47 CFR Part 2.1091 Radiofrequency radiation exposure  
evaluation: mobile devices.  
Test Lab : Hsin Chu Laboratory  
Address : No.372-2, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu  
County 310, Taiwan, R.O.C.  
TEL: +886-3-582-8001 / FAX: +886-3-582-8958  
Test Result : Complied

Tested By :

*Max Chang*

( Max Chang / Senior Engineer )

Approved By :

*Louis Hsu*

( Louis Hsu / Deputy Manager )

### Revision History

Version	Description	Issued Date
V1.0	Initial issue of report	Dec. 17, 2020

### 1.1. Test Facility

Ambient conditions in the laboratory:

Items	Required	Test Site
Temperature (°C)	15-35	1
Humidity (%RH)	25-75	

Note: Test site information refers to Laboratory Information.

### Laboratory Information

**USA : FCC Registration Number: TW3024**  
**Canada : IC Registration Number: 22397-1 / 22397-2 / 22397-3**

The address and introduction of DEKRA Testing and Certification Co., Ltd. laboratories can be founded in our

Web site: <http://www.dekra.com.tw>

If you have any comments, please don't hesitate to contact us. Our test sites as below:

Test Laboratory	DEKRA Testing and Certification Co., Ltd.
Address	1. No.372, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County 31061, Taiwan, R.O.C. 2. No.372-2, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County 31061, Taiwan, R.O.C.
Phone number	1. +886-3-582-8001 2. +886-3-582-8001
Fax number	1. +886-3-582-8958 2. +886-3-582-8958
Email address	<a href="mailto:info.tw@dekra.com">info.tw@dekra.com</a>
Website	<a href="http://www.dekra.com.tw">http://www.dekra.com.tw</a>

## 1.2. List of Test Equipment

Peak Output Power / SR12-H

Instrument	Manufacturer	Model No.	Serial No.	Cal. Date	Next Cal. Date
Signal & Spectrum Analyzer	R&S	FSV40	101049	2020/03/30	2021/03/29
EXA Signal Analyzer	Keysight	N9010A	MY51440132	2020/02/21	2021/02/20
Spectrum Analyzer	Keysight	N9030B	MY57140404	2020/06/03	2021/06/02
Spectrum Analyzer	Keysight	N9010B	MY57110159	2020/04/15	2021/04/14
Wireless Conn. Tseter	R&S	CMW500	157118	2020/07/23	2021/07/22
Wideband Radio Communication Tester	R&S	CMW500	106071	2020/02/03	2021/02/02

Note: All equipment upon which need to calibrated are with calibration period of 1 year.

## 1.3. Uncertainty

Test item	Uncertainty
Peak Output Power	$\pm 1.27$ dB

Note: Determining compliance shall be based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

## 2. RF Exposure Evaluation

### 2.1. Limits

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

#### LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm <sup>2</sup> )	Average Time (Minutes)
(A) Limits for Occupational/ Control Exposures				
300-1500	--	--	F/300	6
1500-100,000	--	--	5	6
(B) Limits for General Population/ Uncontrolled Exposures				
300-1500	--	--	F/1500	6
1500-100,000	--	--	1	30

F= Frequency in MHz

#### RF Field Strength Limits for Controlled Use Devices (Controlled Environment)

Frequency Range (MHz)	Electric Field (V/m rms)	Magnetic Field (A/m rms)	Power Density (W/m <sup>2</sup> )	Reference Period (minutes)
0.003-1023	170	180	-	Instantaneous*
0.1-10	-	1.6/ <i>f</i>	-	6**
1.29-10	193/ <i>f</i> 0.5	-	-	6**
10-20	61.4	0.163	10	6
20-48	129.8/ <i>f</i> 0.25	0.3444/ <i>f</i> 0.25	44.72/ <i>f</i> 0.5	6
48-100	49.33	0.1309	6.455	6
100-6000	15.60 <i>f</i> 0.25	0.04138 <i>f</i> 0.25	0.6455 <i>f</i> 0.5	6
6000-15000	137	0.364	50	6
15000-150000	137	0.364	50	616000/ <i>f</i> 1.2
150000-300000	0.354 <i>f</i> 0.5	9.40 x 10 <sup>-4</sup> <i>f</i> 0.5	3.33 x 10 <sup>-4</sup> <i>f</i>	616000/ <i>f</i> 1.2

**Note:** *f* is frequency in MHz. \*Based on nerve stimulation (NS). \*\* Based on specific absorption rate (SAR).

Friis Formula

Friis transmission formula:  $P_d = (P_{out} * G) / (4 * \pi * r^2)$

Where

$P_d$  = power density in  $mW/cm^2$

$P_{out}$  = output power to antenna in mW

$G$  = gain of antenna in linear scale

$\pi$  = 3.1416

$R$  = distance between observation point and center of the radiator in cm

$P_d$  is the limit of MPE,  $1 mW/cm^2$ . If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance  $r$  where the MPE limit is reached.

## 2.2. Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

### 2.3. Test Result of RF Exposure Evaluation

Product	LGA module		
Test Mode	Transmit Mode		
Test Condition	RF Exposure Evaluation		
Date of Test	2020/12/01	Test Site	SR12-H
Temperature(°C)	24.0	Humidity (%RH)	67.0

Band	Frequency (MHz) (Lowest Frequency)	Maximum conducted output power (per tune-up) (dBm)	Maximum conducted output power (per tune-up) (mW)	Power Density (mW/cm <sup>2</sup> )	Antenna Gain (dBi)	Antenna Gain (linear)	Duty cycle (%)	FCC MPE limit (mW/cm <sup>2</sup> )	FCC EIRP /ERP limit (W)	Evaluation distance for compliance with MPE limits (cm)	Antenna gain to meet FCC MPE limit (dBi)	Antenna gain to meet FCC EIRP/ERP limit (dBi)	Maximum antenna gain to meet all the limits (dBi)
LTE Band 4	1710.7	25.700	371.535	0.107	1.620	1.452	100	1.000	1.00	20	8.70	4.30	4.30
LTE Band 13	779.5	25.700	371.535	0.108	1.660	1.466	100	0.520	3.00	20	6.00	11.22	6.00