

RF Exposure Report

Report No.: SABEOP-WTW-P20100005

FCC ID: NKRM18QAG

Test Model: M18QAG

Received Date: July 10, 2020

Test Date: Oct. 20, 2020

Issued Date: Nov. 12, 2020

Applicant: Wistron NeWeb Corporation

Address: 20 Park Ave. II, Hsinchu Science Park, Hsinchu 308, Taiwan

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
Hsin Chu Laboratory

Lab Address: E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300,
Taiwan

Test Location: E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300,
Taiwan

**FCC Registration /
Designation Number:** 723255 / TW2022

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification.

Table of Contents

Release Control Record	3
1 Certificate of Conformity	4
2 RF Exposure	5
2.1 Limits for Maximum Permissible Exposure (MPE)	5
2.1 MPE Calculation Formula	5
2.2 Classification	5
2.3 Antenna Gain	6
2.4 Calculation Result	7

Release Control Record

Issue No.	Description	Date Issued
SABEOP-WTW-P20100005	Original release.	Nov. 12, 2020

1 Certificate of Conformity

Product: M2M DATA MODULE

Brand: Wistron NeWeb Corporation

Test Model: M18QAG

Sample Status: ENGINEERING SAMPLE

Applicant: Wistron NeWeb Corporation

Test Date: Oct. 20, 2020

Standards: FCC Part 2 (Section 2.1091)

KDB 447498 D01 General RF Exposure Guidance v06

IEEE C95.3 -2002

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

Prepared by : Vivian Huang , **Date:** Nov. 12, 2020
Vivian Huang / Specialist

Approved by : Clark Lin , **Date:** Nov. 12, 2020
Clark Lin / Technical Manager

2 RF Exposure

2.1 Limits for Maximum Permissible Exposure (MPE)

2 Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)
Limits For General Population / Uncontrolled Exposure				
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f ²)*	30
30-300	27.5	0.073	0.2	30
300-1500	f/1500	30
1500-100,000	1.0	30

f = Frequency in MHz ; *Plane-wave equivalent power density

2.1 MPE Calculation Formula

$$Pd = (Pout * G) / (4 * \pi * r^2)$$

where

Pd = power density in mW/cm²

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

2.2 Classification

The antenna of this product, under normal use condition, is at least 20 cm away from the body of the user. So, this device is classified as **Mobile Device**.

2.3 Antenna Gain

For GPS					
Antenna No.	Band	Freq. Range (MHz)	Antenna Net Gain (dBi)	Antenna Type	Connector Type
1	GPS	1602	2.24	Dipole	SMA
For WWAN					
Antenna No.	Band	Freq. Range (MHz)	Antenna Net Gain (dBi)	Antenna Type	Connector Type
2	LTE / WCDMA (2)	1850~1910	1.56	Dipole	SMA
	LTE / WCDMA (4)	1710~1755	1.62	Dipole	SMA
	LTE / WCDMA (5)	824~849	3.2	Dipole	SMA
	LTE / WCDMA (12)	699~716	1.49	Dipole	SMA
	LTE / WCDMA (14)	788~798	1.66	Dipole	SMA

*The above Antenna information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications, the laboratory shall not be held responsible.

2.4 Calculation Result

Operation Mode	Evaluation Frequency (MHz)	Max. Conducted Power		Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
		(mW)	(dBm)				
WCDMA B2	1850-1910	261.818	24.18	1.56	20	0.07460	1
WCDMA B5	824-849	305.492	24.85	3.20	20	0.12698	0.54933*
LTE B2	1850-1910	247.742	23.94	1.56	20	0.07059	1
LTE B4	1710-1755	242.661	23.85	1.62	20	0.07010	1
LTE B5	824-849	267.916	24.28	3.20	20	0.11136	0.54933*
LTE B12	699-716	255.27	24.07	1.49	20	0.07157	0.466*
LTE B14	788-798	240.436	23.81	1.66	20	0.07010	0.52533*

* Limit of Power Density = $f/1500$ (For frequency below 1500MHz)

Note:

- Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

--- END ---