





Turbo Mode (Channel 4) Peak data



Turbo Mode (Channel 4) Average data



Turbo Mode (Channel 5) Peak data**Turbo Mode (Channel 5) Average Data**

4.7 RF Exposure Measurement [Section 15.407(f)(4) & 1.1307(b)]

Refer to MPE Test Report

4.8 Frequency Stability [Section 15.407(g)]


4.8.1 Limits of Frequency Stability Measurement

The frequency tolerance of the carrier sing shall be maintained within +/- 0.02% of the operating frequency over the operation temperature range of EUT (0°C ~ 35°C), and variation in the primary supply voltage from 85% to 115% of the rated supply voltage (115V AC) at 20°C .

4.8.2 Test Procedure

1. The EUT was placed in the Temperature/Humidity Chamber and powered by a Voltage/Frequency Power converter.
2. Connect the RF output of EUT to Spectrum. Turn on the EUT.
3. Turn the EUT off and set the chamber to the highest temperature specified.
4. Allow sufficient time (approximately 30 min) for the chamber temperature to stabilize. Turn the EUT on and measure the operating frequency after 2, 5, 10 minutes.
5. Set the Voltage/Frequency Power Converter to 85% and 115% of supply voltage, then repeat step 2, 3, 4 respectively.
6. Repeat step 2 , 3, 4, 5 with the temperature of chamber set to the lowest temperature.
7. Repeat step 2 , 3, 4, 5 with the temperature of chamber set to 20°C .

4.8.3 Test Setup



4.8.4 Test Data

Test Engineer:Jerry
Chiou

Operating 5180(Mhz)
Frequency: **Limit: +/- 0.02%**

Temp.	Power Supply	2 minutes		5 minutes		10 minutes	
		(°C)	(V AC)	(MHz)	(%)	(MHz)	(%)
35	132	5180.0016	0.0000	5180.0048	0.0001	5180.0208	0.0004
	115	5180.0052	0.0001	5180.0122	0.0002	5180.0211	0.0004
	97	5180.0036	0.0001	5180.0122	0.0002	5180.0013	0.0000
0	132	5180.0052	0.0001	5180.0153	0.0003	5180.0094	0.0002
	115	5180.0111	0.0002	5180.0233	0.0004	5180.0199	0.0004
	97	5180.0307	0.0006	5180.0193	0.0004	5180.0202	0.0004
20	132	5180.0043	0.0001	5180.0127	0.0002	5180.0087	0.0002
	115	5180.0108	0.0002	5180.0172	0.0003	5180.0121	0.0002
	97	5179.9922	-0.0002	5180.0249	0.0005	5179.9940	-0.0001

5. TEST RESULTS (802.11b)

5.1 Powerline Conducted Emissions [Section 15.207]

5.1.1 EUT Configuration

The EUT was set up on the non-conductive table that is 1.0 by 1.5 meter, 80cm above ground. The wall of the shielded room was located 40cm to the rear of the EUT.

Power to the EUT was provided through the LISN. The impedance vs. frequency characteristic of the LISN is complied with the limit used.

Both lines (neutral and hot) were connected to the LISN in series at testing. A coaxial-type connector which provides one 50 ohms terminating impedance was provided for connecting the test instrument. The excess length of the power cord was folded back and forth at the center of the lead so as to form a bundle not exceeding 40cm in length.

Any changes made to the configuration, or modifications made to the EUT, during testing are noted in the following test record.

If the EUT is a Personal Computer or a peripheral of personal computer, and the personal computer has an auxiliary AC outlet which can be used for providing power to an external monitor, then all measurements will be made with the monitor power from first the computer-mounted AC outlet and then a floor-mounted AC outlet.

5.1.2 Test Procedure

The system was set up as described above, with the EMI diagnostic software running. The main power line conducted EMI tests were run on the hot and neutral conductors of the power cord and the results were recorded. The effect of varying the position of the interface cables has been investigated to find the configuration that produces maximum emission.

At the frequencies where the peak values of the emissions were higher than 6dB below the applicable limits, the emissions were also measured with the quasi-peak detectors. At the frequencies where the quasi-peak values of the emissions were higher than 6dB below the applicable average limits, the emissions were also measured with the average detectors.

The highest emissions were analyzed in details by operating the spectrum analyzer in fixed tuned mode to determine the nature of the emissions and to provide information which could be useful in reducing their amplitude.

5.1.3 EMI Receiver/Spectrum Analyzer Configuration (for the frequencies tested)

Frequency Range	150 KHz--30MHz
Detector Function	Quasi-Peak/Average
Bandwidth (RBW)	9KHz

5.1.4 Test Data:

Power Line Conducted Emissions (Hot) Channel 1, 6, 11


Operator: Jerry Chiou

Temperature (C): 27

05:58:50 PM, Sunday, August 21, 2005

Humidity (%): 58

Frequency	LISN Loss	Cable Loss	QP Corrct.	QP Limit	QP Margin
0.8593	0.18	0.07	31.88	47.96	-16.08
0.8904	0.18	0.07	36.08	47.96	-11.88
1.1792	0.28	0.07	30.52	47.96	-17.44
1.2275	0.28	0.07	34.91	47.96	-13.05
2.5970	0.20	0.10	30.90	47.96	-17.06
2.9273	0.20	0.11	30.57	47.96	-17.39
3.2258	0.20	0.12	31.59	47.96	-16.37
4.1975	0.20	0.14	29.48	47.96	-18.48
23.130	0.86	0.33	34.32	47.96	-13.64



Power Line Conducted Emissions (Neutral) Channel 1, 6, 11


Operator: Jerry Chiou

Temperature (C): 27

06:13:37 PM, Sunday, August 21, 2005

Humidity (%): 58

Frequency	LISN Loss	Cable Loss	QP Corrct.	QP Limit	QP Margin
0.5478	0.12	0.07	29.21	47.96	-18.75
1.1727	0.20	0.07	24.75	47.96	-23.21
1.2873	0.20	0.08	26.82	47.96	-21.14
1.7424	0.20	0.08	30.29	47.96	-17.67
2.3997	0.20	0.10	30.48	47.96	-17.48
2.7742	0.20	0.11	30.09	47.96	-17.87
3.2179	0.20	0.12	29.07	47.96	-18.89
3.7683	0.20	0.13	28.92	47.96	-19.04
23.130	0.43	0.33	33.39	47.96	-14.57



* NOTE: During the test, the EMI receiver was set to Max. Hold then switch the EUT Channel between 1 , 6, 11 to get the maximum reading of all these channels.

Margin = Amplitude + Insertion Loss- Limit

A margin of -8dB means that the emission is 8dB below the limit


5.2 Bandwidth for DSSS [Section 15.247 (a)(2)]

5.2.1 Test Procedure

The Transmitter output of EUT was connected to the spectrum analyzer. The 6 dB bandwidth of the fundamental frequency was measured. The setting of spectrum analyzer is as follows

Equipment mode	Spectrum analyzer
Detector function	Peak mode
RBW	100KHz
VBW	100KHz

5.2.2 Test Setup



5.2.3 Test Data:

6dB Bandwidth

Temperature ():25

Test Engineer:Jerry Chiou

Humidity (%):50

Channel	Frequency (MHz)	6dB Bandwidth (MHz)	Limit (MHz)	Pass/Fail
1	2412	12.60	0.5	Pass
6	2437	12.60	0.5	Pass
11	2462	12.60	0.5	Pass

Channel 1:



Channel 6:



Channel 11:




5.3 DSSS Maximum Peak Output Power [Section 15.247 (b)(1)]

5.3.1 Test Procedure

The Transmitter output of EUT was connected to the peak power analyzer.

5.3.2 Test Setup



5.3.3 Test Data

Maximum Peak Output Power

Temperature ():25

Test Engineer:Jerry Chiou

Humidity (%):50

Channel	Frequency (Mhz)	Analyzer Reading (dBm)	Cable Loss (dB)	Peak Power Output (mW)	Peak Power Output (dBm)	Limit (dBm)	Pass/Fail
1	2412	19.60	1.30	123.03	20.90	30	Pass
6	2437	19.82	1.30	129.42	21.12	30	Pass
11	2462	20.55	1.30	153.11	21.85	30	Pass

Note: Two RF output(Left & Right) have been test,the worse data shown above.

5.4 Radiated Emission Measurement [Section [15.247(c)(4)]]

5.4.1 EUT Configuration

The equipment under test was set up on the 10 meter chamber with measurement distance of 3 meters. The EUT was placed on a non-conductive table 80cm above ground.

Any changes made to the configuration, or modifications made to the EUT, during testing are noted in the following test record.

5.4.2 Test Procedure

The system was set up as described above, with the EMI diagnostic software running. We found the maximum readings by varying the height of antenna and then rotating the turntable. Both polarization of antenna, horizontal and vertical, are measured.

30M to 1GHz: The highest emissions between 30 MHz to 1000 MHz were also analyzed in details by operating the spectrum analyzer and/or EMI receiver in quasi-peak mode to determine the precise amplitude of the emissions. While doing so, the interconnecting cables and major parts of the system were moved around, the antenna height was varied between one and four meters, its polarization was varied between vertical and horizontal, and the turntable was slowly rotated, to maximize the emission.

1GHz – 25GHz: The highest emissions were also analyzed in details by operating the spectrum analyzer and/or EMI receiver in peak mode to determine the precise amplitude of the emission. While doing so, the interconnecting cables and major parts of the system were moved around, the antenna height was varied between one and four meters, its polarization was varied between vertical and horizontal, and the turntable was slowly rotated, to maximize the emission. During test the EMI receiver and spectrum was setup according to *EMI Receiver/Spectrum Analyzer Configuration*.

For the test of 2nd to 10th harmonics frequencies , the equipment setup was also refer to *EMI Receiver/Spectrum Analyzer Configuration*. The frequencies were tested using Peak mode first, if the test data is higher than the emissions limit, an additional measurement using Average mode will be performed and the average reading will be compared to the limit and record in test report.

5.4.3 EMI Receiver/Spectrum Analyzer Configuration (for the frequencies tested)

Frequency Range Tested: 30MHz~1000MHz

Detector Function: Quasi-Peak Mode

Resolution Bandwidth (RBW): 120KHz

Video Bandwidth (VBW) 1MHz

Frequency Range Tested: 1GHz – 25 GHz

Detector Function: Peak Mode

Resolution Bandwidth (RBW): 1MHz

Video Bandwidth (VBW) 3MHz

Frequency Range Tested: 1GHz – 25 GHz

Detector Function: Average Mode

Resolution Bandwidth (RBW): 1MHz

Video Bandwidth (VBW) 10 Hz

5.4.4 Test Data (30MHz – 1GHz):

30M – 1GHz Open Field Radiated Emissions (Horizontal) Channel 1, 6, 11

05:53:04 PM, Saturday, August 20, 2005

Operator: Jerry Chiou
Temperature (C): 23
Humidity (%): 54

Frequency	Rx Amp.	Ant Fact	CableLoss	PreAmpGain	Corrct. Emi.	Limit	Margin	Ant. Pos.	Table Pos.
MHz	(dBuV)	(dB/m)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	(cm)	(deg)
41.64	17.97	11.38	1.13	0.00	30.48	40.00	-9.52	103.00	72.00
44.55	19.03	9.92	1.13	0.00	30.09	40.00	-9.91	103.00	138.00
106.63	19.41	11.10	1.99	0.00	32.49	43.50	-11.01	103.00	89.00
329.73	15.97	16.08	3.92	0.00	35.97	46.00	-10.03	196.00	58.00
358.83	14.60	16.15	4.17	0.00	34.92	46.00	-11.08	196.00	173.00
366.59	13.60	16.10	4.22	0.00	33.92	46.00	-12.08	196.00	173.00
374.35	21.75	16.05	4.27	0.00	42.07	46.00	-3.93	103.00	23.00
379.2	12.86	16.02	4.30	0.00	33.18	46.00	-12.82	196.00	8.00
381.14	12.87	16.01	4.31	0.00	33.20	46.00	-12.80	196.00	173.00
499.48	11.72	17.39	5.28	0.00	34.39	46.00	-11.61	196.00	337.00

30M – 1GHz Open Field Radiated Emissions (Vertical) Channel 1, 6, 11

05:53:04 PM, Saturday, August 20, 2005

Operator: Jerry Chiou
Temperature (C): 23
Humidity (%): 54

Frequency	Rx Amp.	Ant Fact	CableLoss	PreAmpGain	Corrct. Emi.	Limit	Margin	Ant. Pos.	Table Pos.
MHz	(dBuV)	(dB/m)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	(cm)	(deg)
41.64	17.65	11.38	1.13	0.00	30.16	40.00	-9.84	103.00	72.00
106.63	22.53	11.10	1.99	0.00	35.62	43.50	-7.88	103.00	89.00
109.54	18.44	11.44	2.03	0.00	31.92	43.50	-11.58	103.00	334.00
125.06	19.60	11.45	2.11	0.00	33.16	43.50	-10.34	103.00	220.00
278.32	15.31	13.57	3.35	0.00	32.23	46.00	-13.77	196.00	353.00
329.73	14.16	16.08	3.92	0.00	34.17	46.00	-11.83	196.00	58.00
374.35	15.52	16.05	4.27	0.00	35.84	46.00	-10.16	103.00	23.00
499.48	11.76	17.39	5.28	0.00	34.43	46.00	-11.57	196.00	337.00
549.92	9.64	18.60	5.53	0.00	33.77	46.00	-12.23	103.00	89.00
624.61	11.98	18.85	6.12	0.00	36.94	46.00	-9.06	103.00	285.00

NOTE:

- During the Pre-test, the EUT has been tested for Channel 1 , 6, 11 transmit from Main and Aux antenna respectively to get all the critical emission frequencies. In the final test all the critical emission frequencies has been tested and the test data are listed above.
- Margin = Corrected Amplitude – Limit
Corrected Amplitude = Radiated Amplitude + Antenna Correction Factor + Cable Loss - Pre-Amplifier Gain
A margin of -8dB means that the emission is 8dB below the limit

All frequencies from 30MHz to 1GHz have been tested

5.4.5 Test Data (1GHz – 25 GHz) .

1GHz~ 25 GHz (Horizontal), Channel 1: 2412 MHz

Operator: Jerry Chiou

RBW: 1MHz

Humidity (%): 41

Temperature (C): 27

Frequency	Rx_R.	Ant_F.	Cab_L.	PreAmpl	Emission	Limit	Margin	A.Tower	T.Table
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	cm	deg
1159.84	51.36 pk	25.24	2.19	34.02	44.77 pk	54.00 av	-9.23	102	101
1194.81	52.10 pk	25.4	2.19	34.04	45.66 pk	54.00 av	-8.34	102	99
1202.3	51.94 pk	25.43	2.19	34.04	45.52 pk	54.00 av	-8.48	102	98
1209.79	51.91 pk	25.47	2.2	34.04	45.52 pk	54.00 av	-8.48	102	98
1546.95	54.55 pk	27.19	2.26	34.29	49.71 pk	54.00 av	-4.29	101	74
1794.21	50.18 pk	29.27	2.45	34.78	47.12 pk	54.00 av	-6.88	100	57
1874.13	47.06 pk	29.94	2.51	34.93	44.58 pk	54.00 av	-9.42	100	52
3150.35	46.88 pk	31.22	1.53	35.08	44.55 pk	54.00 av	-9.45	103	318
3287.71	47.26 pk	31.33	1.6	35.38	44.81 pk	54.00 av	-9.19	103	283
4824.16	53.97 pk	34.93	2.12	37.72	53.31 pk	74.00 pk	-20.69	100	291
4824.16	45.96 av	34.93	2.12	37.72	45.29 av	54.00 av	-8.71	100	291
7235.74	55.45 pk	39.48	2.69	36.83	60.78 pk	74.00 pk	-13.22	100	39
7235.74	42.09 av	39.48	2.69	36.83	47.43 av	54.00 av	-6.57	100	39
9648.05	45.91 pk	40.57	3.25	34.33	55.40 pk	74.00 pk	-18.6	100	201
9648.05	30.43 av	40.57	3.25	34.33	39.92 av	54.00 av	-14.08	100	201

1GHz~ 25 GHz (Vertical), Channel 1: 2412 MHz

Operator: Jerry Chiou

RBW: 1MHz

Humidity (%): 41

Temperature (C): 27

Frequency	Rx_R.	Ant_F.	Cab_L.	PreAmpl	Emission	Limit	Margin	A.Tower	T.Table
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	cm	deg
1012.49	51.18 pk	24.56	2.17	33.94	43.97 pk	54.00 av	-10.03	102	111
1227.27	53.91 pk	25.55	2.2	34.05	47.60 pk	54.00 av	-6.4	102	96
1252.25	51.62 pk	25.66	2.2	34.07	45.41 pk	54.00 av	-8.59	101	95
1264.74	52.13 pk	25.72	2.2	34.07	45.97 pk	54.00 av	-8.03	101	94
1794.21	49.24 pk	29.27	2.45	34.78	46.18 pk	54.00 av	-7.82	100	57
1881.62	48.82 pk	30.01	2.51	34.95	46.39 pk	54.00 av	-7.61	100	51
1984.02	46.06 pk	30.87	2.59	35.15	44.37 pk	54.00 av	-9.63	100	44
3297.7	46.63 pk	31.34	1.6	35.4	44.18 pk	54.00 av	-9.82	103	280
3357.64	46.89 pk	31.39	1.64	35.53	44.38 pk	54.00 av	-9.62	103	265
4823.88	62.95 pk	34.93	2.12	37.72	62.29 pk	74.00 pk	-11.71	100	202
4824.01	51.09 av	34.93	2.12	37.72	50.42 av	54.00 av	-3.58	100	202
7235.76	59.83 pk	39.48	2.69	36.83	65.16 pk	74.00 pk	-8.84	100	173
7235.86	45.02 av	39.48	2.68	36.83	50.35 av	54.00 av	-3.65	100	173
9647.94	47.74 pk	40.57	3.25	34.33	57.23 pk	74.00 pk	-16.77	100	98
9647.94	35.13 av	40.57	3.25	34.33	44.62 av	54.00 av	-9.38	100	98

Note:

- According to the standards used, Where limits are specified by agencies for both average and peak (or quasi-peak) detection , if the peak (or quasi-peak) measured value complies with the average limit , it is unnecessary to perform an average measurement.
- “ * ”: Fundamental Frequency
- “**”: Not in the restricted band, Limit level=Fundamental Emission-20dB
- “ pk”: peak mode
- “av”: average mode
- “--”: No meter reading data due to the emission level is smaller than spectrum noise level.
- The Spectrum noise level+Correction Factor < Limit - 6 dB
- Margin=Corrected Amplitude – Limit
- Corrected Amplitude=Radiated Amplitude+Antenna Correction Factor+Cable Loss-Pre-Amplifier Gain
- A margin of -8dB means that the emission is 8dB below the limit.

All frequencies from 1GHz to 25 GHz have been tested.

1GHz~ 25 GHz (Horizontal) , Channel 6 : 2437 MHz

Operator: Jerry Chiou

RBW: 1MHz

Humidity (%): 41

Temperature (C): 27

Frequency	Rx_R.	Ant_F.	Cab_L.	PreAmp	Emission	Limit	Margin	A.Tower	T.Table
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	cm	deg
1204.8	50.68 pk	25.44	2.19	34.04	44.28 pk	54.00 av	-9.72	102	98
1482.02	50.00 pk	26.72	2.23	34.19	44.75 pk	54.00 av	-9.25	101	79
1497	49.84 pk	26.79	2.23	34.2	44.66 pk	54.00 av	-9.34	101	78
1551.95	49.58 pk	27.24	2.27	34.3	44.78 pk	54.00 av	-9.22	101	74
1624.38	48.54 pk	27.84	2.32	34.44	44.26 pk	54.00 av	-9.74	101	69
1796.7	50.99 pk	29.29	2.45	34.78	47.95 pk	54.00 av	-6.05	100	57
3142.86	46.74 pk	31.21	1.52	35.06	44.42 pk	54.00 av	-9.58	103	320
3275.22	46.45 pk	31.32	1.59	35.35	44.01 pk	54.00 av	-9.99	103	286
3420.08	46.91 pk	31.44	1.67	35.67	44.35 pk	54.00 av	-9.65	103	249
4873.9	52.93 pk	35.12	2.14	37.77	52.42 pk	54.00 av	-1.58	100	74
7310.78	59.66 pk	39.6	2.55	36.7	65.11 pk	74.00 pk	-8.89	100	41
7310.78	44.77 av	39.6	2.55	36.7	51.22 av	54.00 av	-3.78	100	41
9747.82	48.83 pk	40.35	3.3	34.37	58.11 pk	74.00 pk	-15.89	100	98
9747.82	34.81 av	40.35	3.3	34.37	44.09 av	54.00 av	-9.91	100	98

1GHz~ 25 GHz (Vertical), Channel 6 : 2437 MHz

Operator: Jerry Chiou

RBW: 1MHz

Humidity (%): 41

Temperature (C): 27

Frequency	Rx_R.	Ant_F.	Cab_L.	PreAmp	Emission	Limit	Margin	A.Tower	T.Table
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	cm	deg
1012.49	54.91 pk	24.56	2.17	33.94	47.71 pk	54.00 av	-6.29	102	111
1229.77	51.08 pk	25.56	2.2	34.05	44.78 pk	54.00 av	-9.22	102	96
1234.77	51.09 pk	25.58	2.2	34.06	44.81 pk	54.00 av	-9.19	102	96
1239.76	50.77 pk	25.6	2.2	34.06	44.51 pk	54.00 av	-9.49	102	95
4873.84	58.03 pk	35.12	2.14	37.77	57.52 pk	74.00 pk	-16.48	100	244
4874.06	47.61 av	35.12	2.14	37.77	47.10 av	54.00 av	-6.9	100	244
7310.8	60.47 pk	39.6	2.55	36.7	65.92 pk	74.00 pk	-8.08	100	121
7310.86	44.83 av	39.6	2.55	36.7	50.28 av	54.00 av	-3.72	100	121
9747.94	50.64 pk	40.35	3.3	34.37	59.92 pk	74.00 pk	-14.08	100	87
9747.94	40.86 av	40.35	3.3	34.37	50.14 av	54.00 av	-3.86	100	87

Note:

- According to the standards used, Where limits are specified by agencies for both average and peak (or quasi-peak) detection , if the peak (or quasi-peak) measured value complies with the average limit , it is unnecessary to perform an average measurement.
- “*”: Fundamental Frequency
- “**”: Not in the restricted band, Limit level=Fundamental Emission-20dB
- “pk”: peak mode
- “av”: average mode
- “---”: No meter reading data due to the emission level is smaller than spectrum noise level.
- The Spectrum noise level+Correction Factor < Limit - 6 dB
- Margin=Corrected Amplitude – Limit
- Corrected Amplitude=Radiated Amplitude+Antenna Correction Factor+Cable Loss+Pre-Amplifier Gain
- A margin of -8dB means that the emission is 8dB below the limit.

All frequencies from 1GHz to 25 GHz have been tested.

1GHz~ 25 GHz (Horizontal), Channel 11: 2462 MHz

Operator: Jerry Chiou

RBW: 1MHz

Humidity (%): 41

Temperature (C): 27

Frequency	Rx_R.	Ant_F.	Cab_L.	PreAmpl	Emission	Limit	Margin	A.Tower	T.Table
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	cm	deg
1162.34	52.20 pk	25.25	2.19	34.02	45.61pk	54.00 av	-8.39	102	101
1457.04	50.34 pk	26.6	2.22	34.18	44.99pk	54.00 av	-9.01	101	80
1469.53	51.44 pk	26.66	2.23	34.18	46.14pk	54.00 av	-7.86	101	80
1489.51	50.08 pk	26.75	2.23	34.19	44.86pk	54.00 av	-9.14	101	78
1794.21	49.91 pk	29.27	2.45	34.78	46.85pk	54.00 av	-7.15	100	57
3097.9	46.44 pk	31.18	1.5	34.96	44.15pk	54.00 av	-9.85	103	332
4924.09	54.84 pk	35.31	2.15	37.83	54.48pk	74.00 pk	-19.52	100	174
4924.09	43.58 av	35.31	2.15	37.83	43.21av	54.00 av	-10.79	100	174
7385.88	53.69 pk	39.72	2.42	36.56	59.27pk	74.00 pk	-14.73	100	42
7385.88	45.15 av	39.72	2.42	36.56	50.73av	54.00 av	-3.27	100	42
9848.02	47.60 pk	40.13	3.35	34.41	56.68pk	74.00 pk	-17.32	100	292
9848.02	38.39 av	40.13	3.35	34.41	47.46av	54.00 av	-6.54	100	292

1GHz~ 25 GHz (Vertical), Channel 11 : 2462 MHz

Operator: Jerry Chiou

RBW: 1MHz

Humidity (%): 41

Temperature (C): 27

Frequency	Rx_R.	Ant_F.	Cab_L.	PreAmpl	Emission	Limit	Margin	A.Tower	T.Table
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	cm	deg
1224.78	52.19 pk	25.53	2.2	34.05	45.87 pk	54.00 av	-8.13	102	96
1247.25	52.84 pk	25.64	2.2	34.06	46.61 pk	54.00 av	-7.39	102	95
1791.71	47.70 pk	29.25	2.45	34.77	44.62 pk	54.00 av	-9.38	100	57
3015.48	46.73 pk	31.11	1.46	34.78	44.52 pk	54.00 av	-9.48	103	353
3065.43	47.11 pk	31.15	1.48	34.89	44.85 pk	54.00 av	-9.15	103	340
3125.37	46.35 pk	31.2	1.52	35.02	44.04 pk	54.00 av	-9.96	103	325
3295.2	46.57 pk	31.34	1.6	35.39	44.12 pk	54.00 av	-9.88	103	281
4923.94	58.27 pk	35.31	2.15	37.83	57.90 pk	74.00 pk	-16.1	100	137
4923.94	47.20 av	35.31	2.15	37.83	46.83 av	54.00 av	-7.17	100	137
7385.77	59.52 pk	39.72	2.42	36.56	65.10 pk	74.00 pk	-8.9	100	132
7385.77	44.96 av	39.72	2.42	36.56	50.54 av	54.00 av	-3.46	100	132
9847.8	53.15 pk	40.13	3.35	34.41	62.23 pk	74.00 pk	-11.77	100	89
9847.8	43.05 av	40.13	3.35	34.41	50.12 av	54.00 av	-3.88	100	89

Note:

- According to the standards used, Where limits are specified by agencies for both average and peak (or quasi-peak) detection , if the peak (or quasi-peak) measured value complies with the average limit , it is unnecessary to perform an average measurement.
- “*”: Fundamental Frequency
- “**”: Not in the restricted band, Limit level=Fundamental Emission-20dB
- “pk”: peak mode
- “av”: average mode
- “---”: No meter reading data due to the emission level is smaller than spectrum noise level.
- The Spectrum noise level+Correction Factor < Limit - 6 dB
- Margin=Corrected Amplitude – Limit
- Corrected Amplitude=Radiated Amplitude+Antenna Correction Factor+Cable Loss+Pre-Amplifier Gain
- A margin of -8dB means that the emission is 8dB below the limit.


All frequencies from 1GHz to 25 GHz have been tested.

5.5 Band Edge Measurement

5.5.1 Test Procedure (Conducted)

1. The transmitter output of EUT was connected to the spectrum analyzer.
Equipment mode: Spectrum analyzer
Detector function: Peak mode
SPAN: 100MHz
RBW: 100KHz
VBW: 100KHz
Center frequency: 2.4GHz, 2.4835GHz.
2. Using Peak Search to read the peak power of Carrier frequencies after Maximum Hold function is completed
3. Find the next peak frequency outside the operation frequency band

5.5.2 Test Setup (Conducted)



5.5.3 Test Data:

Table: Band Edge measurement (Conducted)



Temperature ():25

Test Engineer:Jerry Chiou

Humidity (%):50

Channel	Frequency (MHz)	Spectrum Reading (dBuV)	Carrier - Outsideband Limit: >20dB (dB)	Pass/Fail
1	2411.4	115.07	---	---
Outside band	2396.9	76.11	38.96	Pass
11	2461.4	116.00	---	---
Outside band	2476.9	78.79	37.21	Pass

Note: Two RF output(Left & Right) have been test,the worse data shown above.

Band Edge Conducted measurement**Band Edge Conducted Measurement**

5.5.4 Test Procedure (Radiated)

1. Antenna and Turntable test procedure same as Radiated Emission Measurement.
Equipment mode: Spectrum analyzer
Detector function: Peak mode
SPAN: 100MHz
RBW: 1MHz
VBW: 3MHz
Center frequency: 2.395GHz, 2.48GHz.
2. Using Peak Search to read the peak power of Carrier frequencies after Maximum Hold function is completed.
3. Find the next peak frequency outside the operation frequency band
4. For peak frequency emission level measurement in Restricted Band
Change RBW: 1MHz
VBW: 10Hz
Span: 100MHz.
5. Get the spectrum reading after Maximum Hold function is completed.

5.5.5 Test Setup (Radiated)

Same as *Radiated Emission Measurement*

5.5.6 Test Data

Table Band Edge measurement (Radiated)

Test Engineer:Jerry Chiou

Temperature ():27


Humidity (%):45

Description	Frequency (MHz)	Spectrum Reading (dBuV)	Correction Factor (dB/m)	Emission Level (dBuV/m)	dBc (Limit: > 20dBc)	Limit (dBuV/m)	Equip. Setup VBW	Pass or Fail
Channel_1 (average mode)	2410.8	68.44	35.48	103.92	---	---	10Hz	---
Channel_1 (peak mode)	2409.4	72.80	35.48	108.28	---	---	3MHz	---
Outside band (peak mode)	2397.3	35.96	35.48	71.44	36.84	---	3MHz	Pass
<hr/>								
Channel_11 (average mode)	2463.8	68.64	35.50	104.14	---	---	10Hz	---
Channel_11 (peak mode)	2461.7	71.93	35.50	107.43	---	---	3MHz	---
Outside band (peak mode)	2475.4	37.94	35.51	73.45	33.98	---	3MHz	Pass
<hr/>								
Channel_1 Restricted band (peak mode)	2385.7	26.11	35.47	61.58	---	74	3MHz	Pass
Restricted band (average mode)	2385.8	14.19	35.47	49.66	---	54	10Hz	Pass
<hr/>								
Channel_11 Restricted band (peak mode)	2485.1	32.40	35.51	67.91	---	74	3MHz	Pass
Restricted band (average mode)	2487.7	13.38	35.51	48.89	---	54	10Hz	Pass


Note:

- The Spectrum plot of emission level measurement in Restricted band is attached.
- Emission Level=Spectrum Reading+Correction Factor
- Correction Factor=Antenna Factor+cable loss–amplifier gain
- Both Horizontal and Vertical polarization have been tested and the worst data is listed above.


Band Edge measurement for radiated emission in Restricted Band(Radiated) Peak Mode (Channel 1)




Band Edge measurement for radiated emission in Restricted Band(Radiated) Average Mode (Channel 1)



Band Edge measurement for radiated emission in Restricted Band(Radiated) Peak Mode (Channel 11)



Band Edge measurement for radiated emission in Restricted Band(Radiated) Average Mode (Channel 11)



5.6 RF Exposure Measurement [Section 15.247(b)(4) & 1.1307(b)]

See MPE report

5.7 DSSS Peak Power Spectral Density [Section 15.247(d)]

5.7.1 Test Procedure

1. The Transmitter output of EUT was connected to the spectrum analyzer.
Equipment mode: Spectrum analyzer
Detector function: Peak mode
SPAN:1.5MHz
RBW: 3KHz
VBW: 30KHz
Center frequency: fundamental frequency tested.
Sweep time= 500 sec.
2. Using Peak Search to read the peak power after Maximum Hold function is completed.

5.7.2 Test Setup



5.7.3 Test Data

Maximum Peak Output Power Density

Temperature ():25


Test Engineer:Jerry Chiou

Humidity (%):50


Channel	Frequency (MHz)	Spectrum Reading (dBm/3KHz)	Cable Loss (dB)	Peak Power Output (dBm/3KHz)	Limit (dBm/3KHz)	Pass/Fail
1	2412	-3.38	1.30	-2.08	8	Pass
6	2437	-3.25	1.30	-1.95	8	Pass
11	2462	-3.10	1.30	-1.80	8	Pass

Note: Two RF output(Left & Right) have been test,the worse data shown above.


Channel 1



Channel 6



Channel 11



International Standards Laboratory

HC LAB:NVLAP:200234-0;VCCI: R-341,C-354;NEMKO:ELA 113a,113c;BSMI:SL2-IN-E-0037;SL2-R1-E-0037;CNLA:1178
LT LAB:NVLAP:200234-0;VCCI: R-1435,C-1440;NEMKO:ELA 113b,113d;BSMI:SL2-IN-E-0013;CNLA:0997

Report Number: 05LR021FC

6. TEST RESULTS (802.11g)

6.1 Powerline Conducted Emissions [Section 15.207]

6.1.1 EUT Configuration

The EUT was set up on the non-conductive table that is 1.0 by 1.5 meter, 80cm above ground. The wall of the shielded room was located 40cm to the rear of the EUT.

Power to the EUT was provided through the LISN. The impedance vs. frequency characteristic of the LISN is complied with the limit used.

Both lines (neutral and hot) were connected to the LISN in series at testing. A coaxial-type connector which provides one 50 ohms terminating impedance was provided for connecting the test instrument. The excess length of the power cord was folded back and forth at the center of the lead so as to form a bundle not exceeding 40cm in length.

Any changes made to the configuration, or modifications made to the EUT, during testing are noted in the following test record.

If the EUT is a Personal Computer or a peripheral of personal computer, and the personal computer has an auxiliary AC outlet which can be used for providing power to an external monitor, then all measurements will be made with the monitor power from first the computer-mounted AC outlet and then a floor-mounted AC outlet.

6.1.2 Test Procedure

The system was set up as described above, with the EMI diagnostic software running. The main power line conducted EMI tests were run on the hot and neutral conductors of the power cord and the results were recorded. The effect of varying the position of the interface cables has been investigated to find the configuration that produces maximum emission.

At the frequencies where the peak values of the emissions were higher than 6dB below the applicable limits, the emissions were also measured with the quasi-peak detectors. At the frequencies where the quasi-peak values of the emissions were higher than 6dB below the applicable average limits, the emissions were also measured with the average detectors.

The highest emissions were analyzed in details by operating the spectrum analyzer in fixed tuned mode to determine the nature of the emissions and to provide information which could be useful in reducing their amplitude.

6.1.3 EMI Receiver/Spectrum Analyzer Configuration (for the frequencies tested)

Frequency Range	150 KHz--30MHz
Detector Function	Quasi-Peak/Average
Bandwidth (RBW)	9KHz

6.1.4 Test Data:

Power Line Conducted Emissions (Hot) Channel 1, 6, 11


Operator: Jerry Chiou

Temperature (C): 27

05:50:01 PM, Sunday, August 21, 2005

Humidity (%): 58

Frequency	LISN Loss	Cable Loss	QP Corrct.	QP Limit	QP Margin
0.5634	0.13	0.07	34.66	47.96	-13.30
0.8901	0.18	0.07	34.66	47.96	-13.30
1.1967	0.28	0.07	34.13	47.96	-13.83
1.2039	0.28	0.07	34.84	47.96	-13.12
2.1934	0.20	0.09	32.11	47.96	-15.85
2.8842	0.20	0.11	30.35	47.96	-17.61
3.2462	0.20	0.12	27.96	47.96	-20.00
3.6762	0.20	0.13	28.52	47.96	-19.44
23.129	0.86	0.33	34.50	47.96	-13.46



Power Line Conducted Emissions (Neutral) Channel 1, 6, 11


Operator: Jerry Chiou

Temperature (C): 27

05:33:27 PM, Sunday, August 21, 2005

Humidity (%): 58

Frequency	LISN Loss	Cable Loss	QP Corrct.	QP Limit	QP Margin
0.5372	0.12	0.07	28.86	47.96	-19.10
1.2461	0.20	0.07	30.73	47.96	-17.23
1.3822	0.20	0.08	29.47	47.96	-18.49
1.7317	0.20	0.08	26.81	47.96	-21.15
2.3714	0.20	0.10	30.64	47.96	-17.32
3.5392	0.20	0.13	27.90	47.96	-20.06
3.8635	0.20	0.14	28.80	47.96	-19.16
4.1847	0.20	0.14	29.75	47.96	-18.21
23.129	0.43	0.33	33.43	47.96	-14.53



* NOTE: During the test, the EMI receiver was set to Max. Hold then switch the EUT Channel between 1 , 6, 11 to get the maximum reading of all these channels.

Margin = Amplitude + Insertion Loss- Limit

A margin of -8dB means that the emission is 8dB below the limit

6.2 Bandwidth for DSSS [Section 15.247 (a)(2)]

6.2.1 Test Procedure

The Transmitter output of EUT was connected to the spectrum analyzer. The 6 dB bandwidth of the fundamental frequency was measured. The setting of spectrum analyzer is as follows

Equipment mode	Spectrum analyzer
Detector function	Peak mode
RBW	100KHz
VBW	100KHz

6.2.2 Test Setup



6.2.3 Test Data:

6dB Bandwidth


Temperature ():25

Test Engineer:Jerry Chiou


Humidity (%):50

Channel	Frequency (MHz)	6dB Bandwidth (MHz)	Limit (MHz)	Pass/Fail
1	2412	16.56	0.5	Pass
6	2437	16.56	0.5	Pass
11	2462	16.56	0.5	Pass


Channel 1:



Channel 6:



Channel 11:



6.3 DSSS Maximum Peak Output Power [Section 15.247 (b)(1)]

6.3.1 Test Procedure

The Transmitter output of EUT was connected to the peak power analyzer.

6.3.2 Test Setup



6.3.3 Test Data

Maximum Peak Output Power

Temperature ():25

Test Engineer:Jerry Chiou

Humidity (%):50

Channel	Frequency (Mhz)	Analyzer Reading (dBm)	Cable Loss (dB)	Peak Power Output (mW)	Peak Power Output (dBm)	Limit (dBm)	Pass/Fail
1	2412	18.90	1.30	104.71	20.20	30	Pass
6	2437	18.66	1.30	99.08	19.96	30	Pass
11	2462	18.79	1.30	102.09	20.09	30	Pass

Note: Two RF output(Left & Right) have been test, the worse data shown above.

6.4 Radiated Emission Measurement [Section [15.247(c)(4)]]

6.4.1 EUT Configuration

The equipment under test was set up on the 10 meter chamber with measurement distance of 3 meters. The EUT was placed on a non-conductive table 80cm above ground.

Any changes made to the configuration, or modifications made to the EUT, during testing are noted in the following test record.

6.4.2 Test Procedure

The system was set up as described above, with the EMI diagnostic software running. We found the maximum readings by varying the height of antenna and then rotating the turntable. Both polarization of antenna, horizontal and vertical, are measured.

30M to 1GHz: The highest emissions between 30 MHz to 1000 MHz were also analyzed in details by operating the spectrum analyzer and/or EMI receiver in quasi-peak mode to determine the precise amplitude of the emissions. While doing so, the interconnecting cables and major parts of the system were moved around, the antenna height was varied between one and four meters, its polarization was varied between vertical and horizontal, and the turntable was slowly rotated, to maximize the emission.

1GHz – 25GHz: The highest emissions were also analyzed in details by operating the spectrum analyzer and/or EMI receiver in peak mode to determine the precise amplitude of the emission. While doing so, the interconnecting cables and major parts of the system were moved around, the antenna height was varied between one and four meters, its polarization was varied between vertical and horizontal, and the turntable was slowly rotated, to maximize the emission. During test the EMI receiver and spectrum was setup according to *EMI Receiver/Spectrum Analyzer Configuration*.

For the test of 2nd to 10th harmonics frequencies , the equipment setup was also refer to *EMI Receiver/Spectrum Analyzer Configuration*. The frequencies were tested using Peak mode first, if the test data is higher than the emissions limit, an additional measurement using Average mode will be performed and the average reading will be compared to the limit and record in test report.

6.4.3 EMI Receiver/Spectrum Analyzer Configuration (for the frequencies tested)

Frequency Range Tested: 30MHz~1000MHz

Detector Function: Quasi-Peak Mode

Resolution Bandwidth (RBW): 120KHz

Video Bandwidth (VBW) 1MHz

Frequency Range Tested: 1GHz – 25 GHz

Detector Function: Peak Mode

Resolution Bandwidth (RBW): 1MHz

Video Bandwidth (VBW) 3MHz

Frequency Range Tested: 1GHz – 25 GHz

Detector Function: Average Mode

Resolution Bandwidth (RBW): 1MHz

Video Bandwidth (VBW) 10 Hz

6.4.4 Test Data (30MHz – 1GHz):**30M – 1GHz Open Field Radiated Emissions (Horizontal) Channel 1, 6, 11**

Operator: Jerry Chiou
 Temperature (C): 23
 05:45:11 PM, Saturday, August 20, 2005
 Humidity (%): 54

Frequency	Rx Amp.	Ant Fact	CableLoss	PreAmpGain	Corrct. Emi.	Limit	Margin	Ant. Pos.	Table Pos.
MHz	(dBuV)	(dB/m)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	(cm)	(deg)
106.63	20.02	11.10	1.99	0.00	33.11	43.50	-10.39	103.00	138.00
271.53	20.88	13.43	3.25	0.00	37.57	46.00	-8.43	196.00	353.00
279.29	17.84	13.59	3.37	0.00	34.80	46.00	-11.20	196.00	353.00
284.14	17.41	13.93	3.40	0.00	34.75	46.00	-11.25	196.00	353.00
329.73	15.67	16.08	3.92	0.00	35.67	46.00	-10.33	196.00	57.00
351.07	13.34	16.19	4.12	0.00	33.65	46.00	-12.35	196.00	287.00
366.59	12.05	16.10	4.22	0.00	32.36	46.00	-13.64	103.00	6.00
374.35	21.26	16.05	4.27	0.00	41.58	46.00	-4.42	103.00	23.00
499.48	12.73	17.39	5.28	0.00	35.41	46.00	-10.59	196.00	337.00
624.61	7.58	18.85	6.12	0.00	32.54	46.00	-13.46	103.00	303.00

30M – 1GHz Open Field Radiated Emissions (Vertical) Channel 1, 6, 11

Operator: Jerry Chiou
 Temperature (C): 23
 05:45:11 PM, Saturday, August 20, 2005
 Humidity (%): 54

Frequency	Rx Amp.	Ant Fact	CableLoss	PreAmpGain	Corrct. Emi.	Limit	Margin	Ant. Pos.	Table Pos.
MHz	(dBuV)	(dB/m)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	(cm)	(deg)
41.64	18.52	11.38	1.13	0.00	31.03	40.00	-8.97	103.00	351.00
109.54	18.80	11.44	2.03	0.00	32.28	43.50	-11.22	103.00	303.00
125.06	17.89	11.45	2.11	0.00	31.45	43.50	-12.05	103.00	204.00
278.32	15.49	13.57	3.35	0.00	32.41	46.00	-13.59	196.00	353.00
329.73	14.13	16.08	3.92	0.00	34.13	46.00	-11.87	196.00	57.00
374.35	17.16	16.05	4.27	0.00	37.48	46.00	-8.52	103.00	23.00
499.48	10.40	17.39	5.28	0.00	33.07	46.00	-12.93	196.00	337.00
549.92	8.77	18.60	5.53	0.00	32.89	46.00	-13.11	103.00	122.00
624.61	10.13	18.85	6.12	0.00	35.10	46.00	-10.90	103.00	303.00
769.14	3.44	20.16	7.09	0.00	30.69	46.00	-15.31	103.00	303.00

NOTE:

- During the Pre-test, the EUT has been tested for Channel 1 , 6, 11 transmit from Main and Aux antenna respectively to get all the critical emission frequencies. In the final test all the critical emission frequencies has been tested and the test data are listed above.
- Margin = Corrected Amplitude – Limit
 Corrected Amplitude = Radiated Amplitude + Antenna Correction Factor + Cable Loss - Pre-Amplifier Gain

A margin of -8dB means that the emission is 8dB below the limit

All frequencies from 30MHz to 1GHz have been tested

6.4.5 Test Data (1GHz – 25 GHz) .

1GHz~ 25 GHz (Horizontal), Channel 1: 2412 MHz

Operator: Jerry Chiou

RBW: 1MHz

Humidity (%): 41

Temperature (C): 27

Frequency	Rx_R.	Ant_F.	Cab_L.	PreAmp	Emission	Limit	Margin	A.Tower	T.Table
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	cm	deg
1012.49	54.20 pk	24.56	2.17	33.94	46.99 pk	54.00 av	-7.01	102	111
1167.33	51.86 pk	25.27	2.19	34.02	45.30 pk	54.00 av	-8.7	102	100
1214.79	53.91 pk	25.49	2.2	34.05	47.55 pk	54.00 av	-6.45	102	97
1237.26	53.63 pk	25.59	2.2	34.06	47.36 pk	54.00 av	-6.64	102	96
1249.75	53.47 pk	25.65	2.2	34.06	47.25 pk	54.00 av	-6.75	102	95
1874.13	48.04 pk	29.94	2.51	34.93	45.56 pk	54.00 av	-8.44	100	52
3100.4	47.55 pk	31.18	1.5	34.97	45.26 pk	54.00 av	-8.74	103	331
3357.64	48.01 pk	31.39	1.64	35.53	45.50 pk	54.00 av	-8.5	103	265
4825.28	45.26 pk	34.94	2.12	37.72	44.60 pk	54.00 av	-9.4	100	180
7236.8	49.73 pk	39.48	2.68	36.83	55.06 pk	74.00 pk	-18.94	100	51
7236.8	31.45 av	39.48	2.68	36.83	36.78 av	54.00 av	-17.22	100	51
9645.97	41.85 pk	40.58	3.25	34.33	51.34 pk	54.00 av	-2.66	100	288

1GHz~ 25 GHz (Vertical), Channel 1: 2412 MHz

Operator: Jerry Chiou

RBW: 1MHz

Humidity (%): 41

Temperature (C): 27

Frequency	Rx_R.	Ant_F.	Cab_L.	PreAmp	Emission	Limit	Margin	A.Tower	T.Table
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	cm	deg
1012.49	52.98 pk	24.56	2.17	33.94	45.77 pk	54.00 av	-8.23	102	111
1252.25	51.25 pk	25.66	2.2	34.07	45.04 pk	54.00 av	-8.96	101	95
1876.62	47.54 pk	29.96	2.51	34.94	45.07 pk	54.00 av	-8.93	100	52
3050.45	46.91 pk	31.14	1.48	34.86	44.67 pk	54.00 av	-9.33	103	344
3292.71	46.47 pk	31.33	1.6	35.39	44.02 pk	54.00 av	-9.98	103	282
4823.4	47.00 pk	34.93	2.12	37.72	46.34 pk	54.00 av	-7.66	100	256
7236.91	57.92 pk	39.48	2.68	36.83	63.25 pk	74.00 pk	-10.75	100	174
7236.91	37.02 av	39.48	2.68	36.83	42.35 av	54.00 av	-11.65	100	174
9648.86	42.27 pk	40.57	3.25	34.33	51.76 pk	54.00 av	-2.24	100	13

Note:

- According to the standards used, Where limits are specified by agencies for both average and peak (or quasi-peak) detection , if the peak (or quasi-peak) measured value complies with the average limit , it is unnecessary to perform an average measurement.
- “*”: Fundamental Frequency
- “**”: Not in the restricted band, Limit level=Fundamental Emission-20dB
- “pk”: peak mode
- “av”: average mode
- “_”: No meter reading data due to the emission level is smaller than spectrum noise level.
- The Spectrum noise level+Correction Factor < Limit - 6 dB
- Margin=Corrected Amplitude – Limit
- Corrected Amplitude=Radiated Amplitude+Antenna Correction Factor+Cable Loss-Pre-Amplifier Gain
- A margin of -8dB means that the emission is 8dB below the limit.

All frequencies from 1GHz to 25 GHz have been tested.

1GHz~ 25 GHz (Horizontal) , Channel 6 : 2437 MHz

Operator: Jerry Chiou

RBW: 1MHz

Humidity (%): 41

Temperature (C): 27

Frequency	Rx_R.	Ant_F.	Cab_L.	PreAmpl	Emission	Limit	Margin	A.Tower	T.Table
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	cm	Deg
1214.79	52.09 pk	25.49	2.2	34.05	45.72 pk	54.00 av	-8.28	102	97
1469.53	57.20 pk	26.66	2.23	34.18	51.91 pk	54.00 av	-2.09	101	80
1474.53	54.25 pk	26.68	2.23	34.19	48.97 pk	54.00 av	-5.03	101	79
1794.21	48.76 pk	29.27	2.45	34.78	45.70 pk	54.00 av	-8.3	100	57
1876.62	48.20 pk	29.96	2.51	34.94	45.74 pk	54.00 av	-8.26	100	52
3297.7	48.05 pk	31.34	1.6	35.4	45.60 pk	54.00 av	-8.4	103	280
3357.64	48.48 pk	31.39	1.64	35.53	45.98 pk	54.00 av	-8.02	103	265
4874.91	47.70 pk	35.12	2.14	37.77	47.19 pk	54.00 av	-6.81	100	242
7308.5	49.05 pk	39.59	2.56	36.7	54.50 pk	74.00 pk	-19.5	100	62
7308.5	30.66 av	39.59	2.56	36.7	36.11 av	54.00 av	-17.89	100	62
9747.1	42.65 pk	40.36	3.3	34.37	51.94 pk	54.00 av	-2.06	100	271

1GHz~ 25 GHz (Vertical), Channel 6 : 2437 MHz

Operator: Jerry Chiou

RBW: 1MHz

Humidity (%): 41

Temperature (C): 27

Frequency	Rx_R.	Ant_F.	Cab_L.	PreAmpl	Emission	Limit	Margin	A.Tower	T.Table
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	cm	Deg
1154.85	51.74 pk	25.21	2.19	34.01	45.13 pk	54.00 av	-8.87	102	101
1217.28	49.73 pk	25.5	2.2	34.05	43.38 pk	54.00 av	-10.62	102	97
1714.29	47.87 pk	28.6	2.39	34.62	44.24 pk	54.00 av	-9.76	101	63
1764.24	46.17 pk	29.02	2.43	34.72	42.90 pk	54.00 av	-11.1	100	59
1796.7	46.66 pk	29.29	2.45	34.78	43.62 pk	54.00 av	-10.38	100	57
1914.09	45.47 pk	30.28	2.54	35.01	43.27 pk	54.00 av	-10.73	100	49
1994.01	45.75 pk	30.95	2.6	35.17	44.13 pk	54.00 av	-9.87	100	43
3160.34	46.23 pk	31.23	1.53	35.1	43.89 pk	54.00 av	-10.11	103	316
3295.2	46.05 pk	31.34	1.6	35.39	43.59 pk	54.00 av	-10.41	103	281
4876.33	49.80 pk	35.13	2.14	37.77	49.29 pk	54.00 av	-4.71	100	190
7313.4	56.66 pk	39.6	2.55	36.69	62.12 pk	74.00 pk	-11.88	100	167
7313.4	34.93 av	39.6	2.55	36.69	40.39 av	54.00 av	-13.61	100	167
9747	43.32 pk	40.36	3.3	34.37	52.61 pk	54.00 av	-1.39	100	237

Note:

- According to the standards used, Where limits are specified by agencies for both average and peak (or quasi-peak) detection , if the peak (or quasi-peak) measured value complies with the average limit , it is unnecessary to perform an average measurement.
- “*”: Fundamental Frequency
- “**”: Not in the restricted band, Limit level=Fundamental Emission-20dB
- “pk”: peak mode
- “av”: average mode
- “---”: No meter reading data due to the emission level is smaller than spectrum noise level.
- The Spectrum noise level+Correction Factor < Limit - 6 dB
- Margin=Corrected Amplitude – Limit
- Corrected Amplitude=Radiated Amplitude+Antenna Correction Factor+Cable Loss+Pre-Amplifier Gain
- A margin of -8dB means that the emission is 8dB below the limit.

All frequencies from 1GHz to 25 GHz have been tested.

1GHz~ 25 GHz (Horizontal), Channel 11: 2462 MHz

Operator: Jerry Chiou

RBW: 1MHz

Humidity (%): 41

Temperature (C): 27

Frequency	Rx_R.	Ant_F.	Cab_L.	PreAmpl	Emission	Limit	Margin	A.Tower	T.Table
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	cm	deg
1217.28	54.30 pk	25.5	2.2	34.05	47.95 pk	54.00 av	-6.05	102	97
1469.53	51.27 pk	26.66	2.23	34.18	45.97 pk	54.00 av	-8.03	101	80
1549.45	53.14 pk	27.22	2.27	34.3	48.33 pk	54.00 av	-5.67	101	74
1794.21	48.13 pk	29.27	2.45	34.78	45.07 pk	54.00 av	-8.93	100	57
3127.87	47.63 pk	31.2	1.52	35.03	45.32 pk	54.00 av	-8.68	103	324
4925.55	46.27 pk	35.32	2.15	37.83	45.91 pk	54.00 av	-8.09	100	235
7385.21	49.64 pk	39.72	2.42	36.56	55.21 pk	74.00 pk	-18.79	100	47
7385.21	28.74 av	39.72	2.42	36.56	34.32 av	54.00 av	-19.68	100	47
9846.19	43.99 pk	40.14	3.35	34.4	53.07 pk	74.00 pk	-20.93	100	198
9846.19	25.04 av	40.14	3.35	34.4	34.13 av	54.00 av	-19.87	100	198

1GHz~ 25 GHz (Vertical), Channel 11 : 2462 MHz

Operator: Jerry Chiou

RBW: 1MHz

Humidity (%): 41

Temperature (C): 27

Frequency	Rx_R.	Ant_F.	Cab_L.	PreAmpl	Emission	Limit	Margin	A.Tower	T.Table
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	cm	deg
1794.21	46.12 pk	29.27	2.45	34.78	43.06 pk	54.00 av	-10.94	100	57
1806.69	45.78 pk	29.38	2.46	34.8	42.81 pk	54.00 av	-11.19	100	56
1856.64	46.09 pk	29.8	2.49	34.9	43.48 pk	54.00 av	-10.52	100	53
1969.03	45.81 pk	30.74	2.58	35.12	44.01 pk	54.00 av	-9.99	100	45
3125.37	46.31 pk	31.2	1.52	35.02	44.00 pk	54.00 av	-10	103	325
3297.7	46.20 pk	31.34	1.6	35.4	43.74 pk	54.00 av	-10.26	103	280
4925.9	50.81 pk	35.32	2.15	37.83	50.45 pk	54.00 av	-3.55	100	212
7388.28	51.55 pk	39.72	2.42	36.56	57.13 pk	74.00 pk	-16.87	100	176
7388.28	32.13 av	39.72	2.42	36.56	38.71 av	54.00 av	-15.29	100	176
9849.12	43.53 pk	40.13	3.35	34.41	52.61 pk	54.00 av	-1.39	100	78

Note:

- According to the standards used, Where limits are specified by agencies for both average and peak (or quasi-peak) detection , if the peak (or quasi-peak) measured value complies with the average limit , it is unnecessary to perform an average measurement.
- “ * ”: Fundamental Frequency
- “***”: Not in the restricted band, Limit level=Fundamental Emission-20dB
- “ pk”: peak mode
- “av”: average mode
- “--”: No meter reading data due to the emission level is smaller than spectrum noise level.
- The Spectrum noise level+Correction Factor < Limit - 6 dB
- Margin=Corrected Amplitude – Limit
- Corrected Amplitude=Radiated Amplitude+Antenna Correction Factor+Cable Loss-Pre-Amplifier Gain
- A margin of -8dB means that the emission is 8dB below the limit.


All frequencies from 1GHz to 25 GHz have been tested.

6.5 Band Edge Measurement

6.5.1 Test Procedure (Conducted)

4. The transmitter output of EUT was connected to the spectrum analyzer.
Equipment mode: Spectrum analyzer
Detector function: Peak mode
SPAN: 100MHz
RBW: 100KHz
VBW: 100KHz
Center frequency: 2.4GHz, 2.4835GHz.
5. Using Peak Search to read the peak power of Carrier frequencies after Maximum Hold function is completed
6. Find the next peak frequency outside the operation frequency band

6.5.2 Test Setup (Conducted)



6.5.3 Test Data:

Table: Band Edge measurement (Conducted)



Temperature ():25

Test Engineer:Jerry Chiou

Humidity (%):50

Channel	Frequency (MHz)	Spectrum Reading (dBuV)	Carrier - Outsideband Limit: >20dB (dB)	Pass/Fail
1	2405.7	109.83	---	---
Outside band	2399.9	82.80	27.03	Pass
11	2466.9	109.61	---	---
Outside band	2475.6	79.34	30.27	Pass

Note: Two RF output(Left & Right) have been test, the worse data shown above.

Band Edge Conducted measurement**Band Edge Conducted Measurement**

6.5.4 Test Procedure (Radiated)

1. Antenna and Turntable test procedure same as Radiated Emission Measurement.
Equipment mode: Spectrum analyzer
Detector function: Peak mode
SPAN: 100MHz
RBW: 1MHz
VBW: 3MHz
Center frequency: 2.395GHz, 2.48GHz.
2. Using Peak Search to read the peak power of Carrier frequencies after Maximum Hold function is completed.
3. Find the next peak frequency outside the operation frequency band
4. For peak frequency emission level measurement in Restricted Band ,
Change RBW: 1MHz
VBW: 10Hz
Span: 100MHz.
5. Get the spectrum reading after Maximum Hold function is completed.

6.5.5 Test Setup (Radiated)

Same as *Radiated Emission Measurement*

6.5.6 Test Data**Table Band Edge measurement (Radiated)**

Test Engineer:Jerry Chiou

Temperature ():27



Humidity (%):45

Description	Frequency (MHz)	Spectrum Reading (dBuV)	Correction Factor (dB/m)	Emission Level (dBuV/m)	dBc (Limit: > 20dBc)	Limit (dBuV/m)	Equip. Setup VBW	Pass or Fail
Channel_1 (average mode)	2405.3	64.38	35.48	99.86	---	---	10Hz	---
Channel_1 (peak mode)	2405.7	65.93	35.48	101.41	---	---	300KHz	---
Outside band (peak mode)	2400.0	38.77	35.48	74.25	27.16	---	300KHz	Pass
<hr/>								
Channel_11 (average mode)	2468.1	62.59	35.50	98.09	---	---	10Hz	---
Channel_11 (peak mode)	2469.5	64.30	35.50	99.80	---	---	300KHz	---
Outside band (peak mode)	2474.0	36.27	35.51	71.78	28.02	---	300KHz	Pass
<hr/>								
Channel_1 Restricted band (peak mode)	2389.9	36.03	35.47	71.50	---	74	3MHz	Pass
Restricted band (average mode)	2390.0	15.63	35.47	51.10	---	54	10Hz	Pass
<hr/>								
Channel_11 Restricted band (peak mode)	2483.5	34.34	35.51	69.85	---	74	3MHz	Pass
Restricted band (average mode)	2483.5	14.93	35.51	50.44	---	54	10Hz	Pass


Note:

- The Spectrum plot of emission level measurement in Restricted band is attached.
- Emission Level=Spectrum Reading+Correction Factor
- Correction Factor=Antenna Factor+cable loss–amplifier gain
- Both Horizontal and Vertical polarization have been tested and the worst data is listed above.


Band Edge measurement for radiated emission in Restricted Band(Radiated) Peak Mode (Channel 1)




Band Edge measurement for radiated emission in Restricted Band(Radiated) Average Mode (Channel 1)




Band Edge measurement for radiated emission in Restricted Band(Radiated) Peak Mode (Channel 11)





Band Edge measurement for radiated emission in Restricted Band(Radiated) Average Mode (Channel 11)



6.6 RF Exposure Measurement [Section 15.247(b)(4) & 1.1307(b)]

See MPE report

6.7 DSSS Peak Power Spectral Density [Section 15.247(d)]

6.7.1 Test Procedure

1. The Transmitter output of EUT was connected to the spectrum analyzer.
Equipment mode: Spectrum analyzer
Detector function: Peak mode
SPAN:1.5MHz
RBW: 3KHz
VBW: 30KHz
Center frequency: fundamental frequency tested.
Sweep time= 500 sec.
2. Using Peak Search to read the peak power after Maximum Hold function is completed.

6.7.2 Test Setup



6.7.3 Test Data

Maximum Peak Output Power Density

Temperature ():25

Test Engineer:Jerry Chiou

Humidity (%):50

Channel	Frequency (MHz)	Spectrum Reading (dBm/3KHz)	Cable Loss (dB)	Peak Power Output (dBm/3KHz)	Limit (dBm/3KHz)	Pass/Fail
1	2412	-5.63	1.30	-4.33	8	Pass
6	2437	-4.80	1.30	-3.50	8	Pass
11	2462	-4.90	1.30	-3.60	8	Pass

Note: Two RF output(Left & Right) have been test,the worse data shown above.

Channel 1



Channel 6



Channel 11



International Standards Laboratory

HC LAB:NVLAP:200234-0;VCCI: R-341,C-354;NEMKO:ELA 113a,113c;BSMI:SL2-IN-E-0037;SL2-R1-E-0037;CNLA:1178
LT LAB:NVLAP:200234-0;VCCI: R-1435,C-1440;NEMKO:ELA 113b,113d;BSMI:SL2-IN-E-0013;CNLA:0997

Report Number: 05LR021FC

7. Appendix

7.1 Appendix A: Measurement Procedure for Power line Conducted Emissions

The measurements are performed in a 3.5m x 3.4m x 2.5m shielded room, which referred as Conduction 01 test site, or a 3m x 3m x 2.3m test site, which referred as Conduction 02 test site. The EUT was placed on non-conduction 1.0m x 1.5m table, which is 0.8 meters above an earth-grounded.

Power to the EUT was provided through the LISN which has the Impedance (50ohm/50uH) vs. Frequency Characteristic in accordance with the required standard. Power to the LISNs were filtered to eliminate ambient signal interference and these filters were bonded to the ground plane. Peripheral equipment required to provide a functional system (support equipment) for EUT testing was powered from the second LISN through a ganged, metal power outlet box which is bonded to the ground plane at the LISN.

If the EUT is supplied with a flexible power cord, the power cord length in excess of the distance separating the EUT from the LISN shall be folded back and forth at the center of the lead so as to form a bundle not exceeding 40cm in length. If the EUT is provided with a permanently coiled power cord, bundling of the cord is not required. If the EUT is supplied without a power cord, the EUT shall be connected to the LISN by a power cord of the type specified by the manufacturer which shall not be longer than 1 meter. The excess power cord shall be bundled as described above. If a non-flexible power cord is provided with the EUT, it shall be cut to the length necessary to attach the EUT to the LISN and shall not be bundled.

The interconnecting cables were arranged and moved to get the maximum emission. Both the line of power cord, hot and neutral, were measured.

The highest emissions were analyzed in details by operating the spectrum analyzer in fixed tuned mode to determine the nature of the emissions and to provide information which could be useful in reducing their amplitude.

7.2 Appendix B: Test Procedure for Radiated Emissions

Preliminary Measurements in the Anechoic Chamber

The radiated emissions are initially measured in the anechoic chamber at a measurement distance of 3 meters. Desktop EUT are placed on a wooden stand 0.8 meter in height. The measurement antenna is 3 meters from the EUT. The test setup in anechoic chamber is the same as open site. The turntable rotated 360°C. The antenna height is varied from 1-2.5m. The primary objective of the radiated measurements in the anechoic chamber is to identify the frequency spectrum in the absence of the electromagnetic environment existing on the open test site. The frequencies can then be pre-selected on the open test site to obtain the corresponding amplitude. The initial scan is made with the spectrum analyzer in automatic sweep mode. The spectrum peaks are then measured manually to determine the exact frequencies.

Measurements on the Open Site or 10m EMC Chamber

The radiated emissions test will then be repeated on the open site or 10m EMC chamber to measure the amplitudes accurately and without the multiple reflections existing in the shielded room. The EUT and support equipment are set up on the turntable of one of the 3 or 10 meter open field sites. Desktop EUT are set up on a wooden stand 0.8 meter above the ground.

For the initial measurements, the receiving antenna is varied from 1-4 meter height and is changed in the vertical plane from vertical to horizontal polarization at each frequency. Both reading are recorded with the quasi-peak detector with 120KHz bandwidth. For frequency between 30 MHz and 1000MHz, the reading is recorded with peak detector or quasi-peak detector. For frequency above 1 GHz, the reading is recorded with peak detector or average detector with 1 MHz bandwidth.

At the highest amplitudes observed, the EUT is rotated in the horizontal plane while changing the antenna polarization in the vertical plane to maximize the reading. The interconnecting cables were arranged and moved to get the maximum emission. Once the maximum reading is obtained, the antenna elevation and polarization will be varied between specified limits to maximize the readings.

7.3 Appendix C: Test Equipment

7.3.1 Test Equipment List

Location	Equipment Name	Brand	Model	S/N	Last Cal. Date	Next Cal. Date
Conduction	Coaxial Cable 1F-C2	Harbourindustries	RG400	1F-C2	05/20/2005	05/20/2006
Conduction	Digital Hygro-Thermometer Conduct	MicroLife	HT-2126G	ISL-Conductio n02	11/30/2004	11/30/2005
Conduction	EMI Receiver 02	HP	85460A	3448A00183	10/01/2004	10/01/2005
Conduction	LISN 01	R&S	ESH2-Z5	890485/013	05/05/2005	05/05/2006
Conduction	LISN 06	R&S	ESH3-Z5	828874/009	12/18/2004	12/18/2005
Radiation	BILOG Antenna 08	Schaffner	CBL6112B	2756	06/02/2004	06/02/2005
Radiation	Coaxial Cable Chmb 02-10M	Belden	RG-8/U	Chmb 02-10M	11/16/2004	11/16/2005
Radiation	Digital Hygro-Thermometer Chmb 02	MicroLife	HT-2126G	Chmb 02	11/30/2004	12/30/2005
Radiation	EMI Receiver 03	HP	85460A	3448A00209	03/24/2005	03/24/2006
Radiation	Spectrum Analyzer 13	Advantest	R3132	121200411	02/16/2005	02/16/2006
Radiation	Horn Antenna 02	Com-Power	AH-118	10088	07/22/2005	07/22/2006
Radiation	Horn Antenna 04	Com-Power	AH-826	081-001	01/13/2005	01/13/2006
Radiation	Horn Antenna 05	Com-Power	AH-640	100A	09/22/2004	09/22/2005
Radiation	Microwave Cable RF SK-01	HUBER+SUH NERAG.	Sucoflex 102	22139 /2	07/07/2005	07/07/2006
Chamber 05	Peak Power Analyzer	HP	8990A	3621A01269	02/15/2005	02/15/2006
Chamber 05	Power Sensor Radar	HP	84815A	3318A01828	02/15/2005	02/15/2006
Radiation	Preamplifier 02	MITEQ	AFS44-00102 650-40-10P-44	728229	01/28/2005	01/28/2006
Radiation	Preamplifier 10	MITEQ	JS-26004000-2 7-5A	818471	02/28/2005	02/28/2006
Radiation	High Pass Filter 01	HEWLETT-P ACKARD	84300-80038	001	N/A	N/A
Radiation	High Pass Filter 02	HEWLETT-P ACKARD	84300-80039	005	N/A	N/A
Radiation	Spectrum Analyzer 07	Advantest	R3182	110600649	04/21/2005	04/21/2006


Note: Calibration is traceable to NIST or national or international standards.

7.3.2 Software for Controlling Spectrum/Receiver and Calculating Test Data


Radiation/Conduction	Filename	Version	Issued Date
Conduction	Tile.exe	1.12E	7/7/2000
Radiation	Tile.exe	1.12C	6/16/2000

7.4 Appendix D: Layout of EUT and Support Equipment

7.4.1 General Conducted Test Configuration



7.4.2 General Radiation Test Configuration



7.5 Appendix E: Description of Support Equipment

7.5.1 Description of Support Equipment

Support Unit 1:

Description:	DELL Notebook Personal Computer
Model:	Latitude D400
Serial Number:	N/A
CPU:	Pentium M- 1.5GHz(FSB 400 MHz)
A/C Adapter Type:	HIPRO 65W(Model:HP-OQ065B83)3 Pins
Hard Disk Driver:	Toshiba (Model: MK4019GAX) 40 GB
MDC Modem:	Conexant (Model: RD01-D480)
VGA Connector:	One 15 Pins
Serial Connector:	One 9 Pins
RJ11 Connector:	One 2 Pins
RJ45 Connector:	One 8 Pins
USB Connector:	Two 4 Pins
1394 Connector:	One 4 Pins
Smart Card Slot:	One
PCMCIA Slot:	One
Earphone Port:	One
Microphone Port:	One
Power In Port:	One
Battery:	Sanyo 6-cell (Model: 6T087)
RAM:	Nanya DDR 256MB x 1
LCD Panel and Inverter:	Toshiba 12.1"XGA (Model: LTM12C505D) ; RICOH KEIKI Inverter (Model: K3E19T5 0090)
Power Cord:	Non-shielded, Detachable

7.5.2 Software for Controlling Support Unit

Test programs exercising various part of EUT were used. The programs were executed as follows:

- A. Read and write to the disk drives.
- B. The RF software makes the transmitter continuously sending RF signals
- C. Repeat the above steps.

	Filename	Issued Date
Atheros test software (Art48)	ART.exe	2004/04/12

7.5.3 I/O Cable Condition of EUT and Support Units

Description	Path	Cable Length	Cable Type	Connector Type
AC Power Cord	110V (~240V) to AC Power Cord Inlet (3-pin)	1.8M	Nonshielded, Detachable	Plastic Head

7.6 Appendix F: Accuracy of Measurement

Test Site: Conduction 02

Item	Source of Uncertainty	Probability Distribution	Total Uncertainties (dB)		Standard Uncertainty (dB)	
1	Systematic Effects: (Assessment from 20 repeat observation; 1 reading on EUT)	Normal	k=2	0.104	k=1	0.052
2	Random Effects: (Assessment from 20 random observations; 1 reading on EUT)	Normal	k=2	0.330	k=1	0.165
3	Receiver Calibration	Rectangular	k=1.73	1.000	k=1	0.577
4	LISN Factor Calibration	Normal	k=2	1.200	k=1	0.600
5	Cable Loss Calibration	Normal	k=2	1.000	k=1	0.500
6	Combined Standard Uncertainty Uc(y)	Normal			k=1	0.850
7	Total Uncertainty @95% min. Confidence Level	Normal	k=2	1.701		

Measurement Uncertainty Calculations:

$$U_c(y) = \text{square root} (u_1(y)^2 + u_2(y)^2 + \dots + u_n(y)^2)$$

$$U = 2 * U_c(y)$$

Note: The measurement Uncertainties mentioned above also refer to NIS 81-1994 of NAMAS :
The treatment of Uncertainty in EMC Measurement.

Test Site: Chamber 02-3M

Item	Source of Uncertainty	Probability Distribution	Total Uncertainties (dB)		Standard Uncertainty (dB)	
1	Systematic Effects: (Assessment from 20 repeat observation; 1 reading on EUT)	Normal	k=2	0.067	k=1	0.034
2	Random Effects: (Assessment from 20 random observations; 1 reading on EUT)	Normal	k=2	0.103	k=1	0.052
3	Receiver Calibration	Rectangular	k=1.73	1.000	k=1	0.577
4	Antenna Factor Calibration	Normal	k=2	1.700	k=1	0.850
5	Cable Loss Calibration	Normal	k=2	1.000	k=1	0.500
6	Combined Standard Uncertainty Uc(y)	Normal			k=1	1.029
7	Total Uncertainty @95% mim. Confidence Level	Normal	k=2	2.059		

Measurement Uncertainty Calculations:

$$U_c(y) = \text{square root} (u_1(y)^2 + u_2(y)^2 + \dots + u_n(y)^2)$$

$$U = 2 * U_c(y)$$

Note: The measurement Uncertainties mentioned above also refer to NIS 81-1994 of NAMAS :
The treatment of Uncertainty in EMC Measurement.

7.7 Appendix G: Photographs of EUT Configuration Test Set Up




The Front View of Highest Conducted Set-up For EUT


The Back View of Highest Conducted Set-up For EUT



The Front View of Highest Radiated Set-up For EUT



The Back View of Highest Radiated Set-up For EUT



7.8 Appendix H: Antenna Spec.

Please refer to the attached file.